


# FCC SAR Test Report

APPLICANT : Xiaomi Communications Co., Ltd.  
EQUIPMENT : Mobile Phone  
BRAND NAME : Redmi  
MODEL NAME : M2101K6G  
FCC ID : 2AFZZK6G  
STANDARD : FCC 47 CFR Part 2 (2.1093)

The product was received on Nov. 28, 2020 and testing was started from Dec. 04, 2020 and completed on Dec. 30, 2020. We, Sporton International (Kunshan) Inc, would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Reviewed by: Rose Wang / Supervisor



Approved by: Kat Yin / Manager



**Sporton International (Kunshan) Inc.**

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China



Table of Contents

1. Statement of Compliance ..... 4
2. Administration Data ..... 5
3. Guidance Applied ..... 5
4. Equipment Under Test (EUT) Information ..... 6
4.1 General Information ..... 6
4.2 General LTE SAR Test and Reporting Considerations ..... 7
5. Proximity Sensor Triggering Test ..... 9
5.1 Proximity sensor triggering distances(Per KDB616217§6.2) ..... 9
6. RF Exposure Limits ..... 10
6.1 Uncontrolled Environment ..... 10
6.2 Controlled Environment ..... 10
7. Specific Absorption Rate (SAR) ..... 11
7.1 Introduction ..... 11
7.2 SAR Definition ..... 11
8. System Description and Setup ..... 12
8.1 E-Field Probe ..... 13
8.2 Data Acquisition Electronics (DAE) ..... 13
8.3 Phantom ..... 14
8.4 Device Holder ..... 15
9. Measurement Procedures ..... 16
9.1 Spatial Peak SAR Evaluation ..... 16
9.2 Power Reference Measurement ..... 17
9.3 Area Scan ..... 17
9.4 Zoom Scan ..... 18
9.5 Volume Scan Procedures ..... 18
9.6 Power Drift Monitoring ..... 18
10. Test Equipment List ..... 19
11. System Verification ..... 20
11.1 Tissue Simulating Liquids ..... 20
11.2 Tissue Verification ..... 21
11.3 System Performance Check Results ..... 22
12. RF Exposure Positions ..... 23
12.1 Ear and handset reference point ..... 23
12.2 Definition of the cheek position ..... 24
12.3 Definition of the tilt position ..... 25
12.4 Body Worn Accessory ..... 26
12.5 Product Specific 10g SAR Exposure ..... 27
12.6 Wireless Router ..... 27
13. Conducted RF Output Power (Unit: dBm) ..... 28
14. Antenna Location ..... 41
15. SAR Test Results ..... 42
15.1 Head SAR ..... 44
15.2 Hotspot SAR ..... 50
15.3 Body Worn Accessory SAR ..... 56
15.4 Product specific 10g SAR ..... 59
16. Simultaneous Transmission Analysis ..... 60
16.1 Head Exposure Conditions ..... 61
16.2 Hotspot Exposure Conditions ..... 63
16.3 Body-Worn Accessory Exposure Conditions ..... 67
16.4 Product specific 10g SAR Exposure Conditions ..... 69
17. Uncertainty Assessment ..... 70
18. References ..... 71
Appendix A. Plots of System Performance Check
Appendix B. Plots of High SAR Measurement
Appendix C. DASy Calibration Certificate
Appendix D. Test Setup Photos
Appendix E. Conducted RF Output Power Table





### 1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Xiaomi Communications Co., Ltd., Mobile Phone, M2101K6G**, are as follows.

Highest 1g SAR Summary						
Equipment Class	Frequency Band		Head (Separation 0mm)	Hotspot (Separation 10mm)	Body-worn (Separation 15mm)	Highest Simultaneous Transmission 1g SAR (W/kg)
			1g SAR (W/kg)			
Licensed	GSM	GSM850	0.41	0.15	0.17	1.59
		GSM1900	0.53	0.48	0.37	
	WCDMA	Band V	0.64	0.48	0.24	
		Band IV	0.65	0.61	0.69	
		Band II	0.56	<b>1.02</b>	1.04	
	LTE	Band 5	0.67	0.27	0.25	
		Band 4	0.65	0.64	1.01	
		Band 2	0.60	0.74	<b>1.06</b>	
		Band 7	<b>1.09</b>	0.40	0.65	
		Band 38	1.06	0.89	0.44	
	Band 41	1.07	0.80	0.41		
DTS	WLAN	2.4GHz WLAN	0.99	0.49	0.19	1.54
NII		5GHz WLAN	1.02	0.67	0.85	1.59
DSS	Bluetooth	2.4GHz Bluetooth	0.11	<0.10	<0.10	1.59
Highest 10g SAR Summary						
Equipment Class	Frequency Band		Product Specific 10g SAR (W/kg) (Separation 0mm)			Highest Simultaneous Transmission 10g SAR (W/kg)
Licensed	WCDMA	Band II	2.30			2.36
	LTE	Band 2	<b>2.36</b>			
NII	WLAN	5GHz WLAN	2.00			2.36
Date of Testing:			2020/12/4 ~ 2020/12/30			

**Declaration of Conformity:**  
 The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**  
 The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.  
 This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.



### 2. Administration Data

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory		
Test Firm	Sporton International (Kunshan) Inc.	
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958	
Test Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CN1257	314309

Applicant	
Company Name	Xiaomi Communications Co., Ltd.
Address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

Manufacturer	
Company Name	Xiaomi Communications Co., Ltd.
Address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

### 3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D05A Rel.10 LTE SAR Test Guidance v01r02
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01



## 4. Equipment Under Test (EUT) Information

### 4.1 General Information

Product Feature & Specification	
Equipment Name	Mobile Phone
Brand Name	Redmi
Model Name	M2101K6G
FCC ID	2AFZZK6G
IMEI Code	SIM1: 861489050009425 SIM2: 861489050009433
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41: 2537.5 MHz ~ 2652.5 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC: 13.56 MHz
Mode	GSM/GPRS/EGPRS RMC/AMR 12.2Kbps HSDPA HSUPA DC-HSDPA HSPA+(16QAM uplink is not supported) LTE: QPSK, 16QAM, 64QAM, 256QAM(Downlink only) WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE NFC:ASK
HW Version	P2
SW Version	MIUI 12
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Identical Prototype
<b>Remark:</b>	
<ol style="list-style-type: none"> <li>This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation.</li> <li>This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications.</li> <li>This device 2.4GHz WLAN/5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.3GHz / 5.5GHz supports WiFi Direct (GC only).</li> <li>This device does not support DTM operation and supports GRPS/EGRPS mode up to multi-slot class 33.</li> <li>For dual SIM card mobile has two SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (single active). After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 slot to perform all tests.</li> <li>The device implements Proximity sensors/receiver detect mechanism/hotspot trigger reduced power for the power management for SAR compliance at different exposure conditions (head, body-worn, hotspot, extremity). The device will invoke corresponding work scenarios power level base on frequency bands/antennas, which can refer to</li> </ol>	



appendix E. power table. Full power table and reduced power table (DS1 1: receiver on reduced power for head; DS1 3: handheld on reduced power for extremity; DS1 5: hotspot on reduced power for hotspot).  
 7. There are three types of EUT, the sample 1 is 6+64GB capacity, the sample 2 is 6+128GB capacity. and the sample 3 is 8+128GB capacity. According to the difference, we only choose sample 1 to perform full SAR testing.

**4.2 General LTE SAR Test and Reporting Considerations**

Summarized necessary items addressed in KDB 941225 D05 v02r05																																																															
FCC ID	2AFZZK6G																																																														
Equipment Name	Mobile Phone																																																														
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41: 2537.5 MHz ~ 2652.5 MHz																																																														
Channel Bandwidth	LTE Band 2: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 4: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 5: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 38: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 41: 5MHz, 10MHz, 15MHz, 20MHz																																																														
uplink modulations used	QPSK / 16QAM / 64QAM /256QAM(Downlink only)																																																														
LTE Voice / Data requirements	Voice and Data																																																														
LTE Release Version	R11, Cat12																																																														
CA Support	Supported, Uplink and Downlink																																																														
LTE MPR permanently built-in by design	<p><b>Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3</b></p> <table border="1"> <thead> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (N<sub>RB</sub>)</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>&gt; 5</td> <td>&gt; 4</td> <td>&gt; 8</td> <td>&gt; 12</td> <td>&gt; 16</td> <td>&gt; 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>64 QAM</td> <td>&gt; 5</td> <td>&gt; 4</td> <td>&gt; 8</td> <td>&gt; 12</td> <td>&gt; 16</td> <td>&gt; 18</td> <td>≤ 2</td> </tr> <tr> <td>256 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>&gt; 5</td> <td>&gt; 4</td> <td>&gt; 8</td> <td>&gt; 12</td> <td>&gt; 16</td> <td>&gt; 18</td> <td>≤ 3</td> </tr> <tr> <td>256 QAM</td> <td colspan="6">≥ 1</td> <td>≤ 5</td> </tr> </tbody> </table>	Modulation	Channel bandwidth / Transmission bandwidth (N <sub>RB</sub> )						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2	256 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3	256 QAM	≥ 1						≤ 5
Modulation	Channel bandwidth / Transmission bandwidth (N <sub>RB</sub> )						MPR (dB)																																																								
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																									
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																																								
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																																								
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																																								
256 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2																																																								
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3																																																								
256 QAM	≥ 1						≤ 5																																																								
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																																														
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																														
Power reduction applied to satisfy SAR compliance	Yes, head/body-worn/ hotspot/extremity will trigger reduced power for some LTE bands, the detail please referred to section 13.																																																														
LTE Carrier Aggregation Combinations	Inter-Band and Intra-Band possible combinations and the detail power verification please referred to section 13.																																																														
LTE Carrier Aggregation Additional Information	1. This device supports LTE Carrier Aggregation (CA) in the uplink for 2C/7C/38C with two component carriers in the uplink. SAR Measurements and conducted powers were evaluated per FCC Guidance. 2. This device supports maximum of 3 carriers in the downlink and 2 carriers in the uplink.																																																														




Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829	20525	836.5	20525	836.5
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510	21100	2535	21100	2535
M	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560				
LTE Band 38												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	37775	2572.5	37800	2575	37825	2577.5	37850	2580	38000	2595	38000	2595
M	38000	2595	38000	2595	38000	2595	38000	2595	38000	2595	38000	2595
H	38225	2617.5	38200	2615	38175	2612.5	38150	2610				
LTE Band 41												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	40065	2537.5	40090	2540	40115	2542.5	40140	2545	40353	2566.3	40390	2570
LM	40353	2566.3	40365	2567.5	40378	2568.8	40390	2570	40640	2595	40640	2595
M	40640	2595	40640	2595	40640	2595	40640	2595	40928	2623.8	40890	2620
HM	40928	2623.8	40915	2622.5	40903	2621.3	40890	2620	41215	2652.5	41140	2645
H	41215	2652.5	41190	2650	41165	2647.5	41140	2645				



## 5. Proximity Sensor Triggering Test

### 5.1 Proximity sensor triggering distances(Per KDB616217§6.2)

1. Proximity sensor triggering distance testing was performed according to the procedures outlined in KDB 616217 D04 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed.
2. In the preliminary triggering distance testing, the tissue-equivalent medium for different frequency bands were used for verification; no other frequency bands tissue-equivalent medium was found to result in shortest triggering distance than that for 1900MHz, and the tissue-equivalent medium for 1900MHz was used for formal proximity sensor triggering testing.
3. Capacitive proximity sensor placed coincident with antenna elements at the top/bottom end of the phone are utilized to determine when the device comes in proximity of the user's body at the front or back or top or bottom or left side surface of the device. There is no need to do sensor coverage testing for the proximity sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the proximity sensor entirely covers the antenna.
4. P-sensor can detect handheld state, GSM850/1900/WCDMA band II/IV, LTE band 2/4/7/41 for front/back/top/bottom/left sides of product specific 10g SAR condition reduced powers will be active for handheld SAR base on different antenna. The proximity sensors trigger distance can refer to the following table.
5. The detailed proximity sensor trigger diagram plot can refer to proximity sensor operation description.



### <Handheld>

#### Antenna 1:

Position	Front		Back		Bottom Side	
	Moving towards	Moving away	Moving towards	Moving towards	Moving towards	Moving away
Minimum	16	16	16	16	16	16

#### Antenna 2:

Position	Front		Back		Left Side		Top Side	
	Moving towards	Moving away	Moving towards	Moving away	Moving towards	Moving away	Moving towards	Moving away
Minimum	6	6	6	6	6	6	6	6

## **6. RF Exposure Limits**

### **6.1 Uncontrolled Environment**

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### **6.2 Controlled Environment**

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Limits for Occupational/Controlled Exposure (W/kg)**

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

**Limits for General Population/Uncontrolled Exposure (W/kg)**

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

## **7. Specific Absorption Rate (SAR)**

### **7.1 Introduction**

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### **7.2 SAR Definition**

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

## 8. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:




- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

**8.1 E-Field Probe**

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG).The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

**<EX3DV4 Probe>**

<b>Construction</b>	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
<b>Frequency</b>	10 MHz – >6 GHz Linearity: ±0.2 dB (30 MHz – 6 GHz)	
<b>Directivity</b>	±0.3 dB in TSL (rotation around probe axis) ±0.5 dB in TSL (rotation normal to probe axis)	
<b>Dynamic Range</b>	10 µW/g – >100 mW/g Linearity: ±0.2 dB (noise: typically <1 µW/g)	
<b>Dimensions</b>	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

**8.2 Data Acquisition Electronics (DAE)**

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.


The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



**Photo of DAE**


### 8.3 Phantom

#### <SAM Twin Phantom>

<b>Shell Thickness</b>	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
<b>Filling Volume</b>	Approx. 25 liters	
<b>Dimensions</b>	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
<b>Measurement Areas</b>	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

#### <ELI Phantom>

<b>Shell Thickness</b>	2 ± 0.2 mm (sagging: <1%)	
<b>Filling Volume</b>	Approx. 30 liters	
<b>Dimensions</b>	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

## 8.4 Device Holder

### <Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

### <Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

## 9. Measurement Procedures

The measurement procedures are as follows:

### <Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

### <SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

### 9.1 **Spatial Peak SAR Evaluation**

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g



### 9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

### 9.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	$\leq 3$ GHz	$> 3$ GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	$5 \pm 1$ mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{Area}$ , $\Delta y_{Area}$	$\leq 2$ GHz: $\leq 15$ mm $2 - 3$ GHz: $\leq 12$ mm	$3 - 4$ GHz: $\leq 12$ mm $4 - 6$ GHz: $\leq 10$ mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

### 9.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

		$\leq 3$ GHz	$> 3$ GHz	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}$ , $\Delta y_{Zoom}$		$\leq 2$ GHz: $\leq 8$ mm 2 – 3 GHz: $\leq 5$ mm*	3 – 4 GHz: $\leq 5$ mm* 4 – 6 GHz: $\leq 4$ mm*	
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	$\leq 5$ mm	3 – 4 GHz: $\leq 4$ mm 4 – 5 GHz: $\leq 3$ mm 5 – 6 GHz: $\leq 2$ mm	
	graded grid	$\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	$\leq 4$ mm	3 – 4 GHz: $\leq 3$ mm 4 – 5 GHz: $\leq 2.5$ mm 5 – 6 GHz: $\leq 2$ mm
		$\Delta z_{Zoom}(n>1)$ : between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	$\geq 30$ mm	3 – 4 GHz: $\geq 28$ mm 4 – 5 GHz: $\geq 25$ mm 5 – 6 GHz: $\geq 22$ mm	
<p>Note: <math>\delta</math> is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.</p> <p>* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is <math>\leq 1.4</math> W/kg, <math>\leq 8</math> mm, <math>\leq 7</math> mm and <math>\leq 5</math> mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.</p>				

### 9.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

### 9.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



### 10. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	4d151	2019/3/27	2022/3/26
SPEAG	1750MHz System Validation Kit	D1750V2	1090	2019/3/27	2022/3/26
SPEAG	1900MHz System Validation Kit	D1900V2	5d170	2019/3/26	2022/3/25
SPEAG	2450MHz System Validation Kit	D2450V2	908	2019/3/25	2022/3/24
SPEAG	2600MHz System Validation Kit	D2600V2	1070	2018/12/7	2021/11/24
SPEAG	5000MHz System Validation Kit	D5GHzV2	1113	2019/9/24	2022/9/23
SPEAG	Data Acquisition Electronics	DAE4	690	2020/3/26	2021/3/25
SPEAG	Dosimetric E-Field Probe	EX3DV4	7592	2020/5/22	2021/5/21
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1697	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Anritsu	Radio Communication Analyzer	MT8821C	6201432831	2020/4/16	2021/4/15
Agilent	Wireless Communication Test Set	E5515C	MY52102706	2020/4/16	2021/4/15
Agilent	ENA Series Network Analyzer	E5071C	MY46111157	2020/4/16	2021/4/15
SPEAG	Dielectric Probe Kit	DAK-3.5	1071	2020/10/27	2021/10/26
Anritsu	Vector Signal Generator	MG3710A	6201682672	2020/1/8	2021/1/7
Rohde & Schwarz	Power Meter	NRVD	102081	2020/8/14	2021/8/13
Rohde & Schwarz	Power Sensor	NRV-Z5	100538	2020/8/13	2021/8/12
Rohde & Schwarz	Power Sensor	NRV-Z5	100539	2020/8/13	2021/8/12
R&S	CBT BLUETOOTH TESTER	CBT	101641	2020/1/8	2021/1/7
EXA	Spectrum Analyzer	FSV7	101631	2020/1/8	2021/1/7
Testo	Hygrometer	608-H1	1241332088	2020/1/8	2021/1/7
FLUKE	DIGITAC THERMOMETER	51II	97240029	2020/8/14	2021/8/13
ARRA	Power Divider	A3200-2	N/A	Note 1	
MCL	Attenuation1	BW-S10W5+	N/A	Note 1	
MCL	Attenuation2	BW-S10W5+	N/A	Note 1	
MCL	Attenuation3	BW-S10W5+	N/A	Note 1	
Agilent	Dual Directional Coupler	778D	20500	Note 1	
Agilent	Dual Directional Coupler	11691D	MY48151020	Note 1	
BONN	POWER AMPLIFIER	BLMA 0830-3	087193A	Note 1	
BONN	POWER AMPLIFIER	BLMA 2060-2	087193B	Note 1	

**Note:**

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check
2. Referring to KDB 865664 D01v01r04, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

## 11. System Verification

### 11.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.2.



Fig 11.1 Photo of Liquid Height for Head SAR



Fig 11.2 Photo of Liquid Height for Body SAR



### 11.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity ( $\sigma$ )	Permittivity ( $\epsilon_r$ )
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0

#### Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

#### <Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity ( $\sigma$ )	Permittivity ( $\epsilon_r$ )	Conductivity Target ( $\sigma$ )	Permittivity Target ( $\epsilon_r$ )	Delta ( $\sigma$ ) (%)	Delta ( $\epsilon_r$ ) (%)	Limit (%)	Date
835	Head	22.7	0.942	41.096	0.90	41.50	4.67	-0.97	±5	2020/12/5
1750	Head	22.6	1.351	40.380	1.37	40.10	-1.39	0.70	±5	2020/12/7
1900	Head	22.8	1.459	40.007	1.40	40.00	4.21	0.02	±5	2020/12/8
2450	Head	22.8	1.853	39.080	1.80	39.20	2.94	-0.31	±5	2020/12/4
2600	Head	22.7	1.981	39.077	1.96	39.00	1.07	0.20	±5	2020/12/6
5250	Head	22.6	4.564	35.431	4.71	35.90	-3.10	-1.31	±5	2020/12/10
5600	Head	22.8	4.946	34.825	5.07	35.50	-2.45	-1.90	±5	2020/12/11
5750	Head	22.7	5.128	34.550	5.22	35.40	-1.76	-2.40	±5	2020/12/13
835	Head	22.7	0.943	41.901	0.90	41.50	4.78	0.97	±5	2020/12/16
1750	Head	22.6	1.363	40.838	1.37	40.10	-0.51	1.84	±5	2020/12/18
1900	Head	22.8	1.455	40.651	1.40	40.00	3.93	1.63	±5	2020/12/20
2450	Head	22.9	1.836	39.855	1.80	39.20	2.00	1.67	±5	2020/12/22
2600	Head	22.7	1.959	39.618	1.96	39.00	-0.05	1.58	±5	2020/12/24
5250	Head	22.6	4.646	35.062	4.71	35.90	-1.36	-2.33	±5	2020/12/26
5600	Head	22.8	5.051	34.416	5.07	35.50	-0.37	-3.05	±5	2020/12/28
5750	Head	22.7	5.226	34.126	5.22	35.40	0.11	-3.60	±5	2020/12/30

### 11.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

**<1g SAR>**

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2020/12/5	835	Head	250	4d151	7592	690	2.43	9.30	9.72	4.52
2020/12/7	1750	Head	250	1090	7592	690	8.86	36.40	35.44	-2.64
2020/12/8	1900	Head	250	5d170	7592	690	10.10	39.00	40.4	3.59
2020/12/4	2450	Head	250	908	7592	690	12.80	52.80	51.2	-3.03
2020/12/6	2600	Head	250	1070	7592	690	13.90	58.10	55.6	-4.30
2020/12/10	5250	Head	100	1113	7592	690	7.53	80.50	75.3	-6.46
2020/12/11	5600	Head	100	1113	7592	690	8.42	83.40	84.2	0.96
2020/12/13	5750	Head	100	1113	7592	690	7.57	80.00	75.7	-5.38
2020/12/16	835	Head	250	4d151	7592	690	2.41	9.30	9.64	3.66
2020/12/18	1750	Head	250	1090	7592	690	8.94	36.40	35.76	-1.76
2020/12/20	1900	Head	250	5d170	7592	690	10.10	39.00	40.4	3.59
2020/12/22	2450	Head	250	908	7592	690	12.70	52.80	50.8	-3.79
2020/12/24	2600	Head	250	1070	7592	690	13.80	58.10	55.2	-4.99
2020/12/26	5250	Head	100	1113	7592	690	7.66	80.50	76.6	-4.84
2020/12/28	5600	Head	100	1113	7592	690	8.60	83.40	86	3.12
2020/12/30	5750	Head	100	1113	7592	690	7.72	80.00	77.2	-3.50

**<10g SAR>**

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2020/12/20	1900	Head	250	5d170	7592	690	5.26	20.30	21.04	3.65
2020/12/26	5250	Head	100	1113	7592	690	2.24	23.10	22.4	-3.03
2020/12/28	5600	Head	100	1113	7592	690	2.48	23.80	24.8	4.20




Fig 11.3.1 System Performance Check Setup



Fig 11.3.2 Setup Photo

## 12. RF Exposure Positions

### 12.1 Ear and handset reference point

Figure 12.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 12.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 12.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 12.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 12.1.1 Front, back, and side views of SAM twin phantom




Fig 12.1.2 Close-up side view of phantom showing the ear region.




Fig 12.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

### 12.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width  $w_t$  of the handset at the level of the acoustic output (point A in Figure 12.2.1 and Figure 12.2.2), and the midpoint of the width  $w_b$  of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 12.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 12.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 12.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 12.2.3. The actual rotation angles should be documented in the test report.




Fig 12.2.1 Handset vertical and horizontal reference lines—“fixed case”




Fig 12.2.2 Handset vertical and horizontal reference lines—“clam-shell case”





Fig 12.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.



**12.3 Definition of the tilt position**

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 12.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point



**Fig 12.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.**

## 12.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 12.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is  $> 1.2$  W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 12.4 Body Worn Position



## 12.5 Product Specific 10g SAR Exposure

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at  $\leq 25$  mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.6 The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

## 12.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ( $L \times W \geq 9$  cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.



### **13. Conducted RF Output Power (Unit: dBm)**

The detailed conducted power table can refer to Appendix E.

#### **<GSM Conducted Power>**

1. Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS 2Tx slots for GSM850, GPRS 1Tx slots for GSM1900 are considered as the primary mode.
3. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq \frac{1}{4}$  dB higher than the primary mode, SAR measurement is not required for the secondary mode.

#### **<WCDMA Conducted Power>**

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

#### **HSDPA Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
  - i. Set Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters were set according to each
  - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
  - iii. Set RMC 12.2Kbps + HSDPA mode.
  - iv. Set Cell Power = -86 dBm
  - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
  - vi. Select HSDPA Uplink Parameters
  - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
  - viii. Set Ack-Nack Repetition Factor to 3
  - ix. Set CQI Feedback Cycle (k) to 4 ms
  - x. Set CQI Repetition Factor to 2
  - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.



**Table C.10.1.4:  $\beta$  values for transmitter characteristics tests with HS-DPCCH**

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{HS}$ (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{HS} = 30/15 * \beta_c$ .

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA,  $\Delta_{ACK}$  and  $\Delta_{NACK} = 30/15$  with  $\beta_{HS} = 30/15 * \beta_c$ , and  $\Delta_{CQI} = 24/15$  with  $\beta_{HS} = 24/15 * \beta_c$ .

Note 3: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{HS}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

**Setup Configuration**

**HSUPA Setup Configuration:**

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting \* :
  - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
  - ii. Set the Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
  - iii. Set Cell Power = -86 dBm
  - iv. Set Channel Type = 12.2k + HSPA
  - v. Set UE Target Power
  - vi. Power Ctrl Mode= Alternating bits
  - vii. Set and observe the E-TFCI
  - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

**Table C.11.1.3:  $\beta$  values for transmitter characteristics tests with HS-DPCCH and E-DCH**

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c/\beta_d$	$\beta_{HS}$ (Note1)	$\beta_{ec}$	$\beta_{ed}$ (Note 4) (Note 5)	$\beta_{ed}$ (SF)	$\beta_{ed}$ (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}$ : 47/15 $\beta_{ed2}$ : 47/15	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4,  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{hs} = 30/15 * \beta_c$ . For sub-test 5,  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 5/15$  with  $\beta_{hs} = 5/15 * \beta_c$ .

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF0) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5:  $\beta_{ed}$  can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

**Setup Configuration**

**DC-HSDPA 3GPP release 8 Setup Configuration:**


- a. The EUT was connected to Base Station referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
  - i. Set RMC 12.2Kbps + HSDPA mode.
  - ii. Set Cell Power = -25 dBm
  - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
  - iv. Select HSDPA Uplink Parameters
  - v. Set Gain Factors ( $\beta_c$  and  $\beta_d$ ) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
    - a). Subtest 1:  $\beta_c/\beta_d=2/15$
    - b). Subtest 2:  $\beta_c/\beta_d=12/15$
    - c). Subtest 3:  $\beta_c/\beta_d=15/8$
    - d). Subtest 4:  $\beta_c/\beta_d=15/4$
  - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
  - vii. Set Ack-Nack Repetition Factor to 3
  - viii. Set CQI Feedback Cycle (k) to 4 ms
  - ix. Set CQI Repetition Factor to 2
  - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

**C.8.1.12 Fixed Reference Channel Definition H-Set 12**

**Table C.8.1.12: Fixed Reference Channel H-Set 12**

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload ( $N_{inf}$ )	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		



**Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)**

**Setup Configuration**



**<WCDMA Conducted Power>**

**General Note:**


1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is  $\leq \frac{1}{4}$  dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSDPA / HSUPA / DC-HSDPA) are less than  $\frac{1}{4}$  dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA




**<LTE Conducted Power>**

**General Note:**

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM/64QAM output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, 16QAM/64QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, smaller bandwidth output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4 / B5 / B38 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



**64QAM**




**16QAM**

**<TDD LTE SAR Measurement>**

TDD LTE configuration setup for SAR measurement

SAR was tested with a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by 3GPP.

- a. 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations
- b. "special subframe S" contains both uplink and downlink transmissions, it has been taken into consideration to determine the transmission duty factor according to the worst case uplink and downlink cyclic prefix requirements for UpPTS
- c. Establishing connections with base station simulators ensure a consistent means for testing SAR and recommended for evaluating SAR. The Anritsu MT8820C (firmware: #22.52#004) was used for LTE output power measurements and SAR testing.



**Figure 4.2-1: Frame structure type 2 (for 5 ms switch-point periodicity).**

**Table 4.2-2: Uplink-downlink configurations.**

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

**Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).**

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$			$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-		
9	$13168 \cdot T_s$	-	-	-	-	-

Special subframe (30720·T <sub>s</sub> ): Normal cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~4	7.13%	8.33%
	5~9	14.3%	16.7%

Special subframe(30720·T <sub>s</sub> ): Extended cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~3	7.13%	8.33%
	4~7	14.3%	16.7%

The highest duty factor is resulted from:

For LTE Band 41 Power class 3

- i. Uplink-downlink configuration: 0. In a half-frame consisted of 5 subframes, uplink operation is in 3 uplink subframes and 1 special subframe.
- ii. special subframe configuration: 5-9 for normal cyclic prefix in downlink, 4-7 for extended cyclic prefix in downlink
- iii. for special subframe with extended cyclic prefix in uplink, the total uplink duty factor in one half-frame is:  $(3+0.167)/5 = 63.3\%$
- iv. for special subframe with normal cyclic prefix in uplink, the total uplink duty factor in one half-frame is:  $(3+0.143)/5 = 62.9\%$
- v. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix  $63.3\%/62.9\% = 1.006$  is applied to scale-up the measured SAR result. The scaled TDD LTE SAR = measured SAR (W/kg)\* Tune-up Scaling Factor\* scaling factor for extended cyclic prefix.



<LTE Carrier Aggregation>

General Note:

- 1. This device supports Carrier Aggregation on downlink for inter and intra band. For the device supports bands and bandwidths and configurations are provided as follow table was according to 3GPP.
- 2. In applying the existing power measurement procedures of KDB 941225 D05A for DL CA SAR test exclusion, only the subset with the largest number of combinations of frequency bands and CCs in each row need combination, and for this device that all the configurations were choose to power measurement.
- 3. The gray color table is covered by other combinations and no need to verify power.

2CC Downlink Carrier Aggregation			3CC Downlink Carrier Aggregation		
Number	Combination	Covered by Measurement Superset	Number	Combination	Covered by Measurement Superset
2CC #1	CA_7A-7A		3CC #1	CA_4A-7C	
2CC #2	CA_41A-41A		3CC #2	CA_5A-7A-7A	
2CC #3	CA_2A-5A		3CC #3	CA_5A-7C	
2CC #4	CA_4A-5A				
2CC #5	CA_4A-7A				
2CC #6	CA_5A-7A				

**LTE Carrier Aggregation Conducted Power (Downlink)**

- i. According to KDB941225 D05A v01r02, Uplink maximum output power measurement with downlink carrier aggregation active should be measured, using the highest output channel measured without downlink carrier aggregation, to confirm that uplink maximum output power with downlink carrier aggregation active remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output measured without downlink carrier aggregation active.
- ii. Uplink maximum output power with downlink carrier aggregation active does not show more than ¼ dB higher than the maximum output power without downlink carrier aggregation active, therefore SAR evaluation with downlink carrier aggregation active can be excluded.
- iii. The device supports downlink two carrier aggregation. For power measurement were control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
- iv. Selected highest measured power when downlink carrier aggregation is inactive for conducted power comparison with downlink carrier aggregation is active, to confirm that when downlink carrier aggregation is active uplink maximum output power remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output power measured when downlink carrier aggregation inactive.
- v. For inter-band CA, the SCC selected highest bandwidth and near the middle of its transmission band. For SCC DL RB size and offset will base on the PCC corresponding RB allocation.
- vi. For non-contiguous intra-band CA, the SCC selected to provide maximum separation from the PCC and must remain fully within the downlink transmission band.
- vii. For Intra-band, contiguous CA, the downlink channels selected to perform the uplink power measurement must satisfy 3GPP channel spacing (5.4.1A of 3GPP TS 36.521 or equivalent) and channel bandwidth (5.4.2A) requirements.

$$\text{Nominal channel spacing} = \left\lceil \frac{BW_{\text{Channel}(1)} + BW_{\text{Channel}(2)} - 0.1|BW_{\text{Channel}(1)} - BW_{\text{Channel}(2)}|}{0.6} \right\rceil 0.3 \text{ [MHz]}$$

**LTE Carrier Aggregation Conducted Power (Uplink)**

1. This device supports uplink carrier aggregation for LTE CA\_2C, LTE CA\_7C, LTE CA\_38C with a maximum of two 20MHz component carriers. For intra band contiguous carrier aggregation scenarios, 3GPP 36.101 Table 6.2.2A-1 specifies that the aggregate maximum allowed output power is equivalent to the single carrier scenario. For the non-contiguously allocated resource blocks which the MPR level is determined by various RB separation and RB sizes requirement, and the allowed MPR levels, settings and the conducted powers are permanently implemented in this device per the 3GPP 36.36.101 section 6.2.3A.1.3 requirements.
2. According to FCC guidance, the output power with uplink CA active was measured for the high / middle / low channel configuration with the highest reported SAR for each exposure condition, the power was measured with wideband signal integration over both component carriers.
3. In applying the power measurement procedures of KDB 941225 D05A for DL CA to qualify for UL SAR test exclusion, power measurement is required only for the subset in each row with the largest combination of frequency bands and CCs
4. Maximum output power measurement is required for each UL CA configuration for the required test channels described in KDB 941225 D05. The required test channel should be associated with the UL PCC. For channels at the ends of a frequency band, the SCC and subsequent CCs are added to the side within the transmission band. Otherwise, the CCs should be added alternatively to either side of the PCC.





**<WLAN Conducted Power>**

**General Note:**


1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
  - a. When the reported SAR of the initial test position is  $\leq 0.4$  W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
  - b. When the reported SAR of the test position is  $> 0.4$  W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is  $\leq 0.8$  W/kg or all required test position are tested.
  - c. For all positions/configurations, when the reported SAR is  $> 0.8$  W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is  $\leq 1.2$  W/kg or all required channels are tested.



<2.4GHz Bluetooth>

General Note:

1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps, due to its highest average power.
2. The Bluetooth duty cycle is 77.03 % as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the maximum duty cycle is 100%, therefore the actual duty cycle will be scaled up to100% for Bluetooth reported SAR calculation







## **14. Antenna Location**

The detailed antenna location information can refer to SAR Test Setup Photos.

## 15. SAR Test Results

### General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
  - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
  - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
  - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)\*Tune-up Scaling Factor
  - d. For BT/WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)\* Duty Cycle scaling factor \* Tune-up scaling factor
  - e. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix  $63.3\%/62.9\% = 1.006$  is applied to scale-up the measured SAR result. The Reported TDD LTE SAR = measured SAR (W/kg)\* Tune-up Scaling Factor\* scaling factor for extended cyclic prefix.
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
  - $\leq 0.8$  W/kg or  $2.0$  W/kg, for 1-g or 10-g respectively, when the transmission band is  $\leq 100$  MHz
  - $\leq 0.6$  W/kg or  $1.5$  W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
  - $\leq 0.4$  W/kg or  $1.0$  W/kg, for 1-g or 10-g respectively, when the transmission band is  $\geq 200$  MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required when the measured SAR is  $\geq 0.8$ W/kg. Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. For dual SIM card mobile has two SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (single active). After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 slot to perform all tests.
5. The device implements Proximity sensors/receiver detect mechanism/hotspot trigger reduced power for the power management for SAR compliance at different exposure conditions (head, body-worn, hotspot, extremity). The device will invoke corresponding work scenarios power level base on frequency bands/antennas, which can refer to appendix E. power table. Full power table and reduced power table (DSI 1: receiver on reduced power for head; DSI 3: handheld on reduced power for extremity; DSI 5: hotspot on reduced power for hotspot).
6. There are three types of EUT, the sample 1 is 6+64GB capacity, the sample 2 is 6+128GB capacity. and the sample 3 is 8+128GB capacity. According to the difference, we only choose sample 1 to perform full SAR testing.
7. Per KDB648474 D04v01r03, for smart phones with a display diagonal dimension  $> 15.0$  cm or an overall diagonal dimension  $> 16.0$  cm, when hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR  $> 1.2$  W/kg, however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold.
  - a. For this device SAR for WWAN transmitter scaled to maximum output power mode for product specific 10g SAR is higher than 1.2W/kg of WCDMA Band II( ANT1), LTE Band 2( ANT1) therefore product specific 10g SAR is necessary.
  - b. WLAN 5.3/5.5GHz tested the product specific 10g SAR since it has no hotspot mode.
  - c. When 10-g product specific 10g SAR is considered, SAR thresholds is specified in the procedures for SAR test reduction and exclusion should be multiplied by 2.5.

### GSM Note:

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS 2Tx slots for GSM850, GPRS 1Tx slots for GSM1900 are considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq 1/4$  dB higher than the primary mode, SAR measurement is not required for the secondary mode.

**WCDMA Note:**

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is  $\leq \frac{1}{4}$  dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSDPA / HSUPA / DC-HSDPA) are less than  $\frac{1}{4}$  dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

**LTE Note:**

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM/64QAM output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, 16QAM/64QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, smaller bandwidth output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq 1.45$  W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4 / B5 / B38 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**WLAN/Bluetooth Note:**

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is  $> 0.4$  W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is  $\leq 0.8$  W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is  $> 0.8$  W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is  $\leq 1.2$  W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.



15.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM 850-Ant 1	GPRS 2 Tx slots	Right Cheek	Full	189	836.4	28.80	30.50	1.479	-0.03	0.070	0.104
	GSM 850-Ant 1	GPRS 2 Tx slots	Right Tilted	Full	189	836.4	28.80	30.50	1.479	-0.04	0.037	0.055
	GSM 850-Ant 1	GPRS 2 Tx slots	Left Cheek	Full	189	836.4	28.80	30.50	1.479	-0.09	0.057	0.084
	GSM 850-Ant 1	GPRS 2 Tx slots	Left Tilted	Full	189	836.4	28.80	30.50	1.479	0.14	0.031	0.046
01	GSM 850-Ant 2	GPRS 2 Tx slots	Right Cheek	Reduced	189	836.4	25.15	27.00	1.531	0.04	0.267	0.409
	GSM 850-Ant 2	GPRS 2 Tx slots	Right Tilted	Reduced	189	836.4	25.15	27.00	1.531	0.08	0.191	0.292
	GSM 850-Ant 2	GPRS 2 Tx slots	Left Cheek	Reduced	189	836.4	25.15	27.00	1.531	0.03	0.241	0.369
	GSM 850-Ant 2	GPRS 2 Tx slots	Left Tilted	Reduced	189	836.4	25.15	27.00	1.531	0.07	0.175	0.268
	GSM1900-Ant 1	GPRS 1 Tx slots	Right Cheek	Full	661	1880	29.70	31.00	1.349	0.1	0.024	0.032
	GSM1900-Ant 1	GPRS 1 Tx slots	Right Tilted	Full	661	1880	29.70	31.00	1.349	-0.06	0.025	0.034
	GSM1900-Ant 1	GPRS 1 Tx slots	Left Cheek	Full	661	1880	29.70	31.00	1.349	-0.05	0.029	0.039
	GSM1900-Ant 1	GPRS 1 Tx slots	Left Tilted	Full	661	1880	29.70	31.00	1.349	-0.02	0.030	0.040
	GSM1900-Ant 2	GPRS 1 Tx slots	Right Cheek	Reduced	661	1880	25.54	27.00	1.400	-0.03	0.243	0.340
02	GSM1900-Ant 2	GPRS 1 Tx slots	Right Tilted	Reduced	661	1880	25.54	27.00	1.400	0.07	0.377	0.528
	GSM1900-Ant 2	GPRS 1 Tx slots	Left Cheek	Reduced	661	1880	25.54	27.00	1.400	-0.01	0.243	0.340
	GSM1900-Ant 2	GPRS 1 Tx slots	Left Tilted	Reduced	661	1880	25.54	27.00	1.400	0.05	0.279	0.390

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V-Ant 1	RMC 12.2Kbps	Right Cheek	Full	4182	836.4	23.62	25.00	1.374	-0.02	0.144	0.198
	WCDMA V-Ant 1	RMC 12.2Kbps	Right Tilted	Full	4182	836.4	23.62	25.00	1.374	0.08	0.073	0.100
	WCDMA V-Ant 1	RMC 12.2Kbps	Left Cheek	Full	4182	836.4	23.62	25.00	1.374	0.07	0.111	0.153
	WCDMA V-Ant 1	RMC 12.2Kbps	Left Tilted	Full	4182	836.4	23.62	25.00	1.374	0.11	0.062	0.085
03	WCDMA V-Ant 2	RMC 12.2Kbps	Right Cheek	Reduced	4182	836.4	20.94	22.50	1.432	-0.07	0.447	0.640
	WCDMA V-Ant 2	RMC 12.2Kbps	Right Tilted	Reduced	4182	836.4	20.94	22.50	1.432	0.02	0.354	0.507
	WCDMA V-Ant 2	RMC 12.2Kbps	Left Cheek	Reduced	4182	836.4	20.94	22.50	1.432	-0.01	0.403	0.577
	WCDMA V-Ant 2	RMC 12.2Kbps	Left Tilted	Reduced	4182	836.4	20.94	22.50	1.432	0.09	0.343	0.491
	WCDMA IV-Ant 1	RMC 12.2Kbps	Right Cheek	Full	1413	1732.6	23.51	25.00	1.409	0.03	0.225	0.317
	WCDMA IV-Ant 1	RMC 12.2Kbps	Right Tilted	Full	1413	1732.6	23.51	25.00	1.409	0.08	0.178	0.251
	WCDMA IV-Ant 1	RMC 12.2Kbps	Left Cheek	Full	1413	1732.6	23.51	25.00	1.409	0.09	0.161	0.227
	WCDMA IV-Ant 1	RMC 12.2Kbps	Left Tilted	Full	1413	1732.6	23.51	25.00	1.409	-0.01	0.204	0.287
	WCDMA IV-Ant 2	RMC 12.2Kbps	Right Cheek	Reduced	1413	1732.6	13.79	15.20	1.384	0.07	0.417	0.577
04	WCDMA IV-Ant 2	RMC 12.2Kbps	Right Tilted	Reduced	1413	1732.6	13.79	15.20	1.384	0.05	0.467	0.646
	WCDMA IV-Ant 2	RMC 12.2Kbps	Left Cheek	Reduced	1413	1732.6	13.79	15.20	1.384	-0.02	0.275	0.380
	WCDMA IV-Ant 2	RMC 12.2Kbps	Left Tilted	Reduced	1413	1732.6	13.79	15.20	1.384	0.01	0.402	0.556
	WCDMA II-Ant 1	RMC 12.2Kbps	Right Cheek	Full	9400	1880	23.56	25.00	1.393	-0.01	0.089	0.124
	WCDMA II-Ant 1	RMC 12.2Kbps	Right Tilted	Full	9400	1880	23.56	25.00	1.393	0.03	0.079	0.110
	WCDMA II-Ant 1	RMC 12.2Kbps	Left Cheek	Full	9400	1880	23.56	25.00	1.393	0.01	0.080	0.111
	WCDMA II-Ant 1	RMC 12.2Kbps	Left Tilted	Full	9400	1880	23.56	25.00	1.393	0.03	0.107	0.149
	WCDMA II-Ant 2	RMC 12.2Kbps	Right Cheek	Reduced	9400	1880	15.74	17.20	1.400	0.07	0.299	0.418
05	WCDMA II-Ant 2	RMC 12.2Kbps	Right Tilted	Reduced	9400	1880	15.74	17.20	1.400	0.03	0.400	0.560
	WCDMA II-Ant 2	RMC 12.2Kbps	Left Cheek	Reduced	9400	1880	15.74	17.20	1.400	0.11	0.256	0.358
	WCDMA II-Ant 2	RMC 12.2Kbps	Left Tilted	Reduced	9400	1880	15.74	17.20	1.400	-0.04	0.353	0.494



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 5-Ant 1	10M	QPSK	1	0	Right Cheek	Full	20525	836.5	24.04	25.50	1.400	0.03	0.148	0.207
	LTE Band 5-Ant 1	10M	QPSK	25	0	Right Cheek	Full	20525	836.5	23.05	24.50	1.396	0.11	0.121	0.169
	LTE Band 5-Ant 1	10M	QPSK	1	0	Right Tilted	Full	20525	836.5	24.04	25.50	1.400	-0.04	0.065	0.091
	LTE Band 5-Ant 1	10M	QPSK	25	0	Right Tilted	Full	20525	836.5	23.05	24.50	1.396	0.05	0.054	0.075
	LTE Band 5-Ant 1	10M	QPSK	1	0	Left Cheek	Full	20525	836.5	24.04	25.50	1.400	0.19	0.111	0.155
	LTE Band 5-Ant 1	10M	QPSK	25	0	Left Cheek	Full	20525	836.5	23.05	24.50	1.396	-0.01	0.092	0.128
	LTE Band 5-Ant 1	10M	QPSK	1	0	Left Tilted	Full	20525	836.5	24.04	25.50	1.400	0.18	0.059	0.083
	LTE Band 5-Ant 1	10M	QPSK	25	0	Left Tilted	Full	20525	836.5	23.05	24.50	1.396	-0.04	0.051	0.071
06	LTE Band 5-Ant 2	10M	QPSK	1	0	Right Cheek	Reduced	20525	836.5	21.29	22.70	1.384	-0.03	0.483	<b>0.668</b>
	LTE Band 5-Ant 2	10M	QPSK	25	0	Right Cheek	Reduced	20525	836.5	21.17	22.70	1.422	0.11	0.463	0.659
	LTE Band 5-Ant 2	10M	QPSK	1	0	Right Tilted	Reduced	20525	836.5	21.29	22.70	1.384	0.08	0.324	0.448
	LTE Band 5-Ant 2	10M	QPSK	25	0	Right Tilted	Reduced	20525	836.5	21.17	22.70	1.422	-0.04	0.325	0.462
	LTE Band 5-Ant 2	10M	QPSK	1	0	Left Cheek	Reduced	20525	836.5	21.29	22.70	1.384	0.16	0.351	0.486
	LTE Band 5-Ant 2	10M	QPSK	25	0	Left Cheek	Reduced	20525	836.5	21.17	22.70	1.422	0.04	0.350	0.498
	LTE Band 5-Ant 2	10M	QPSK	1	0	Left Tilted	Reduced	20525	836.5	21.29	22.70	1.384	-0.06	0.286	0.396
	LTE Band 5-Ant 2	10M	QPSK	25	0	Left Tilted	Reduced	20525	836.5	21.17	22.70	1.422	-0.04	0.285	0.405
	LTE Band 4-Ant 1	20M	QPSK	1	0	Right Cheek	Full	20175	1732.5	24.08	25.50	1.387	0.16	0.197	0.273
	LTE Band 4-Ant 1	20M	QPSK	50	0	Right Cheek	Full	20175	1732.5	22.89	24.50	1.449	0.02	0.163	0.236
	LTE Band 4-Ant 1	20M	QPSK	1	0	Right Tilted	Full	20175	1732.5	24.08	25.50	1.387	0.01	0.202	0.280
	LTE Band 4-Ant 1	20M	QPSK	50	0	Right Tilted	Full	20175	1732.5	22.89	24.50	1.449	0.08	0.166	0.240
	LTE Band 4-Ant 1	20M	QPSK	1	0	Left Cheek	Full	20175	1732.5	24.08	25.50	1.387	0.01	0.119	0.165
	LTE Band 4-Ant 1	20M	QPSK	50	0	Left Cheek	Full	20175	1732.5	22.89	24.50	1.449	-0.03	0.097	0.141
	LTE Band 4-Ant 1	20M	QPSK	1	0	Left Tilted	Full	20175	1732.5	24.08	25.50	1.387	0.08	0.145	0.201
	LTE Band 4-Ant 1	20M	QPSK	50	0	Left Tilted	Full	20175	1732.5	22.89	24.50	1.449	0.01	0.117	0.170
	LTE Band 4-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	20175	1732.5	14.40	15.70	1.349	0.01	0.367	0.495
	LTE Band 4-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	20175	1732.5	14.19	15.70	1.416	0.07	0.406	0.575
07	LTE Band 4-Ant 2	20M	QPSK	1	0	Right Tilted	Reduced	20175	1732.5	14.40	15.70	1.349	0.04	0.479	<b>0.646</b>
	LTE Band 4-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	20175	1732.5	14.19	15.70	1.416	0.01	0.452	0.640
	LTE Band 4-Ant 2	20M	QPSK	1	0	Left Cheek	Reduced	20175	1732.5	14.40	15.70	1.349	0.07	0.219	0.295
	LTE Band 4-Ant 2	20M	QPSK	50	0	Left Cheek	Reduced	20175	1732.5	14.19	15.70	1.416	0.11	0.228	0.323
	LTE Band 4-Ant 2	20M	QPSK	1	0	Left Tilted	Reduced	20175	1732.5	14.40	15.70	1.349	-0.04	0.299	0.403
	LTE Band 4-Ant 2	20M	QPSK	50	0	Left Tilted	Reduced	20175	1732.5	14.19	15.70	1.416	0.01	0.297	0.420
	LTE Band 2-Ant 1	20M	QPSK	1	0	Right Cheek	Full	18900	1880	23.96	25.50	1.426	0.08	0.094	0.134
	LTE Band 2 C-Ant 1	20M	QPSK	1	0	Right Cheek	Full	18900+18702	1880+1860.2	23.78	25.50	1.486	0.03	0.078	0.116
	LTE Band 2-Ant 1	20M	QPSK	50	0	Right Cheek	Full	18900	1880	22.93	24.50	1.435	-0.07	0.073	0.105
	LTE Band 2-Ant 1	20M	QPSK	1	0	Right Tilted	Full	18900	1880	23.96	25.50	1.426	0.02	0.082	0.117
	LTE Band 2-Ant 1	20M	QPSK	50	0	Right Tilted	Full	18900	1880	22.93	24.50	1.435	-0.08	0.065	0.093
	LTE Band 2-Ant 1	20M	QPSK	1	0	Left Cheek	Full	18900	1880	23.96	25.50	1.426	0.15	0.068	0.097
	LTE Band 2-Ant 1	20M	QPSK	50	0	Left Cheek	Full	18900	1880	22.93	24.50	1.435	0.09	0.054	0.078
	LTE Band 2-Ant 1	20M	QPSK	1	0	Left Tilted	Full	18900	1880	23.96	25.50	1.426	0.06	0.081	0.115
	LTE Band 2-Ant 1	20M	QPSK	50	0	Left Tilted	Full	18900	1880	22.93	24.50	1.435	0.05	0.063	0.090
	LTE Band 2-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	18900	1880	16.46	17.70	1.330	-0.02	0.351	0.467
	LTE Band 2-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	18900	1880	16.29	17.70	1.384	0.04	0.341	0.472
08	LTE Band 2-Ant 2	20M	QPSK	1	0	Right Tilted	Reduced	18900	1880	16.46	17.70	1.330	-0.05	0.452	<b>0.601</b>
	LTE Band 2 C-Ant 2	20M	QPSK	1	0	Right Tilted	Reduced	18900+18702	1880+1860.2	16.26	17.70	1.393	0.01	0.419	0.584
	LTE Band 2-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	18900	1880	16.29	17.70	1.384	0.01	0.434	0.600
	LTE Band 2-Ant 2	20M	QPSK	1	0	Left Cheek	Reduced	18900	1880	16.46	17.70	1.330	0.07	0.269	0.358
	LTE Band 2-Ant 2	20M	QPSK	50	0	Left Cheek	Reduced	18900	1880	16.29	17.70	1.384	0.05	0.273	0.378
	LTE Band 2-Ant 2	20M	QPSK	1	0	Left Tilted	Reduced	18900	1880	16.46	17.70	1.330	0.05	0.371	0.494
	LTE Band 2-Ant 2	20M	QPSK	50	0	Left Tilted	Reduced	18900	1880	16.29	17.70	1.384	0.09	0.351	0.486



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 7-Ant 1	20M	QPSK	1	0	Right Cheek	Full	21100	2535	23.87	25.50	1.455	0.19	0.204	0.297
	LTE Band 7-Ant 1	20M	QPSK	50	0	Right Cheek	Full	21100	2535	22.60	24.50	1.549	0.06	0.161	0.249
	LTE Band 7-Ant 1	20M	QPSK	1	0	Right Tilted	Full	21100	2535	23.87	25.50	1.455	-0.01	0.210	0.306
	LTE Band 7-Ant 1	20M	QPSK	50	0	Right Tilted	Full	21100	2535	22.60	24.50	1.549	0.03	0.162	0.251
	LTE Band 7-Ant 1	20M	QPSK	1	0	Left Cheek	Full	21100	2535	23.87	25.50	1.455	-0.03	0.410	0.597
	LTE Band 7 C-Ant 1	20M	QPSK	1	0	Left Cheek	Full	21100+20902	2535+2515.2	23.10	25.50	1.738	0.01	0.333	0.579
	LTE Band 7-Ant 1	20M	QPSK	50	0	Left Cheek	Full	21100	2535	22.60	24.50	1.549	0.08	0.306	0.474
	LTE Band 7-Ant 1	20M	QPSK	1	0	Left Tilted	Full	21100	2535	23.87	25.50	1.455	0.01	0.196	0.285
	LTE Band 7-Ant 1	20M	QPSK	50	0	Left Tilted	Full	21100	2535	22.60	24.50	1.549	0.11	0.156	0.242
09	LTE Band 7-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	21100	2535	17.27	18.70	1.390	-0.06	0.782	1.087
	LTE Band 7 C-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	21100+20902	2535+2515.2	16.87	18.70	1.524	0.03	0.705	1.074
	LTE Band 7-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	20850	2510	17.05	18.70	1.462	0.01	0.712	1.041
	LTE Band 7-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	21350	2560	17.19	18.70	1.416	0.03	0.738	1.045
	LTE Band 7-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	21100	2535	17.19	18.70	1.416	-0.02	0.699	0.990
	LTE Band 7-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	20850	2510	16.96	18.70	1.493	0.05	0.710	1.060
	LTE Band 7-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	21350	2560	17.06	18.70	1.459	0.08	0.741	1.081
	LTE Band 7-Ant 2	20M	QPSK	100	0	Right Cheek	Reduced	21100	2535	17.16	18.70	1.426	0.06	0.714	1.018
	LTE Band 7-Ant 2	20M	QPSK	1	0	Right Tilted	Reduced	21100	2535	17.27	18.70	1.390	0.03	0.583	0.810
	LTE Band 7-Ant 2	20M	QPSK	1	0	Right Tilted	Reduced	20850	2510	17.05	18.70	1.462	0.08	0.539	0.788
	LTE Band 7-Ant 2	20M	QPSK	1	0	Right Tilted	Reduced	21350	2560	17.19	18.70	1.416	0.01	0.593	0.840
	LTE Band 7-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	21100	2535	17.19	18.70	1.416	-0.02	0.597	0.845
	LTE Band 7-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	20850	2510	16.96	18.70	1.493	0.07	0.553	0.826
	LTE Band 7-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	21350	2560	17.06	18.70	1.459	0.06	0.607	0.886
	LTE Band 7-Ant 2	20M	QPSK	100	0	Right Tilted	Reduced	21100	2535	17.16	18.70	1.426	0.07	0.710	1.012
	LTE Band 7-Ant 2	20M	QPSK	1	0	Left Cheek	Reduced	21100	2535	17.27	18.70	1.390	0.01	0.336	0.467
	LTE Band 7-Ant 2	20M	QPSK	50	0	Left Cheek	Reduced	21100	2535	17.19	18.70	1.416	0.11	0.330	0.467
	LTE Band 7-Ant 2	20M	QPSK	1	0	Left Tilted	Reduced	21100	2535	17.27	18.70	1.390	0.17	0.420	0.584
	LTE Band 7-Ant 2	20M	QPSK	50	0	Left Tilted	Reduced	21100	2535	17.19	18.70	1.416	0.09	0.436	0.617



<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 38-Ant 1	20M	QPSK	1	0	Right Cheek	Full	38000	2595	23.97	25.50	1.422	62.9	1.006	0.01	0.117	0.167
	LTE Band 38-Ant 1	20M	QPSK	50	0	Right Cheek	Full	38000	2595	22.84	24.50	1.466	62.9	1.006	0.1	0.095	0.140
	LTE Band 38-Ant 1	20M	QPSK	1	0	Right Tilted	Full	38000	2595	23.97	25.50	1.422	62.9	1.006	0.03	0.107	0.153
	LTE Band 38-Ant 1	20M	QPSK	50	0	Right Tilted	Full	38000	2595	22.84	24.50	1.466	62.9	1.006	0.18	0.083	0.122
	LTE Band 38-Ant 1	20M	QPSK	1	0	Left Cheek	Full	38000	2595	23.97	25.50	1.422	62.9	1.006	0.06	0.255	0.365
	LTE Band 38 C-Ant 1	20M	QPSK	1	0	Left Cheek	Full	37901+38099	2585.1+2604.9	23.92	25.50	1.439	62.9	1.006	0.06	0.255	0.369
	LTE Band 38-Ant 1	20M	QPSK	50	0	Left Cheek	Full	38000	2595	22.84	24.50	1.466	62.9	1.006	0.02	0.178	0.262
	LTE Band 38-Ant 1	20M	QPSK	1	0	Left Tilted	Full	38000	2595	23.97	25.50	1.422	62.9	1.006	0.05	0.115	0.165
	LTE Band 38-Ant 1	20M	QPSK	50	0	Left Tilted	Full	38000	2595	22.84	24.50	1.466	62.9	1.006	0.03	0.091	0.134
	LTE Band 38-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	38000	2595	19.32	20.70	1.374	62.9	1.006	0.07	0.644	0.890
10	LTE Band 38-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	37850	2580	19.23	20.70	1.403	62.9	1.006	-0.08	0.753	1.063
	LTE Band 38 C-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	37850+38048	2580+2599.8	19.16	20.70	1.426	62.9	1.006	0.02	0.711	1.020
	LTE Band 38-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	38150	2610	19.02	20.70	1.472	62.9	1.006	0.08	0.645	0.955
	LTE Band 38-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	38000	2595	19.15	20.70	1.429	62.9	1.006	0.09	0.673	0.967
	LTE Band 38-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	37850	2580	19.11	20.70	1.442	62.9	1.006	0.02	0.679	0.985
	LTE Band 38-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	38150	2610	19.01	20.70	1.476	62.9	1.006	0.08	0.643	0.955
	LTE Band 38-Ant 2	20M	QPSK	100	0	Right Cheek	Reduced	38000	2595	19.10	20.70	1.445	62.9	1.006	0.01	0.655	0.952
	LTE Band 38-Ant 2	20M	QPSK	1	0	Right Tilted	Reduced	38000	2595	19.32	20.70	1.374	62.9	1.006	0.1	0.563	0.778
	LTE Band 38-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	38000	2595	19.15	20.70	1.429	62.9	1.006	0.11	0.622	0.894
	LTE Band 38-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	37850	2580	19.11	20.70	1.442	62.9	1.006	0.02	0.625	0.907
	LTE Band 38-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	38150	2610	19.01	20.70	1.476	62.9	1.006	0.05	0.598	0.888
	LTE Band 38-Ant 2	20M	QPSK	100	0	Right Tilted	Reduced	38000	2595	19.10	20.70	1.445	62.9	1.006	-0.09	0.610	0.887
	LTE Band 38-Ant 2	20M	QPSK	1	0	Left Cheek	Reduced	38000	2595	19.32	20.70	1.374	62.9	1.006	0.05	0.326	0.451
	LTE Band 38-Ant 2	20M	QPSK	50	0	Left Cheek	Reduced	38000	2595	19.15	20.70	1.429	62.9	1.006	-0.02	0.333	0.479
	LTE Band 38-Ant 2	20M	QPSK	1	0	Left Tilted	Reduced	38000	2595	19.32	20.70	1.374	62.9	1.006	0.04	0.425	0.587
	LTE Band 38-Ant 2	20M	QPSK	50	0	Left Tilted	Reduced	38000	2595	19.15	20.70	1.429	62.9	1.006	-0.05	0.460	0.661



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41-Ant 1	20M	QPSK	1	0	Right Cheek	Full	40640	2595	23.98	25.50	1.419	62.9	1.006	0.12	0.115	0.164
	LTE Band 41-Ant 1	20M	QPSK	50	0	Right Cheek	Full	40640	2595	22.87	24.50	1.455	62.9	1.006	0.08	0.094	0.138
	LTE Band 41-Ant 1	20M	QPSK	1	0	Right Tilted	Full	40640	2595	23.98	25.50	1.419	62.9	1.006	-0.01	0.102	0.146
	LTE Band 41-Ant 1	20M	QPSK	50	0	Right Tilted	Full	40640	2595	22.87	24.50	1.455	62.9	1.006	0.14	0.083	0.122
	LTE Band 41-Ant 1	20M	QPSK	1	0	Left Cheek	Full	40640	2595	23.98	25.50	1.419	62.9	1.006	0.07	0.247	0.353
	LTE Band 41-Ant 1	20M	QPSK	50	0	Left Cheek	Full	40640	2595	22.87	24.50	1.455	62.9	1.006	-0.05	0.177	0.259
	LTE Band 41-Ant 1	20M	QPSK	1	0	Left Tilted	Full	40640	2595	23.98	25.50	1.419	62.9	1.006	0.04	0.112	0.160
	LTE Band 41-Ant 1	20M	QPSK	50	0	Left Tilted	Full	40640	2595	22.87	24.50	1.455	62.9	1.006	0.03	0.090	0.132
	LTE Band 41-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	40640	2595	19.15	20.70	1.429	62.9	1.006	-0.04	0.634	0.911
	LTE Band 41-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	40140	2545	19.02	20.70	1.472	62.9	1.006	0.04	0.650	0.963
	LTE Band 41-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	40390	2570	18.95	20.70	1.496	62.9	1.006	0.07	0.640	0.963
	LTE Band 41-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	40890	2620	18.89	20.70	1.517	62.9	1.006	0.16	0.645	0.984
	LTE Band 41-Ant 2	20M	QPSK	1	0	Right Cheek	Reduced	41140	2645	18.93	20.70	1.503	62.9	1.006	-0.09	0.633	0.957
11	LTE Band 41-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	40640	2595	19.07	20.70	1.455	62.9	1.006	-0.07	0.730	1.069
	LTE Band 41-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	40140	2545	19.06	20.70	1.459	62.9	1.006	-0.02	0.669	0.982
	LTE Band 41-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	40390	2570	18.98	20.70	1.486	62.9	1.006	0.03	0.663	0.991
	LTE Band 41-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	40890	2620	18.87	20.70	1.524	62.9	1.006	0.04	0.647	0.992
	LTE Band 41-Ant 2	20M	QPSK	50	0	Right Cheek	Reduced	41140	2645	18.73	20.70	1.574	62.9	1.006	0.04	0.633	1.002
	LTE Band 41-Ant 2	20M	QPSK	100	0	Right Cheek	Reduced	40640	2595	19.05	20.70	1.462	62.9	1.006	0.01	0.660	0.971
	LTE Band 41-Ant 2	20M	QPSK	1	0	Right Tilted	Reduced	40640	2595	19.15	20.70	1.429	62.9	1.006	0.05	0.565	0.812
	LTE Band 41-Ant 2	20M	QPSK	1	0	Right Tilted	Reduced	40140	2545	19.02	20.70	1.472	62.9	1.006	-0.16	0.571	0.846
	LTE Band 41-Ant 2	20M	QPSK	1	0	Right Tilted	Reduced	40390	2570	18.95	20.70	1.496	62.9	1.006	-0.11	0.585	0.881
	LTE Band 41-Ant 2	20M	QPSK	1	0	Right Tilted	Reduced	40890	2620	18.89	20.70	1.517	62.9	1.006	-0.05	0.622	0.949
	LTE Band 41-Ant 2	20M	QPSK	1	0	Right Tilted	Reduced	41140	2645	18.93	20.70	1.503	62.9	1.006	0.05	0.589	0.891
	LTE Band 41-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	40640	2595	19.07	20.70	1.455	62.9	1.006	-0.18	0.615	0.900
	LTE Band 41-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	40140	2545	19.06	20.70	1.459	62.9	1.006	0.02	0.565	0.829
	LTE Band 41-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	40390	2570	18.98	20.70	1.486	62.9	1.006	0.05	0.600	0.897
	LTE Band 41-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	40890	2620	18.87	20.70	1.524	62.9	1.006	-0.05	0.617	0.946
	LTE Band 41-Ant 2	20M	QPSK	50	0	Right Tilted	Reduced	41140	2645	18.73	20.70	1.574	62.9	1.006	-0.02	0.636	1.007
	LTE Band 41-Ant 2	20M	QPSK	100	0	Right Tilted	Reduced	40640	2595	19.05	20.70	1.462	62.9	1.006	-0.01	0.624	0.918
	LTE Band 41-Ant 2	20M	QPSK	1	0	Left Cheek	Reduced	40640	2595	19.15	20.70	1.429	62.9	1.006	-0.05	0.320	0.460
	LTE Band 41-Ant 2	20M	QPSK	50	0	Left Cheek	Reduced	40640	2595	19.07	20.70	1.455	62.9	1.006	0.02	0.332	0.486
	LTE Band 41-Ant 2	20M	QPSK	1	0	Left Tilted	Reduced	40640	1880	19.15	20.70	1.429	62.9	1.006	-0.05	0.419	0.602
	LTE Band 41-Ant 2	20M	QPSK	50	0	Left Tilted	Reduced	40640	2595	19.07	20.70	1.455	62.9	1.006	-0.07	0.455	0.666





<WLAN2.4G SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	Reduced	11	2462	16.57	18.00	1.390	100	1.000	0.03	0.260	0.361
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	Reduced	11	2462	16.57	18.00	1.390	100	1.000	0.01	0.301	0.418
12	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	Reduced	11	2462	16.57	18.00	1.390	100	1.000	0.01	0.712	0.990
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	Reduced	6	2437	15.30	17.00	1.479	100	1.000	0.08	0.515	0.762
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	Reduced	11	2462	16.57	18.00	1.390	100	1.000	0.08	0.708	0.984
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	Reduced	6	2437	15.30	17.00	1.479	100	1.000	0.08	0.479	0.708
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	Reduced -Simultaneous	11	2462	16.57	17.50	1.239	100	1.000	0.01	0.712	0.882
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	Reduced -Simultaneous	11	2462	16.57	17.50	1.239	100	1.000	0.08	0.708	0.877

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Right Cheek	Reduced	62	5310	12.22	13.50	1.343	96.32	1.038	-0.03	0.397	0.553
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Right Tilted	Reduced	62	5310	12.22	13.50	1.343	96.32	1.038	0.01	0.482	0.672
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Left Cheek	Reduced	62	5310	12.22	13.50	1.343	96.32	1.038	0.08	0.615	0.857
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Left Cheek	Reduced	54	5270	12.03	13.50	1.403	96.32	1.038	-0.01	0.449	0.654
13	WLAN5.3GHz	802.11ac-VHT40 MCS0	Left Tilted	Reduced	62	5310	12.22	13.50	1.343	96.32	1.038	-0.11	0.725	1.010
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Left Tilted	Reduced	54	5270	12.03	13.50	1.403	96.32	1.038	-0.08	0.670	0.976
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Right Cheek	Reduced -Simultaneous	62	5310	10.25	11.50	1.334	96.32	1.038	0.01	0.193	0.267
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Right Tilted	Reduced -Simultaneous	62	5310	10.25	11.50	1.334	96.32	1.038	0.02	0.259	0.359
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Left Cheek	Reduced -Simultaneous	62	5310	10.25	11.50	1.334	96.32	1.038	0.05	0.310	0.429
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Left Tilted	Reduced -Simultaneous	62	5310	10.25	11.50	1.334	96.32	1.038	-0.01	0.400	0.554
	WLAN5.5GHz	802.11ac-VHT40 MCS0	Right Cheek	Reduced	102	5510	12.29	13.50	1.321	96.32	1.038	0.02	0.500	0.686
	WLAN5.5GHz	802.11ac-VHT40 MCS0	Right Tilted	Reduced	102	5510	12.29	13.50	1.321	96.32	1.038	0.04	0.581	0.797
	WLAN5.5GHz	802.11ac-VHT40 MCS0	Left Cheek	Reduced	102	5510	12.29	13.50	1.321	96.32	1.038	0.09	0.525	0.720
14	WLAN5.5GHz	802.11ac-VHT40 MCS0	Left Tilted	Reduced	102	5510	12.29	13.50	1.321	96.32	1.038	-0.09	0.642	0.881
	WLAN5.5GHz	802.11ac-VHT40 MCS0	Left Tilted	Reduced	110	5550	11.82	13.50	1.472	96.32	1.038	-0.02	0.574	0.877
	WLAN5.5GHz	802.11ac-VHT40 MCS0	Right Cheek	Reduced -Simultaneous	102	5510	9.81	11.00	1.315	96.32	1.038	-0.05	0.236	0.322
	WLAN5.5GHz	802.11ac-VHT40 MCS0	Right Tilted	Reduced -Simultaneous	102	5510	9.81	11.00	1.315	96.32	1.038	-0.01	0.262	0.358
	WLAN5.5GHz	802.11ac-VHT40 MCS0	Left Cheek	Reduced -Simultaneous	102	5510	9.81	11.00	1.315	96.32	1.038	-0.09	0.259	0.354
	WLAN5.5GHz	802.11ac-VHT40 MCS0	Left Tilted	Reduced -Simultaneous	102	5510	9.81	11.00	1.315	96.32	1.038	-0.09	0.300	0.410
	WLAN5.8GHz	802.11ac-VHT40 MCS0	Right Cheek	Reduced	151	5755	11.95	13.50	1.429	96.32	1.038	0.01	0.495	0.734
	WLAN5.8GHz	802.11ac-VHT40 MCS0	Right Tilted	Reduced	151	5755	11.95	13.50	1.429	96.32	1.038	0.06	0.536	0.795
	WLAN5.8GHz	802.11ac-VHT40 MCS0	Left Cheek	Reduced	151	5755	11.95	13.50	1.429	96.32	1.038	0.04	0.477	0.707
15	WLAN5.8GHz	802.11ac-VHT40 MCS0	Left Tilted	Reduced	151	5755	11.95	13.50	1.429	96.32	1.038	-0.01	0.689	1.022
	WLAN5.8GHz	802.11ac-VHT40 MCS0	Right Cheek	Reduced -Simultaneous	151	5755	10.44	12.00	1.432	96.32	1.038	0.01	0.251	0.373
	WLAN5.8GHz	802.11ac-VHT40 MCS0	Right Tilted	Reduced -Simultaneous	151	5755	10.44	12.00	1.432	96.32	1.038	0.06	0.318	0.473
	WLAN5.8GHz	802.11ac-VHT40 MCS0	Left Cheek	Reduced -Simultaneous	151	5755	10.44	12.00	1.432	96.32	1.038	0.04	0.329	0.489
	WLAN5.8GHz	802.11ac-VHT40 MCS0	Left Tilted	Reduced -Simultaneous	151	5755	10.44	12.00	1.432	96.32	1.038	0.09	0.455	0.676

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Right Cheek	0	2402	11.25	12.00	1.189	77.03	1.298	-0.01	0.040	0.062
	Bluetooth	1Mbps	Right Tilted	0	2402	11.25	12.00	1.189	77.03	1.298	0.08	0.044	0.068
16	Bluetooth	1Mbps	Left Cheek	0	2402	11.25	12.00	1.189	77.03	1.298	0.05	0.073	0.113
	Bluetooth	1Mbps	Left Tilted	0	2402	11.25	12.00	1.189	77.03	1.298	0.04	0.072	0.111



15.2 Hotspot SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM 850-Ant 1	GPRS 2 Tx slots	Front	10mm	Full	189	836.4	28.80	30.50	1.479	-0.01	0.069	0.102
	GSM 850-Ant 1	GPRS 2 Tx slots	Back	10mm	Full	189	836.4	28.80	30.50	1.479	0.16	0.055	0.081
	GSM 850-Ant 1	GPRS 2 Tx slots	Left Side	10mm	Full	189	836.4	28.80	30.50	1.479	0.11	0.022	0.033
	GSM 850-Ant 1	GPRS 2 Tx slots	Right Side	10mm	Full	189	836.4	28.80	30.50	1.479	0.03	0.044	0.065
	GSM 850-Ant 1	GPRS 2 Tx slots	Bottom Side	10mm	Full	189	836.4	28.80	30.50	1.479	-0.01	0.048	0.071
	GSM 850-Ant 2	GPRS 2 Tx slots	Front	10mm	Reduced	189	836.4	25.15	27.00	1.531	0.01	0.089	0.136
17	GSM 850-Ant 2	GPRS 2 Tx slots	Back	10mm	Reduced	189	836.4	25.15	27.00	1.531	-0.03	0.095	0.145
	GSM 850-Ant 2	GPRS 2 Tx slots	Left Side	10mm	Reduced	189	836.4	25.15	27.00	1.531	-0.06	0.055	0.084
	GSM 850-Ant 2	GPRS 2 Tx slots	Right Side	10mm	Reduced	189	836.4	25.15	27.00	1.531	0.13	0.074	0.113
	GSM 850-Ant 2	GPRS 2 Tx slots	Top Side	10mm	Reduced	189	836.4	25.15	27.00	1.531	0.01	0.074	0.113
	GSM1900-Ant 1	GPRS 1 Tx slots	Front	10mm	Reduced	661	1880	25.13	27.00	1.538	0.01	0.185	0.285
	GSM1900-Ant 1	GPRS 1 Tx slots	Back	10mm	Reduced	661	1880	25.13	27.00	1.538	0.08	0.159	0.245
	GSM1900-Ant 1	GPRS 1 Tx slots	Left Side	10mm	Reduced	661	1880	25.13	27.00	1.538	0.13	0.028	0.043
	GSM1900-Ant 1	GPRS 1 Tx slots	Right Side	10mm	Reduced	661	1880	25.13	27.00	1.538	-0.05	0.011	0.017
18	GSM1900-Ant 1	GPRS 1 Tx slots	Bottom Side	10mm	Reduced	661	1880	25.13	27.00	1.538	-0.02	0.309	0.475
	GSM1900-Ant 2	GPRS 1 Tx slots	Front	10mm	Reduced	661	1880	25.54	27.00	1.400	0.01	0.067	0.094
	GSM1900-Ant 2	GPRS 1 Tx slots	Back	10mm	Reduced	661	1880	25.54	27.00	1.400	0.03	0.062	0.087
	GSM1900-Ant 2	GPRS 1 Tx slots	Left Side	10mm	Reduced	661	1880	25.54	27.00	1.400	-0.05	0.023	0.032
	GSM1900-Ant 2	GPRS 1 Tx slots	Right Side	10mm	Reduced	661	1880	25.54	27.00	1.400	-0.07	0.017	0.024
	GSM1900-Ant 2	GPRS 1 Tx slots	Top Side	10mm	Reduced	661	1880	25.54	27.00	1.400	0.05	0.225	0.315



<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V-Ant 1	RMC 12.2Kbps	Front	10mm	Full	4182	836.4	23.62	25.00	1.374	0.05	0.158	0.217
	WCDMA V-Ant 1	RMC 12.2Kbps	Back	10mm	Full	4182	836.4	23.62	25.00	1.374	0.01	0.224	0.308
	WCDMA V-Ant 1	RMC 12.2Kbps	Left Side	10mm	Full	4182	836.4	23.62	25.00	1.374	0.07	0.086	0.118
	WCDMA V-Ant 1	RMC 12.2Kbps	Right Side	10mm	Full	4182	836.4	23.62	25.00	1.374	0.01	0.173	0.238
	WCDMA V-Ant 1	RMC 12.2Kbps	Bottom Side	10mm	Full	4182	836.4	23.62	25.00	1.374	0.02	0.232	0.319
	WCDMA V-Ant 2	RMC 12.2Kbps	Front	10mm	Reduced	4182	836.4	20.94	22.50	1.432	0.05	0.203	0.291
19	WCDMA V-Ant 2	RMC 12.2Kbps	Back	10mm	Reduced	4182	836.4	20.94	22.50	1.432	-0.01	0.333	0.477
	WCDMA V-Ant 2	RMC 12.2Kbps	Left Side	10mm	Reduced	4182	836.4	20.94	22.50	1.432	0.14	0.130	0.186
	WCDMA V-Ant 2	RMC 12.2Kbps	Right Side	10mm	Reduced	4182	836.4	20.94	22.50	1.432	0.02	0.156	0.223
	WCDMA V-Ant 2	RMC 12.2Kbps	Top Side	10mm	Reduced	4182	836.4	20.94	22.50	1.432	0.11	0.172	0.246
	WCDMA IV-Ant 1	RMC 12.2Kbps	Front	10mm	Reduced	1413	1732.6	19.57	21.00	1.390	0.11	0.231	0.321
	WCDMA IV-Ant 1	RMC 12.2Kbps	Back	10mm	Reduced	1413	1732.6	19.57	21.00	1.390	0.16	0.324	0.450
	WCDMA IV-Ant 1	RMC 12.2Kbps	Left Side	10mm	Reduced	1413	1732.6	19.57	21.00	1.390	-0.1	0.055	0.076
	WCDMA IV-Ant 1	RMC 12.2Kbps	Right Side	10mm	Reduced	1413	1732.6	19.57	21.00	1.390	0.15	0.092	0.128
20	WCDMA IV-Ant 1	RMC 12.2Kbps	Bottom Side	10mm	Reduced	1413	1732.6	19.57	21.00	1.390	0.05	0.442	0.614
	WCDMA IV-Ant 2	RMC 12.2Kbps	Front	10mm	Reduced	1413	1732.6	13.79	15.20	1.384	0.14	0.094	0.130
	WCDMA IV-Ant 2	RMC 12.2Kbps	Back	10mm	Reduced	1413	1732.6	13.79	15.20	1.384	0.01	0.149	0.206
	WCDMA IV-Ant 2	RMC 12.2Kbps	Left Side	10mm	Reduced	1413	1732.6	13.79	15.20	1.384	0.07	0.017	0.024
	WCDMA IV-Ant 2	RMC 12.2Kbps	Right Side	10mm	Reduced	1413	1732.6	13.79	15.20	1.384	-0.03	0.009	0.012
	WCDMA IV-Ant 2	RMC 12.2Kbps	Top Side	10mm	Reduced	1413	1732.6	13.79	15.20	1.384	0.06	0.256	0.354
	WCDMA II-Ant 1	RMC 12.2Kbps	Front	10mm	Reduced	9400	1880	17.37	19.00	1.455	0.15	0.190	0.277
	WCDMA II-Ant 1	RMC 12.2Kbps	Back	10mm	Reduced	9400	1880	17.37	19.00	1.455	0.12	0.274	0.399
	WCDMA II-Ant 1	RMC 12.2Kbps	Left Side	10mm	Reduced	9400	1880	17.37	19.00	1.455	0.01	0.026	0.038
	WCDMA II-Ant 1	RMC 12.2Kbps	Right Side	10mm	Reduced	9400	1880	17.37	19.00	1.455	0.06	0.029	0.042
21	WCDMA II-Ant 1	RMC 12.2Kbps	Bottom Side	10mm	Reduced	9400	1880	17.37	19.00	1.455	-0.04	0.701	1.020
	WCDMA II-Ant 1	RMC 12.2Kbps	Bottom Side	10mm	Reduced	9262	1852.4	17.23	19.00	1.503	0.06	0.538	0.809
	WCDMA II-Ant 1	RMC 12.2Kbps	Bottom Side	10mm	Reduced	9538	1907.6	17.35	19.00	1.462	0.02	0.645	0.943
	WCDMA II-Ant 2	RMC 12.2Kbps	Front	10mm	Reduced	9400	1880	15.74	17.20	1.400	0.11	0.072	0.101
	WCDMA II-Ant 2	RMC 12.2Kbps	Back	10mm	Reduced	9400	1880	15.74	17.20	1.400	0.03	0.112	0.157
	WCDMA II-Ant 2	RMC 12.2Kbps	Left Side	10mm	Reduced	9400	1880	15.74	17.20	1.400	0.04	0.016	0.022
	WCDMA II-Ant 2	RMC 12.2Kbps	Right Side	10mm	Reduced	9400	1880	15.74	17.20	1.400	-0.01	0.019	0.027
	WCDMA II-Ant 2	RMC 12.2Kbps	Top Side	10mm	Reduced	9400	1880	15.74	17.20	1.400	0.05	0.259	0.362



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 5-Ant 1	10M	QPSK	1	0	Front	10mm	Full	20525	836.5	24.04	25.50	1.400	-0.05	0.157	0.220
	LTE Band 5-Ant 1	10M	QPSK	25	0	Front	10mm	Full	20525	836.5	23.05	24.50	1.396	0.05	0.126	0.176
	LTE Band 5-Ant 1	10M	QPSK	1	0	Back	10mm	Full	20525	836.5	24.04	25.50	1.400	0.17	0.152	0.213
	LTE Band 5-Ant 1	10M	QPSK	25	0	Back	10mm	Full	20525	836.5	23.05	24.50	1.396	-0.01	0.147	0.205
	LTE Band 5-Ant 1	10M	QPSK	1	0	Left Side	10mm	Full	20525	836.5	24.04	25.50	1.400	-0.09	0.058	0.081
	LTE Band 5-Ant 1	10M	QPSK	25	0	Left Side	10mm	Full	20525	836.5	23.05	24.50	1.396	0.14	0.048	0.067
	LTE Band 5-Ant 1	10M	QPSK	1	0	Right Side	10mm	Full	20525	836.5	24.04	25.50	1.400	-0.1	0.138	0.193
	LTE Band 5-Ant 1	10M	QPSK	25	0	Right Side	10mm	Full	20525	836.5	23.05	24.50	1.396	-0.08	0.115	0.161
	LTE Band 5-Ant 1	10M	QPSK	1	0	Bottom Side	10mm	Full	20525	836.5	24.04	25.50	1.400	-0.03	0.130	0.182
	LTE Band 5-Ant 1	10M	QPSK	25	0	Bottom Side	10mm	Full	20525	836.5	23.05	24.50	1.396	-0.03	0.107	0.149
	LTE Band 5-Ant 2	10M	QPSK	1	0	Front	10mm	Reduced	20525	836.5	21.29	22.70	1.384	0.01	0.177	0.245
	LTE Band 5-Ant 2	10M	QPSK	25	0	Front	10mm	Reduced	20525	836.5	21.17	22.70	1.422	0.14	0.175	0.249
	LTE Band 5-Ant 2	10M	QPSK	1	0	Back	10mm	Reduced	20525	836.5	21.29	22.70	1.384	0.11	0.188	0.260
22	LTE Band 5-Ant 2	10M	QPSK	25	0	Back	10mm	Reduced	20525	836.5	21.17	22.70	1.422	-0.07	0.190	0.270
	LTE Band 5-Ant 2	10M	QPSK	1	0	Left Side	10mm	Reduced	20525	836.5	21.29	22.70	1.384	0.04	0.113	0.156
	LTE Band 5-Ant 2	10M	QPSK	25	0	Left Side	10mm	Reduced	20525	836.5	21.17	22.70	1.422	0.17	0.110	0.156
	LTE Band 5-Ant 2	10M	QPSK	1	0	Right Side	10mm	Reduced	20525	836.5	21.29	22.70	1.384	0.11	0.108	0.149
	LTE Band 5-Ant 2	10M	QPSK	25	0	Right Side	10mm	Reduced	20525	836.5	21.17	22.70	1.422	0.05	0.103	0.146
	LTE Band 5-Ant 2	10M	QPSK	1	0	Top Side	10mm	Reduced	20525	836.5	21.29	22.70	1.384	0.06	0.150	0.208
	LTE Band 5-Ant 2	10M	QPSK	25	0	Top Side	10mm	Reduced	20525	836.5	21.17	22.70	1.422	-0.02	0.153	0.218
	LTE Band 4-Ant 1	20M	QPSK	1	0	Front	10mm	Reduced	20175	1732.5	20.15	21.50	1.365	0.06	0.345	0.471
	LTE Band 4-Ant 1	20M	QPSK	50	0	Front	10mm	Reduced	20175	1732.5	19.90	21.50	1.445	0.17	0.362	0.523
	LTE Band 4-Ant 1	20M	QPSK	1	0	Back	10mm	Reduced	20175	1732.5	20.15	21.50	1.365	0.06	0.362	0.494
	LTE Band 4-Ant 1	20M	QPSK	50	0	Back	10mm	Reduced	20175	1732.5	19.90	21.50	1.445	0.01	0.381	0.551
	LTE Band 4-Ant 1	20M	QPSK	1	0	Left Side	10mm	Reduced	20175	1732.5	20.15	21.50	1.365	-0.09	0.089	0.121
	LTE Band 4-Ant 1	20M	QPSK	50	0	Left Side	10mm	Reduced	20175	1732.5	19.90	21.50	1.445	0.11	0.090	0.130
	LTE Band 4-Ant 1	20M	QPSK	1	0	Right Side	10mm	Reduced	20175	1732.5	20.15	21.50	1.365	0.07	0.090	0.123
	LTE Band 4-Ant 1	20M	QPSK	50	0	Right Side	10mm	Reduced	20175	1732.5	19.90	21.50	1.445	0.08	0.093	0.134
	LTE Band 4-Ant 1	20M	QPSK	1	0	Bottom Side	10mm	Reduced	20175	1732.5	20.15	21.50	1.365	0.14	0.419	0.572
23	LTE Band 4-Ant 1	20M	QPSK	50	0	Bottom Side	10mm	Reduced	20175	1732.5	19.90	21.50	1.445	0.05	0.443	0.640
	LTE Band 4-Ant 2	20M	QPSK	1	0	Front	10mm	Reduced	20175	1732.5	14.40	15.70	1.349	0.02	0.104	0.140
	LTE Band 4-Ant 2	20M	QPSK	50	0	Front	10mm	Reduced	20175	1732.5	14.19	15.70	1.416	0.05	0.112	0.159
	LTE Band 4-Ant 2	20M	QPSK	1	0	Back	10mm	Reduced	20175	1732.5	14.40	15.70	1.349	-0.05	0.107	0.144
	LTE Band 4-Ant 2	20M	QPSK	50	0	Back	10mm	Reduced	20175	1732.5	14.19	15.70	1.416	-0.02	0.113	0.160
	LTE Band 4-Ant 2	20M	QPSK	1	0	Left Side	10mm	Reduced	20175	1732.5	14.40	15.70	1.349	-0.01	0.011	0.015
	LTE Band 4-Ant 2	20M	QPSK	50	0	Left Side	10mm	Reduced	20175	1732.5	14.19	15.70	1.416	-0.05	0.013	0.018
	LTE Band 4-Ant 2	20M	QPSK	1	0	Right Side	10mm	Reduced	20175	1732.5	14.40	15.70	1.349	-0.11	0.010	0.013
	LTE Band 4-Ant 2	20M	QPSK	50	0	Right Side	10mm	Reduced	20175	1732.5	14.19	15.70	1.416	0.04	0.009	0.013
	LTE Band 4-Ant 2	20M	QPSK	1	0	Top Side	10mm	Reduced	20175	1732.5	14.40	15.70	1.349	0.09	0.261	0.352
	LTE Band 4-Ant 2	20M	QPSK	50	0	Top Side	10mm	Reduced	20175	1732.5	14.19	15.70	1.416	-0.1	0.267	0.378



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2-Ant 1	20M	QPSK	1	0	Front	10mm	Reduced	18900	1880	17.15	18.50	1.365	0.16	0.290	0.396
	LTE Band 2-Ant 1	20M	QPSK	50	0	Front	10mm	Reduced	18900	1880	17.12	18.50	1.374	-0.08	0.291	0.400
	LTE Band 2-Ant 1	20M	QPSK	1	0	Back	10mm	Reduced	18900	1880	17.15	18.50	1.365	-0.1	0.264	0.360
	LTE Band 2-Ant 1	20M	QPSK	50	0	Back	10mm	Reduced	18900	1880	17.12	18.50	1.374	0.13	0.267	0.367
	LTE Band 2-Ant 1	20M	QPSK	1	0	Left Side	10mm	Reduced	18900	1880	17.15	18.50	1.365	0.05	0.033	0.045
	LTE Band 2-Ant 1	20M	QPSK	50	0	Left Side	10mm	Reduced	18900	1880	17.12	18.50	1.374	0.06	0.033	0.045
	LTE Band 2-Ant 1	20M	QPSK	1	0	Right Side	10mm	Reduced	18900	1880	17.15	18.50	1.365	-0.04	0.017	0.023
	LTE Band 2-Ant 1	20M	QPSK	50	0	Right Side	10mm	Reduced	18900	1880	17.12	18.50	1.374	0.06	0.016	0.022
	LTE Band 2-Ant 1	20M	QPSK	1	0	Bottom Side	10mm	Reduced	18900	1880	17.15	18.50	1.365	0.11	0.528	0.720
24	LTE Band 2-Ant 1	20M	QPSK	50	0	Bottom Side	10mm	Reduced	18900	1880	17.12	18.50	1.374	-0.03	0.540	0.742
	LTE Band 2 C-Ant 1	20M	QPSK	1	0	Bottom Side	10mm	Reduced	18900+18702	1880+1860.2	17.04	18.50	1.400	0.02	0.512	0.717
	LTE Band 2-Ant 2	20M	QPSK	1	0	Front	10mm	Reduced	18900	1880	16.46	17.70	1.330	0.11	0.091	0.121
	LTE Band 2-Ant 2	20M	QPSK	50	0	Front	10mm	Reduced	18900	1880	16.29	17.70	1.384	-0.02	0.092	0.127
	LTE Band 2-Ant 2	20M	QPSK	1	0	Back	10mm	Reduced	18900	1880	16.46	17.70	1.330	0.03	0.093	0.124
	LTE Band 2-Ant 2	20M	QPSK	50	0	Back	10mm	Reduced	18900	1880	16.29	17.70	1.384	0.03	0.088	0.122
	LTE Band 2-Ant 2	20M	QPSK	1	0	Left Side	10mm	Reduced	18900	1880	16.46	17.70	1.330	-0.05	0.025	0.033
	LTE Band 2-Ant 2	20M	QPSK	50	0	Left Side	10mm	Reduced	18900	1880	16.29	17.70	1.384	-0.09	0.024	0.033
	LTE Band 2-Ant 2	20M	QPSK	1	0	Right Side	10mm	Reduced	18900	1880	16.46	17.70	1.330	0.05	0.024	0.032
	LTE Band 2-Ant 2	20M	QPSK	50	0	Right Side	10mm	Reduced	18900	1880	16.29	17.70	1.384	0.01	0.022	0.030
	LTE Band 2-Ant 2	20M	QPSK	1	0	Top Side	10mm	Reduced	18900	1880	16.46	17.70	1.330	-0.05	0.280	0.373
	LTE Band 2-Ant 2	20M	QPSK	50	0	Top Side	10mm	Reduced	18900	1880	16.29	17.70	1.384	0.06	0.276	0.382
	LTE Band 2 C-Ant 2	20M	QPSK	1	0	Top Side	10mm	Reduced	18900+18702	1880+1860.2	16.26	17.70	1.393	0.03	0.241	0.336
	LTE Band 7-Ant 1	20M	QPSK	1	0	Front	10mm	Reduced	21100	2535	21.30	22.50	1.318	0.02	0.298	0.393
	LTE Band 7 C-Ant 1	20M	QPSK	1	0	Front	10mm	Reduced	21100+20902	2535+2515.2	21.11	22.50	1.377	0.05	0.264	0.364
	LTE Band 7-Ant 1	20M	QPSK	50	0	Front	10mm	Reduced	21100	2535	21.28	22.50	1.324	0.12	0.296	0.392
	LTE Band 7-Ant 1	20M	QPSK	1	0	Back	10mm	Reduced	21100	2535	21.30	22.50	1.318	-0.01	0.287	0.378
	LTE Band 7-Ant 1	20M	QPSK	50	0	Back	10mm	Reduced	21100	2535	21.28	22.50	1.324	0.03	0.296	0.392
	LTE Band 7-Ant 1	20M	QPSK	1	0	Left Side	10mm	Reduced	21100	2535	21.30	22.50	1.318	0.02	0.194	0.256
	LTE Band 7-Ant 1	20M	QPSK	50	0	Left Side	10mm	Reduced	21100	2535	21.28	22.50	1.324	-0.01	0.192	0.254
	LTE Band 7-Ant 1	20M	QPSK	1	0	Right Side	10mm	Reduced	21100	2535	21.30	22.50	1.318	0.15	0.021	0.028
	LTE Band 7-Ant 1	20M	QPSK	50	0	Right Side	10mm	Reduced	21100	2535	21.28	22.50	1.324	0.08	0.021	0.028
	LTE Band 7-Ant 1	20M	QPSK	1	0	Bottom Side	10mm	Reduced	21100	2535	21.30	22.50	1.318	0.07	0.255	0.336
	LTE Band 7-Ant 1	20M	QPSK	50	0	Bottom Side	10mm	Reduced	21100	2535	21.28	22.50	1.324	-0.09	0.252	0.334
	LTE Band 7-Ant 2	20M	QPSK	1	0	Front	10mm	Reduced	21100	2535	19.28	20.70	1.387	-0.01	0.195	0.270
	LTE Band 7-Ant 2	20M	QPSK	50	0	Front	10mm	Reduced	21100	2535	19.16	20.70	1.426	0.02	0.198	0.282
	LTE Band 7-Ant 2	20M	QPSK	1	0	Back	10mm	Reduced	21100	2535	19.28	20.70	1.387	0.05	0.154	0.214
	LTE Band 7-Ant 2	20M	QPSK	50	0	Back	10mm	Reduced	21100	2535	19.16	20.70	1.426	-0.05	0.152	0.217
	LTE Band 7-Ant 2	20M	QPSK	1	0	Left Side	10mm	Reduced	21100	2535	19.28	20.70	1.387	-0.02	0.180	0.250
	LTE Band 7-Ant 2	20M	QPSK	50	0	Left Side	10mm	Reduced	21100	2535	19.16	20.70	1.426	-0.01	0.181	0.258
	LTE Band 7-Ant 2	20M	QPSK	1	0	Right Side	10mm	Reduced	21100	2535	19.28	20.70	1.387	0.07	0.031	0.043
	LTE Band 7-Ant 2	20M	QPSK	50	0	Right Side	10mm	Reduced	21100	2535	19.16	20.70	1.426	0.01	0.030	0.043
	LTE Band 7-Ant 2	20M	QPSK	1	0	Top Side	10mm	Reduced	21100	2535	19.28	20.70	1.387	0.11	0.279	0.387
25	LTE Band 7-Ant 2	20M	QPSK	50	0	Top Side	10mm	Reduced	21100	2535	19.16	20.70	1.426	-0.06	0.283	0.403
	LTE Band 7 C-Ant 2	20M	QPSK	1	0	Top Side	10mm	Reduced	21100+20902	2535+2515.2	19.06	20.70	1.459	-0.03	0.271	0.395



<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 38-Ant 1	20M	QPSK	1	0	Front	10mm	Full	38000	2595	23.97	25.50	1.422	62.9	1.006	0.01	0.317	0.454
	LTE Band 38-Ant 1	20M	QPSK	50	0	Front	10mm	Full	38000	2595	22.84	24.50	1.466	62.9	1.006	0.04	0.262	0.386
26	LTE Band 38-Ant 1	20M	QPSK	1	0	Back	10mm	Full	38000	2595	23.97	25.50	1.422	62.9	1.006	-0.07	0.620	0.887
	LTE Band 38 C-Ant 1	20M	QPSK	1	0	Back	10mm	Full	37901+38099	2585.1+2604.9	23.92	25.50	1.439	62.9	1.006	0.02	0.606	0.877
	LTE Band 38-Ant 1	20M	QPSK	1	0	Back	10mm	Full	37850	2850	23.86	25.50	1.459	62.9	1.006	0.05	0.571	0.838
	LTE Band 38-Ant 1	20M	QPSK	1	0	Back	10mm	Full	38150	2610	23.86	25.50	1.459	62.9	1.006	0.09	0.599	0.879
	LTE Band 38-Ant 1	20M	QPSK	50	0	Back	10mm	Full	38000	2595	22.84	24.50	1.466	62.9	1.006	0.15	0.501	0.739
	LTE Band 38-Ant 1	20M	QPSK	100	0	Back	10mm	Full	38000	2595	22.88	24.50	1.452	62.9	1.006	0.08	0.480	0.701
	LTE Band 38-Ant 1	20M	QPSK	1	0	Left Side	10mm	Full	38000	2595	23.97	25.50	1.422	62.9	1.006	0.01	0.356	0.509
	LTE Band 38-Ant 1	20M	QPSK	50	0	Left Side	10mm	Full	38000	2595	22.84	24.50	1.466	62.9	1.006	-0.04	0.287	0.423
	LTE Band 38-Ant 1	20M	QPSK	1	0	Right Side	10mm	Full	38000	2595	23.97	25.50	1.422	62.9	1.006	-0.1	0.054	0.077
	LTE Band 38-Ant 1	20M	QPSK	50	0	Right Side	10mm	Full	38000	2595	22.84	24.50	1.466	62.9	1.006	0.08	0.044	0.065
	LTE Band 38-Ant 1	20M	QPSK	1	0	Bottom Side	10mm	Full	38000	2595	23.97	25.50	1.422	62.9	1.006	0.08	0.465	0.665
	LTE Band 38-Ant 1	20M	QPSK	50	0	Bottom Side	10mm	Full	38000	2595	22.84	24.50	1.466	62.9	1.006	0.04	0.363	0.535
	LTE Band 38-Ant 2	20M	QPSK	1	0	Front	10mm	Reduced	38000	2595	22.28	23.70	1.387	62.9	1.006	0.07	0.271	0.378
	LTE Band 38-Ant 2	20M	QPSK	50	0	Front	10mm	Reduced	38000	2595	22.24	23.70	1.400	62.9	1.006	0.15	0.284	0.400
	LTE Band 38-Ant 2	20M	QPSK	1	0	Back	10mm	Reduced	38000	2595	22.28	23.70	1.387	62.9	1.006	0.09	0.187	0.261
	LTE Band 38-Ant 2	20M	QPSK	50	0	Back	10mm	Reduced	38000	2595	22.24	23.70	1.400	62.9	1.006	0.01	0.196	0.276
	LTE Band 38-Ant 2	20M	QPSK	1	0	Left Side	10mm	Reduced	38000	2595	22.28	23.70	1.387	62.9	1.006	0.11	0.238	0.332
	LTE Band 38-Ant 2	20M	QPSK	50	0	Left Side	10mm	Reduced	38000	2595	22.24	23.70	1.400	62.9	1.006	0.05	0.249	0.351
	LTE Band 38-Ant 2	20M	QPSK	1	0	Right Side	10mm	Reduced	38000	2595	22.28	23.70	1.387	62.9	1.006	-0.02	0.035	0.049
	LTE Band 38-Ant 2	20M	QPSK	50	0	Right Side	10mm	Reduced	38000	2595	22.24	23.70	1.400	62.9	1.006	0.13	0.036	0.051
	LTE Band 38-Ant 2	20M	QPSK	1	0	Top Side	10mm	Reduced	38000	2595	22.28	23.70	1.387	62.9	1.006	0.14	0.368	0.513
	LTE Band 38 C-Ant 2	20M	QPSK	1	0	Top Side	10mm	Reduced	37901+38099	2585.1+2604.9	22.18	23.70	1.419	62.9	1.006	0.06	0.361	0.515
	LTE Band 38-Ant 2	20M	QPSK	50	0	Top Side	10mm	Reduced	38000	2595	22.24	23.70	1.400	62.9	1.006	0.1	0.389	0.548
	LTE Band 41-Ant 1	20M	QPSK	1	0	Front	10mm	Reduced	40640	2595	22.81	24.50	1.476	62.9	1.006	0.11	0.484	0.719
	LTE Band 41-Ant 1	20M	QPSK	50	0	Front	10mm	Reduced	40640	2595	22.75	24.50	1.496	62.9	1.006	0.1	0.483	0.727
	LTE Band 41-Ant 1	20M	QPSK	1	0	Back	10mm	Reduced	40640	2595	22.81	24.50	1.476	62.9	1.006	-0.05	0.524	0.778
27	LTE Band 41-Ant 1	20M	QPSK	50	0	Back	10mm	Reduced	40640	2595	22.75	24.50	1.496	62.9	1.006	0.01	0.529	0.796
	LTE Band 41-Ant 1	20M	QPSK	1	0	Left Side	10mm	Reduced	40640	2595	22.81	24.50	1.476	62.9	1.006	0.06	0.300	0.445
	LTE Band 41-Ant 1	20M	QPSK	50	0	Left Side	10mm	Reduced	40640	2595	22.75	24.50	1.496	62.9	1.006	-0.04	0.303	0.456
	LTE Band 41-Ant 1	20M	QPSK	1	0	Right Side	10mm	Reduced	40640	2595	22.81	24.50	1.476	62.9	1.006	0.14	0.048	0.071
	LTE Band 41-Ant 1	20M	QPSK	50	0	Right Side	10mm	Reduced	40640	2595	22.75	24.50	1.496	62.9	1.006	0.06	0.043	0.065
	LTE Band 41-Ant 1	20M	QPSK	1	0	Bottom Side	10mm	Reduced	40640	2595	22.81	24.50	1.476	62.9	1.006	0.18	0.355	0.527
	LTE Band 41-Ant 1	20M	QPSK	50	0	Bottom Side	10mm	Reduced	40640	2595	22.75	24.50	1.496	62.9	1.006	-0.02	0.371	0.558
	LTE Band 41-Ant 2	20M	QPSK	1	0	Front	10mm	Reduced	40640	2595	21.31	22.70	1.377	62.9	1.006	-0.04	0.211	0.292
	LTE Band 41-Ant 2	20M	QPSK	50	0	Front	10mm	Reduced	40640	2595	21.20	22.70	1.413	62.9	1.006	0.06	0.218	0.310
	LTE Band 41-Ant 2	20M	QPSK	1	0	Back	10mm	Reduced	40640	2595	21.31	22.70	1.377	62.9	1.006	0.03	0.145	0.201
	LTE Band 41-Ant 2	20M	QPSK	50	0	Back	10mm	Reduced	40640	2595	21.20	22.70	1.413	62.9	1.006	-0.01	0.150	0.213
	LTE Band 41-Ant 2	20M	QPSK	1	0	Left Side	10mm	Reduced	40640	2595	21.31	22.70	1.377	62.9	1.006	0.1	0.188	0.260
	LTE Band 41-Ant 2	20M	QPSK	50	0	Left Side	10mm	Reduced	40640	2595	21.20	22.70	1.413	62.9	1.006	0.16	0.193	0.274
	LTE Band 41-Ant 2	20M	QPSK	1	0	Right Side	10mm	Reduced	40640	2595	21.31	22.70	1.377	62.9	1.006	-0.05	0.028	0.039
	LTE Band 41-Ant 2	20M	QPSK	50	0	Right Side	10mm	Reduced	40640	2595	21.20	22.70	1.413	62.9	1.006	-0.01	0.028	0.040
	LTE Band 41-Ant 2	20M	QPSK	1	0	Top Side	10mm	Reduced	40640	2595	21.31	22.70	1.377	62.9	1.006	-0.02	0.292	0.405
	LTE Band 41-Ant 2	20M	QPSK	50	0	Top Side	10mm	Reduced	40640	2595	21.20	22.70	1.413	62.9	1.006	0.04	0.303	0.431



<WLAN2.4G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant3	Full	11	2462	17.35	19.00	1.462	100	1.000	0.03	0.184	0.269
28	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant3	Full	11	2462	17.35	19.00	1.462	100	1.000	-0.04	0.337	0.493
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant3	Full	11	2462	17.35	19.00	1.462	100	1.000	0.05	0.034	0.050
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	Ant3	Full	11	2462	17.35	19.00	1.462	100	1.000	0.07	0.240	0.351
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	Ant3	Full	11	2462	17.35	19.00	1.462	100	1.000	0.08	0.235	0.344

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN5.2GHz	802.11ac-VHT40 MCS0	Front	10mm	Ant3	Reduced	46	5230	12.49	14.00	1.416	96.32	1.038	-0.02	0.117	0.172
29	WLAN5.2GHz	802.11ac-VHT40 MCS0	Back	10mm	Ant3	Reduced	46	5230	12.49	14.00	1.416	96.32	1.038	-0.01	0.457	0.672
	WLAN5.2GHz	802.11ac-VHT40 MCS0	Left Side	10mm	Ant3	Reduced	46	5230	12.49	14.00	1.416	96.32	1.038	0.09	0.040	0.059
	WLAN5.2GHz	802.11ac-VHT40 MCS0	Right Side	10mm	Ant3	Reduced	46	5230	12.49	14.00	1.416	96.32	1.038	0.01	0.157	0.231
	WLAN5.2GHz	802.11ac-VHT40 MCS0	Top Side	10mm	Ant3	Reduced	46	5230	12.49	14.00	1.416	96.32	1.038	-0.06	0.443	0.651
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant3	Reduced	155	5775	11.38	13.00	1.452	92.77	1.078	0.07	0.107	0.168
30	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	10mm	Ant3	Reduced	155	5775	11.38	13.00	1.452	92.77	1.078	0.02	0.380	0.595
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Side	10mm	Ant3	Reduced	155	5775	11.38	13.00	1.452	92.77	1.078	0.01	0.025	0.039
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Side	10mm	Ant3	Reduced	155	5775	11.38	13.00	1.452	92.77	1.078	0.08	0.125	0.196
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Top Side	10mm	Ant3	Reduced	155	5775	11.38	13.00	1.452	92.77	1.078	-0.08	0.331	0.517

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	10mm	Ant3	0	2402	11.25	12.00	1.189	77.03	1.298	-0.01	0.016	0.025
31	Bluetooth	1Mbps	Back	10mm	Ant3	0	2402	11.25	12.00	1.189	77.03	1.298	0.06	0.019	0.029
	Bluetooth	1Mbps	Left Side	10mm	Ant3	0	2402	11.25	12.00	1.189	77.03	1.298	0.01	0.004	0.006
	Bluetooth	1Mbps	Right Side	10mm	Ant3	0	2402	11.25	12.00	1.189	77.03	1.298	0.01	0.014	0.022
	Bluetooth	1Mbps	Top Side	10mm	Ant3	0	2402	11.25	12.00	1.189	77.03	1.298	0.04	0.016	0.025



15.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM 850-Ant 1	GPRS 2 Tx slots	Front	15mm	Full	189	836.4	28.80	30.50	1.479	0.07	0.064	0.095
	GSM 850-Ant 1	GPRS 2 Tx slots	Back	15mm	Full	189	836.4	28.80	30.50	1.479	-0.02	0.085	0.126
	GSM 850-Ant 2	GPRS 2 Tx slots	Front	15mm	Full	189	836.4	29.54	31.00	1.400	0.04	0.103	0.144
32	GSM 850-Ant 2	GPRS 2 Tx slots	Back	15mm	Full	189	836.4	29.54	31.00	1.400	0.08	0.119	0.167
	GSM1900-Ant 1	GPRS 1 Tx slots	Front	15mm	Full	661	1880	29.70	31.00	1.349	-0.06	0.202	0.272
33	GSM1900-Ant 1	GPRS 1 Tx slots	Back	15mm	Full	661	1880	29.70	31.00	1.349	-0.02	0.276	0.372
	GSM1900-Ant 2	GPRS 1 Tx slots	Front	15mm	Full	661	1880	30.43	31.50	1.279	0.06	0.116	0.148
	GSM1900-Ant 2	GPRS 1 Tx slots	Back	15mm	Full	661	1880	30.43	31.50	1.279	0.01	0.119	0.152

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V-Ant 1	RMC 12.2Kbps	Front	15mm	Full	4182	836.4	23.62	25.00	1.374	0.11	0.131	0.180
34	WCDMA V-Ant 1	RMC 12.2Kbps	Back	15mm	Full	4182	836.4	23.62	25.00	1.374	0.02	0.172	0.236
	WCDMA V-Ant 2	RMC 12.2Kbps	Front	15mm	Full	4182	836.4	23.92	25.50	1.439	0.04	0.107	0.154
	WCDMA V-Ant 2	RMC 12.2Kbps	Back	15mm	Full	4182	836.4	23.92	25.50	1.439	0.02	0.144	0.207
	WCDMA IV-Ant 1	RMC 12.2Kbps	Front	15mm	Full	1413	1732.6	23.51	25.00	1.409	0.1	0.322	0.454
	WCDMA IV-Ant 1	RMC 12.2Kbps	Back	15mm	Full	1413	1732.6	23.51	25.00	1.409	-0.06	0.461	0.650
	WCDMA IV-Ant 2	RMC 12.2Kbps	Front	15mm	Full	1413	1732.6	23.81	25.20	1.377	0.11	0.361	0.497
35	WCDMA IV-Ant 2	RMC 12.2Kbps	Back	15mm	Full	1413	1732.6	23.81	25.20	1.377	0.07	0.504	0.694
	WCDMA IV-Ant 2	RMC 12.2Kbps	Back	15mm	Full	1312	1712.4	23.68	25.20	1.419	-0.05	0.478	0.678
	WCDMA IV-Ant 2	RMC 12.2Kbps	Back	15mm	Full	1513	1752.6	23.72	25.20	1.406	0.06	0.489	0.688
	WCDMA II-Ant 1	RMC 12.2Kbps	Front	15mm	Full	9400	1880	23.56	25.00	1.393	0.05	0.430	0.599
	WCDMA II-Ant 1	RMC 12.2Kbps	Back	15mm	Full	9400	1880	23.56	25.00	1.393	0.07	0.602	0.839
36	WCDMA II-Ant 1	RMC 12.2Kbps	Back	15mm	Full	9262	1852.4	23.55	25.00	1.396	-0.07	0.743	1.038
	WCDMA II-Ant 1	RMC 12.2Kbps	Back	15mm	Full	9538	1907.6	23.26	25.00	1.493	0.13	0.689	1.029
	WCDMA II-Ant 2	RMC 12.2Kbps	Front	15mm	Full	9400	1880	24.06	25.20	1.300	0.01	0.172	0.224
	WCDMA II-Ant 2	RMC 12.2Kbps	Back	15mm	Full	9400	1880	24.06	25.20	1.300	0.06	0.224	0.291





<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 5-Ant 1	10M	QPSK	1	0	Front	15mm	Full	20525	836.5	24.04	25.50	1.400	0.13	0.137	0.192
	LTE Band 5-Ant 1	10M	QPSK	25	0	Front	15mm	Full	20525	836.5	23.05	24.50	1.396	0.02	0.116	0.162
37	LTE Band 5-Ant 1	10M	QPSK	1	0	Back	15mm	Full	20525	836.5	24.04	25.50	1.400	0.04	0.179	0.251
	LTE Band 5-Ant 1	10M	QPSK	25	0	Back	15mm	Full	20525	836.5	23.05	24.50	1.396	0.08	0.153	0.214
	LTE Band 5-Ant 2	10M	QPSK	1	0	Front	15mm	Full	20525	836.5	24.12	25.70	1.439	-0.05	0.130	0.187
	LTE Band 5-Ant 2	10M	QPSK	25	0	Front	15mm	Full	20525	836.5	23.15	24.70	1.429	0.01	0.106	0.151
	LTE Band 5-Ant 2	10M	QPSK	1	0	Back	15mm	Full	20525	836.5	24.12	25.70	1.439	-0.06	0.110	0.158
	LTE Band 5-Ant 2	10M	QPSK	25	0	Back	15mm	Full	20525	836.5	23.15	24.70	1.429	0.04	0.087	0.124
	LTE Band 4-Ant 1	20M	QPSK	1	0	Front	15mm	Full	20175	1732.5	24.08	25.50	1.387	0.02	0.325	0.451
	LTE Band 4-Ant 1	20M	QPSK	50	0	Front	15mm	Full	20175	1732.5	22.89	24.50	1.449	0.07	0.271	0.393
	LTE Band 4-Ant 1	20M	QPSK	1	0	Back	15mm	Full	20175	1732.5	24.08	25.50	1.387	-0.04	0.476	0.660
	LTE Band 4-Ant 1	20M	QPSK	50	0	Back	15mm	Full	20175	1732.5	22.89	24.50	1.449	0.05	0.403	0.584
	LTE Band 4-Ant 2	20M	QPSK	1	0	Front	15mm	Full	20175	1732.5	24.18	25.70	1.419	-0.01	0.660	0.937
	LTE Band 4-Ant 2	20M	QPSK	50	0	Front	15mm	Full	20175	1732.5	23.09	24.70	1.449	0.04	0.558	0.808
	LTE Band 4-Ant 2	20M	QPSK	100	0	Front	15mm	Full	20175	1732.5	23.10	24.70	1.445	0.07	0.522	0.755
38	LTE Band 4-Ant 2	20M	QPSK	1	0	Back	15mm	Full	20175	1732.5	24.18	25.70	1.419	0.05	0.709	1.006
	LTE Band 4-Ant 2	20M	QPSK	50	0	Back	15mm	Full	20175	1732.5	23.09	24.70	1.449	0.14	0.584	0.846
	LTE Band 4-Ant 2	20M	QPSK	100	0	Back	15mm	Full	20175	1732.5	23.10	24.70	1.445	0.07	0.571	0.825
	LTE Band 2-Ant 1	20M	QPSK	1	0	Front	15mm	Full	18900	1880	23.96	25.50	1.426	0.04	0.485	0.691
	LTE Band 2-Ant 1	20M	QPSK	50	0	Front	15mm	Full	18900	1880	22.93	24.50	1.435	-0.07	0.401	0.576
39	LTE Band 2-Ant 1	20M	QPSK	1	0	Back	15mm	Full	18900	1880	23.96	25.50	1.426	-0.05	0.740	1.055
	LTE Band 2 C-Ant 1	20M	QPSK	1	0	Back	15mm	Full	18900+18702	1880+1860.2	23.78	25.50	1.486	0.04	0.701	1.042
	LTE Band 2-Ant 1	20M	QPSK	1	0	Back	15mm	Full	18700	1860	23.78	25.50	1.486	0.03	0.663	0.985
	LTE Band 2-Ant 1	20M	QPSK	1	0	Back	15mm	Full	19100	1900	23.68	25.50	1.521	0.05	0.646	0.982
	LTE Band 2-Ant 1	20M	QPSK	50	0	Back	15mm	Full	18900	1880	22.93	24.50	1.435	0.06	0.594	0.853
	LTE Band 2-Ant 1	20M	QPSK	50	0	Back	15mm	Full	18700	1860	22.84	24.50	1.466	-0.04	0.519	0.761
	LTE Band 2-Ant 1	20M	QPSK	50	0	Back	15mm	Full	19100	1900	22.75	24.50	1.496	0.08	0.509	0.762
	LTE Band 2-Ant 1	20M	QPSK	100	0	Back	15mm	Full	18900	1880	22.90	24.50	1.445	0.02	0.518	0.749
	LTE Band 2-Ant 2	20M	QPSK	1	0	Front	15mm	Full	18900	1880	24.30	25.70	1.380	0.11	0.278	0.384
	LTE Band 2 C-Ant 2	20M	QPSK	1	0	Front	15mm	Full	18900+18702	1880+1860.2	23.99	25.70	1.483	0.06	0.217	0.322
	LTE Band 2-Ant 2	20M	QPSK	50	0	Front	15mm	Full	18900	1880	23.27	24.70	1.390	0.14	0.216	0.300
	LTE Band 2-Ant 2	20M	QPSK	1	0	Back	15mm	Full	18900	1880	24.30	25.70	1.380	-0.09	0.257	0.355
	LTE Band 2-Ant 2	20M	QPSK	50	0	Back	15mm	Full	18900	1880	23.27	24.70	1.390	0.01	0.204	0.284
	LTE Band 7-Ant 1	20M	QPSK	1	0	Front	15mm	Full	21100	2535	23.87	25.50	1.455	0.02	0.370	0.539
	LTE Band 7-Ant 1	20M	QPSK	50	0	Front	15mm	Full	21100	2535	22.60	24.50	1.549	-0.01	0.295	0.457
40	LTE Band 7-Ant 1	20M	QPSK	1	0	Back	15mm	Full	21100	2535	23.87	25.50	1.455	-0.11	0.445	0.648
	LTE Band 7 C-Ant 1	20M	QPSK	1	0	Back	15mm	Full	21100+20902	2535+2515.2	23.10	25.50	1.738	0.03	0.369	0.641
	LTE Band 7-Ant 1	20M	QPSK	50	0	Back	15mm	Full	21100	2535	22.60	24.50	1.549	0.18	0.359	0.556
	LTE Band 7-Ant 2	20M	QPSK	1	0	Front	15mm	Full	21100	2535	24.25	25.70	1.396	-0.03	0.306	0.427
	LTE Band 7 C-Ant 2	20M	QPSK	1	0	Front	15mm	Full	21100+20902	2535+2515.2	24.06	25.70	1.459	0.05	0.266	0.388
	LTE Band 7-Ant 2	20M	QPSK	50	0	Front	15mm	Full	21100	2535	23.16	24.70	1.426	-0.15	0.248	0.354
	LTE Band 7-Ant 2	20M	QPSK	1	0	Back	15mm	Full	21100	2535	24.25	25.70	1.396	0.09	0.282	0.394
	LTE Band 7-Ant 2	20M	QPSK	50	0	Back	15mm	Full	21100	2535	23.16	24.70	1.426	0.08	0.219	0.312



<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 38-Ant 1	20M	QPSK	1	0	Front	15mm	Full	38000	2595	23.97	25.50	1.422	62.9	1.006	0.01	0.222	0.318
	LTE Band 38-Ant 1	20M	QPSK	50	0	Front	15mm	Full	38000	2595	22.84	24.50	1.466	62.9	1.006	0.05	0.182	0.268
41	LTE Band 38-Ant 1	20M	QPSK	1	0	Back	15mm	Full	38000	2595	23.97	25.50	1.422	62.9	1.006	0.02	0.305	0.436
	LTE Band 38 C-Ant 1	20M	QPSK	1	0	Back	15mm	Full	37901+38099	2585.1+2604.9	23.92	25.50	1.439	62.9	1.006	0.01	0.298	0.431
	LTE Band 38-Ant 1	20M	QPSK	50	0	Back	15mm	Full	38000	2595	22.84	24.50	1.466	62.9	1.006	-0.06	0.251	0.370
	LTE Band 38-Ant 2	20M	QPSK	1	0	Front	15mm	Full	38000	2595	24.25	25.70	1.396	62.9	1.006	-0.01	0.215	0.302
	LTE Band 38 C-Ant 2	20M	QPSK	1	0	Front	15mm	Full	37901+38099	2585.1+2604.9	24.25	25.70	1.396	62.9	1.006	-0.03	0.211	0.296
	LTE Band 38-Ant 2	20M	QPSK	50	0	Front	15mm	Full	38000	2595	23.24	24.70	1.400	62.9	1.006	0.14	0.178	0.251
	LTE Band 38-Ant 2	20M	QPSK	1	0	Back	15mm	Full	38000	2595	24.25	25.70	1.396	62.9	1.006	0.05	0.119	0.167
	LTE Band 38-Ant 2	20M	QPSK	50	0	Back	15mm	Full	38000	2595	23.24	24.70	1.400	62.9	1.006	-0.04	0.095	0.134
	LTE Band 41-Ant 1	20M	QPSK	1	0	Front	15mm	Full	40640	2595	23.98	25.50	1.419	62.9	1.006	0.11	0.218	0.311
	LTE Band 41-Ant 1	20M	QPSK	50	0	Front	15mm	Full	40640	2595	22.87	24.50	1.455	62.9	1.006	0.12	0.179	0.262
42	LTE Band 41-Ant 1	20M	QPSK	1	0	Back	15mm	Full	40640	2595	23.98	25.50	1.419	62.9	1.006	-0.09	0.290	0.414
	LTE Band 41-Ant 1	20M	QPSK	50	0	Back	15mm	Full	40640	2595	22.87	24.50	1.455	62.9	1.006	0.05	0.244	0.357
	LTE Band 41-Ant 2	20M	QPSK	1	0	Front	15mm	Full	40640	2595	24.26	25.70	1.393	62.9	1.006	-0.09	0.208	0.292
	LTE Band 41-Ant 2	20M	QPSK	50	0	Front	15mm	Full	40640	2595	23.30	24.70	1.380	62.9	1.006	0.01	0.172	0.239
	LTE Band 41-Ant 2	20M	QPSK	1	0	Back	15mm	Full	40640	2595	24.26	25.70	1.393	62.9	1.006	0.05	0.112	0.157
	LTE Band 41-Ant 2	20M	QPSK	50	0	Back	15mm	Full	40640	2595	23.30	24.70	1.380	62.9	1.006	-0.01	0.089	0.124

<WLAN2.4G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	15mm	Ant3	Full	11	2462	17.35	19.00	1.462	100	1.000	0.02	0.097	0.142
43	WLAN2.4GHz	802.11b 1Mbps	Back	15mm	Ant3	Full	11	2462	17.35	19.00	1.462	100	1.000	-0.06	0.128	0.187

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Front	15mm	Ant3	Reduced	54	5270	16.12	17.50	1.374	96.32	1.038	0.01	0.154	0.220
44	WLAN5.3GHz	802.11ac-VHT40 MCS0	Back	15mm	Ant3	Reduced	54	5270	16.12	17.50	1.374	96.32	1.038	-0.08	0.598	0.853
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Back	15mm	Ant3	Reduced	62	5310	13.00	14.50	1.413	96.32	1.038	0.07	0.316	0.463
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Back	15mm	Ant3	Reduced-Simultaneous	54	5270	14.03	15.50	1.403	96.32	1.038	0.02	0.350	0.510
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	15mm	Ant3	Reduced	122	5610	13.31	15.00	1.476	92.77	1.078	0.01	0.136	0.216
45	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	15mm	Ant3	Reduced	122	5610	13.31	15.00	1.476	92.77	1.078	0.03	0.405	0.644
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	15mm	Ant3	Reduced-Simultaneous	122	5610	12.01	13.50	1.409	92.77	1.078	-0.04	0.284	0.431
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	15mm	Ant3	Reduced	155	5775	11.38	13.00	1.452	92.77	1.078	0.01	0.128	0.200
46	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	15mm	Ant3	Reduced	155	5775	11.38	13.00	1.452	92.77	1.078	0.02	0.296	0.463

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	15mm	Ant3	0	2402	11.25	12.00	1.189	77.03	1.298	-0.04	0.008	0.012
47	Bluetooth	1Mbps	Back	15mm	Ant3	0	2402	11.25	12.00	1.189	77.03	1.298	-0.09	0.009	0.013



15.4 Product specific 10g SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
48	WCDMA II-Ant 1	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9400	1880	19.02	20.50	1.406	0.02	1.630	2.292
	WCDMA II-Ant 1	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9262	1852.4	19.01	20.50	1.409	-0.05	1.560	2.198
	WCDMA II-Ant 1	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9538	1907.6	18.92	20.50	1.439	0.07	1.590	2.288
	WCDMA II-Ant 1	RMC 12.2Kbps	Bottom Side	15mm	Full	9400	1880	23.56	25.00	1.393	0.03	0.227	0.316

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2-Ant 1	20M	QPSK	1	0	Bottom Side	0mm	Reduced	18900	1880	19.53	21.00	1.403	0.02	1.580	2.216
	LTE Band 2-Ant 1	20M	QPSK	1	0	Bottom Side	0mm	Reduced	18700	1860	19.41	21.00	1.442	0.03	1.510	2.178
	LTE Band 2-Ant 1	20M	QPSK	1	0	Bottom Side	0mm	Reduced	19100	1900	19.37	21.00	1.455	0.04	1.480	2.154
49	LTE Band 2-Ant 1	20M	QPSK	50	0	Bottom Side	0mm	Reduced	18900	1880	19.50	21.00	1.413	-0.01	1.670	2.359
	LTE Band 2 C-Ant 1	20M	QPSK	1	0	Bottom Side	0mm	Reduced	18900+18702	1880+1860.2	19.36	21.00	1.459	0.06	1.610	2.349
	LTE Band 2-Ant 1	20M	QPSK	50	0	Bottom Side	0mm	Reduced	18700	1860	19.41	21.00	1.442	-0.03	1.620	2.336
	LTE Band 2-Ant 1	20M	QPSK	50	0	Bottom Side	0mm	Reduced	19100	1900	19.39	21.00	1.449	0.08	1.610	2.333
	LTE Band 2-Ant 1	20M	QPSK	100	0	Bottom Side	0mm	Reduced	18900	1880	19.49	21.00	1.416	0.06	1.590	2.251
	LTE Band 2-Ant 1	20M	QPSK	1	0	Bottom Side	15mm	Full	18900	1880	23.96	25.50	1.426	-0.01	0.230	0.328

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Front	0mm	Ant3	Full	54	5270	16.12	17.50	1.374	96.32	1.038	0.08	0.568	0.810
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Back	0mm	Ant3	Full	54	5270	16.12	17.50	1.374	96.32	1.038	0.03	0.905	1.291
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Left Side	0mm	Ant3	Full	54	5270	16.12	17.50	1.374	96.32	1.038	0.02	0.079	0.113
	WLAN5.3GHz	802.11ac-VHT40 MCS0	Right Side	0mm	Ant3	Full	54	5270	16.12	17.50	1.374	96.32	1.038	-0.04	0.505	0.720
50	WLAN5.3GHz	802.11ac-VHT40 MCS0	Top Side	0mm	Ant3	Full	54	5270	16.12	17.50	1.374	96.32	1.038	0.02	1.400	1.997
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	0mm	Ant3	Reduced	122	5610	13.31	15.00	1.476	92.77	1.078	-0.09	0.293	0.465
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	0mm	Ant3	Reduced	122	5610	13.31	15.00	1.476	92.77	1.078	0.04	0.554	0.881
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Side	0mm	Ant3	Reduced	122	5610	13.31	15.00	1.476	92.77	1.078	0.03	0.043	0.068
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Side	0mm	Ant3	Reduced	122	5610	13.31	15.00	1.476	92.77	1.078	0.08	0.310	0.493
51	WLAN5.5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Ant3	Reduced	122	5610	13.31	15.00	1.476	92.77	1.078	0.09	0.772	1.228

### 16. Simultaneous Transmission Analysis

No.	Simultaneous Transmission Configurations	Portable Handset			
		Head	Body-worn	Hotspot	Product specific 10g SAR
1.	GSM Voice + WLAN2.4GHz	Yes	Yes		Yes
2.	GPRS/EDGE + WLAN2.4GHz	Yes	Yes	Yes	Yes
3.	WCDMA + WLAN2.4GHz	Yes	Yes	Yes	Yes
4.	LTE + WLAN2.4GHz	Yes	Yes	Yes	Yes
5.	GSM Voice + WLAN5.3/5.5GHz	Yes	Yes		Yes
6.	GPRS/EDGE + WLAN5.3/5.5GHz	Yes	Yes		Yes
7.	WCDMA + WLAN5.3/5.5GHz	Yes	Yes		Yes
8.	LTE + WLAN5.3/5.5GHz	Yes	Yes		Yes
9.	GSM Voice + WLAN5.2/5.8GHz	Yes	Yes		Yes
10.	GPRS/EDGE + WLAN5.2/5.8GHz	Yes	Yes	Yes	Yes
11.	WCDMA + WLAN5.2/5.8GHz	Yes	Yes	Yes	Yes
12.	LTE + WLAN5.2/5.8GHz	Yes	Yes	Yes	Yes
13.	GSM Voice + WLAN5.3/5.5GHz+Bluetooth	Yes	Yes		Yes
14.	GPRS/EDGE + WLAN5.3/5.5GHz+Bluetooth	Yes	Yes		Yes
15.	WCDMA + WLAN5.3/5.5GHz+Bluetooth	Yes	Yes		Yes
16.	LTE + WLAN5.3/5.5GHz+Bluetooth	Yes	Yes		Yes
17.	GSM Voice + WLAN5.2/5.8GHz+Bluetooth	Yes	Yes		Yes
18.	GPRS/EDGE + WLAN5.2/5.8GHz+Bluetooth	Yes	Yes	Yes	Yes
19.	WCDMA + WLAN5.2/5.8GHz+Bluetooth	Yes	Yes	Yes	Yes
20.	LTE + WLAN5.2/5.8GHz+Bluetooth	Yes	Yes	Yes	Yes
21.	WLAN5.2/5.8GHz+ Bluetooth	Yes	Yes	Yes	Yes
22.	WLAN5.3/5.5GHz + Bluetooth	Yes	Yes	Yes	Yes
23.	GSM Voice + Bluetooth	Yes	Yes		Yes
24.	GPRS/EDGE + Bluetooth	Yes	Yes	Yes	Yes
25.	WCDMA + Bluetooth	Yes	Yes	Yes	Yes
26.	LTE + Bluetooth	Yes	Yes	Yes	Yes

**General Note:**

- This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), and LTE supports VoLTE function.
- EUT will choose each GSM, WCDMA and LTE according to the network signal condition; therefore, they will not operate simultaneously at any moment.
- This device WLAN 2.4GHz supports hotspot operation and Bluetooth support tethering applications.
- This device 2.4GHz WLAN/ 5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WLAN Direct (GC/GO), and 5.3GHz / 5.5GHz supports WLAN Direct (GC only).
- EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment though they have independent antenna.
- WLAN 2.4GHz and Bluetooth share the same antenna so can't transmit simultaneously.
- According to the EUT character, WLAN 5GHz and Bluetooth can transmit simultaneously. WWAN+WLAN5GHz+Bluetooth can represent WWAN+WLAN5GHz or WWAN+ Bluetooth, So no need to do co-located analysis separately.
- Chose the worst zoom scan SAR of WLAN correspondingly for co-located with WWAN analysis.
- The reported SAR summation is calculated based on the same configuration and test position
- Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
  - 1g Scalar SAR summation < 1.6W/kg and 10g Scalar SAR summation < 4.0W/kg.
  - $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$ , and the peak separation distance is determined from the square root of  $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$ , where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
  - If  $SPLSR \leq 0.04$  for 1g SAR and  $SPLSR \leq 0.10$  for 10g SAR, simultaneously transmission SAR measurement is not necessary.
  - Simultaneously transmission SAR measurement, and the reported multi-band 1g SAR < 1.6W/kg and 10g SAR < 4.0W/kg.



16.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN Ant 3	5GHz WLAN Ant 3	Bluetooth Ant 3		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM 850-Ant 1	Right Cheek	0.104	0.361	0.373	0.062	0.47	0.54
		Right Tilted	0.055	0.418	0.473	0.068	0.47	0.60
		Left Cheek	0.084	0.882	0.489	0.113	0.97	0.69
		Left Tilted	0.046	0.877	0.676	0.111	0.92	0.83
	GSM1900-Ant 1	Right Cheek	0.032	0.361	0.373	0.062	0.39	0.47
		Right Tilted	0.034	0.418	0.473	0.068	0.45	0.58
		Left Cheek	0.039	0.882	0.489	0.113	0.92	0.64
		Left Tilted	0.040	0.877	0.676	0.111	0.92	0.83
WCDMA	WCDMA II-Ant 1	Right Cheek	0.124	0.361	0.373	0.062	0.49	0.56
		Right Tilted	0.110	0.418	0.473	0.068	0.53	0.65
		Left Cheek	0.111	0.882	0.489	0.113	0.99	0.71
		Left Tilted	0.149	0.877	0.676	0.111	1.03	0.94
	WCDMA IV-Ant 1	Right Cheek	0.317	0.361	0.373	0.062	0.68	0.75
		Right Tilted	0.251	0.418	0.473	0.068	0.67	0.79
		Left Cheek	0.227	0.882	0.489	0.113	1.11	0.83
		Left Tilted	0.287	0.877	0.676	0.111	1.16	1.07
	WCDMA V-Ant 1	Right Cheek	0.198	0.361	0.373	0.062	0.56	0.63
		Right Tilted	0.100	0.418	0.473	0.068	0.52	0.64
		Left Cheek	0.153	0.882	0.489	0.113	1.04	0.76
		Left Tilted	0.085	0.877	0.676	0.111	0.96	0.87
LTE	LTE Band 2-Ant 1	Right Cheek	0.134	0.361	0.373	0.062	0.50	0.57
		Right Tilted	0.117	0.418	0.473	0.068	0.54	0.66
		Left Cheek	0.097	0.882	0.489	0.113	0.98	0.70
		Left Tilted	0.115	0.877	0.676	0.111	0.99	0.90
	LTE Band 4-Ant 1	Right Cheek	0.273	0.361	0.373	0.062	0.63	0.71
		Right Tilted	0.280	0.418	0.473	0.068	0.70	0.82
		Left Cheek	0.165	0.882	0.489	0.113	1.05	0.77
		Left Tilted	0.201	0.877	0.676	0.111	1.08	0.99
	LTE Band 5-Ant 1	Right Cheek	0.207	0.361	0.373	0.062	0.57	0.64
		Right Tilted	0.091	0.418	0.473	0.068	0.51	0.63
		Left Cheek	0.155	0.882	0.489	0.113	1.04	0.76
		Left Tilted	0.083	0.877	0.676	0.111	0.96	0.87
	LTE Band 7-Ant 1	Right Cheek	0.297	0.361	0.373	0.062	0.66	0.73
		Right Tilted	0.306	0.418	0.473	0.068	0.72	0.85
		Left Cheek	0.597	0.882	0.489	0.113	1.48	1.20
		Left Tilted	0.285	0.877	0.676	0.111	1.16	1.07
	LTE Band 38-Ant 1	Right Cheek	0.167	0.361	0.373	0.062	0.53	0.60
		Right Tilted	0.153	0.418	0.473	0.068	0.57	0.69
		Left Cheek	0.369	0.882	0.489	0.113	1.25	0.97
		Left Tilted	0.165	0.877	0.676	0.111	1.04	0.95
LTE Band 41-Ant 1	Right Cheek	0.164	0.361	0.373	0.062	0.53	0.60	
	Right Tilted	0.146	0.418	0.473	0.068	0.56	0.69	
	Left Cheek	0.353	0.882	0.489	0.113	1.24	0.96	
	Left Tilted	0.160	0.877	0.676	0.111	1.04	0.95	



WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN Ant 3	5GHz WLAN Ant 3	Bluetooth Ant 3		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM 850-Ant 2	Right Cheek	0.409	0.361	0.373	0.062	0.77	0.84
		Right Tilted	0.292	0.418	0.473	0.068	0.71	0.83
		Left Cheek	0.369	0.882	0.489	0.113	1.25	0.97
		Left Tilted	0.268	0.877	0.676	0.111	1.15	1.06
	GSM1900-Ant 2	Right Cheek	0.340	0.361	0.373	0.062	0.70	0.78
		Right Tilted	0.528	0.418	0.473	0.068	0.95	1.07
		Left Cheek	0.340	0.882	0.489	0.113	1.22	0.94
		Left Tilted	0.390	0.877	0.676	0.111	1.27	1.18
WCDMA	WCDMA II-Ant 2	Right Cheek	0.418	0.361	0.373	0.062	0.78	0.85
		Right Tilted	0.560	0.418	0.473	0.068	0.98	1.10
		Left Cheek	0.358	0.882	0.489	0.113	1.24	0.96
		Left Tilted	0.494	0.877	0.676	0.111	1.37	1.28
	WCDMA IV-Ant 2	Right Cheek	0.577	0.361	0.373	0.062	0.94	1.01
		Right Tilted	0.646	0.418	0.473	0.068	1.06	1.19
		Left Cheek	0.380	0.882	0.489	0.113	1.26	0.98
		Left Tilted	0.556	0.877	0.676	0.111	1.43	1.34
	WCDMA V-Ant 2	Right Cheek	0.640	0.361	0.373	0.062	1.00	1.08
		Right Tilted	0.507	0.418	0.473	0.068	0.93	1.05
		Left Cheek	0.577	0.882	0.489	0.113	1.46	1.18
		Left Tilted	0.491	0.877	0.676	0.111	1.37	1.28
LTE	LTE Band 2-Ant 2	Right Cheek	0.472	0.361	0.373	0.062	0.83	0.91
		Right Tilted	0.601	0.418	0.473	0.068	1.02	1.14
		Left Cheek	0.378	0.882	0.489	0.113	1.26	0.98
		Left Tilted	0.494	0.877	0.676	0.111	1.37	1.28
	LTE Band 4-Ant 2	Right Cheek	0.575	0.361	0.373	0.062	0.94	1.01
		Right Tilted	0.646	0.418	0.473	0.068	1.06	1.19
		Left Cheek	0.323	0.882	0.489	0.113	1.21	0.93
		Left Tilted	0.420	0.877	0.676	0.111	1.30	1.21
	LTE Band 5-Ant 2	Right Cheek	0.668	0.361	0.373	0.062	1.03	1.10
		Right Tilted	0.462	0.418	0.473	0.068	0.88	1.00
		Left Cheek	0.498	0.882	0.489	0.113	1.38	1.10
		Left Tilted	0.405	0.877	0.676	0.111	1.28	1.19
	LTE Band 7-Ant 2	Right Cheek	1.087	0.361	0.373	0.062	1.45	1.52
		Right Tilted	1.012	0.418	0.473	0.068	1.43	1.55
		Left Cheek	0.467	0.882	0.489	0.113	1.35	1.07
		Left Tilted	0.617	0.877	0.676	0.111	1.49	1.40
	LTE Band 38-Ant 2	Right Cheek	1.063	0.361	0.373	0.062	1.42	1.50
		Right Tilted	0.907	0.418	0.473	0.068	1.33	1.45
		Left Cheek	0.479	0.882	0.489	0.113	1.36	1.08
		Left Tilted	0.661	0.877	0.676	0.111	1.54	1.45
LTE Band 41-Ant 2	Right Cheek	1.069	0.361	0.373	0.062	1.43	1.50	
	Right Tilted	1.007	0.418	0.473	0.068	1.43	1.55	
	Left Cheek	0.486	0.882	0.489	0.113	1.37	1.09	
	Left Tilted	0.666	0.877	0.676	0.111	1.54	1.45	



16.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN Ant 3	5GHz WLAN Ant 3	Bluetooth Ant 3		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM 850-Ant 1	Front	0.102	0.269	0.172	0.025	0.37	0.30
		Back	0.081	0.493	0.672	0.029	0.57	0.78
		Left side	0.033	0.050	0.059	0.006	0.08	0.10
		Right side	0.065	0.351	0.231	0.022	0.42	0.32
		Top side		0.344	0.651	0.025	0.34	0.68
		Bottom side	0.071				0.07	0.07
	GSM1900-Ant 1	Front	0.285	0.269	0.172	0.025	0.55	0.48
		Back	0.245	0.493	0.672	0.029	0.74	0.95
		Left side	0.043	0.050	0.059	0.006	0.09	0.11
		Right side	0.017	0.351	0.231	0.022	0.37	0.27
		Top side		0.344	0.651	0.025	0.34	0.68
		Bottom side	0.475				0.48	0.48
WCDMA	WCDMA II-Ant 1	Front	0.277	0.269	0.172	0.025	0.55	0.47
		Back	0.399	0.493	0.672	0.029	0.89	1.10
		Left side	0.038	0.050	0.059	0.006	0.09	0.10
		Right side	0.042	0.351	0.231	0.022	0.39	0.30
		Top side		0.344	0.651	0.025	0.34	0.68
		Bottom side	1.020				1.02	1.02
	WCDMA IV-Ant 1	Front	0.321	0.269	0.172	0.025	0.59	0.52
		Back	0.450	0.493	0.672	0.029	0.94	1.15
		Left side	0.076	0.050	0.059	0.006	0.13	0.14
		Right side	0.128	0.351	0.231	0.022	0.48	0.38
		Top side		0.344	0.651	0.025	0.34	0.68
		Bottom side	0.614				0.61	0.61
	WCDMA V-Ant 1	Front	0.217	0.269	0.172	0.025	0.49	0.41
		Back	0.308	0.493	0.672	0.029	0.80	1.01
		Left side	0.118	0.050	0.059	0.006	0.17	0.18
		Right side	0.238	0.351	0.231	0.022	0.59	0.49
		Top side		0.344	0.651	0.025	0.34	0.68
		Bottom side	0.319				0.32	0.32
LTE	LTE Band 2-Ant 1	Front	0.400	0.269	0.172	0.025	0.67	0.60
		Back	0.367	0.493	0.672	0.029	0.86	1.07
		Left side	0.045	0.050	0.059	0.006	0.10	0.11
		Right side	0.023	0.351	0.231	0.022	0.37	0.28
		Top side		0.344	0.651	0.025	0.34	0.68
		Bottom side	0.742				0.74	0.74
	LTE Band 4-Ant 1	Front	0.523	0.269	0.172	0.025	0.79	0.72
		Back	0.551	0.493	0.672	0.029	1.04	1.25
		Left side	0.130	0.050	0.059	0.006	0.18	0.20
		Right side	0.134	0.351	0.231	0.022	0.49	0.39
		Top side		0.344	0.651	0.025	0.34	0.68
		Bottom side	0.640				0.64	0.64
	LTE Band 5-Ant 1	Front	0.220	0.269	0.172	0.025	0.49	0.42



		Back	0.213	0.493	0.672	0.029	0.71	0.91
		Left side	0.081	0.050	0.059	0.006	0.13	0.15
		Right side	0.193	0.351	0.231	0.022	0.54	0.45
		Top side		0.344	0.651	0.025	0.34	0.68
		Bottom side	0.182				0.18	0.18
	LTE Band 7-Ant 1	Front	0.393	0.269	0.172	0.025	0.66	0.59
		Back	0.392	0.493	0.672	0.029	0.89	1.09
		Left side	0.256	0.050	0.059	0.006	0.31	0.32
		Right side	0.028	0.351	0.231	0.022	0.38	0.28
		Top side		0.344	0.651	0.025	0.34	0.68
	LTE Band 38-Ant 1	Bottom side	0.336				0.34	0.34
		Front	0.454	0.269	0.172	0.025	0.72	0.65
		Back	0.887	0.493	0.672	0.029	1.38	1.59
		Left side	0.509	0.050	0.059	0.006	0.56	0.57
		Right side	0.077	0.351	0.231	0.022	0.43	0.33
	LTE Band 41-Ant 1	Top side		0.344	0.651	0.025	0.34	0.68
		Bottom side	0.665				0.67	0.67
		Front	0.727	0.269	0.172	0.025	1.00	0.92
		Back	0.796	0.493	0.672	0.029	1.29	1.50
		Left side	0.456	0.050	0.059	0.006	0.51	0.52
	LTE Band 41-Ant 1	Right side	0.071	0.351	0.231	0.022	0.42	0.32
Top side			0.344	0.651	0.025	0.34	0.68	
Bottom side		0.558				0.56	0.56	





WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN Ant 3	5GHz WLAN Ant 3	Bluetooth Ant 3		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM 850-Ant 2	Front	0.136	0.269	0.172	0.025	0.41	0.33
		Back	0.145	0.493	0.672	0.029	0.64	0.85
		Left side	0.084	0.050	0.059	0.006	0.13	0.15
		Right side	0.113	0.351	0.231	0.022	0.46	0.37
		Top side	0.113	0.344	0.651	0.025	0.46	0.79
	GSM1900-Ant 2	Front	0.094	0.269	0.172	0.025	0.36	0.29
		Back	0.087	0.493	0.672	0.029	0.58	0.79
		Left side	0.032	0.050	0.059	0.006	0.08	0.10
		Right side	0.024	0.351	0.231	0.022	0.38	0.28
		Top side	0.315	0.344	0.651	0.025	0.66	0.99
WCDMA	WCDMA II-Ant 2	Front	0.101	0.269	0.172	0.025	0.37	0.30
		Back	0.157	0.493	0.672	0.029	0.65	0.86
		Left side	0.022	0.050	0.059	0.006	0.07	0.09
		Right side	0.027	0.351	0.231	0.022	0.38	0.28
		Top side	0.362	0.344	0.651	0.025	0.71	1.04
	WCDMA IV-Ant 2	Front	0.130	0.269	0.172	0.025	0.40	0.33
		Back	0.206	0.493	0.672	0.029	0.70	0.91
		Left side	0.024	0.050	0.059	0.006	0.07	0.09
		Right side	0.012	0.351	0.231	0.022	0.36	0.27
		Top side	0.354	0.344	0.651	0.025	0.70	1.03
	WCDMA V-Ant 2	Front	0.291	0.269	0.172	0.025	0.56	0.49
		Back	0.477	0.493	0.672	0.029	0.97	1.18
		Left side	0.186	0.050	0.059	0.006	0.24	0.25
		Right side	0.223	0.351	0.231	0.022	0.57	0.48
		Top side	0.246	0.344	0.651	0.025	0.59	0.92
LTE	LTE Band 2-Ant 2	Front	0.127	0.269	0.172	0.025	0.40	0.32
		Back	0.124	0.493	0.672	0.029	0.62	0.83
		Left side	0.033	0.050	0.059	0.006	0.08	0.10
		Right side	0.032	0.351	0.231	0.022	0.38	0.29
		Top side	0.382	0.344	0.651	0.025	0.73	1.06
	LTE Band 4-Ant 2	Front	0.159	0.269	0.172	0.025	0.43	0.36
		Back	0.160	0.493	0.672	0.029	0.65	0.86
		Left side	0.018	0.050	0.059	0.006	0.07	0.08
		Right side	0.013	0.351	0.231	0.022	0.36	0.27
		Top side	0.378	0.344	0.651	0.025	0.72	1.05
	LTE Band 5-Ant 2	Front	0.249	0.269	0.172	0.025	0.52	0.45
		Back	0.270	0.493	0.672	0.029	0.76	0.97
		Left side	0.156	0.050	0.059	0.006	0.21	0.22
		Right side	0.149	0.351	0.231	0.022	0.50	0.40
		Top side	0.218	0.344	0.651	0.025	0.56	0.89
	LTE Band 7-Ant 2	Front	0.282	0.269	0.172	0.025	0.55	0.48
		Back	0.217	0.493	0.672	0.029	0.71	0.92
		Left side	0.258	0.050	0.059	0.006	0.31	0.32
		Right side	0.043	0.351	0.231	0.022	0.39	0.30
		Top side	0.403	0.344	0.651	0.025	0.75	1.08



	LTE Band 38-Ant 2	Front	0.400	0.269	0.172	0.025	0.67	0.60
		Back	0.276	0.493	0.672	0.029	0.77	0.98
		Left side	0.351	0.050	0.059	0.006	0.40	0.42
		Right side	0.051	0.351	0.231	0.022	0.40	0.30
		Top side	0.548	0.344	0.651	0.025	0.89	1.22
	LTE Band 41-Ant 2	Front	0.310	0.269	0.172	0.025	0.58	0.51
		Back	0.213	0.493	0.672	0.029	0.71	0.91
		Left side	0.274	0.050	0.059	0.006	0.32	0.34
		Right side	0.040	0.351	0.231	0.022	0.39	0.29
		Top side	0.431	0.344	0.651	0.025	0.78	1.11



16.3 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN Ant 3	5GHz WLAN Ant 3	Bluetooth Ant 3		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM 850-Ant 1	Front	0.095	0.142	0.220	0.012	0.24	0.33
		Back	0.126	0.187	0.510	0.013	0.31	0.65
	GSM1900-Ant 1	Front	0.272	0.142	0.220	0.012	0.41	0.50
		Back	0.372	0.187	0.510	0.013	0.56	0.90
WCDMA	WCDMA II-Ant 1	Front	0.599	0.142	0.220	0.012	0.74	0.83
		Back	1.038	0.187	0.510	0.013	1.23	1.56
	WCDMA IV-Ant 1	Front	0.454	0.142	0.220	0.012	0.60	0.69
		Back	0.650	0.187	0.510	0.013	0.84	1.17
	WCDMA V-Ant 1	Front	0.180	0.142	0.220	0.012	0.32	0.41
		Back	0.236	0.187	0.510	0.013	0.42	0.76
LTE	LTE Band 2-Ant 1	Front	0.691	0.142	0.220	0.012	0.83	0.92
		Back	1.055	0.187	0.510	0.013	1.24	1.58
	LTE Band 4-Ant 1	Front	0.451	0.142	0.220	0.012	0.59	0.68
		Back	0.660	0.187	0.510	0.013	0.850	1.18
	LTE Band 5-Ant 1	Front	0.192	0.142	0.220	0.012	0.33	0.42
		Back	0.251	0.187	0.510	0.013	0.44	0.77
	LTE Band 7-Ant 1	Front	0.539	0.142	0.220	0.012	0.68	0.77
		Back	0.648	0.187	0.510	0.013	0.84	1.17
	LTE Band 38-Ant 1	Front	0.318	0.142	0.220	0.012	0.46	0.55
		Back	0.436	0.187	0.510	0.013	0.62	0.96
	LTE Band 41-Ant 1	Front	0.311	0.142	0.220	0.012	0.45	0.54
		Back	0.414	0.187	0.510	0.013	0.60	0.94



WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN Ant 3	5GHz WLAN Ant 3	Bluetooth Ant 3		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM 850-Ant 2	Front	0.144	0.142	0.220	0.012	0.29	0.38
		Back	0.167	0.187	0.510	0.013	0.35	0.69
	GSM1900-Ant 2	Front	0.148	0.142	0.220	0.012	0.29	0.38
		Back	0.152	0.187	0.510	0.013	0.34	0.68
WCDMA	WCDMA II-Ant 2	Front	0.224	0.142	0.220	0.012	0.37	0.46
		Back	0.291	0.187	0.510	0.013	0.48	0.81
	WCDMA IV-Ant 2	Front	0.497	0.142	0.220	0.012	0.64	0.73
		Back	0.694	0.187	0.510	0.013	0.88	1.22
	WCDMA V-Ant 2	Front	0.154	0.142	0.220	0.012	0.30	0.39
		Back	0.207	0.187	0.510	0.013	0.39	0.73
LTE	LTE Band 2-Ant 2	Front	0.384	0.142	0.220	0.012	0.53	0.62
		Back	0.355	0.187	0.510	0.013	0.54	0.88
	LTE Band 4-Ant 2	Front	0.937	0.142	0.220	0.012	1.08	1.17
		Back	1.006	0.187	0.510	0.013	1.19	1.53
	LTE Band 5-Ant 2	Front	0.187	0.142	0.220	0.012	0.33	0.42
		Back	0.158	0.187	0.510	0.013	0.35	0.68
	LTE Band 7-Ant 2	Front	0.427	0.142	0.220	0.012	0.57	0.66
		Back	0.394	0.187	0.510	0.013	0.58	0.92
	LTE Band 38-Ant 2	Front	0.302	0.142	0.220	0.012	0.44	0.53
		Back	0.167	0.187	0.510	0.013	0.35	0.69
	LTE Band 41-Ant 2	Front	0.292	0.142	0.220	0.012	0.43	0.52
		Back	0.157	0.187	0.510	0.013	0.34	0.68



**16.4 Product specific 10g SAR Exposure Conditions**

WWAN Band		Exposure Position	1	3	1+3 Summed 10g SAR (W/kg)
			WWAN	5GHz WLAN Ant 3	
			10g SAR (W/kg)	10g SAR (W/kg)	
WCDMA	WCDMA II-Ant 1	Front		0.810	0.81
		Back		1.291	1.29
		Left side		0.113	0.11
		Right side		0.720	0.72
		Top side		1.997	2.00
		Bottom side	2.292		2.29
LTE	LTE Band 2-Ant 1	Front		0.810	0.81
		Back		1.291	1.29
		Left side		0.113	0.11
		Right side		0.720	0.72
		Top side		1.997	2.00
		Bottom side	2.359		<b>2.36</b>

**Remark:**

1. For Bluetooth Product specific 10g stand-alone SAR is not required for a transmitter or antenna, due to 1g hotspot SAR is <1.2W/kg.
2. If SPLSR ≤ 0.10 for 10g SAR, simultaneously transmission SAR measurement is not necessary.

**Test Engineer :** Nick Hu, Hank Chang, Yuankai Kong



## **17. Uncertainty Assessment**

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is  $< 1.5$  W/kg and the measured 10-g SAR within a frequency band is  $< 3.75$  W/kg. The expanded SAR measurement uncertainty must be  $\leq 30\%$ , for a confidence interval of  $k = 2$ . If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.



## 18. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [6] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.
- [7] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [8] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [9] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [10] FCC KDB 616217 D04 v01r02, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", Oct 2015
- [11] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [12] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [13] FCC KDB 941225 D05A v01r02, "Rel. 10 LTE SAR Test Guidance and KDB Inquiries", Oct 2015
- [14] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.

-----THE END-----



## **Appendix A. Plots of System Performance Check**

The plots are shown as follows.



### System Check\_Head\_835MHz

**DUT: D835V2 - SN:4d151**

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL\_835 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.942 \text{ S/m}$ ;  $\epsilon_r = 41.096$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(10.05, 10.05, 10.05); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 3.11 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 52.32 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 3.68 W/kg

**SAR(1 g) = 2.43 W/kg; SAR(10 g) = 1.58 W/kg**

Maximum value of SAR (measured) = 3.10 W/kg



0 dB = 3.10 W/kg = 4.91 dBW/kg

### System Check\_Head\_1750MHz

**DUT: D1750V2 - SN:1090**


Communication System: UID 0, CW (0); Frequency: 1750 MHz; Duty Cycle: 1:1  
Medium: HSL\_1750 Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.351$  S/m;  $\epsilon_r = 40.38$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.2 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(8.41, 8.41, 8.41); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 13.8 W/kg

**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 103.3 V/m; Power Drift = -0.05 dB  
Peak SAR (extrapolated) = 16.7 W/kg  
**SAR(1 g) = 8.86 W/kg; SAR(10 g) = 4.72 W/kg**  
Maximum value of SAR (measured) = 13.9 W/kg



0 dB = 13.9 W/kg = 11.43 dBW/kg

### System Check\_Head\_1900MHz

**DUT: D1900V2 - SN:5d170**

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL\_1900 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.459$  S/m;  $\epsilon_r = 40.007$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(8.22, 8.22, 8.22); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 15.8 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 104.0 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 19.1 W/kg

**SAR(1 g) = 10.1 W/kg; SAR(10 g) = 5.27 W/kg**

Maximum value of SAR (measured) = 15.9 W/kg



0 dB = 15.9 W/kg = 12.01 dBW/kg

### System Check\_Head\_2450MHz

**DUT: D2450V2 - SN:908**


Communication System: UID 0, CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1  
Medium: HSL\_2450 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.853$  S/m;  $\epsilon_r = 39.08$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(7.57, 7.57, 7.57); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=250mW/Area Scan (71x71x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 20.4 W/kg

**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 89.53 V/m; Power Drift = -0.06 dB  
Peak SAR (extrapolated) = 26.6 W/kg  
**SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.92 W/kg**  
Maximum value of SAR (measured) = 19.7 W/kg



0 dB = 19.7 W/kg = 12.94 dBW/kg

### System Check\_Head\_2600MHz

**DUT: D2600V2 - SN:1070**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: HSL\_2600 Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.981$  S/m;  $\epsilon_r = 39.077$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(7.31, 7.31, 7.31); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=250mW/Area Scan (71x71x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 23.7 W/kg


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 111.2 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 29.4 W/kg

**SAR(1 g) = 13.9 W/kg; SAR(10 g) = 6.32 W/kg**

Maximum value of SAR (measured) = 23.7 W/kg



0 dB = 23.7 W/kg = 13.75 dBW/kg

### System Check\_Head\_5250MHz

**DUT: D5GHzV2 - SN:1113**


Communication System: UID 0, CW (0); Frequency: 5250 MHz; Duty Cycle: 1:1  
Medium: HSL\_5250 Medium parameters used:  $f = 5250$  MHz;  $\sigma = 4.564$  S/m;  $\epsilon_r = 35.431$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.2 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(5.24, 5.24, 5.24); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=100mW/Area Scan (71x71x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
Maximum value of SAR (interpolated) = 17.2 W/kg

**Pin=100mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 67.81 V/m; Power Drift = -0.03 dB  
Peak SAR (extrapolated) = 28.3 W/kg  
**SAR(1 g) = 7.53 W/kg; SAR(10 g) = 2.2 W/kg**  
Maximum value of SAR (measured) = 18.5 W/kg



0 dB = 18.5 W/kg = 12.67 dBW/kg

### System Check\_Head\_5600MHz

**DUT: D5GHzV2 - SN:1113**

Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: HSL\_5600 Medium parameters used:  $f = 5600$  MHz;  $\sigma = 4.946$  S/m;  $\epsilon_r = 34.825$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(4.65, 4.65, 4.65); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=100mW/Area Scan (71x71x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 20.6 W/kg


**Pin=100mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 70.33 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 34.7 W/kg

**SAR(1 g) = 8.42 W/kg; SAR(10 g) = 2.43 W/kg**

Maximum value of SAR (measured) = 21.5 W/kg



0 dB = 21.5 W/kg = 13.32 dBW/kg

### System Check\_Head\_5750MHz

**DUT: D5GHzV2 - SN:1113**


Communication System: UID 0, CW (0); Frequency: 5750 MHz; Duty Cycle: 1:1  
Medium: HSL\_5750 Medium parameters used:  $f = 5750$  MHz;  $\sigma = 5.128$  S/m;  $\epsilon_r = 34.55$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(4.69, 4.69, 4.69); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=100mW/Area Scan (71x71x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
Maximum value of SAR (interpolated) = 18.4 W/kg

**Pin=100mW/Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 39.34 V/m; Power Drift = 0.03 dB  
Peak SAR (extrapolated) = 31.7 W/kg  
**SAR(1 g) = 7.57 W/kg; SAR(10 g) = 2.16 W/kg**  
Maximum value of SAR (measured) = 17.6 W/kg



0 dB = 17.6 W/kg = 12.46 dBW/kg



### System Check\_Head\_835MHz

**DUT: D835V2 - SN:4d151**


Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1  
Medium: HSL\_850 Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.943 \text{ S/m}$ ;  $\epsilon_r = 41.901$ ;  $\rho = 1000 \text{ kg/m}^3$   
Ambient Temperature :  $23.1 \text{ }^\circ\text{C}$ ; Liquid Temperature :  $22.7 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(10.05, 10.05, 10.05); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
Maximum value of SAR (interpolated) =  $3.11 \text{ W/kg}$

**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
Reference Value =  $52.32 \text{ V/m}$ ; Power Drift =  $0.03 \text{ dB}$   
Peak SAR (extrapolated) =  $3.68 \text{ W/kg}$   
**SAR(1 g) =  $2.41 \text{ W/kg}$ ; SAR(10 g) =  $1.45 \text{ W/kg}$**   
Maximum value of SAR (measured) =  $3.10 \text{ W/kg}$



0 dB =  $3.10 \text{ W/kg} = 4.91 \text{ dBW/kg}$

### System Check\_Head\_1750MHz

**DUT: D1750V2 - SN:1090**

Communication System: UID 0, CW (0); Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: HSL\_1750 Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.363$  S/m;  $\epsilon_r = 40.838$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(8.41, 8.41, 8.41); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 14.0 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 103.3 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 16.8 W/kg

**SAR(1 g) = 8.94 W/kg; SAR(10 g) = 4.76 W/kg**

Maximum value of SAR (measured) = 14.0 W/kg



0 dB = 14.0 W/kg = 11.46 dBW/kg

### System Check\_Head\_1900MHz

**DUT: D1900V2 - SN:5d170**

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL\_1900 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.455$  S/m;  $\epsilon_r = 40.651$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(8.22, 8.22, 8.22); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=250mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 15.8 W/kg


**Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 104.0 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 19.0 W/kg

**SAR(1 g) = 10.1 W/kg; SAR(10 g) = 5.26 W/kg**

Maximum value of SAR (measured) = 15.9 W/kg



0 dB = 15.9 W/kg = 12.01 dBW/kg

### System Check\_Head\_2450MHz

**DUT: D2450V2 - SN:908**

Communication System: UID 0, CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL\_2450 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.836$  S/m;  $\epsilon_r = 39.855$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(7.57, 7.57, 7.57); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=250mW/Area Scan (71x71x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 20.2 W/kg


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 89.53 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 26.3 W/kg

**SAR(1 g) = 12.7 W/kg; SAR(10 g) = 5.86 W/kg**

Maximum value of SAR (measured) = 19.5 W/kg



0 dB = 19.5 W/kg = 12.90 dBW/kg

### System Check\_Head\_2600MHz

**DUT: D2600V2 - SN:1070**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: HSL\_2600 Medium parameters used:  $f = 2600$  MHz;  $\sigma = 1.959$  S/m;  $\epsilon_r = 39.618$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(7.31, 7.31, 7.31); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=250mW/Area Scan (71x71x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 23.5 W/kg


**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 111.2 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 29.1 W/kg

**SAR(1 g) = 13.8 W/kg; SAR(10 g) = 6.24 W/kg**

Maximum value of SAR (measured) = 23.4 W/kg



0 dB = 23.4 W/kg = 13.69 dBW/kg

### System Check\_Head\_5250MHz

**DUT: D5GHzV2 - SN:1113**


Communication System: UID 0, CW (0); Frequency: 5250 MHz;Duty Cycle: 1:1  
Medium: HSL\_5000 Medium parameters used:  $f = 5250$  MHz;  $\sigma = 4.646$  S/m;  $\epsilon_r = 35.062$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(5.24, 5.24, 5.24); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=100mW/Area Scan (71x71x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
Maximum value of SAR (interpolated) = 17.5 W/kg

**Pin=100mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 67.81 V/m; Power Drift = -0.03 dB  
Peak SAR (extrapolated) = 28.8 W/kg  
**SAR(1 g) = 7.66 W/kg; SAR(10 g) = 2.24 W/kg**  
Maximum value of SAR (measured) = 18.9 W/kg



0 dB = 18.9 W/kg = 12.76 dBW/kg

### System Check\_Head\_5600MHz

**DUT: D5GHzV2 - SN:1113**

Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: HSL\_5000 Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.051$  S/m;  $\epsilon_r = 34.416$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(4.65, 4.65, 4.65); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=100mW/Area Scan (71x71x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 21.0 W/kg


**Pin=100mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 70.33 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 35.4 W/kg

**SAR(1 g) = 8.6 W/kg; SAR(10 g) = 2.48 W/kg**

Maximum value of SAR (measured) = 22.0 W/kg



0 dB = 22.0 W/kg = 13.42 dBW/kg

### System Check\_Head\_5750MHz

**DUT: D5GHzV2 - SN:1113**

Communication System: UID 0, CW (0); Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: HSL\_5000 Medium parameters used:  $f = 5750$  MHz;  $\sigma = 5.226$  S/m;  $\epsilon_r = 34.126$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(4.69, 4.69, 4.69); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=100mW/Area Scan (71x71x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 18.7 W/kg


**Pin=100mW/Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 39.34 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 32.3 W/kg

**SAR(1 g) = 7.72 W/kg; SAR(10 g) = 2.21 W/kg**

Maximum value of SAR (measured) = 17.9 W/kg



0 dB = 17.9 W/kg = 12.53 dBW/kg





**Appendix B. Plots of High SAR Measurement**

The plots are shown as follows.

**01\_GSM850-Ant 2\_GPRS 2 Tx slots\_Right Cheek\_0mm\_Ch189**


Communication System: UID 0, GSM850 (0); Frequency: 836.4 MHz;Duty Cycle: 1:4.15  
 Medium: HSL\_850 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.943$  S/m;  $\epsilon_r = 41.092$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN7592; ConvF(10.05, 10.05, 10.05); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
 Maximum value of SAR (interpolated) = 0.440 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Reference Value = 17.58 V/m; Power Drift = 0.04 dB  
 Peak SAR (extrapolated) = 0.665 W/kg  
**SAR(1 g) = 0.267 W/kg; SAR(10 g) = 0.158 W/kg**  
 Maximum value of SAR (measured) = 0.491 W/kg



0 dB = 0.491 W/kg = -3.09 dBW/kg

## 02\_GSM1900-Ant 2\_GPRS 1 Tx slots\_Right Tilted\_0mm\_Ch661


Communication System: UID 0, PCS (0); Frequency: 1880 MHz; Duty Cycle: 1:8.3  
Medium: HSL\_1900 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.448$  S/m;  $\epsilon_r = 40.016$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.2 °C; Liquid Temperature : 22.8 °C

### DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(8.22, 8.22, 8.22); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.463 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 13.39 V/m; Power Drift = 0.07 dB  
Peak SAR (extrapolated) = 0.727 W/kg  
**SAR(1 g) = 0.377 W/kg; SAR(10 g) = 0.180 W/kg**  
Maximum value of SAR (measured) = 0.615 W/kg



0 dB = 0.615 W/kg = -2.11 dBW/kg

### 03\_WCDMA V-Ant 2\_RMC 12.2Kbps\_Right Cheek\_0mm\_Ch4182


Communication System: UID 0, WCDMA (0); Frequency: 836.4 MHz; Duty Cycle: 1:1  
Medium: HSL\_850 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.943$  S/m;  $\epsilon_r = 41.092$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(10.05, 10.05, 10.05); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.734 W/kg

**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 22.94 V/m; Power Drift = -0.07 dB  
Peak SAR (extrapolated) = 0.936 W/kg  
**SAR(1 g) = 0.447 W/kg; SAR(10 g) = 0.283 W/kg**  
Maximum value of SAR (measured) = 0.734 W/kg



0 dB = 0.734 W/kg = -1.34 dBW/kg

**04\_WCDMA IV-Ant 2\_RMC 12.2Kbps\_Right Tilted\_0mm\_Ch1413**

Communication System: UID 0, WCDMA (0); Frequency: 1732.6 MHz; Duty Cycle: 1:1  
 Medium: HSL\_1750 Medium parameters used:  $f = 1733 \text{ MHz}$ ;  $\sigma = 1.333 \text{ S/m}$ ;  $\epsilon_r = 40.452$ ;  $\rho = 1000 \text{ kg/m}^3$


Ambient Temperature : 23.2 °C; Liquid Temperature : 22.6 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN7592; ConvF(8.41, 8.41, 8.41); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x71x1):** Interpolated grid:  $dx=1.500 \text{ mm}$ ,  $dy=1.500 \text{ mm}$   
 Maximum value of SAR (interpolated) = 0.593 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 10.18 V/m; Power Drift = 0.05 dB  
 Peak SAR (extrapolated) = 0.956 W/kg  
**SAR(1 g) = 0.467 W/kg; SAR(10 g) = 0.214 W/kg**  
 Maximum value of SAR (measured) = 0.732 W/kg



0 dB = 0.732 W/kg = -1.35 dBW/kg

**05\_WCDMA II-Ant 2\_RMC 12.2Kbps\_Right Tilted\_0mm\_Ch9400**


Communication System: UID 0, WCDMA (0); Frequency: 1880 MHz;Duty Cycle: 1:1  
 Medium: HSL\_1900 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.448$  S/m;  $\epsilon_r = 40.016$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.2 °C; Liquid Temperature : 22.8 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN7592; ConvF(8.22, 8.22, 8.22); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
 Maximum value of SAR (interpolated) = 0.497 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Reference Value = 13.81 V/m; Power Drift = 0.03 dB  
 Peak SAR (extrapolated) = 0.763 W/kg  
**SAR(1 g) = 0.400 W/kg; SAR(10 g) = 0.193 W/kg**  
 Maximum value of SAR (measured) = 0.602 W/kg



0 dB = 0.602 W/kg = -2.20 dBW/kg

### 06\_LTE Band 5-Ant 2\_10M\_QPSK\_1RB\_0Offset\_Right Cheek\_0mm\_Ch20525


Communication System: UID 0, LTE-FDD (0); Frequency: 836.5 MHz; Duty Cycle: 1:1  
Medium: HSL\_850 Medium parameters used:  $f = 836.5$  MHz;  $\sigma = 0.943$  S/m;  $\epsilon_r = 41.092$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(10.05, 10.05, 10.05); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.825 W/kg

**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 25.22 V/m; Power Drift = -0.03 dB  
Peak SAR (extrapolated) = 1.07 W/kg  
**SAR(1 g) = 0.483 W/kg; SAR(10 g) = 0.307 W/kg**  
Maximum value of SAR (measured) = 0.808 W/kg



0 dB = 0.808 W/kg = -0.93 dBW/kg

**07\_LTE Band 4-Ant 2\_20M\_QPSK\_1RB\_0Offset\_Right Tilted\_0mm\_Ch20175**

Communication System: UID 0, LTE-FDD (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1  
 Medium: HSL\_1750 Medium parameters used:  $f = 1733$  MHz;  $\sigma = 1.333$  S/m;  $\epsilon_r = 40.452$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.6 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN7592; ConvF(8.41, 8.41, 8.41); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.630 W/kg


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.28 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.987 W/kg

**SAR(1 g) = 0.479 W/kg; SAR(10 g) = 0.219 W/kg**

Maximum value of SAR (measured) = 0.781 W/kg



0 dB = 0.781 W/kg = -1.07 dBW/kg



**08\_LTE Band 2-Ant 2\_20M\_QPSK\_1RB\_0Offset\_Right Tilted\_0mm\_Ch18900**

Communication System: UID 0, LTE-FDD (0); Frequency: 1880 MHz;Duty Cycle: 1:1  
Medium: HSL\_1900 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.448$  S/m;  $\epsilon_r = 40.016$ ;  $\rho = 1000$  kg/m<sup>3</sup>


Ambient Temperature : 23.2 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(8.22, 8.22, 8.22); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.553 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 15.31 V/m; Power Drift = -0.05 dB  
Peak SAR (extrapolated) = 0.870 W/kg  
**SAR(1 g) = 0.452 W/kg; SAR(10 g) = 0.217 W/kg**  
Maximum value of SAR (measured) = 0.722 W/kg



0 dB = 0.722 W/kg = -1.41 dBW/kg

**09\_LTE Band 7-Ant 2\_20M\_QPSK\_1RB\_0Offset\_Right Cheek\_0mm\_Ch21100**

Communication System: UID 0, LTE-FDD (0); Frequency: 2535 MHz;Duty Cycle: 1:1  
Medium: HSL\_2600 Medium parameters used:  $f = 2535$  MHz;  $\sigma = 1.911$  S/m;  $\epsilon_r = 39.066$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(7.31, 7.31, 7.31); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x91x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.38 W/kg


**Zoom Scan (7x8x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.75 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.69 W/kg

**SAR(1 g) = 0.782 W/kg; SAR(10 g) = 0.377 W/kg**

Maximum value of SAR (measured) = 1.26 W/kg



0 dB = 1.26 W/kg = 1.00 dBW/kg

### 10\_LTE Band 38-Ant 2\_20M\_QPSK\_1RB\_0Offset\_Right Cheek\_0mm\_Ch37850

Communication System: UID 0, LTE-TDD (0); Frequency: 2580 MHz; Duty Cycle: 1:1.59  
Medium: HSL\_2600 Medium parameters used:  $f = 2580$  MHz;  $\sigma = 1.964$  S/m;  $\epsilon_r = 39.09$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(7.31, 7.31, 7.31); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x91x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.38 W/kg


**Zoom Scan (7x8x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.54 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.66 W/kg

**SAR(1 g) = 0.753 W/kg; SAR(10 g) = 0.362 W/kg**

Maximum value of SAR (measured) = 1.24 W/kg



0 dB = 1.24 W/kg = 0.93 dBW/kg

### 11\_LTE Band 41-Ant 2\_20M\_QPSK\_50RB\_0Offset\_Right Cheek\_0mm\_Ch40640

Communication System: UID 0, LTE-TDD (0); Frequency: 2595 MHz; Duty Cycle: 1:1.59  
Medium: HSL\_2600 Medium parameters used:  $f = 2595$  MHz;  $\sigma = 1.978$  S/m;  $\epsilon_r = 39.086$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(7.31, 7.31, 7.31); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x91x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.37 W/kg


**Zoom Scan (7x8x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.63 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.61 W/kg

**SAR(1 g) = 0.730 W/kg; SAR(10 g) = 0.352 W/kg**

Maximum value of SAR (measured) = 1.21 W/kg



0 dB = 1.21 W/kg = 0.83 dBW/kg

### 12\_WLAN2.4GHz\_Ant 3\_802.11b 1Mbps\_Left Cheek\_0mm\_Ch11


Communication System: UID 0, 802.11b (0); Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium: HSL\_2450 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.868$  S/m;  $\epsilon_r = 39.113$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C; Liquid Temperature : 22.8 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(7.57, 7.57, 7.57); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x91x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm  
Maximum value of SAR (interpolated) = 1.24 W/kg

**Zoom Scan (7x9x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 10.73 V/m; Power Drift = 0.01 dB  
Peak SAR (extrapolated) = 1.32 W/kg  
**SAR(1 g) = 0.712 W/kg; SAR(10 g) = 0.381 W/kg**  
Maximum value of SAR (measured) = 1.07 W/kg



0 dB = 1.07 W/kg = 0.29 dBW/kg

### 13\_WLAN5GHz\_Ant 3\_802.11ac-VHT40 MCS0\_Left Tilted\_0mm\_Ch62


Communication System: UID 0, 802.11ac (0); Frequency: 5310 MHz; Duty Cycle: 1:1.038  
Medium: HSL\_5000 Medium parameters used:  $f = 5310$  MHz;  $\sigma = 4.61$  S/m;  $\epsilon_r = 35.211$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.2 °C; Liquid Temperature : 22.6 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(5.24, 5.24, 5.24); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (101x101x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
Maximum value of SAR (interpolated) = 1.68 W/kg

**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 8.468 V/m; Power Drift = -0.11 dB  
Peak SAR (extrapolated) = 2.97 W/kg  
**SAR(1 g) = 0.725 W/kg; SAR(10 g) = 0.211 W/kg**  
Maximum value of SAR (measured) = 1.84 W/kg



0 dB = 1.84 W/kg = 2.65 dBW/kg

### 14\_WLAN5GHz\_Ant 3\_802.11ac-VHT40 MCS0\_Left Tilted\_0mm\_Ch102


Communication System: UID 0, 802.11ac (0); Frequency: 5510 MHz; Duty Cycle: 1:1.038  
Medium: HSL\_5000 Medium parameters used:  $f = 5510$  MHz;  $\sigma = 4.841$  S/m;  $\epsilon_r = 35.305$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.3 °C; Liquid Temperature : 22.8 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(4.65, 4.65, 4.65); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (101x101x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm  
Maximum value of SAR (interpolated) = 1.93 W/kg

**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 8.687 V/m; Power Drift = -0.09 dB  
Peak SAR (extrapolated) = 2.84 W/kg  
**SAR(1 g) = 0.642 W/kg; SAR(10 g) = 0.183 W/kg**  
Maximum value of SAR (measured) = 1.69 W/kg



0 dB = 1.69 W/kg = 2.28 dBW/kg

### 15\_WLAN5GHz\_Ant 3\_802.11ac-VHT40 MCS0\_Left Tilted\_0mm\_Ch151

Communication System: UID 0, 802.11ac (0); Frequency: 5755 MHz; Duty Cycle: 1:1.038  
Medium: HSL\_5000 Medium parameters used:  $f = 5755$  MHz;  $\sigma = 5.136$  S/m;  $\epsilon_r = 34.549$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(4.69, 4.69, 4.69); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (101x101x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 2.46 W/kg


**Zoom Scan (9x9x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 9.233 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.21 W/kg

**SAR(1 g) = 0.689 W/kg; SAR(10 g) = 0.191 W/kg**

Maximum value of SAR (measured) = 1.87 W/kg



0 dB = 1.87 W/kg = 2.72 dBW/kg



### 16\_Bluetooth\_Ant 3\_1Mbps\_Left Cheek\_0mm\_Ch0

Communication System: UID 0, Bluetooth (0); Frequency: 2402 MHz; Duty Cycle: 1:1.298  
Medium: HSL\_2450 Medium parameters used:  $f = 2402$  MHz;  $\sigma = 1.815$  S/m;  $\epsilon_r = 39.205$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.8 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(7.57, 7.57, 7.57); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (91x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.115 W/kg


**Zoom Scan (8x8x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.509 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.135 W/kg

**SAR(1 g) = 0.073 W/kg; SAR(10 g) = 0.040 W/kg**

Maximum value of SAR (measured) = 0.109 W/kg



### 17\_GSM 850-Ant 2\_GPRS 2 Tx slots\_Back\_10mm\_Ch189

Communication System: UID 0, GSM850 (0); Frequency: 836.4 MHz; Duty Cycle: 1:4.15  
Medium: HSL\_850 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.944$  S/m;  $\epsilon_r = 41.878$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.1 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(10.05, 10.05, 10.05); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x131x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.145 W/kg


**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.550 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.176 W/kg

**SAR(1 g) = 0.095 W/kg; SAR(10 g) = 0.057 W/kg**

Maximum value of SAR (measured) = 0.143 W/kg



0 dB = 0.143 W/kg = -8.45 dBW/kg

**18\_GSM 1900-Ant 1\_GPRS 1 Tx slots\_Bottom Side\_10mm\_Ch661**


Communication System: UID 0, PCS (0); Frequency: 1880 MHz; Duty Cycle: 1:8.3  
 Medium: HSL\_1900 Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.443$  S/m;  $\epsilon_r = 40.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.2 °C; Liquid Temperature : 22.8 °C

**DASY5 Configuration:**

- Probe: EX3DV4 - SN7592; ConvF(8.22, 8.22, 8.22); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (41x71x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
 Maximum value of SAR (interpolated) = 0.534 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Reference Value = 18.55 V/m; Power Drift = -0.02 dB  
 Peak SAR (extrapolated) = 0.578 W/kg  
**SAR(1 g) = 0.309 W/kg; SAR(10 g) = 0.155 W/kg**  
 Maximum value of SAR (measured) = 0.479 W/kg



0 dB = 0.479 W/kg = -3.20 dBW/kg

### 19\_WCDMA V-Ant 2\_RMC 12.2Kbps\_Back\_10mm\_Ch4182


Communication System: UID 0, WCDMA (0); Frequency: 836.4 MHz; Duty Cycle: 1:1  
Medium: HSL\_850 Medium parameters used:  $f = 836.4$  MHz;  $\sigma = 0.944$  S/m;  $\epsilon_r = 41.878$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Ambient Temperature : 23.1 °C; Liquid Temperature : 22.7 °C

#### DASY5 Configuration:

- Probe: EX3DV4 - SN7592; ConvF(10.05, 10.05, 10.05); Calibrated: 2020.5.22
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn690; Calibrated: 2020.3.26
- Phantom: SAM1; Type: SAM; Serial: TP-1697
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Area Scan (71x91x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm  
Maximum value of SAR (interpolated) = 0.559 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
Reference Value = 14.38 V/m; Power Drift = -0.01 dB  
Peak SAR (extrapolated) = 0.588 W/kg  
**SAR(1 g) = 0.333 W/kg; SAR(10 g) = 0.202 W/kg**  
Maximum value of SAR (measured) = 0.487 W/kg



0 dB = 0.487 W/kg = -3.12 dBW/kg