



# FCC RF Test Report

**APPLICANT** : Xiaomi Communications Co., Ltd.  
**EQUIPMENT** : Mobile Phone  
**BRAND NAME** : Xiaomi  
**MODEL NAME** : 23078PND5G  
**FCC ID** : 2AFZZND5G  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System  
**TEST DATE(S)** : May 18, 2023 ~ Jun. 14, 2023

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

**Sporton International Inc. (ShenZhen)**

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055**

**People's Republic of China**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant ..... 5

    1.2 Manufacturer ..... 5

    1.3 Product Feature of Equipment Under Test..... 5

    1.4 Product Specification of Equipment Under Test..... 6

    1.5 Modification of EUT ..... 6

    1.6 Testing Location ..... 7

    1.7 Test Software..... 7

    1.8 Applicable Standards..... 7

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 8**

    2.1 Carrier Frequency and Channel ..... 8

    2.2 Test Mode..... 9

    2.3 Connection Diagram of Test System ..... 10

    2.4 Support Unit used in test configuration and system ..... 10

    2.5 EUT Operation Test Setup ..... 11

    2.6 Measurement Results Explanation Example..... 11

**3 TEST RESULT ..... 12**

    3.1 6dB and 99% Bandwidth Measurement ..... 12

    3.2 Output Power Measurement..... 13

    3.3 Power Spectral Density Measurement ..... 14

    3.4 Conducted Band Edges and Spurious Emission Measurement ..... 16

    3.5 Radiated Band Edges and Spurious Emission Measurement ..... 17

    3.6 AC Conducted Emission Measurement..... 21

    3.7 Antenna Requirements ..... 23

**4 LIST OF MEASURING EQUIPMENT ..... 24**

**5 MEASUREMENT UNCERTAINTY ..... 25**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. AC CONDUCTED EMISSION TEST RESULT**

**APPENDIX C. RADIATED SPURIOUS EMISSION AND PLOTS**

**APPENDIX D. DUTY CYCLE PLOTS**

**APPENDIX E. SETUP PHOTOGRAPHS**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Report Only	-
3.2	15.247(b)	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.33 dB at 2389.95 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 16.40 dB at 1.000 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

**Conformity Assessment Condition:**

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



# 1 General Description

## 1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Xiaomi
Model Name	23078PND5G
FCC ID	2AFZZND5G
IMEI Code	Conducted: 861585060041561/861585060041579 861585060056965/861585060056973 Conduction: 861585060055702/861585060055710 Radiation: 861585060047220/861585060047238 861585060055041/861585060055058
HW Version	P2.0
SW Version	MIUI 14
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Channel Frequency Range</b>	2412 MHz ~ 2462 MHz
<b>Maximum (Peak) Output Power to antenna</b>	<b>&lt;Ant. 17+6&gt;</b> 802.11b : 23.94 dBm (0.2477 W) 802.11g : 28.94 dBm (0.7834 W) 802.11n HT20 : 28.44 dBm (0.6982 W) 802.11n HT40 : 28.32 dBm (0.6792 W) 802.11ax HE20 : 28.71 dBm (0.7430 W) 802.11ax HE40 : 28.57 dBm (0.7194 W) 802.11be EHT20 : 28.96 dBm (0.7870 W) 802.11be EHT40 : 28.79 dBm (0.7568 W)
<b>99% Occupied Bandwidth</b>	<b>&lt;Ant.17 / Ant.6&gt;</b> 802.11b : 12.947 MHz 802.11g : 16.863 MHz 802.11be EHT20 : 18.941 MHz 802.11be EHT40 : 38.042 MHz
<b>Antenna Type / Gain</b>	<b>&lt;Ant.17&gt;</b> : Fixed Internal Antenna with gain -2.62 dBi <b>&lt;Ant.6&gt;</b> : Fixed Internal Antenna with gain -1.72 dBi
<b>Type of Modulation</b>	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM) 802.11be: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM / 4096QAM)

**Note:**

1. The device supports WLAN MIMO CDD mode.
2. For WLAN SISO & MIMO mode, the whole testing has assessed only MIMO mode by referring to the higher normal output power.
3. For 802.11n/11ax/11be mode, the whole testing have assessed only 802.11be EHT20/EHT40 by referring to the higher output power.
4. 802.11ax/be support OFDMA full RU tone and partial RU tone, both full RU and partial RU-left (for low CH) and partial RU-right (for high CH) test output power, the full RU power/PSD > partial RU, therefore the full RU perform full, and partial RU verify bandedge/spurious.
5. 802.11be support OFDMA for small size RU, 52Tone + 26 Tone or 106Tone + 26Tone, test combination as below,
  - a. For Low channel, 52Tone\_Index38 + 26Tone\_Index1 and 106Tone\_Index53 + 26Tone\_Index4
  - b. For High channel, 52Tone\_Index39 + 26Tone\_Index7 and 106Tone\_Index54 + 26Tone\_Index4
6. The worse cases of RSE for partial RU and small size RU are shown in this report.

### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.6 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

<b>Test Firm</b>	Sporton International Inc. (ShenZhen)		
<b>Test Site Location</b>	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-SZ TH01-SZ	CN1256	421272

<b>Test Firm</b>	Sporton International Inc. (ShenZhen)		
<b>Test Site Location</b>	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City Guangdong Province China 518103 TEL: +86-755-33202398		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	03CH04-SZ	CN1256	421272

### 1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b

### 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

### 2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-





## 2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

### MIMO Antenna


Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11be EHT20	MCS0
802.11be EHT40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :GSM 850 Idle + Bluetooth Link + WLAN Link(2.4G) + USB Cable (Charging from Adapter) + Battery

Co-location
802.11g CH01_TX + BLE 125kbps_CH39 TX + LTE Band48_Link

**Remark:** For Radiated Test Cases, The tests were performance with Adapter and USB Cable.

### 2.3 Connection Diagram of Test System



### 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station(LTE)	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded,1.8m
3.	WLAN AP	Dlink	DIR-820L	KA2IR820LA1	N/A	Unshielded,1.8m
4.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A



## 2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 2.02 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 2.02 + 10 = 12.02 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 6dB and 99% Bandwidth Measurement

##### 3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.

##### 3.1.4 Test Setup



##### 3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

## 3.2 Output Power Measurement

### 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

### 3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.



### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.


If measurements performed using method (2) plus  $10 \log(N)$  exceeds the emission limit, the test should choose method (1) before declaring that the device fails the emission limit.

Method (1): Measure and sum the spectra across the outputs.

The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

Method (2): Measure and add  $10 \log(N)$  dB, where N is the number of outputs. (N=2)

### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.4.4 Test Setup



### 3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.





### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




### 3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.  
For average measurement:
    - VBW = 10 Hz, when duty cycle is no less than 98 percent.
    - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





### **3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

### **3.5.6 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix C

### **3.5.7 Duty Cycle**

Please refer to Appendix D.

### **3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)**

Please refer to Appendix C

## 3.6 AC Conducted Emission Measurement

### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



### 3.7 Antenna Requirements

#### 3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

#### 3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

#### 3.7.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain =  $G_{ANT}$  + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain =  $10 \log(N_{ANT}/N_{SS}=1)$  dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$ .

Directional gain may be calculated by using the formulas applicable to equal gain antennas with  $G_{ANT}$  set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain  $G_{ANT}$  is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<b>&lt;CDD Modes&gt;</b>						
			<b>DG</b>	<b>DG</b>	<b>Power</b>	<b>PSD</b>
			<b>for</b>	<b>for</b>	<b>Limit</b>	<b>Limit</b>
	<b>Ant. 17</b>	<b>Ant. 6</b>	<b>Power</b>	<b>PSD</b>	<b>Reduction</b>	<b>Reduction</b>
	<b>(dBi)</b>	<b>(dBi)</b>	<b>(dBi)</b>	<b>(dBi)</b>	<b>(dB)</b>	<b>(dB)</b>
<b>2.4 GHz</b>	-2.62	-1.72	-1.72	0.85	0.00	0.00

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 06, 2023	May 20, 2023 ~Jun. 08, 2023	Apr. 05, 2024	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 27, 2022	May 20, 2023 ~Jun. 08, 2023	Dec. 26, 2023	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1542004	50MHz Bandwidth	Dec. 27, 2022	May 20, 2023 ~Jun. 08, 2023	Dec. 26, 2023	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Oct. 19, 2022	May 18, 2023 ~Jun. 14, 2023	Oct. 18, 2023	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 07, 2022	May 18, 2023 ~Jun. 14, 2023	Jul. 06, 2023	Radiation (03CH04-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jun. 28, 2022	May 18, 2023 ~Jun. 14, 2023	Jun. 27, 2024	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	May. 14, 2023	May 18, 2023 ~Jun. 14, 2023	May. 13, 2024	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1474	1GHz~18GHz	Jul. 07, 2022	May 18, 2023 ~Jun. 14, 2023	Jul. 06, 2023	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	9170#679	15GHz~40GHz	Jul. 07, 2022	May 18, 2023 ~Jun. 14, 2023	Jul. 06, 2023	Radiation (03CH04-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz~3000MHz	Oct. 19, 2022	May 18, 2023 ~Jun. 14, 2023	Oct. 18, 2023	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 19, 2022	May 18, 2023 ~Jun. 14, 2023	Oct. 18, 2023	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 06, 2022	May 18, 2023 ~Jun. 14, 2023	Jul. 05, 2023	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY57280136	500MHz~26.5GHz	Sep. 30, 2022	May 18, 2023 ~Jun. 14, 2023	Sep. 29, 2023	Radiation (03CH04-SZ)
AC Power Source	APC	AFV-S-600B	F119050019	N/A	Nov. 10, 2022	May 18, 2023 ~Jun. 14, 2023	Nov. 10, 2023	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	May 18, 2023 ~Jun. 14, 2023	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	May 18, 2023 ~Jun. 14, 2023	NCR	Radiation (03CH04-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jul. 07, 2022	May 23, 2023	Jul. 06, 2023	Conduction (CO01-SZ)
AC LISN	R&S	ENV216	100063	9kHz~30MHz	Sep. 15, 2022	May 23, 2023	Sep. 14, 2023	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 17, 2022	May 23, 2023	Oct. 16, 2023	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 07, 2022	May 23, 2023	Jul. 06, 2023	Conduction (CO01-SZ)

NCR: No Calibration Required





## 5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.2dB
---------------------------------------------------------------------	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1dB
---------------------------------------------------------------------	-------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.8dB
---------------------------------------------------------------------	-------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1dB
---------------------------------------------------------------------	-------

----- THE END -----



## Appendix A. Conducted Test Results

## A1. Conducted Test Results

Test Engineer:	Tang ZhaoYang	Temperature:	21~25	°C
Test Date:	2023/5/20~2023/6/08	Relative Humidity:	51~54	%

**TEST RESULTS DATA**  
**Peak Output Power**

2.4GHz Band MIMO																
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant17	Ant6	SUM	Ant17	Ant6	Ant17	Ant6	Ant17	Ant6	Ant17	Ant6	
11b	1Mbps	2	1	2412	20.59	20.68	23.65	30.00		-1.72		21.93		36.00	Pass	
11b	1Mbps	2	6	2437	20.66	21.18	23.94	30.00		-1.72		22.22		36.00	Pass	
11b	1Mbps	2	11	2462	20.82	21.02	23.93	30.00		-1.72		22.21		36.00	Pass	
11g	6Mbps	2	1	2412	25.28	25.52	28.41	30.00		-1.72		26.69		36.00	Pass	
11g	6Mbps	2	6	2437	26.02	25.83	28.94	30.00		-1.72		27.22		36.00	Pass	
11g	6Mbps	2	11	2462	25.72	25.49	28.62	30.00		-1.72		26.90		36.00	Pass	
HT20	MCS0	2	1	2412	25.22	25.05	28.15	30.00		-1.72		26.43		36.00	Pass	
HT20	MCS0	2	6	2437	25.63	25.22	28.44	30.00		-1.72		26.72		36.00	Pass	
HT20	MCS0	2	11	2462	24.76	24.58	27.68	30.00		-1.72		25.96		36.00	Pass	
HT40	MCS0	2	3	2422	25.36	25.25	28.32	30.00		-1.72		26.60		36.00	Pass	
HT40	MCS0	2	6	2437	24.75	24.93	27.85	30.00		-1.72		26.13		36.00	Pass	
HT40	MCS0	2	9	2452	23.87	23.61	26.75	30.00		-1.72		25.03		36.00	Pass	

Note: Measured power (dBm) has offset with cable loss.

**TEST RESULTS DATA**  
**Average Output Power**  
**(Report Only)**

2.4GHz Band MIMO																
Mod.	Data Rate	N <sub>TX</sub>	CH.	Freq. (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant17	Ant6	SUM	Ant17	Ant6	Ant17	Ant6	Ant17	Ant6	Ant17	Ant6	
11b	1Mbps	2	1	2412	17.90	17.70	20.81	30.00		-1.72		19.09		36.00	Pass	
11b	1Mbps	2	6	2437	17.30	18.00	20.67	30.00		-1.72		18.95		36.00	Pass	
11b	1Mbps	2	11	2462	17.60	17.80	20.71	30.00		-1.72		18.99		36.00	Pass	
11g	6Mbps	2	1	2412	17.70	17.50	20.61	30.00		-1.72		18.89		36.00	Pass	
11g	6Mbps	2	6	2437	17.90	18.50	21.22	30.00		-1.72		19.50		36.00	Pass	
11g	6Mbps	2	11	2462	17.90	17.90	20.91	30.00		-1.72		19.19		36.00	Pass	
HT20	MCS0	2	1	2412	17.15	17.05	20.11	30.00		-1.72		18.39		36.00	Pass	
HT20	MCS0	2	6	2437	17.01	17.42	20.23	30.00		-1.72		18.51		36.00	Pass	
HT20	MCS0	2	11	2462	16.87	17.00	19.95	30.00		-1.72		18.23		36.00	Pass	
HT40	MCS0	2	3	2422	16.40	16.40	19.41	30.00		-1.72		17.69		36.00	Pass	
HT40	MCS0	2	6	2437	16.40	17.00	19.72	30.00		-1.72		18.00		36.00	Pass	
HT40	MCS0	2	9	2452	15.30	15.70	18.51	30.00		-1.72		16.79		36.00	Pass	

Note: Measured power (dBm) has offset with cable loss.

**TEST RESULTS DATA**  
**Peak Output Power**

2.4GHz Band MIMO																	
Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	RU Config.	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant17	Ant6	SUM	Ant17	Ant6	Ant17	Ant6	Ant17	Ant6	Ant17	Ant6	
HE20	MCS0	2	1	2412	Full	25.50	25.37	28.45	30.00		-1.72		26.73		36.00		Pass
HE20	MCS0	2	1	2412	26/0	19.97	19.89	22.94	30.00		-1.72		21.22		36.00		Pass
HE20	MCS0	2	1	2412	52/37	21.36	21.21	24.30	30.00		-1.72		22.58		36.00		Pass
HE20	MCS0	2	1	2412	106/53	23.03	22.77	25.91	30.00		-1.72		24.19		36.00		Pass
HE20	MCS0	2	6	2437	Full	25.96	25.43	28.71	30.00		-1.72		26.99		36.00		Pass
HE20	MCS0	2	11	2462	Full	24.97	24.76	27.88	30.00		-1.72		26.16		36.00		Pass
HE20	MCS0	2	11	2462	26/8	19.46	19.21	22.35	30.00		-1.72		20.63		36.00		Pass
HE20	MCS0	2	11	2462	52/40	21.16	20.53	23.87	30.00		-1.72		22.15		36.00		Pass
HE20	MCS0	2	11	2462	106/54	22.37	22.16	25.28	30.00		-1.72		23.56		36.00		Pass
HE40	MCS0	2	3	2422	Full	25.59	25.52	28.57	30.00		-1.72		26.85		36.00		Pass
HE40	MCS0	2	6	2437	Full	24.99	25.12	28.07	30.00		-1.72		26.35		36.00		Pass
HE40	MCS0	2	9	2452	Full	24.09	23.82	26.97	30.00		-1.72		25.25		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.

**TEST RESULTS DATA**  
**Average Output Power**  
**(Report Only)**

2.4GHz Band MIMO																	
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant17	Ant6	SUM	Ant17	Ant6	Ant17	Ant6	Ant17	Ant6	Ant17	Ant6	
HE20	MCS0	2	1	2412	Full	17.28	17.18	20.24	30.00		-1.72		18.52		36.00		Pass
HE20	MCS0	2	1	2412	26/0	8.27	7.91	11.10	30.00		-1.72		9.38		36.00		Pass
HE20	MCS0	2	1	2412	52/37	10.90	11.02	13.97	30.00		-1.72		12.25		36.00		Pass
HE20	MCS0	2	1	2412	106/53	14.11	13.74	16.94	30.00		-1.72		15.22		36.00		Pass
HE20	MCS0	2	6	2437	Full	17.08	17.58	20.35	30.00		-1.72		18.63		36.00		Pass
HE20	MCS0	2	11	2462	Full	16.98	17.08	20.04	30.00		-1.72		18.32		36.00		Pass
HE20	MCS0	2	11	2462	26/8	8.42	8.46	11.45	30.00		-1.72		9.73		36.00		Pass
HE20	MCS0	2	11	2462	52/40	11.49	11.47	14.49	30.00		-1.72		12.77		36.00		Pass
HE20	MCS0	2	11	2462	106/54	14.03	14.17	17.11	30.00		-1.72		15.39		36.00		Pass
HE40	MCS0	2	3	2422	Full	16.50	16.50	19.51	30.00		-1.72		17.79		36.00		Pass
HE40	MCS0	2	6	2437	Full	16.50	17.10	19.82	30.00		-1.72		18.10		36.00		Pass
HE40	MCS0	2	9	2452	Full	15.40	15.80	18.61	30.00		-1.72		16.89		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.

**TEST RESULTS DATA**  
**Peak Output Power**

2.4GHz Band MIMO																	
Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	RU Config.	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant17	Ant6	SUM	Ant17	Ant6	Ant17	Ant6	Ant17	Ant6	Ant17	Ant6	
EHT20	MCS0	2	1	2412	Full	25.75	25.62	28.70	30.00		-1.72		26.98		36.00		Pass
EHT20	MCS0	2	1	2412	26/0	20.22	20.14	23.19	30.00		-1.72		21.47		36.00		Pass
EHT20	MCS0	2	1	2412	52/37	21.61	21.46	24.55	30.00		-1.72		22.83		36.00		Pass
EHT20	MCS0	2	1	2412	106/53	23.28	23.02	26.16	30.00		-1.72		24.44		36.00		Pass
EHT20	MCS0	2	6	2437	Full	26.21	25.68	28.96	30.00		-1.72		27.24		36.00		Pass
EHT20	MCS0	2	11	2462	Full	25.22	25.01	28.13	30.00		-1.72		26.41		36.00		Pass
EHT20	MCS0	2	11	2462	26/8	19.71	19.46	22.60	30.00		-1.72		20.88		36.00		Pass
EHT20	MCS0	2	11	2462	52/40	21.41	20.78	24.12	30.00		-1.72		22.40		36.00		Pass
EHT20	MCS0	2	11	2462	106/54	22.62	22.41	25.53	30.00		-1.72		23.81		36.00		Pass
EHT40	MCS0	2	3	2422	Full	25.81	25.74	28.79	30.00		-1.72		27.07		36.00		Pass
EHT40	MCS0	2	6	2437	Full	25.21	25.34	28.29	30.00		-1.72		26.57		36.00		Pass
EHT40	MCS0	2	9	2452	Full	24.31	24.04	27.19	30.00		-1.72		25.47		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.



**TEST RESULTS DATA**  
**Average Output Power**  
**(Report Only)**

2.4GHz Band MIMO																	
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant17	Ant6	SUM	Ant17	Ant6	Ant17	Ant6	Ant17	Ant6	Ant17	Ant6	
EHT20	MCS0	2	1	2412	Full	17.40	17.30	20.36	30.00		-1.72		18.64		36.00		Pass
EHT20	MCS0	2	1	2412	26/0	8.39	8.03	11.22	30.00		-1.72		9.50		36.00		Pass
EHT20	MCS0	2	1	2412	52/37	11.02	11.14	14.09	30.00		-1.72		12.37		36.00		Pass
EHT20	MCS0	2	1	2412	106/53	14.23	13.86	17.06	30.00		-1.72		15.34		36.00		Pass
EHT20	MCS0	2	6	2437	Full	17.20	17.70	20.47	30.00		-1.72		18.75		36.00		Pass
EHT20	MCS0	2	11	2462	Full	17.10	17.20	20.16	30.00		-1.72		18.44		36.00		Pass
EHT20	MCS0	2	11	2462	26/8	8.54	8.58	11.57	30.00		-1.72		9.85		36.00		Pass
EHT20	MCS0	2	11	2462	52/40	11.61	11.59	14.61	30.00		-1.72		12.89		36.00		Pass
EHT20	MCS0	2	11	2462	106/54	14.15	14.29	17.23	30.00		-1.72		15.51		36.00		Pass
EHT40	MCS0	2	3	2422	Full	16.60	16.60	19.61	30.00		-1.72		17.89		36.00		Pass
EHT40	MCS0	2	6	2437	Full	16.60	17.20	19.92	30.00		-1.72		18.20		36.00		Pass
EHT40	MCS0	2	9	2452	Full	15.50	15.90	18.71	30.00		-1.72		16.99		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.



Ambient Condition: <u>24~26 °C, 45~55 %RH</u>
Test Date: <u>2023/5/20~2023/6/08</u> Test Engineer: <u>Zhang Xue Yi</u>



### DTS Bandwidth

#### Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B-CDD	Ant17	2412	8.04	2407.96	2416.00	0.5	PASS
	Ant6	2412	8.08	2407.96	2416.04	0.5	PASS
	Ant17	2437	8.04	2432.96	2441.00	0.5	PASS
	Ant6	2437	8.04	2432.96	2441.00	0.5	PASS
	Ant17	2462	8.04	2457.96	2466.00	0.5	PASS
	Ant6	2462	8.04	2457.96	2466.00	0.5	PASS
11G-CDD	Ant17	2412	16.28	2403.84	2420.12	0.5	PASS
	Ant6	2412	16.32	2403.84	2420.16	0.5	PASS
	Ant17	2437	15.92	2428.84	2444.76	0.5	PASS
	Ant6	2437	16.08	2428.80	2444.88	0.5	PASS
	Ant17	2462	15.68	2454.08	2469.76	0.5	PASS
	Ant6	2462	15.92	2453.84	2469.76	0.5	PASS
11BE20MIMO	Ant17	2412	18.56	2402.76	2421.32	0.5	PASS
	Ant6	2412	18.72	2402.72	2421.44	0.5	PASS
	Ant17	2437	18.40	2427.72	2446.12	0.5	PASS
	Ant6	2437	18.16	2427.56	2445.72	0.5	PASS
	Ant17	2462	17.76	2452.88	2470.64	0.5	PASS
	Ant6	2462	17.52	2452.72	2470.24	0.5	PASS
11BE40MIMO	Ant17	2422	37.52	2403.12	2440.64	0.5	PASS
	Ant6	2422	35.12	2404.40	2439.52	0.5	PASS
	Ant17	2437	35.92	2418.60	2454.52	0.5	PASS
	Ant6	2437	37.12	2418.20	2455.32	0.5	PASS
	Ant17	2452	37.28	2433.12	2470.40	0.5	PASS
	Ant6	2452	36.48	2433.12	2469.60	0.5	PASS




Test Graphs






11B-CDD\_Ant17\_2437



Date: 20.MAY.2023 12:02:01


11B-CDD\_Ant6\_2437




Date: 20.MAY.2023 12:02:57





11B-CDD\_Ant17\_2462



11B-CDD\_Ant6\_2462





**11G-CDD\_Ant6\_2412**






11G-CDD\_Ant17\_2462




11G-CDD\_Ant6\_2462








11BE20MIMO\_Ant17\_2412






Date: 20.MAY.2023 12:16:07

11BE20MIMO\_Ant6\_2412




Date: 20.MAY.2023 12:17:14








11BE40MIMO\_Ant17\_2422




11BE40MIMO\_Ant6\_2422






11BE40MIMO\_Ant17\_2437




Date: 20.MAY.2023 12:25:30

11BE40MIMO\_Ant6\_2437



Date: 20.MAY.2023 12:26:27







### Occupied Channel Bandwidth

#### Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]
11B-CDD	Ant17	2412	12.947	2405.5265	2418.4735
	Ant6	2412	12.867	2405.6064	2418.4735
	Ant17	2437	12.827	2430.5265	2443.3536
	Ant6	2437	12.907	2430.4066	2443.3137
	Ant17	2462	12.867	2455.5265	2468.3936
	Ant6	2462	12.667	2455.6064	2468.2737
11G-CDD	Ant17	2412	16.863	2403.5684	2420.4316
	Ant6	2412	16.543	2403.7283	2420.2717
	Ant17	2437	16.583	2428.6883	2445.2717
	Ant6	2437	16.703	2428.5684	2445.2717
	Ant17	2462	16.783	2453.5684	2470.3516
	Ant6	2462	16.543	2453.7283	2470.2717
11BE20MIMO	Ant17	2412	18.941	2402.5295	2421.4705
	Ant6	2412	18.941	2402.5694	2421.5105
	Ant17	2437	18.901	2427.5295	2446.4306
	Ant6	2437	18.941	2427.4496	2446.3906
	Ant17	2462	18.941	2452.4895	2471.4306
	Ant6	2462	18.861	2452.4895	2471.3506
11BE40MIMO	Ant17	2422	38.042	2402.9790	2441.0210
	Ant6	2422	37.882	2403.1389	2441.0210
	Ant17	2437	37.882	2418.0589	2455.9411
	Ant6	2437	37.802	2418.1389	2455.9411
	Ant17	2452	38.042	2432.8192	2470.8611
	Ant6	2452	38.042	2432.8991	2470.9411




Test Graphs








11B-CDD\_Ant17\_2437




11B-CDD\_Ant6\_2437






11B-CDD\_Ant17\_2462



Date: 20.MAY.2023 12:04:36


11B-CDD\_Ant6\_2462



Date: 20.MAY.2023 12:05:42




11G-CDD\_Ant17\_2412



Date: 20.MAY.2023 12:09:11


11G-CDD\_Ant6\_2412



Date: 20.MAY.2023 12:10:18




11G-CDD\_Ant17\_2437



Date: 20.MAY.2023 12:11:39


11G-CDD\_Ant6\_2437



Date: 20.MAY.2023 12:12:36




11G-CDD\_Ant17\_2462







Date: 20.MAY.2023 12:13:46



11G-CDD\_Ant6\_2462





Date: 20.MAY.2023 12:14:52















11BE40MIMO\_Ant17\_2437



Date: 20.MAY.2023 12:25:36


11BE40MIMO\_Ant6\_2437



Date: 20.MAY.2023 12:26:33




11BE40MIMO\_Ant17\_2452



Date: 20.MAY.2023 12:28:06

11BE40MIMO\_Ant6\_2452



Date: 20.MAY.2023 12:29:13



### Maximum power spectral density

#### Test Result

TestMode	Antenna	Freq(MHz)	Result	Limit	Verdict
11B-CDD	Ant17	2412	-4.06	≤8.00	PASS
	Ant6	2412	-4.22	≤8.00	PASS
	total	2412	-1.13	≤8.00	PASS
	Ant17	2437	-4.68	≤8.00	PASS
	Ant6	2437	-4.12	≤8.00	PASS
	total	2437	-1.38	≤8.00	PASS
	Ant17	2462	-4.05	≤8.00	PASS
	Ant6	2462	-3.95	≤8.00	PASS
	total	2462	-0.99	≤8.00	PASS
11G-CDD	Ant17	2412	-5.16	≤8.00	PASS
	Ant6	2412	-5.79	≤8.00	PASS
	total	2412	-2.45	≤8.00	PASS
	Ant17	2437	-6.21	≤8.00	PASS
	Ant6	2437	-4.94	≤8.00	PASS
	total	2437	-2.52	≤8.00	PASS
	Ant17	2462	-5.08	≤8.00	PASS
	Ant6	2462	-5.32	≤8.00	PASS
	total	2462	-2.19	≤8.00	PASS
11BE20MIMO	Ant17	2412	-8.03	≤8.00	PASS
	Ant6	2412	-8.04	≤8.00	PASS
	total	2412	-5.02	≤8.00	PASS
	Ant17	2437	-6.93	≤8.00	PASS
	Ant6	2437	-7.1	≤8.00	PASS
	total	2437	-4.00	≤8.00	PASS
	Ant17	2462	-7.79	≤8.00	PASS
	Ant6	2462	-7.49	≤8.00	PASS
	total	2462	-4.63	≤8.00	PASS
11BE40MIMO	Ant17	2422	-12.39	≤8.00	PASS
	Ant6	2422	-11.21	≤8.00	PASS
	total	2422	-8.75	≤8.00	PASS
	Ant17	2437	-11.64	≤8.00	PASS
	Ant6	2437	-11.22	≤8.00	PASS
	total	2437	-8.41	≤8.00	PASS
	Ant17	2452	-11.82	≤8.00	PASS
	Ant6	2452	-11.54	≤8.00	PASS
	total	2452	-8.67	≤8.00	PASS



Test Graphs

