

01_NFC_ASK_Back_0mm

Communication System: UID 0, NRF (0); Frequency: 13.56 MHz; Duty Cycle: 1:1
Medium: HSL_13 Medium parameters used: $f = 14 \text{ MHz}$; $\sigma = 0.753 \text{ S/m}$; $\epsilon_r = 54.139$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3819; ConvF(15.28, 15.28, 15.28); Calibrated: 2023/6/6
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1437; Calibrated: 2024/3/14
- Phantom: ELI V5.0; Type: QD OVA 002 AA; Serial: TP:1233
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

Area Scan (71x131x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$

Maximum value of SAR (interpolated) = 0.0443 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$


Reference Value = 0.3820 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.0730 W/kg

SAR(1 g) = 0.019 W/kg; SAR(10 g) = 0.0064 W/kg

Ratio of SAR at M2 to SAR at M1 = 35%

Maximum value of SAR (measured) = 0.0459 W/kg



0 dB = 0.0459 W/kg