



Power reduction mechanism verification

According to the May 2017 TCBC Workshop, Demonstration of proper functioning of the detection and triggering mechanisms is required to support the corresponding RF exposure conditions. The verification is through a base station simulator is used to establish a conducted RF connection and monitor output power under different operating conditions related to the power reduction mechanisms. Detail of power reduction mechanisms referring to Operational Description

1. Power Verification Procedure

The power verification was performed according to the following procedure:

1. A base station simulator was used to establish a conducted RF connection and the output power was monitored. The power measurements were confirmed to be within expected tolerances for all states before and after a power reduction mechanism was triggered.
2. Step 1 was repeated for all relevant modes and frequency bands for the mechanism being investigated.
3. Steps 1 and 2 were repeated for all individual power reduction mechanisms and combinations thereof. For the combination cases, one mechanism was switched to a 'triggered' state at a time; powers were confirmed to be within tolerances after each additional mechanism was activated.

General Note:

This device uses different Exposure Condition Index (ECI) to configure different time averaged power levels based on certain exposure scenarios as the following table:

Exposure Condition	ECI	Trigger conditions
Head SAR	ECI1	Earpiece On
Hotspot Mode SAR	ECI5	Hotspot On
Body worn/ Extremity Mode SAR	ECI4	Sensor Off/ receiver off
Body worn/ Extremity Mode SAR	ECI3	Sensor On

1. Select the bands with the largest power reduction for power verification :
 - a. Establish voice call and audio routed through the earpiece to monitor output power under head power states.
 - Tradition voice call for GSM/WCDMA, voice over IP CMRS operations for LTE/ 5G FR1
 - GSM850 is set to GPRS 4TX slot, LTE Band 7 is set at 'highest BW, 1RB, RB Offset = 0, QPSK', WCDMA IV is set AMR 12.2Kbps, 5G FR1 n7 is set at highest BW, 1RB, RB offset = 1.
 - b. Establish data connection monitor hotspot power state.
 - GSM850 is set to GPRS 4TX slot, LTE Band 7 is set at 'highest BW, 1RB, RB Offset = 0, QPSK', WCDMA IV is set AMR 12.2Kbps, 5G FR1 n41 is set at highest BW, 1RB, RB offset = 1.
 - c. Establish data connection monitor body worn power state.
 - LTE Band 7 is set at 'highest BW, 1RB, RB Offset = 0, QPSK' WCDMA IV is set RMC 12.2Kbps, 5G FR1 n78 is set at highest BW, 1RB, RB offset = 1.
 - Body Detect mechanism was performed for the in-hand and on a stationary object (placed on a table)
 - d. Establish data connection monitor extremity power state.
 - LTE Band 7 is set at 'highest BW, 1RB, RB Offset = 0, QPSK' WCDMA IV is set RMC 12.2Kbps, 5G FR1 n78 is set at highest BW, 1RB, RB offset = 1.
 - Body Detect mechanism was performed for the in-hand and on a stationary object (placed on a table).
2. In this power validation purpose is to demonstrate of proper functioning of the detection and triggering mechanisms to support the corresponding RF exposure conditions.
3. Verification performed for one technology/Band to demonstrate that the power reduction applies for same technology/band and call origination.

2. Verification output Power Results

Head exposure conditions

Head Exposure condition					
Ear acoustic output Status		OFF		ON	
Power state		WWAN ECI 4		WWAN ECI 1	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
GSM850 (4 Tx slots)	Ant 1	26.37	27.50	23.59	24.50
WCDMA IV	Ant 4	24.05	25.00	18.57	19.50
LTE Band 7	Ant 3	24.44	25.50	17.47	18.50
n7	Ant 3	23.11	24.00	17.41	18.50

Hotspot exposure condition

Hotspot exposure condition					
Hotspot		OFF		ON	
Power state		WWAN ECI 4		WWAN ECI 5	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
GSM850 (4 Tx slots)	Ant 1	26.37	27.50	23.52	24.50
WCDMA IV	Ant 4	24.05	25.00	18.62	19.50
LTE Band 7	Ant 3	24.44	25.50	17.51	18.50
n41	Ant 4	26.73	27.50	20.52	21.50

Body worn and Extremity exposure condition

Extremity exposure condition					
Sensor output Status		OFF		ON	
Power state		WWAN ECI 4		WWAN ECI 3	
Wireless technology	Antenna	Measured (dBm)	Max. Tune-up (dBm)	Measured (dBm)	Max. Tune-up (dBm)
WCDMA IV	Ant 4	24.05	25.00	22.39	23.50
LTE Band 7	Ant 3	24.44	25.50	17.85	19.00
n78	Ant 9	20.14	21.00	16.62	17.50