



FCC RF Test Report

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : Xiaomi
MODEL NAME : 2406APNFAG
FCC ID : 2AFZZPNFAG
STANDARD : 47 CFR Part 2, and 90(S)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : May 12, 2024 ~ Jun. 13, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test 5

 1.5 Modification of EUT 5

 1.6 Maximum Conducted Power and Emission Designator 6

 1.7 Testing Site..... 6

 1.8 Test Software 6

 1.9 Applied Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Test Mode..... 8

 2.2 Connection Diagram of Test System 9

 2.3 Support Unit used in test configuration and system 9

 2.4 Measurement Results Explanation Example 9

 2.5 Frequency List of Low/Middle/High Channels 10

3 TEST RESULT 11

 3.1 Conducted Output Power Measurement 11

 3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 12

 3.3 Emissions Mask Measurement 13

 3.4 Emissions Mask – Out Of Band Emissions Measurement..... 15

 3.5 Field Strength of Spurious Radiation Measurement 16

 3.6 Frequency Stability Measurement..... 19

4 LIST OF MEASURING EQUIPMENT 21

5 MEASUREMENT UNCERTAINTY 22

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG442515D	Rev. 01	Initial issue of report	Jun. 14, 2024



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	—	Report only	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	—	Report only	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	$< 50+10\log_{10}(P[\text{Watts}])$	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 45.15 dB at 2440.000 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	$< 2.5 \text{ ppm}$	PASS	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Xiaomi
Model Name	2406APNFAG
FCC ID	2AFZZPNFAG
IMEI Code	Conducted: 868329070074947/868329070074954 Radiation: 868329070126986/868329070126994
HW Version	1351N12A
SW Version	Xiaomi HyperOS 1.0
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	814 ~ 824 MHz
Rx Frequency	859 ~ 869 MHz
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz
Maximum Output Power to Antenna	<Ant. 0>25.05 dBm <Ant. 1>24.20 dBm
Antenna Gain	<Ant. 0>-4.51 dBi <Ant. 1>-4.10 dBi
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

Note: Only maximum conducted Power of Ant.0 is shown in the report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Conducted Power and Emission Designator

LTE Band 26		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum Conducted power (W)	Emission Designator (99%OBW)	Maximum Conducted power (W)	Emission Designator (99%OBW)
1.4	814.7 ~ 823.3	0.3141	1M10G7D	0.2529	1M10W7D
3	815.5 ~ 822.5	0.3155	2M72G7D	0.2518	2M72W7D
5	816.5 ~ 821.5	0.3155	4M49G7D	0.2523	4M49W7D
10	819.0	0.3126	9M05G7D	0.2495	9M05W7D
15	824	0.3199	14M4G7D	0.3126	13M5W7D

Note:

1. All modulations have been tested, and only the worst test results of PSK & QAM are shown in the report.
2. The device supports two PAs for LTE Band 26, the maximum power of main PA is higher than the other PA, therefore, we chose higher power of main PA to show in the report.

1.7 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	TH01-KS	SPORTON	FCC LTE_Ver2.0 Auto_china_210503	2.0
2.	03CH04-KS	AUDIX	E3	210616



1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 90(S)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test


2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.(Z-Plane-Adapter mode)

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Test Items	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16 QAM	64 QAM	256 QAM	1	Half	Full	L	M	H
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	26	v	v	v	v	v	-	v	v					v	v	v	v
Emission masks In-band emissions	26	v	v	v	v	v	-	v	v	v	v	v		v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v				v			v	v	v
Frequency Stability	26				v		-	v						v		v	
Radiated Spurious Emission	26	Worse Case														v	
Note	<ol style="list-style-type: none"> The mark “v ” means that this configuration is chosen for testing The mark “-“ means that this bandwidth is not supported. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies. For QAM modulation mode, the whole testing has assessed 16QAM&64QAM mode by referring to the higher conducted power. 																

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss

$$\text{Offset} = \text{RF cable loss}$$

The following shows an offset computation example with RF cable loss 4.6 dB

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 4.6 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	26740	-
	Frequency	-	819	-
5	Channel	26715	26740	26765
	Frequency	816.5	819	821.5
3	Channel	26705	26740	26775
	Frequency	815.5	819	822.5
1.4	Channel	26697	26740	26783
	Frequency	814.7	819	823.3

LTE Band 26 Cross-rule Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	-	Middle	-
15	Channel	-	26790	-
	Frequency	-	824	-
10	Channel	-	26790	-
	Frequency	-	824	-
5	Channel	-	26790	-
	Frequency	-	824	-
3	Channel	-	26790	-
	Frequency	-	824	-
1.4	Channel	-	26790	-
	Frequency	-	824	-

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.



3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a):

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \text{ Log}_{10}(f/6.1)$ decibels or $50 + 10 \text{ Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \text{ Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The emissions mask of low and high channels for the highest RF powers were measured.
3. The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor $10 \log (1\% \text{ of OBW}/\text{measured RBW})(\text{dB})$ was compensated, if required.
4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

3.4 Emissions Mask – Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least $43 + 10 \log (P)$ dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.



3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43+10\log_{10}(P[\text{Watts}])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.5.4 Test Setup


For radiated test from 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the
4. battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	May 12, 2024~ Jun. 13, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H201401144 0	-40~+150°C 20%~95%RH	Jul. 06, 2023	May 12, 2024~ Jun. 13, 2024	Jul. 05, 2024	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY5747107 9	10Hz~44G,MAX 30dB	Oct. 10, 2023	Jun. 04, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 10, 2023	Jun. 04, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz-1GHz	Aug. 19, 2023	Jun. 04, 2024	Aug. 18, 2024	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00251694	1GHz~18GHz	Jul. 12, 2023	Jun. 04, 2024	Jul. 11, 2024	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2024	Jun. 04, 2024	Jan. 04, 2025	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	380827	9KHz-1GHz	Jul. 06, 2023	Jun. 04, 2024	Jul. 05, 2024	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 05, 2024	Jun. 04, 2024	Jan. 04, 2025	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060840	1Ghz-18Ghz	Oct. 10, 2023	Jun. 04, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
Amplifier	Agilent	8449B	3008A02370	1Ghz-18Ghz	Oct. 10, 2023	Jun. 04, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jun. 04, 2024	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jun. 04, 2024	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jun. 04, 2024	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required



5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.26 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.46 dB
Peak to Average Ratio	±0.46 dB
Frequency Stability	±0.4 Hz

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.83dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.83dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.82dB
---	--------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Simle Wang	Temperature :	22~23°C
		Relative Humidity :	40~42%

Conducted Output Power (Average power)

For Ant 0:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.
Channel					26790	
Frequency (MHz)					824	
15	QPSK	1	0		25.05	
15	QPSK	1	37		24.89	
15	QPSK	1	74		24.89	
15	QPSK	36	0		23.97	
15	QPSK	36	20		23.84	
15	QPSK	36	39		23.84	
15	QPSK	75	0		23.87	
15	16QAM	1	0		24.02	
15	16QAM	1	37		24.05	
15	16QAM	1	74		24.05	
15	16QAM	36	0		22.89	
15	16QAM	36	20		22.81	
15	16QAM	36	39		22.85	
15	16QAM	75	0		22.84	
15	64QAM	1	0		22.97	
15	64QAM	1	37		23.00	
15	64QAM	1	74		23.00	
15	64QAM	36	0		21.88	
15	64QAM	36	20		21.81	
15	64QAM	36	39		21.84	
15	64QAM	75	0		21.83	
15	256QAM	1	0		20.21	
15	256QAM	1	37		20.20	
15	256QAM	1	74		20.12	
15	256QAM	36	0		20.03	
15	256QAM	36	20		19.96	
15	256QAM	36	39		19.99	
15	256QAM	75	0		20.03	
Channel					26740	
Frequency (MHz)					819	
10	QPSK	1	0		24.95	
10	QPSK	1	25		24.71	
10	QPSK	1	49		24.93	
10	QPSK	25	0		23.85	
10	QPSK	25	12		23.74	



10	QPSK	25	25		23.81	
10	QPSK	50	0		23.77	
10	16QAM	1	0		23.87	
10	16QAM	1	25		23.82	
10	16QAM	1	49		23.97	
10	16QAM	25	0		22.74	
10	16QAM	25	12		22.73	
10	16QAM	25	25		22.81	
10	16QAM	50	0		22.77	
10	64QAM	1	0		22.83	
10	64QAM	1	25		22.86	
10	64QAM	1	49		22.97	
10	64QAM	25	0		21.76	
10	64QAM	25	12		21.78	
10	64QAM	25	25		21.78	
10	64QAM	50	0		21.75	
10	256QAM	1	0		20.23	
10	256QAM	1	25		20.14	
10	256QAM	1	49		20.17	
10	256QAM	25	0		20.01	
10	256QAM	25	12		19.94	
10	256QAM	25	25		20.03	
10	256QAM	50	0		19.91	
Channel				26715	26740	26765
Frequency (MHz)				816.5	819	821.5
5	QPSK	1	0	24.95	24.99	24.76
5	QPSK	1	12	24.71	24.83	24.63
5	QPSK	1	24	24.96	24.82	24.75
5	QPSK	12	0	23.91	23.94	23.67
5	QPSK	12	7	23.82	23.80	23.60
5	QPSK	12	13	23.81	23.80	23.66
5	QPSK	25	0	23.77	23.77	23.70
5	16QAM	1	0	23.92	23.91	24.00
5	16QAM	1	12	23.83	24.02	23.77
5	16QAM	1	24	23.95	23.99	23.85
5	16QAM	12	0	22.73	22.78	22.68
5	16QAM	12	7	22.77	22.72	22.64
5	16QAM	12	13	22.76	22.79	22.64
5	16QAM	25	0	22.75	22.80	22.67
5	64QAM	1	0	22.91	22.88	22.91
5	64QAM	1	12	22.84	22.97	22.76
5	64QAM	1	24	23.00	22.93	22.84
5	64QAM	12	0	21.71	21.81	21.62
5	64QAM	12	7	21.76	21.70	21.65
5	64QAM	12	13	21.80	21.76	21.63
5	64QAM	25	0	21.76	21.76	21.66
5	256QAM	1	0	20.16	20.26	20.22
5	256QAM	1	12	20.24	20.26	20.16
5	256QAM	1	24	20.11	20.18	20.10
5	256QAM	12	0	20.09	20.04	20.11



5	256QAM	12	7	20.07	20.01	19.91
5	256QAM	12	13	20.07	19.94	19.93
5	256QAM	25	0	20.05	20.11	19.94
Channel				26705	26740	26775
Frequency (MHz)				815.5	819	822.5
3	QPSK	1	0	24.99	24.98	24.81
3	QPSK	1	8	24.69	24.81	24.64
3	QPSK	1	14	24.97	24.79	24.70
3	QPSK	8	0	23.85	23.93	23.66
3	QPSK	8	4	23.79	23.82	23.58
3	QPSK	8	7	23.81	23.77	23.66
3	QPSK	15	0	23.77	23.83	23.64
3	16QAM	1	0	23.88	23.99	24.00
3	16QAM	1	8	23.87	23.95	23.71
3	16QAM	1	14	23.96	24.01	23.86
3	16QAM	8	0	22.71	22.78	22.72
3	16QAM	8	4	22.77	22.75	22.64
3	16QAM	8	7	22.76	22.75	22.68
3	16QAM	15	0	22.76	22.81	22.69
3	64QAM	1	0	22.87	22.91	22.92
3	64QAM	1	8	22.82	22.95	22.72
3	64QAM	1	14	22.94	22.96	22.87
3	64QAM	8	0	21.75	21.86	21.67
3	64QAM	8	4	21.73	21.70	21.58
3	64QAM	8	7	21.83	21.82	21.63
3	64QAM	15	0	21.76	21.72	21.68
3	256QAM	1	0	20.20	20.19	20.17
3	256QAM	1	8	20.13	20.25	20.04
3	256QAM	1	14	20.13	20.18	20.02
3	256QAM	8	0	20.17	20.00	20.00
3	256QAM	8	4	20.04	19.94	19.95
3	256QAM	8	7	20.03	20.03	20.00
3	256QAM	15	0	20.06	20.05	20.03
Channel				26697	26740	26783
Frequency (MHz)				814.7	819	823.3
1.4	QPSK	1	0	24.96	24.97	24.75
1.4	QPSK	1	3	24.74	24.84	24.59
1.4	QPSK	1	5	24.94	24.85	24.74
1.4	QPSK	3	0	24.91	24.94	24.80
1.4	QPSK	3	1	24.70	24.84	24.61
1.4	QPSK	3	3	24.97	24.82	24.75
1.4	QPSK	6	0	23.91	23.91	23.72
1.4	16QAM	1	0	23.79	23.78	23.62
1.4	16QAM	1	3	23.82	23.78	23.66
1.4	16QAM	1	5	23.73	23.83	23.72
1.4	16QAM	3	0	23.87	23.93	24.03
1.4	16QAM	3	1	23.85	24.00	23.75
1.4	16QAM	3	3	23.94	24.01	23.94
1.4	16QAM	6	0	22.70	22.78	22.64
1.4	64QAM	1	0	22.79	22.71	22.63



1.4	64QAM	1	3	22.81	22.79	22.67
1.4	64QAM	1	5	22.77	22.74	22.70
1.4	64QAM	3	0	22.84	22.86	22.97
1.4	64QAM	3	1	22.79	22.98	22.73
1.4	64QAM	3	3	22.97	22.91	22.82
1.4	64QAM	6	0	21.72	21.82	21.70
1.4	256QAM	1	0	20.10	20.17	20.21
1.4	256QAM	1	3	20.20	20.17	20.16
1.4	256QAM	1	5	20.05	20.07	20.09
1.4	256QAM	3	0	20.12	19.95	19.99
1.4	256QAM	3	1	20.01	19.99	20.00
1.4	256QAM	3	3	20.04	20.04	19.89
1.4	256QAM	6	0	19.93	20.05	19.94



LTE Band 26


26dB Bandwidth

Mode	LTE Band 26 : 26dB BW(MHz)	
BW	15MHz	
Mod.	QPSK	16QAM
Mid CH	14.66	14.60
BW	10MHz	
Mod.	QPSK	16QAM
Mid CH	9.65	9.71
BW	5MHz	
Mod.	QPSK	16QAM
Mid CH	4.88	4.75
BW	3MHz	
Mod.	QPSK	16QAM
Mid CH	3.00	2.98
BW	1.4MHz	
Mod.	QPSK	16QAM
Mid CH	1.29	1.26




LTE Band 26

Middle Channel / 15MHz / QPSK




Date: 12.MAY.2024 04:30:35

Middle Channel / 15MHz / 16QAM




Date: 12.MAY.2024 04:31:41

Middle Channel / 10MHz / QPSK



Date: 12.MAY.2024 04:38:03


Middle Channel / 10MHz / 16QAM



Date: 12.MAY.2024 04:38:25


LTE Band 26

Middle Channel / 5MHz / QPSK



Date: 12.MAY.2024 04:39:33

Middle Channel / 5MHz / 16QAM




Date: 12.MAY.2024 04:39:55




LTE Band 26

Middle Channel / 3MHz / QPSK



Date: 12.MAY.2024 04:41:03


Middle Channel / 3MHz / 16QAM



Date: 12.MAY.2024 04:41:25


LTE Band 26

Middle Channel / 1.4MHz / QPSK



Date: 12.MAY.2024 04:42:33

Middle Channel / 1.4MHz / 16QAM



Date: 12.MAY.2024 04:42:55




Occupied Bandwidth

Mode	LTE Band 26 : 99%OBW(MHz)	
BW	15MHz	
Mod.	QPSK	16QAM
Mid CH	14.43	13.37
BW	10MHz	
Mod.	QPSK	16QAM
Mid CH	9.05	8.99
BW	5MHz	
Mod.	QPSK	16QAM
Mid CH	4.48	4.49
BW	3MHz	
Mod.	QPSK	16QAM
Mid CH	2.72	2.72
BW	1.4MHz	
Mod.	QPSK	16QAM
Mid CH	1.10	1.10




LTE Band 26

Middle Channel / 15MHz / QPSK




Date: 12.MAY.2024 04:30:57

Middle Channel / 15MHz / 16QAM




Date: 12.MAY.2024 04:31:20

Middle Channel / 10MHz / QPSK



Date: 12.MAY.2024 04:37:41


Middle Channel / 10MHz / 16QAM



Date: 12.MAY.2024 04:38:46


LTE Band 26

Middle Channel / 5MHz / QPSK



Date: 12.MAY.2024 04:39:10

Middle Channel / 5MHz / 16QAM




Date: 12.MAY.2024 04:40:17




LTE Band 26

Middle Channel I / 3MHz / QPSK




Middle Channel / 3MHz / 16QAM




LTE Band 26

Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM






Conducted Band Edge


LTE Band 26 / 1.4MHz / QPSK

Lowest Band Edge / 1RB




Date: 12.MAY.2024 02:22:15

Highest Band Edge / 1RB




Date: 12.MAY.2024 02:49:59

Lowest Band Edge / Full RB



Date: 12.MAY.2024 02:28:40

Highest Band Edge / Full RB





Date: 12.MAY.2024 02:56:26



LTE Band 26 / 1.4MHz / 16QAM

Lowest Band Edge / 1 RB

Highest Band Edge / 1 RB





Date: 12.MAY.2024 02:23:54

Date: 12.MAY.2024 02:51:38

Lowest Band Edge / Full RB

Highest Band Edge / Full RB




Date: 12.MAY.2024 02:30:15

Date: 12.MAY.2024 02:58:01




LTE Band 26 / 1.4MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 12.MAY.2024 02:25:29

Highest Band Edge / 1 RB




Date: 12.MAY.2024 02:53:13

Lowest Band Edge / Full RB



Date: 12.MAY.2024 02:31:51

Highest Band Edge / Full RB




Date: 12.MAY.2024 02:59:37




LTE Band 26 / 1.4MHz / 256QAM

Lowest Band Edge / 1 RB




Date: 12.MAY.2024 02:27:04

Highest Band Edge / 1 RB




Date: 12.MAY.2024 02:54:50

Lowest Band Edge / Full RB



Date: 12.MAY.2024 02:33:26

Highest Band Edge / Full RB




Date: 12.MAY.2024 03:01:12




LTE Band 26 / 3MHz / QPSK

Lowest Band Edge / 1RB




Date: 12.MAY.2024 03:07:04

Highest Band Edge / 1 RB




Date: 12.MAY.2024 04:47:46

Lowest Band Edge / Full RB



Date: 12.MAY.2024 03:13:31

Highest Band Edge / Full RB




Date: 12.MAY.2024 03:30:23




LTE Band 26 / 3MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 12.MAY.2024 03:08:43

Highest Band Edge / 1 RB




Date: 12.MAY.2024 03:25:33

Lowest Band Edge / Full RB



Date: 12.MAY.2024 03:15:08

Highest Band Edge / Full RB




Date: 12.MAY.2024 03:31:59




LTE Band 26 / 3MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 12.MAY.2024 03:10:20

Highest Band Edge / 1 RB




Date: 12.MAY.2024 03:27:10

Lowest Band Edge / Full RB



Date: 12.MAY.2024 03:16:43

Highest Band Edge / Full RB





Date: 12.MAY.2024 03:33:35



LTE Band 26 / 3MHz / 256QAM

Lowest Band Edge / 1 RB

Highest Band Edge / 1 RB





Date: 12.MAY.2024 03:11:56

Date: 12.MAY.2024 03:28:47

Lowest Band Edge / Full RB

Highest Band Edge / Full RB



Date: 12.MAY.2024 03:18:18



Date: 12.MAY.2024 03:35:12



LTE Band 26 / 5MHz / QPSK

Lowest Band Edge / 1 RB

Highest Band Edge / 1 RB





Date: 12.MAY.2024 03:38:57

Date: 12.MAY.2024 03:50:48

Lowest Band Edge / Full RB

Highest Band Edge / Full RB




Date: 12.MAY.2024 03:43:24

Date: 12.MAY.2024 03:54:59




LTE Band 26 / 5MHz / 16QAM

Lowest Band Edge / 1RB




Date: 12.MAY.2024 03:40:21

Highest Band Edge / 1 RB




Date: 12.MAY.2024 03:51:42

Lowest Band Edge / Full RB



Date: 12.MAY.2024 03:44:15

Highest Band Edge / Full RB





Date: 12.MAY.2024 03:55:50



LTE Band 26 / 5MHz / 64QAM

Lowest Band Edge / 1RB

Highest Band Edge / 1 RB





Date: 12.MAY.2024 03:41:41

Date: 12.MAY.2024 03:52:34

Lowest Band Edge / Full RB

Highest Band Edge / Full RB



Date: 12.MAY.2024 03:45:07



Date: 12.MAY.2024 03:56:41



LTE Band 26 / 5MHz / 256QAM

Lowest Band Edge / 1RB

Highest Band Edge / 1 RB





Date: 12.MAY.2024 03:42:32

Date: 12.MAY.2024 03:53:23

Lowest Band Edge / Full RB

Highest Band Edge / Full RB



Date: 12.MAY.2024 03:45:58



Date: 12.MAY.2024 03:57:32



LTE Band 26 / 10MHz / QPSK

Middle Band Edge / 1 RB


Middle Band Edge / 1 RB max



Date: 12.MAY.2024 04:00:32

Date: 12.MAY.2024 04:12:38

Band Edge / Full RB





Date: 12.MAY.2024 04:03:56



LTE Band 26 / 10MHz / 16QAM

Middle Band Edge / 1 RB


Middle Band Edge / 1 RB max



Date: 12.MAY.2024 04:01:25

Date: 12.MAY.2024 04:04:48

Band Edge / Full RB





Date: 12.MAY.2024 04:13:32



LTE Band 26 / 10MHz / 64QAM

Middle Band Edge / 1 RB


Middle Band Edge / 1 RB max



Date: 12.MAY.2024 04:02:15

Date: 12.MAY.2024 04:10:11

Band Edge / Full RB





Date: 12.MAY.2024 04:14:23



LTE Band 26 / 10MHz / 256QAM

Middle Band Edge / 1 RB


Middle Band Edge / 1 RB max



Date: 12.MAY.2024 04:03:06

Date: 12.MAY.2024 04:11:02

Band Edge / Full RB




Date: 12.MAY.2024 04:15:13




LTE Band 26 / 15MHz / QPSK

Middle Band Edge / 1 RB

Middle Band Edge / 1 RB max




Date: 12.MAY.2024 04:19:20



Date: 12.MAY.2024 04:23:29

Band Edge / Full RB





Date: 12.MAY.2024 04:27:41



LTE Band 26 / 15MHz / 16QAM

Middle Band Edge / 1 RB


Middle Band Edge / 1 RB max



Date: 12.MAY.2024 04:20:13

Date: 12.MAY.2024 04:24:22

Band Edge / Full RB




Date: 12.MAY.2024 04:28:31




LTE Band 26 / 15MHz / 64QAM

Middle Band Edge / 1 RB

Middle Band Edge / 1 RB max




Date: 12.MAY.2024 04:21:03



Date: 12.MAY.2024 04:25:13

Band Edge / Full RB



Date: 12.MAY.2024 04:29:21