



# FCC RF Test Report

**APPLICANT** : Xiaomi Communications Co., Ltd.  
**EQUIPMENT** : Mobile Phone  
**BRAND NAME** : Redmi  
**MODEL NAME** : 23090RA98G  
**FCC ID** : 2AFZZRA98G  
**STANDARD** : 47 CFR Part 2, Part 27 Subpart Q  
**CLASSIFICATION** : PCS Licensed Transmitter Held to Ear (PCE)  
**TEST DATE(S)** : Aug. 15, 2023 ~ Aug. 20, 2023

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

**Sporton International Inc. (ShenZhen)**

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055**

**People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY..... 3
SUMMARY OF TEST RESULT ..... 4
1 GENERAL DESCRIPTION ..... 5
1.1 Applicant..... 5
1.2 Manufacturer..... 5
1.3 Product Feature of Equipment Under Test..... 5
1.4 Product Specification of Equipment Under Test..... 6
1.5 Modification of EUT ..... 6
1.6 Maximum EIRP Power and Emission Designator ..... 7
1.7 Testing Site..... 8
1.8 Test Software..... 8
1.9 Applied Standards ..... 9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 10
2.1 Test Mode..... 10
2.2 Connection Diagram of Test System..... 11
2.3 Support Unit used in test configuration and system ..... 11
2.4 Measurement Results Explanation Example..... 11
2.5 Frequency List of Low/Middle/High Channels ..... 12
3 CONDUCTED TEST ITEMS ..... 14
3.1 Measuring Instruments ..... 14
3.2 Test Setup ..... 14
3.3 Test Result of Conducted Test ..... 14
3.4 Conducted Output Power Measurement ..... 15
3.5 Peak-to-Average Ratio ..... 16
3.6 EIRP ..... 17
3.7 Occupied Bandwidth..... 18
3.8 Conducted Band Edge Measurement ..... 19
3.9 Conducted Spurious Emission Measurement ..... 20
3.10 Frequency Stability Measurement ..... 21
4 RADIATED TEST ITEMS ..... 22
4.1 Measuring Instruments ..... 22
4.2 Test Setup ..... 22
4.3 Test Result of Radiated Test ..... 23
4.4 Radiated Spurious Emission Measurement ..... 24
5 LIST OF MEASURING EQUIPMENT ..... 25
6 MEASUREMENT UNCERTAINTY ..... 26
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS



### REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG380206H	Rev. 01	Initial issue of report	Sep. 15, 2023



### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	—	Report Only	-
3.5	§27.50 (k)(4)	Peak-to-Average Ratio	<13dB	PASS	
3.6	§27.50 (k)(3)	EIRP	EIRP < 1W (30dBm)	PASS	-
3.7	§2.1049	Occupied Bandwidth	—	Report Only	-
3.8	§2.1051 §27.53 (n)(2)	Conducted Band Edge Measurement	-13dBm/MHz	PASS	-
3.9	§2.1051 §27.53 (n)(2)	Conducted Spurious Emission	-13dBm/MHz	PASS	-
3.10	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within the band	PASS	-
4.4	§2.1053 §27.53 (n)(2)	Radiated Spurious Emission	-13dBm/MHz	PASS	Under limit 32.05 dB at 10362.00 MHz

**Conformity Assessment Condition:**

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

# 1 General Description

## 1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Redmi
Model Name	23090RA98G
FCC ID	2AFZZRA98G
IMEI Code	Conducted : 864595060044447/864595060044454 Radiation : 864595060044405/864595060044413
HW Version	1351N16UM0A01
SW Version	MIUI 14
EUT Stage	Identical Prototype

## 1.4 Product Specification of Equipment Under Test

Product Feature	
<b>Tx/Rx Frequency</b>	5G NR n77: 3450 MHz ~ 3550 MHz 5G NR n78: 3450 MHz ~ 3550 MHz
<b>SCS</b>	30kHz
<b>Bandwidth</b>	n77: 20 / 40 / 50 / 60 / 80 / 90 / 100MHz n78: 20 / 30 / 40 / 50 / 60 / 70 / 80 / 90 / 100MHz
<b>Antenna Gain</b>	<p><b>&lt;Ant. 1&gt;</b> 5G NR n77: -2.3 dBi 5G NR n78: -2.3 dBi</p> <p><b>&lt;Ant. 6&gt;</b> 5G NR n77: 1.9 dBi 5G NR n78: 1.9 dBi</p> <p><b>&lt;Ant. 7&gt;</b> 5G NR n77: -1.2 dBi 5G NR n78: -1.2 dBi</p> <p><b>&lt;Ant. 8&gt;</b> 5G NR n77: 1.2 dBi 5G NR n78: 1.2 dBi</p>
<b>Type of Modulation</b>	CP-OFDM: QPSK / 16QAM / 64QAM / 256QAM DFT-s-OFDM: PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM

**Remark:**

1. The maximum EIRP is calculated from max output power and max antenna gain, only the maximum EIRP of Antenna 6 for 5G NR n77/n78 is shown in the report.
2. The device supports n77(1T4R) SRS resources on Antenna 1/6/7/8, only the test data of worst Antenna 6 is showed in the report according to the maximum power.
3. 5G NR n78 support SA and NSA mode, n77 supports SA mode only. The whole testing has assessed SA mode for n77 by referring to the higher conducted power for conducted test items, and n78 additional test BW 30M/70MHz.
4. The device supports HPUE mode for 5G NR n77/n78.
5. The EN-DC mode combination could be referred to the product spec.

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Maximum EIRP Power and Emission Designator

5G NR n77 SA		PI/2 BPSK / QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
20	3460.02 ~ 3540.00	0.7244	18M2G7D	0.5598	18M2W7D
40	3470.01 ~ 3529.98	0.6531	37M8G7D	0.5445	37M8W7D
50	3475.02 ~ 3525.00	0.7145	47M4G7D	0.5559	47M5W7D
60	3480.00 ~ 3519.99	0.6934	57M7G7D	0.5395	57M9W7D
80	3490.02 ~ 3510.00	0.6683	77M5G7D	0.5200	77M4W7D
90	3495.00 ~ 3504.99	0.6427	87M3G7D	0.5012	87M5W7D
100	3500.01	0.7261	97M2G7D	0.5754	97M4W7D

5G NR n78 SA		PI/2 BPSK / QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
20	3460.02 ~ 3540.00	0.7244	18M2G7D	0.5598	18M2W7D
30	3465.00 ~ 3534.99	0.6934	27M9G7D	0.5420	27M8W7D
40	3470.01 ~ 3529.98	0.6531	37M8G7D	0.5445	37M8W7D
50	3475.02 ~ 3525.00	0.7145	47M4G7D	0.5559	47M5W7D
60	3480.00 ~ 3519.99	0.6934	57M7G7D	0.5395	57M9W7D
70	3485.01 ~ 3514.98	0.6887	67M3G7D	0.5260	67M5W7D
80	3490.02 ~ 3510.00	0.6683	77M5G7D	0.5200	77M4W7D
90	3495.00 ~ 3504.99	0.6427	87M3G7D	0.5012	87M5W7D
100	3500.01	0.7261	97M2G7D	0.5754	97M4W7D

**Note:**

1. 5G NR Band n77 overlaps the entire frequency range of Band n78, and n77 power > n78 power, therefore the conducted test results of n77 provided in this report cover n78 except the bandwidth of 30M and 70M.
2. All modulations have been tested, and only the worst test results of PSK & QAM are shown in the report.

### 1.7 Testing Site

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

<b>Test Firm</b>	Sporton International Inc. (ShenZhen)		
<b>Test Site Location</b>	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	TH01-SZ	CN1256	421272

<b>Test Firm</b>	Sporton International Inc. (ShenZhen)		
<b>Test Site Location</b>	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	03CH03-SZ	CN1256	421272

### 1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH03-SZ	AUDIX	E3	6.2009-8-24





## 1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, Part 27 Subpart Q
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 Power Meas License Digital Systems D01 v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.


Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission. (Y Plane)

Test Cases	Band	Bandwidth (MHz)	Modulation	RB #	Test Channel
		eg. 5M, 10M, 15M, 20M	eg. PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM	1RB, Partial RB, Full RB	L/M/H
Max. Output Power	5G n77	20M, 40M, 50M, 60M, 80M, 90M ,100M	All Modulations	1RB, Full RB	L, M, H
	5G n78	30M, 70M	All Modulations	1RB, Full RB	L, M, H
Peak-to-Average Ratio	5G n77	20M	PI/2 BPSK, QPSK	1RB, Full RB	M,
E.I.R.P	5G n77	20M, 40M, 50M, 60M, , 80M, 90M ,100M	All Modulations	1RB, Full RB	L, M, H
	5G n78	30M, 70M	All Modulations	1RB, Full RB	L, M, H
26dB and 99% Bandwidth	5G n77	20M, 40M, 50M, 60M, 80M, 90M ,100M	All Modulations	Full RB	M
	5G n78	30M, 70M	QPSK, 16QAM, 64QAM, 256QAM	Full RB	M
Conducted Band Edge	5G n77	20M, 60M, 100M	PI/2 BPSK, QPSK	1RB, Full RB	L, H
	5G n78	30M, 70M	BPSK, QPSK	1RB, Full RB	L, H
Conducted Spurious Emission	5G n77	20M, 60M, 100M	PI/2 BPSK, QPSK	1RB	L, M, H
	5G n78	30M, 70M	BPSK, QPSK	1RB	L, M, H
Frequency Stability	5G n77	20M	QPSK	Full RB	M
Radiated Spurious Emission	5G n77	Worst case from maximum power			M
	5G n78	Worst case from maximum power			M

**Note:**

1. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.
2. Frequency Stability: Normal Voltage = 3.88V ; Low Voltage =3.6V.; High Voltage =4.3V.

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	NR Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded, 1.8 m

## 2.4 Measurement Results Explanation Example

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 5.82 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5.82 + 10 = 15.82 \text{ (dB)} \end{aligned}$$



### 2.5 Frequency List of Low/Middle/High Channels

5G n77 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
100	Channel	-	633334	-
	Frequency	-	3500.01	-
90	Channel	633000	633334	633666
	Frequency	3495	3500.01	3504.99
80	Channel	632668	633334	634000
	Frequency	3490.02	3500.01	3510
60	Channel	632000	633334	634666
	Frequency	3480	3500.01	3519.99
50	Channel	631668	633334	635000
	Frequency	3475.02	3500.01	3525
40	Channel	631334	633334	635332
	Frequency	3470.01	3500.01	3529.98
20	Channel	630668	633334	636000
	Frequency	3460.02	3500.01	3540



5G n78 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
100	Channel	-	633334	-
	Frequency	-	3500.01	-
90	Channel	633000	633334	633666
	Frequency	3495	3500.01	3504.99
80	Channel	632668	633334	634000
	Frequency	3490.02	3500.01	3510
70	Channel	632334	633334	634332
	Frequency	3485.01	3500.01	3514.98
60	Channel	632000	633334	634666
	Frequency	3480	3500.01	3519.99
50	Channel	631668	633334	635000
	Frequency	3475.02	3500.01	3525
40	Channel	631334	633334	635332
	Frequency	3470.01	3500.01	3529.98
30	Channel	631000	633334	635666
	Frequency	3465	3500.01	3534.99
20	Channel	630668	633334	636000
	Frequency	3460.02	3500.01	3540


### 3 Conducted Test Items

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup


##### 3.2.1 Conducted Output Power



##### 3.2.2 Peak-to-Average Ratio, Occupied / 26dB Bandwidth, Band-Edge and Conducted Spurious Emission



##### 3.2.3 Frequency Stability



### 3.3 Test Result of Conducted Test

Please refer to Appendix A.



## 3.4 Conducted Output Power Measurement

### 3.4.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

### 3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

## **3.5 Peak-to-Average Ratio**

### **3.5.1 Description of the PAR Measurement**

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### **3.5.2 Test Procedures**

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



## 3.6 EIRP

### 3.6.1 Description of EIRP Limit

#### § 27.50 (k)(3)

Mobile devices are limited to 1Watt (30 dBm) EIRP. Mobile devices operating in these bands must employ a means for limiting power to the minimum necessary for successful communications

### 3.6.2 Test Procedures

1. According to KDB 412172 D01 Power Approach,
2.  $EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where  
 $P_T$  = transmitter output power in dBm  
 $G_T$  = gain of the transmitting antenna in dBi  
 $L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

## 3.7 Occupied Bandwidth

### 3.7.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

### 3.7.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.  
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

## 3.8 Conducted Band Edge Measurement

### 3.8.1 Description of Conducted Band Edge Measurement

#### § 27.53 (n)(2)

For mobile operations in the 3450-3550 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed  $-13$  dBm/MHz.

Compliance with this paragraph is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed, but limited to a maximum of 200 kHz. In the bands between 1 and 5 MHz removed from the licensee's frequency block, the minimum resolution bandwidth for the measurement shall be 500 kHz.

### 3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW  $\geq$  1% EBW but limited to a maximum of 200 kHz in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz and 5 MHz removed from the band edge, set RBW  $\geq$  500KHz.
6. Beyond the 5 MHz removed from the band edge, set RBW = 1MHz.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. Checked that all the results comply with the emission limit line.

## 3.9 Conducted Spurious Emission Measurement

### 3.9.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges shall not exceed -13 dBm/MHz.

It is measured by means of a calibrated spectrum analyzer and scanned from 9 kHz up to a frequency including its 10<sup>th</sup> harmonic.

### 3.9.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.  
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. Checked that all the results comply with the emission limit line.

## 3.10 Frequency Stability Measurement

### 3.10.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block.

### 3.10.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.10.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at  $20\pm 5^{\circ}\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup


#### 4.2.1 For radiated test below 30MHz



#### 4.2.2 For radiated test from 30MHz to 1GHz



### 4.2.3 For radiated test above 1GHz



### 4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

## 4.4 Radiated Spurious Emission Measurement

### 4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission outside of the authorized operating frequency ranges shall not exceed -13 dBm/MHz.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.  
$$\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$$
$$\text{ERP (dBm)} = \text{EIRP} - 2.15$$
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.





## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 06, 2023	Aug. 15, 2023~ Aug. 16, 2023	Apr. 05, 2024	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V , 3A	Oct. 17, 2022	Aug. 15, 2023~ Aug. 16, 2023	Oct. 16, 2023	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 25, 2022	Aug. 15, 2023~ Aug. 16, 2023	Dec. 24, 2023	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 05, 2023	Aug. 15, 2023~ Aug. 16, 2023	Jul. 04, 2024	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 04, 2023	Aug. 20, 2023	Apr. 03, 2024	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 04, 2023	Aug. 20, 2023	Apr. 03, 2024	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jun. 28, 2022	Aug. 20, 2023	Jun. 27, 2024	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz-2GHz	Aug. 20, 2023	Aug. 20, 2023	Aug. 19, 2025	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Apr. 08, 2023	Aug. 20, 2023	Apr. 07, 2024	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 08, 2023	Aug. 20, 2023	Apr. 07, 2024	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 19, 2022	Aug. 20, 2023	Oct. 18, 2023	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 07, 2023	Aug. 20, 2023	Jul.06, 2024	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Dec. 26, 2022	Aug. 20, 2023	Dec. 25, 2023	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010002729	N/A	Nov. 10, 2022	Aug. 20, 2023	Nov. 09, 2023	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Aug. 20, 2023	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Aug. 20, 2023	NCR	Radiation (03CH03-SZ)

NCR: No Calibration Required

## 6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±1.34 dB
Conducted Emissions	±1.34 dB
Occupied Channel Bandwidth	±0.13 %

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3dB
---	-----

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.6dB
---	-------

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.8dB
---	-------

----- THE END -----



## Appendix A. Test Results of Conducted Test

Test Engineer :	Jung Guo	Temperature :	22~23°C
		Relative Humidity :	40~42%

# FR1 N77(ANT6)

## Transmitter Conducted Output Power And EIRP, (G<sub>T</sub> - L<sub>C</sub>)=1.9dB

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
77	30	20	630668	3460.02	DFT-s-OFDM QPSK	1@1	26.55	28.45	0.6998
77	30	20	630668	3460.02	DFT-s-OFDM 16 QAM	1@1	25.44	27.34	0.5420
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.68	28.58	0.7211
77	30	20	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.57	27.47	0.5585
77	30	20	636000	3540.0	DFT-s-OFDM QPSK	1@1	26.7	28.6	0.7244
77	30	20	636000	3540.0	DFT-s-OFDM 16 QAM	1@1	25.58	27.48	0.5598
77	30	40	631334	3470.01	DFT-s-OFDM QPSK	1@1	26.21	28.11	0.6471
77	30	40	631334	3470.01	DFT-s-OFDM 16 QAM	1@1	25.37	27.27	0.5333
77	30	40	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.22	28.12	0.6486
77	30	40	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.12	27.02	0.5035
77	30	40	635332	3529.98	DFT-s-OFDM QPSK	1@1	26.25	28.15	0.6531
77	30	40	635332	3529.98	DFT-s-OFDM 16 QAM	1@1	25.46	27.36	0.5445
77	30	50	631668	3475.02	DFT-s-OFDM QPSK	1@1	26.5	28.4	0.6918
77	30	50	631668	3475.02	DFT-s-OFDM 16 QAM	1@1	25.49	27.39	0.5483
77	30	50	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.59	28.49	0.7063
77	30	50	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.5	27.4	0.5495
77	30	50	635000	3525.0	DFT-s-OFDM QPSK	1@1	26.64	28.54	0.7145
77	30	50	635000	3525.0	DFT-s-OFDM 16 QAM	1@1	25.55	27.45	0.5559
77	30	60	632000	3480.0	DFT-s-OFDM QPSK	1@1	26.45	28.35	0.6839
77	30	60	632000	3480.0	DFT-s-OFDM 16 QAM	1@1	25.31	27.21	0.5260
77	30	60	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.43	28.33	0.6808
77	30	60	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.32	27.22	0.5272

77	30	60	634666	3519.99	DFT-s-OFDM QPSK	1@1	26.51	28.41	0.6934
77	30	60	634666	3519.99	DFT-s-OFDM 16 QAM	1@1	25.42	27.32	0.5395
77	30	80	632668	3490.02	DFT-s-OFDM QPSK	1@1	26.32	28.22	0.6637
77	30	80	632668	3490.02	DFT-s-OFDM 16 QAM	1@1	25.17	27.07	0.5093
77	30	80	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.31	28.21	0.6622
77	30	80	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.17	27.07	0.5093
77	30	80	634000	3510.0	DFT-s-OFDM QPSK	1@1	26.35	28.25	0.6683
77	30	80	634000	3510.0	DFT-s-OFDM 16 QAM	1@1	25.26	27.16	0.5200
77	30	90	633000	3495.0	DFT-s-OFDM QPSK	1@1	26.16	28.06	0.6397
77	30	90	633000	3495.0	DFT-s-OFDM 16 QAM	1@1	25.1	27	0.5012
77	30	90	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.12	28.02	0.6339
77	30	90	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.02	26.92	0.4920
77	30	90	633666	3504.99	DFT-s-OFDM QPSK	1@1	26.18	28.08	0.6427
77	30	90	633666	3504.99	DFT-s-OFDM 16 QAM	1@1	25.05	26.95	0.4955
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	135@67	26.68	28.58	0.7211
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.02	27.92	0.6194
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@271	25.59	27.49	0.5610
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	135@67	26.71	28.61	0.7261
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.02	27.92	0.6194
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@271	25.58	27.48	0.5598
77	30	100	633334	3500.01	DFT-s-OFDM 16 QAM	135@67	25.7	27.6	0.5754
77	30	100	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	24.88	26.78	0.4764
77	30	100	633334	3500.01	DFT-s-OFDM 16 QAM	1@271	24.52	26.42	0.4385
77	30	100	633334	3500.01	DFT-s-OFDM 64 QAM	135@67	24.2	26.1	0.4074
77	30	100	633334	3500.01	DFT-s-OFDM 64 QAM	1@1	23.51	25.41	0.3475
77	30	100	633334	3500.01	DFT-s-OFDM 64 QAM	1@271	23.14	25.04	0.3192
77	30	100	633334	3500.01	DFT-s-OFDM 256 QAM	135@67	22.15	24.05	0.2541

<b>77</b>	30	100	633334	3500.01	DFT-s-OFDM 256 QAM	1@1	21.22	23.12	0.2051
<b>77</b>	30	100	633334	3500.01	DFT-s-OFDM 256 QAM	1@271	20.8	22.7	0.1862
<b>77</b>	30	100	633334	3500.01	CP-OFDM QPSK	137@68	25.19	27.09	0.5117
<b>77</b>	30	100	633334	3500.01	CP-OFDM QPSK	1@1	24.56	26.46	0.4426
<b>77</b>	30	100	633334	3500.01	CP-OFDM QPSK	1@271	24.11	26.01	0.3990

## Frequency Stability


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (ppm)	Verdict	Environment
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0034	PASS	NV
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0031	PASS	LV
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0063	PASS	HV
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0031	PASS	-30°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0051	PASS	-20°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0051	PASS	-10°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0041	PASS	0°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0038	PASS	10°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0034	PASS	20°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0050	PASS	30°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0046	PASS	40°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0029	PASS	50°C

## Peak to Average Ratio

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result (dB)	Limit (dB)	Verdict
77	30	20	633334	3500.01	DFT-s-OFDM PI/2 BPSK	50@0	7.1	13	PASS
77	30	20	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@0	7.79	13	PASS
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	8.23	13	PASS
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	1@0	8.43	13	PASS



N77(20M)\_DFT-s-OFDM\_PI\_2-BPSK\_Outer\_Full\_Mid\_CH




N77(20M)\_DFT-s-OFDM\_PI\_2-BPSK\_Edge\_1RB\_Left\_Mid\_CH



N77(20M)\_DFT-s-OFDM\_QPSK\_Outer\_Full\_Mid\_CH



N77(20M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Mid\_CH




## Occupied Bandwidth


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	OBW (MHz)	26dB BW (MHz)
77	30	20	633334	3500.01	CP-OFDM QPSK	51@0	18.181	19.03
77	30	20	633334	3500.01	CP-OFDM 16 QAM	51@0	18.2	19.0
77	30	20	633334	3500.01	CP-OFDM 64 QAM	51@0	18.177	18.95
77	30	20	633334	3500.01	CP-OFDM 256 QAM	51@0	18.215	18.85
77	30	40	633334	3500.01	CP-OFDM QPSK	106@0	37.804	39.15
77	30	40	633334	3500.01	CP-OFDM 16 QAM	106@0	37.823	39.13
77	30	40	633334	3500.01	CP-OFDM 64 QAM	106@0	37.769	39.15
77	30	40	633334	3500.01	CP-OFDM 256 QAM	106@0	37.746	39.06
77	30	50	633334	3500.01	CP-OFDM QPSK	133@0	47.398	49.09
77	30	50	633334	3500.01	CP-OFDM 16 QAM	133@0	47.426	49.11
77	30	50	633334	3500.01	CP-OFDM 64 QAM	133@0	47.337	49.02
77	30	50	633334	3500.01	CP-OFDM 256 QAM	133@0	47.481	49.04
77	30	60	633334	3500.01	CP-OFDM QPSK	162@0	57.683	59.72
77	30	60	633334	3500.01	CP-OFDM 16 QAM	162@0	57.869	59.67
77	30	60	633334	3500.01	CP-OFDM 64 QAM	162@0	57.948	59.61
77	30	60	633334	3500.01	CP-OFDM 256 QAM	162@0	57.738	59.7
77	30	80	633334	3500.01	CP-OFDM QPSK	217@0	77.476	79.87
77	30	80	633334	3500.01	CP-OFDM 16 QAM	217@0	77.437	79.87
77	30	80	633334	3500.01	CP-OFDM 64 QAM	217@0	77.443	79.94
77	30	80	633334	3500.01	CP-OFDM 256 QAM	217@0	77.417	79.92
77	30	90	633334	3500.01	CP-OFDM QPSK	245@0	87.297	90.21
77	30	90	633334	3500.01	CP-OFDM 16 QAM	245@0	87.525	90.17
77	30	90	633334	3500.01	CP-OFDM 64 QAM	245@0	87.438	90.23
77	30	90	633334	3500.01	CP-OFDM 256 QAM	245@0	87.464	90.29
77	30	100	633334	3500.01	CP-OFDM QPSK	273@0	97.21	100.5

<b>77</b>	30	100	633334	3500.01	CP-OFDM 16 QAM	273@0	97.025	100.5
<b>77</b>	30	100	633334	3500.01	CP-OFDM 64 QAM	273@0	97.437	100.5
<b>77</b>	30	100	633334	3500.01	CP-OFDM 256 QAM	273@0	97.141	100.4

### N77(20M)\_CP-OFDM\_QPSK\_Outer\_Full\_Mid\_CH




### N77(20M)\_CP-OFDM\_16QAM\_Outer\_Full\_Mid\_CH




### N77(20M)\_CP-OFDM\_64QAM\_Outer\_Full\_Mid\_CH




### N77(20M)\_CP-OFDM\_256QAM\_Outer\_Full\_Mid\_CH




### N77(40M)\_CP-OFDM\_QPSK\_Outer\_Full\_Mid\_CH




### N77(40M)\_CP-OFDM\_16QAM\_Outer\_Full\_Mid\_CH




### N77(40M)\_CP-OFDM\_64 QAM\_Outer\_Full\_Mid\_CH




### N77(40M)\_CP-OFDM\_256 QAM\_Outer\_Full\_Mid\_CH




### N77(50M)\_CP- OFDM\_QPSK\_Outer\_Full\_Mid\_CH




### N77(50M)\_CP-OFDM\_16 QAM\_Outer\_Full\_Mid\_CH




### N77(50M)\_CP-OFDM\_64 QAM\_Outer\_Full\_Mid\_CH




### N77(50M)\_CP-OFDM\_256 QAM\_Outer\_Full\_Mid\_CH




### N77(60M)\_CP-OFDM\_QPSK\_Outer\_Full\_Mid\_CH




### N77(60M)\_CP-OFDM\_16QAM\_Outer\_Full\_Mid\_CH




### N77(60M)\_CP-OFDM\_64QAM\_Outer\_Full\_Mid\_CH




### N77(60M)\_CP-OFDM\_256QAM\_Outer\_Full\_Mid\_CH




### N77(80M)\_CP-OFDM\_QPSK\_Outer\_Full\_Mid\_CH




### N77(80M)\_CP-OFDM\_16QAM\_Outer\_Full\_Mid\_CH




### N77(80M)\_CP-OFDM\_64 QAM\_Outer\_Full\_Mid\_CH



### N77(80M)\_CP-OFDM\_256 QAM\_Outer\_Full\_Mid\_CH




### N77(90M)\_CP- OFDM\_QPSK\_Outer\_Full\_Mid\_CH




### N77(90M)\_CP-OFDM\_16 QAM\_Outer\_Full\_Mid\_CH




### N77(90M)\_CP-OFDM\_64 QAM\_Outer\_Full\_Mid\_CH




### N77(90M)\_CP-OFDM\_256 QAM\_Outer\_Full\_Mid\_CH



### N77(100M)\_CP- OFDM\_QPSK\_Outer\_Full\_Mid\_CH




### N77(100M)\_CP-OFDM\_16 QAM\_Outer\_Full\_Mid\_CH



### N77(100M)\_CP-OFDM\_64 QAM\_Outer\_Full\_Mid\_CH



### N77(100M)\_CP-OFDM\_256 QAM\_Outer\_Full\_Mid\_CH





## Conducted Spurious Emissions


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
77	30	20	630668	3460.02	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	20	630668	3460.02	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	630668	3460.02	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	630668	3460.02	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	20	630668	3460.02	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	20	630668	3460.02	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	20	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	20	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	20	636000	3540.0	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	20	636000	3540.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	636000	3540.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	636000	3540.0	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	20	636000	3540.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	20	636000	3540.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	60	632000	3480.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM QPSK	1@0	see graph	---

77	30	60	632000	3480.0	DFT-s-OFDM QPSK	1@0	see graph	<b>PASS</b>
77	30	60	632000	3480.0	DFT-s-OFDM QPSK	1@0	see graph	<b>PASS</b>
77	30	60	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	60	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	<b>PASS</b>
77	30	60	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	<b>PASS</b>
77	30	60	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	60	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	<b>PASS</b>
77	30	60	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	<b>PASS</b>
77	30	60	634666	3519.99	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	60	634666	3519.99	DFT-s-OFDM BPSK	1@0	see graph	<b>PASS</b>
77	30	60	634666	3519.99	DFT-s-OFDM BPSK	1@0	see graph	<b>PASS</b>
77	30	60	634666	3519.99	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	60	634666	3519.99	DFT-s-OFDM QPSK	1@0	see graph	<b>PASS</b>
77	30	60	634666	3519.99	DFT-s-OFDM QPSK	1@0	see graph	<b>PASS</b>
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	<b>PASS</b>
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	<b>PASS</b>
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	<b>PASS</b>
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	<b>PASS</b>


N77(20M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_Low\_CH




N77(20M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_Low\_CH




N77(20M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Low\_CH




N77(20M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Low\_CH




N77(20M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_Mid\_CH




N77(20M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_Mid\_CH




N77(20M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Mid\_CH




N77(20M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Mid\_CH




N77(20M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_High\_CH




N77(20M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_High\_CH




N77(20M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_High\_CH




N77(20M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_High\_CH




N77(60M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_Low\_CH




N77(60M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_Low\_CH



N77(60M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Low\_CH




N77(60M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Low\_CH




N77(60M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_Mid\_CH




N77(60M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_Mid\_CH



N77(60M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Mid\_CH




N77(60M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Mid\_CH




N77(60M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_High\_CH




N77(60M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_High\_CH



N77(60M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_High\_CH




N77(60M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_High\_CH



### N77(100M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_Mid\_CH




### N77(100M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_Mid\_CH



### N77(100M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Mid\_CH



### N77(100M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Mid\_CH




## Conducted Band Edge


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
77	30	20	630668	3460.02	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	630668	3460.02	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	20	630668	3460.02	DFT-s-OFDM BPSK	50@0	see graph	PASS
77	30	20	630668	3460.02	DFT-s-OFDM QPSK	50@0	see graph	PASS
77	30	20	636000	3540.0	DFT-s-OFDM BPSK	1@50	see graph	PASS
77	30	20	636000	3540.0	DFT-s-OFDM QPSK	1@50	see graph	PASS
77	30	20	636000	3540.0	DFT-s-OFDM BPSK	50@0	see graph	PASS
77	30	20	636000	3540.0	DFT-s-OFDM QPSK	50@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM BPSK	162@0	see graph	PASS
77	30	60	632000	3480.0	DFT-s-OFDM QPSK	162@0	see graph	PASS
77	30	60	634666	3519.99	DFT-s-OFDM BPSK	1@161	see graph	PASS
77	30	60	634666	3519.99	DFT-s-OFDM QPSK	1@161	see graph	PASS
77	30	60	634666	3519.99	DFT-s-OFDM BPSK	162@0	see graph	PASS
77	30	60	634666	3519.99	DFT-s-OFDM QPSK	162@0	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@272	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@272	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	270@0	see graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	270@0	see graph	PASS




N77(20M)\_DFT-s-  
OFDM\_BPSK\_Edge\_1RB\_Left\_Low\_CH




N77(20M)\_DFT-s-  
OFDM\_QPSK\_Edge\_1RB\_Left\_Low\_CH




N77(20M)\_DFT-s-  
OFDM\_BPSK\_Outer\_Full\_Low\_CH




N77(20M)\_DFT-s-  
OFDM\_QPSK\_Outer\_Full\_Low\_CH



N77(20M)\_DFT-s-  
OFDM\_BPSK\_Edge\_1RB\_Right\_High\_CH




N77(20M)\_DFT-s-  
OFDM\_QPSK\_Edge\_1RB\_Right\_High\_CH




N77(20M)\_DFT-s-OFDM\_BPSK\_Outer\_Full\_High\_CH




N77(20M)\_DFT-s-OFDM\_QPSK\_Outer\_Full\_High\_CH




N77(60M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_Low\_CH




N77(60M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Low\_CH




N77(60M)\_DFT-s-OFDM\_BPSK\_Outer\_Full\_Low\_CH




N77(60M)\_DFT-s-OFDM\_QPSK\_Outer\_Full\_Low\_CH




### N77(60M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Right\_High\_CH




### N77(60M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Right\_High\_CH




### N77(60M)\_DFT-s-OFDM\_BPSK\_Outer\_Full\_High\_CH




### N77(60M)\_DFT-s-OFDM\_QPSK\_Outer\_Full\_High\_CH



### N77(100M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Left\_Mid\_CH




### N77(100M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Left\_Mid\_CH




### N77(100M)\_DFT-s-OFDM\_BPSK\_Edge\_1RB\_Right\_Mid\_CH




### N77(100M)\_DFT-s-OFDM\_QPSK\_Edge\_1RB\_Right\_Mid\_CH



### N77(100M)\_DFT-s-OFDM\_BPSK\_Outer\_Full\_Mid\_CH



### N77(100M)\_DFT-s-OFDM\_QPSK\_Outer\_Full\_Mid\_CH



# FR1 N78(ANT6)


## Transmitter Conducted Output Power And EIRP, ( $G_T - L_C$ )=1.9dB

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
78	30	30	631000	3465.0	DFT-s-OFDM QPSK	1@1	26.46	28.36	0.6855
78	30	30	631000	3465.0	DFT-s-OFDM 16 QAM	1@1	25.35	27.25	0.5309
78	30	30	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.51	28.41	0.6934
78	30	30	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.4	27.3	0.5370
78	30	30	635666	3534.99	DFT-s-OFDM QPSK	1@1	26.48	28.38	0.6887
78	30	30	635666	3534.99	DFT-s-OFDM 16 QAM	1@1	25.44	27.34	0.5420
78	30	70	632334	3485.01	DFT-s-OFDM QPSK	1@1	26.39	28.29	0.6745
78	30	70	632334	3485.01	DFT-s-OFDM 16 QAM	1@1	25.31	27.21	0.5260
78	30	70	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.37	28.27	0.6714
78	30	70	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.31	27.21	0.5260
78	30	70	634332	3514.98	DFT-s-OFDM QPSK	1@1	26.48	28.38	0.6887
78	30	70	634332	3514.98	DFT-s-OFDM 16 QAM	1@1	25.3	27.2	0.5248


## Occupied Bandwidth

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	OBW (MHz)	26dB BW (MHz)
78	30	30	633334	3500.01	CP-OFDM QPSK	78@0	27.882	29.04
78	30	30	633334	3500.01	CP-OFDM 16 QAM	78@0	27.801	28.9
78	30	30	633334	3500.01	CP-OFDM 64 QAM	78@0	27.8	28.8
78	30	30	633334	3500.01	CP-OFDM 256 QAM	78@0	27.788	28.89
78	30	70	633334	3500.01	CP-OFDM QPSK	189@0	67.333	69.55
78	30	70	633334	3500.01	CP-OFDM 16 QAM	189@0	67.522	69.67
78	30	70	633334	3500.01	CP-OFDM 64 QAM	189@0	67.287	69.64
78	30	70	633334	3500.01	CP-OFDM 256 QAM	189@0	67.333	69.68


### N78(30M)\_CP- OFDM\_QPSK\_Outer\_Full\_Mid\_CH




### N78(30M)\_CP-OFDM\_16 QAM\_Outer\_Full\_Mid\_CH




### N78(30M)\_CP-OFDM\_64 QAM\_Outer\_Full\_Mid\_CH




### N78(30M)\_CP-OFDM\_256 QAM\_Outer\_Full\_Mid\_CH




### N78(70M)\_CP- OFDM\_QPSK\_Outer\_Full\_Mid\_CH




### N78(70M)\_CP-OFDM\_16 QAM\_Outer\_Full\_Mid\_CH



## N78(70M)\_CP-OFDM\_64 QAM\_Outer\_Full\_Mid\_CH



## N78(70M)\_CP-OFDM\_256 QAM\_Outer\_Full\_Mid\_CH





## Conducted Spurious Emissions

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
78	30	30	631000	3465.0	DFT-s-OFDM BPSK	1@0	see graph	---
78	30	30	631000	3465.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
78	30	30	631000	3465.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
78	30	30	631000	3465.0	DFT-s-OFDM QPSK	1@0	see graph	---
78	30	30	631000	3465.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
78	30	30	631000	3465.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
78	30	30	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	---
78	30	30	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
78	30	30	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
78	30	30	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	---
78	30	30	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
78	30	30	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
78	30	30	635666	3534.99	DFT-s-OFDM BPSK	1@0	see graph	---
78	30	30	635666	3534.99	DFT-s-OFDM BPSK	1@0	see graph	PASS
78	30	30	635666	3534.99	DFT-s-OFDM BPSK	1@0	see graph	PASS
78	30	30	635666	3534.99	DFT-s-OFDM QPSK	1@0	see graph	---
78	30	30	635666	3534.99	DFT-s-OFDM QPSK	1@0	see graph	PASS
78	30	30	635666	3534.99	DFT-s-OFDM QPSK	1@0	see graph	PASS
78	30	70	632334	3485.01	DFT-s-OFDM BPSK	1@0	see graph	---
78	30	70	632334	3485.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
78	30	70	632334	3485.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
78	30	70	632334	3485.01	DFT-s-OFDM QPSK	1@0	see graph	---

78	30	70	632334	3485.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
78	30	70	632334	3485.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
78	30	70	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	---
78	30	70	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
78	30	70	633334	3500.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
78	30	70	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	---
78	30	70	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
78	30	70	633334	3500.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
78	30	70	634332	3514.98	DFT-s-OFDM BPSK	1@0	see graph	---
78	30	70	634332	3514.98	DFT-s-OFDM BPSK	1@0	see graph	PASS
78	30	70	634332	3514.98	DFT-s-OFDM BPSK	1@0	see graph	PASS
78	30	70	634332	3514.98	DFT-s-OFDM QPSK	1@0	see graph	---
78	30	70	634332	3514.98	DFT-s-OFDM QPSK	1@0	see graph	PASS
78	30	70	634332	3514.98	DFT-s-OFDM QPSK	1@0	see graph	PASS