



# FCC RF Test Report

APPLICANT : Xiaomi Communications Co., Ltd.  
EQUIPMENT : Mobile Phone  
BRAND NAME : POCO  
MODEL NAME : 24122RKC7G  
FCC ID : 2AFZZRKC7G  
STANDARD : FCC Part 15 Subpart C §15.247  
CLASSIFICATION : (DSS) Spread Spectrum Transmitter  
TEST DATE(S) : Sep. 22, 2024 ~ Oct. 20, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

**Sporton International Inc. (Kunshan)**

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION..... 5**

    1.1 Applicant ..... 5

    1.2 Manufacturer ..... 5

    1.3 Product Feature of Equipment Under Test..... 5

    1.4 Product Specification of Equipment Under Test..... 6

    1.5 Modification of EUT ..... 6

    1.6 Testing Location ..... 7

    1.7 Test Software..... 7

    1.8 Applicable Standards..... 7

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 8**

    2.1 Carrier Frequency Channel ..... 8

    2.2 Test Mode..... 9

    2.3 Connection Diagram of Test System..... 10

    2.4 Support Unit used in test configuration and system ..... 11

    2.5 EUT Operation Test Setup ..... 11

    2.6 Measurement Results Explanation Example..... 11

**3 TEST RESULT ..... 12**

    3.1 Number of Channel Measurement ..... 12

    3.2 Hopping Channel Separation Measurement ..... 13

    3.3 Dwell Time Measurement..... 14

    3.4 20dB and 99% Bandwidth Measurement ..... 15

    3.5 Output Power Measurement..... 16

    3.6 Conducted Band Edges Measurement..... 17

    3.7 Conducted Spurious Emission Measurement ..... 18

    3.8 Radiated Band Edges and Spurious Emission Measurement ..... 19

    3.9 AC Conducted Emission Measurement..... 23

    3.10 Antenna Requirements ..... 25

**4 LIST OF MEASURING EQUIPMENT..... 26**

**5 MEASUREMENT UNCERTAINTY ..... 27**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. AC CONDUCTED EMISSION TEST RESULT**

**APPENDIX C. RADIATED SPURIOUS EMISSION**

**APPENDIX D. DUTY CYCLE PLOTS**

**APPENDIX E. SETUP PHOTOGRAPHS**



### REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR491407A	Rev. 01	Initial issue of report	Oct. 31, 2024



### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	≥ 15Chs	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	≥ 2/3 of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	-	Report only	-
3.4	-	99% Bandwidth	-	Report only	-
3.5	15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	-
3.6	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	≤ 20dBc	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 18.03 dB at 2486.49 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 13.71 dB at 0.162 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

**Conformity Assessment Condition:**

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



# 1 General Description

## 1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	POCO
Model Name	24122RKC7G
FCC ID	2AFZZRKC7G
IMEI Code	Conducted: 864775070042025/864775070042033 Conduction: 864775070040185/864775070040193 Radiation: 864775070033545/864775070033552
HW Version	13510O11U
SW Version	Xiaomi HyperOS 2.0
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Frequency Range</b>	2402 MHz ~ 2480 MHz
<b>Number of Channels</b>	79
<b>Carrier Frequency of Each Channel</b>	2402+n*1 MHz; n=0~78
<b>Maximum Output Power to Antenna</b>	<p><b>&lt;Ant 7&gt;</b>  Bluetooth BR(1Mbps) : 15.49 dBm (0.0354 W)  Bluetooth EDR (2Mbps) : 14.95 dBm (0.0313 W)  Bluetooth EDR (3Mbps) : 15.77 dBm (0.0378 W)</p> <p><b>&lt;Ant 16&gt;</b>  Bluetooth BR(1Mbps) : 15.58 dBm (0.0361 W)  Bluetooth EDR (2Mbps) : 15.35 dBm (0.0343 W)  Bluetooth EDR (3Mbps) : 15.98 dBm (0.0396 W)</p> <p><b>&lt;Beamforming Ant 7+16&gt;</b>  Bluetooth BR(1Mbps) : 15.67 dBm (0.0369 W)  Bluetooth EDR (2Mbps) : 13.33 dBm (0.0215 W)  Bluetooth EDR (3Mbps) : 13.70 dBm (0.0234 W)</p>
<b>99% Occupied Bandwidth</b>	<p><b>&lt;Ant 7&gt;</b>  Bluetooth BR(1Mbps) : 0.851MHz  Bluetooth EDR (2Mbps) : 1.175MHz  Bluetooth EDR (3Mbps) : 1.154MHz</p> <p><b>&lt;Ant 16&gt;</b>  Bluetooth BR(1Mbps) : 0.848MHz  Bluetooth EDR (2Mbps) : 1.175MHz  Bluetooth EDR (3Mbps) : 1.160MHz</p> <p><b>&lt;Beamforming Ant 7+16&gt;</b>  Bluetooth BR(1Mbps) : 0.851MHz  Bluetooth EDR (2Mbps) : 1.169MHz  Bluetooth EDR (3Mbps) : 1.157MHz</p>
<b>Antenna Type / Gain</b>	<p><b>&lt;Ant 7&gt;</b> : PIFA Antenna type with gain -2.6 dBi  <b>&lt;Ant 16&gt;</b> : PIFA Antenna type with gain -2.6 dBi</p>
<b>Type of Modulation</b>	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : π/4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

Remark: The device support Bluetooth BR/EDR Beamforming mode for Ant.16+7.

### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International Inc. (Kunshan)		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People’s Republic of China TEL : +86-512-57900158		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-KS 03CH08-KS TH01-KS	CN1257	314309

### 1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH08-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

### 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-



## 2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps π/4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth EDR 3Mbps 8-DPSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
Mode 3: CH78_2480 MHz			
AC Conducted Emission	Mode 1 : GSM 850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable (Charging from Adapter)		
<b>Remark:</b> <ol style="list-style-type: none"> <li>1. For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.</li> <li>2. For Radiated Test Cases, The tests were performed with Adapter and USB Cable.</li> </ol>			

## 2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:





### 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	XIAOMI	LYEJ02LM	N/A	N/A	N/A
2.	LTE Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
4.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
5.	SD Card	Kingston	8GB	N/A	N/A	N/A

### 2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

### 2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 12.19 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset}(dB) &= \text{RF cable loss}(dB) + \text{attenuator factor}(dB). \\
 &= 12.19 + 10 = 22.19 \text{ (dB)}
 \end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup



##### 3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

### 3.4 20dB and 99% Bandwidth Measurement

#### 3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;  
Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.  
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;  
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;  
Sweep = auto; Detector function = peak;  
Trace = max hold.
6. Measure and record the results in the test report.

#### 3.4.4 Test Setup



#### 3.4.5 Test Result of 20dB and 99% Occupied Bandwidth

Please refer to Appendix A.

## 3.5 Output Power Measurement

### 3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

### 3.5.4 Test Setup



### 3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

### 3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup



### 3.6.5 Test Result of Conducted Band Edges

Please refer to Appendix A.

### 3.6.6 Test Result of Conducted Hopping Mode Band Edges

Please refer to Appendix A.

## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.7.4 Test Setup



### 3.7.5 Test Result of Conducted Spurious Emission

Please refer to Appendix A.



### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




### 3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1 \text{ GHz}$ , RBW=1MHz for  $f > 1\text{GHz}$  ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from  $20 \log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





### **3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

### **3.8.6 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix C.

### **3.8.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)**

Please refer to Appendix C.

### **3.8.8 Duty cycle correction factor for average measurement**

Please refer to Appendix D.



### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY564000 23	3Hz~8.5GHz;M ax 30dBm	Jan. 02, 2024	Sep. 24, 2024	Jan. 01, 2025	Radiation (03CH08-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY574410 79	10Hz-44GHz	Oct. 09, 2024	Sep. 24, 2024	Oct. 08, 2025	Radiation (03CH08-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 08, 2024	Sep. 24, 2024	Sep. 07, 2025	Radiation (03CH08-KS)
Bilog Antenna	TESEQ	CBL 6111D	44483	30MHz-1GHz	Dec. 06, 2023	Sep. 24, 2024	Dec. 05, 2024	Radiation (03CH08-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00240138	1GHz~18GHz	Jul. 06, 2024	Sep. 24, 2024	Jul. 05, 2025	Radiation (03CH08-KS)
high gain Amplifier	EM	EM01G18GA	060845	1Ghz-18Ghz	Jan. 03, 2024	Sep. 24, 2024	Jan. 02, 2025	Radiation (03CH08-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 27, 2024	Sep. 24, 2024	Jan. 26, 2025	Radiation (03CH08-KS)
Amplifier	SONOMA	310N	413741	9KHz-1GHz	Jan. 02, 2024	Sep. 24, 2024	Jan. 01, 2025	Radiation (03CH08-KS)
Amplifier	Keysight	83017A	MY532704 17	500MHz~26.5G Hz	Oct. 09, 2024	Sep. 24, 2024	Oct. 08, 2025	Radiation (03CH08-KS)
Amplifier	EM	EM18G40GG A	060728	18~40GHz	Jan. 02, 2024	Sep. 24, 2024	Jan. 01, 2025	Radiation (03CH08-KS)
AC Power Source	Chroma	61601	616010002 473	N/A	NCR	Sep. 24, 2024	NCR	Radiation (03CH08-KS)
Turn Table	EM	EM 1000-T	N/A	0~360 degree	NCR	Sep. 24, 2024	NCR	Radiation (03CH08-KS)
Antenna Mast	EM	EM 1000-A	N/A	1 m~4 m	NCR	Sep. 24, 2024	NCR	Radiation (03CH08-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr 18, 2024	Oct. 17, 2024	Apr 17, 2025	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Aug. 20, 2024	Oct. 17, 2024	Aug. 19, 2025	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Apr 18, 2024	Oct. 17, 2024	Apr 17, 2025	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 09, 2024	Oct. 17, 2024	Oct. 08, 2025	Conduction (CO01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Sep. 22, 2024~ Oct. 20, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2024		Oct. 10, 2025	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GH z	Jan. 02, 2024	Sep. 22, 2024~ Oct. 20, 2024	Jan. 01, 2025	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2024	Sep. 22, 2024~ Oct. 20, 2024	Jan. 01, 2025	Conducted (TH01-KS)

NCR: No Calibration Required



## 5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.22 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.50 dB
Conducted Power Spectral Density	±0.90 dB
Frequency	±0.04 Hz

### Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.84 dB
---	---------

### Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30 dB
---	---------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.04 dB
---	---------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.26 dB
---	---------

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.40 dB
---	---------

----- THE END -----



## Appendix A. Conducted Test Results



Ambient Condition: <u>25</u> °C, <u>45</u> %RH	
According Standard: ■Part15C	
Test Date: <u>2024.9.22~2024.10.20</u>	Test Engineer: <u>Jiang Jun</u>

### SISO Ant 16 / Ant7



### 20dB Emission Bandwidth


#### Test Result


TestMode	Antenna	Freq(MHz)	20dB EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant16	2402	0.95	2401.54	2402.49	---	---
	Ant7	2402	0.95	2401.54	2402.49	---	---
	Ant16	2441	0.95	2440.54	2441.49	---	---
	Ant7	2441	0.95	2440.54	2441.49	---	---
	Ant16	2480	0.95	2479.54	2480.49	---	---
	Ant7	2480	0.95	2479.54	2480.49	---	---
2DH1	Ant16	2402	1.30	2401.34	2402.65	---	---
	Ant7	2402	1.30	2401.34	2402.65	---	---
	Ant16	2441	1.30	2440.34	2441.65	---	---
	Ant7	2441	1.30	2440.34	2441.65	---	---
	Ant16	2480	1.22	2479.38	2480.60	---	---
	Ant7	2480	1.30	2479.34	2480.64	---	---
3DH1	Ant16	2402	1.27	2401.37	2402.64	---	---
	Ant7	2402	1.27	2401.37	2402.64	---	---
	Ant16	2441	1.27	2440.37	2441.64	---	---
	Ant7	2441	1.27	2440.37	2441.64	---	---
	Ant16	2480	1.27	2479.37	2480.64	---	---
	Ant7	2480	1.27	2479.37	2480.64	---	---





### Test Graphs





















3DH1\_Ant16\_2441




Date: 28.SEP.2024 15:40:17

3DH1\_Ant7\_2441



Date: 28.SEP.2024 15:17:58






### Occupied Channel Bandwidth


#### Test Result


TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant16	2402	0.848	2401.5774	2402.4256	---	---
	Ant7	2402	0.848	2401.5774	2402.4256	---	---
	Ant16	2441	0.848	2440.5774	2441.4256	---	---
	Ant7	2441	0.848	2440.5774	2441.4256	---	---
	Ant16	2480	0.848	2479.5774	2480.4256	---	---
	Ant7	2480	0.851	2479.5744	2480.4256	---	---
2DH1	Ant16	2402	1.172	2401.4096	2402.5814	---	---
	Ant7	2402	1.169	2401.4096	2402.5784	---	---
	Ant16	2441	1.172	2440.4096	2441.5814	---	---
	Ant7	2441	1.172	2440.4096	2441.5814	---	---
	Ant16	2480	1.175	2479.4066	2480.5814	---	---
	Ant7	2480	1.175	2479.4066	2480.5814	---	---
3DH1	Ant16	2402	1.157	2401.4336	2402.5904	---	---
	Ant7	2402	1.151	2401.4366	2402.5874	---	---
	Ant16	2441	1.157	2440.4336	2441.5904	---	---
	Ant7	2441	1.154	2440.4366	2441.5904	---	---
	Ant16	2480	1.16	2479.4306	2480.5904	---	---
	Ant7	2480	1.154	2479.4336	2480.5874	---	---





### Test Graphs


















3DH1\_Ant16\_2402



Date: 28.SEP.2024 15:39:05


3DH1\_Ant7\_2402



Date: 28.SEP.2024 15:16:47




3DH1\_Ant16\_2441




Date: 28.SEP.2024 15:40:31

3DH1\_Ant7\_2441



Date: 28.SEP.2024 15:18:13





### Maximum conducted output power

#### Test Result Peak

TestMode	Antenna	CH.	Peak Power (dBm)	Power Limit (dBm)	Pass/Fail
DH5	Ant16	0	15.27	20.97	Pass
		39	<b>15.58</b>	20.97	Pass
		78	15.38	20.97	Pass
2DH1	Ant16	0	14.96	20.97	Pass
		39	15.24	20.97	Pass
		78	<b>15.35</b>	20.97	Pass
3DH1	Ant16	0	15.65	20.97	Pass
		39	15.94	20.97	Pass
		78	<b>15.98</b>	20.97	Pass
DH5	Ant7	0	<b>15.49</b>	20.97	Pass
		39	15.38	20.97	Pass
		78	14.92	20.97	Pass
2DH1	Ant7	0	<b>14.95</b>	20.97	Pass
		39	14.69	20.97	Pass
		78	14.61	20.97	Pass
3DH1	Ant7	0	<b>15.77</b>	20.97	Pass
		39	15.27	20.97	Pass
		78	15.15	20.97	Pass




### Carrier frequency separation

#### Test Result

TestMode	Antenna	Freq(MHz)	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant16	2402	1.009	≥0.633	PASS
	Ant7	2402	1.187	≥0.633	PASS
	Ant16	2441	0.991	≥0.633	PASS
	Ant7	2441	1.009	≥0.633	PASS
	Ant16	2480	1.009	≥0.633	PASS
	Ant7	2480	1	≥0.633	PASS
2DH1	Ant16	2402	1	≥0.867	PASS
	Ant7	2402	0.996	≥0.867	PASS
	Ant16	2441	0.996	≥0.867	PASS
	Ant7	2441	0.996	≥0.867	PASS
	Ant16	2480	0.996	≥0.813	PASS
	Ant7	2480	0.978	≥0.867	PASS
3DH1	Ant16	2402	1.009	≥0.847	PASS
	Ant7	2402	1	≥0.847	PASS
	Ant16	2441	1.004	≥0.847	PASS
	Ant7	2441	1.009	≥0.847	PASS
	Ant16	2480	0.991	≥0.847	PASS
	Ant7	2480	1.143	≥0.847	PASS




### Test Graphs






DH5\_Ant16\_2441



Date: 28.SEP.2024 15:48:54


DH5\_Ant7\_2441



Date: 28.SEP.2024 15:24:25




DH5\_Ant16\_2480



Date: 28.SEP.2024 15:56:40


DH5\_Ant7\_2480



Date: 28.SEP.2024 15:24:53




2DH1\_Ant16\_2402



Date: 28.SEP.2024 15:50:17


2DH1\_Ant7\_2402



Date: 28.SEP.2024 15:25:43




2DH1\_Ant16\_2441



Date: 28.SEP.2024 15:50:52

2DH1\_Ant7\_2441




Date: 28.SEP.2024 15:26:17






3DH1\_Ant16\_2402



Date: 28.SEP.2024 15:53:14


3DH1\_Ant7\_2402




Date: 28.SEP.2024 15:28:17



3DH1\_Ant16\_2441




3DH1\_Ant7\_2441






3DH1\_Ant16\_2480



Date: 28.SEP.2024 15:55:18

3DH1\_Ant7\_2480



Date: 28.SEP.2024 15:29:32




## Time of occupancy

### Test Result

TestMode	Antenna	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec) (MHz)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	Ant16	79	106.67	2.8884	0.31	0.4	Pass
AFH	Ant16	20	53.33	2.8884	0.15	0.4	Pass
Normal	Ant7	79	106.67	2.8971	0.31	0.4	Pass
AFH	Ant7	20	53.33	2.8971	0.15	0.4	Pass



### Test Graphs







## Number of hopping channels

### Test Result

TestMode	Antenna	Freq(MHz)	Result[Num]	Limit[Num]	Verdict
DH5	Ant16	Hop	79	≥15	PASS
	Ant7	Hop	79	≥15	PASS



### Test Graphs






### Band edge measurements


#### Test Result

TestMode	Antenna	ChName	Freq(MHz)	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant16	Low	2402	15.43	-46.64	≤-4.57	PASS
	Ant7	Low	2402	15.36	-48.35	≤-4.64	PASS
	Ant16	High	2480	15.35	-47.67	≤-4.65	PASS
	Ant7	High	2480	14.58	-46.76	≤-5.42	PASS
	Ant16	Low	Hop_2402	13.92	-48.41	≤-6.08	PASS
	Ant7	Low	Hop_2402	14.51	-48.64	≤-5.49	PASS
	Ant16	High	Hop_2480	16.97	-47.31	≤-3.03	PASS
	Ant7	High	Hop_2480	15.43	-48.01	≤-4.57	PASS
2DH1	Ant16	Low	2402	12.10	-36.92	≤-7.9	PASS
	Ant7	Low	2402	11.68	-41.09	≤-8.32	PASS
	Ant16	High	2480	11.92	-47.06	≤-8.08	PASS
	Ant7	High	2480	11.07	-47.81	≤-8.93	PASS
	Ant16	Low	Hop_2402	10.78	-40.6	≤-9.22	PASS
	Ant7	Low	Hop_2402	10.18	-48.21	≤-9.82	PASS
	Ant16	High	Hop_2480	13.18	-47.84	≤-6.82	PASS
	Ant7	High	Hop_2480	11.86	-47.35	≤-8.14	PASS
3DH1	Ant16	Low	2402	12.22	-38.28	≤-7.78	PASS
	Ant7	Low	2402	11.84	-40.39	≤-8.16	PASS
	Ant16	High	2480	12.03	-47.7	≤-7.97	PASS
	Ant7	High	2480	11.06	-47.37	≤-8.94	PASS
	Ant16	Low	Hop_2402	11.14	-47.59	≤-8.86	PASS
	Ant7	Low	Hop_2402	11.22	-46.89	≤-8.78	PASS
	Ant16	High	Hop_2480	13.46	-47.77	≤-6.54	PASS
	Ant7	High	Hop_2480	11.96	-47.47	≤-8.04	PASS




### Test Graphs








DH5\_Ant16\_Low\_Hop\_2402





Date: 28.SEP.2024 15:44:05


DH5\_Ant7\_Low\_Hop\_2402





Date: 28.SEP.2024 15:21:46
























## Conducted Spurious Emission

### Test Result

TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict	
DH5	Ant16	2402	Reference	15.43	15.43	---	PASS	
			30~1000	15.43	-50.13	≤-4.57	PASS	
			1000~26500	15.43	-43.87	≤-4.57	PASS	
	Ant7	2402	Reference	15.35	15.35	---	PASS	
			30~1000	15.35	-50.29	≤-4.65	PASS	
			1000~26500	15.35	-44.53	≤-4.65	PASS	
	Ant16	2441	Reference	15.56	15.56	---	PASS	
			30~1000	15.56	-49.83	≤-4.44	PASS	
			1000~26500	15.56	-43.74	≤-4.44	PASS	
	Ant7	2441	Reference	14.98	14.98	---	PASS	
			30~1000	14.98	-49.8	≤-5.02	PASS	
			1000~26500	14.98	-43.54	≤-5.02	PASS	
	Ant16	2480	Reference	15.53	15.53	---	PASS	
			30~1000	15.53	-49.65	≤-4.47	PASS	
			1000~26500	15.53	-43.19	≤-4.47	PASS	
	Ant7	2480	Reference	14.70	14.70	---	PASS	
			30~1000	14.70	-49.64	≤-5.3	PASS	
			1000~26500	14.70	-43.22	≤-5.3	PASS	
	2DH1	Ant16	2402	Reference	12.03	12.03	---	PASS
				30~1000	12.03	-49.08	≤-7.97	PASS
				1000~26500	12.03	-44.3	≤-7.97	PASS
		Ant7	2402	Reference	11.60	11.60	---	PASS
				30~1000	11.60	-49.88	≤-8.4	PASS
				1000~26500	11.60	-43.62	≤-8.4	PASS
Ant16		2441	Reference	11.86	11.86	---	PASS	
			30~1000	11.86	-50.32	≤-8.14	PASS	
			1000~26500	11.86	-43.4	≤-8.14	PASS	
Ant7		2441	Reference	11.26	11.26	---	PASS	
			30~1000	11.26	-49.96	≤-8.74	PASS	
			1000~26500	11.26	-44.3	≤-8.74	PASS	
Ant16		2480	Reference	12.10	12.10	---	PASS	
			30~1000	12.10	-49.48	≤-7.9	PASS	
			1000~26500	12.10	-43.64	≤-7.9	PASS	



	Ant7	2480	Reference	11.27	11.27	---	PASS
			30~1000	11.27	-49.64	≤-8.73	PASS
			1000~26500	11.27	-44.02	≤-8.73	PASS
3DH1	Ant16	2402	Reference	15.29	15.29	---	PASS
			30~1000	15.29	-49.81	≤-4.71	PASS
			1000~26500	15.29	-44.16	≤-4.71	PASS
	Ant7	2402	Reference	11.79	11.79	---	PASS
			30~1000	11.79	-49.47	≤-8.21	PASS
			1000~26500	11.79	-44.18	≤-8.21	PASS
	Ant16	2441	Reference	12.00	12.00	---	PASS
			30~1000	12.00	-49.81	≤-8	PASS
			1000~26500	12.00	-43.52	≤-8	PASS
	Ant7	2441	Reference	11.44	11.44	---	PASS
			30~1000	11.44	-50.19	≤-8.56	PASS
			1000~26500	11.44	-43.92	≤-8.56	PASS
	Ant16	2480	Reference	14.85	14.85	---	PASS
			30~1000	14.85	-49.23	≤-5.15	PASS
			1000~26500	14.85	-43.1	≤-5.15	PASS
	Ant7	2480	Reference	11.27	11.27	---	PASS
			30~1000	11.27	-49.48	≤-8.73	PASS
			1000~26500	11.27	-43.33	≤-8.73	PASS



Test Graphs

