



Test Report No.: W7L-P23030005RF03



FCC TEST REPORT

(Part 15, Subpart E)



Applicant:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

Manufacturer or Supplier:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Product:	Mobile Phone
Brand Name:	Redmi
Model Name:	23053RN02A
FCC ID:	2AFZZRN02A
Date of tests:	Mar. 06, 2023 ~ Mar. 29, 2023

The tests have been carried out according to the requirements of the following standard:

FCC Part 15, Subpart E, Section 15.407

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
 Date: Mar. 29, 2023	 Date: Mar. 29, 2023

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD 4

1 SUMMARY OF TEST RESULTS 5

1.1 MEASUREMENT UNCERTAINTY 6

2 GENERAL INFORMATION..... 7

2.1 GENERAL DESCRIPTION OF EUT 7

2.2 DESCRIPTION OF TEST MODES 9

 2.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... 12

2.3 DUTY CYCLE OF TEST SIGNAL 17

2.4 DESCRIPTION OF SUPPORT UNITS 18

 2.4.1 CONFIGURATION OF SYSTEM UNDER TEST 19

2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS 20

3 TEST TYPES AND RESULTS..... 21

3.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT 21

 3.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT..... 21

 3.1.2 LIMITS OF UNWANTED EMISSION..... 21

 3.1.3 TEST INSTRUMENTS..... 22

 3.1.4 TEST PROCEDURES 23

 3.1.5 DEVIATION FROM TEST STANDARD 23

 3.1.6 TEST SETUP 24

 3.1.7 EUT OPERATING CONDITION 25

 3.1.8 TEST RESULTS 26

3.2 CONDUCTED EMISSION MEASUREMENT 115

 3.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 115

 3.2.2 TEST INSTRUMENTS..... 115

 3.2.3 TEST PROCEDURES 115

 3.2.4 DEVIATION FROM TEST STANDARD 116

 3.2.5 TEST SETUP 116

 3.2.6 EUT OPERATING CONDITIONS 116

 3.2.7 TEST RESULTS 117

3.3 MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT 119

 3.3.1 LIMITS OF MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT 119

 3.3.2 TEST SETUP 120

 3.3.3 TEST INSTRUMENTS..... 120



3.3.4	TEST PROCEDURE	121
3.3.5	DEVIATION FROM TEST STANDARD	123
3.3.6	EUT OPERATING CONDITIONS	123
3.3.7	TEST RESULTS	124
3.4	MAXIMUM POWER SPECTRAL DENSITY MEASUREMENT.....	125
3.4.1	LIMITS OF MAXIMUM POWER SPECTRAL DENSITY MEASUREMENT	125
3.4.2	TEST SETUP	125
3.4.3	TEST INSTRUMENTS.....	125
3.4.4	TEST PROCEDURES	126
3.4.5	DEVIATION FROM TEST STANDARD	126
3.4.6	EUT OPERATING CONDITIONS	126
3.4.7	TEST RESULTS	127
3.5	AUTOMATICALLY DISCONTINUE TRANSMISSION	128
3.5.1	LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	128
3.5.2	TEST INSTRUMENTS.....	128
3.5.3	TEST RESULT	128
3.6	ANTENNA REQUIREMENTS.....	129
3.6.1	STANDARD APPLICABLE	129
3.6.2	ANTENNA CONNECTED CONSTRUCTION.....	129
3.6.3	ANTENNA GAIN	129
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	130
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	131
6	APPENDIX: RLAN	132



BUREAU
VERITAS

Test Report No.: W7L-P23030005RF03

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P23030005RF03	Original release	Mar. 29, 2023



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART E		
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT
15.407(b)(6)	AC Power Conducted Emission	Compliance
15.407(b) (1/2/3/4/5)	Radiated Emission & Band Edge Measurement	Compliance
15.407(a/1/2/3)	Maximum conducted output Power	Compliance
15.407(a/1/2/3)	Peak Power Spectral Density	Compliance
15.407(i)	26 dB Bandwidth	Compliance
15.407(e)	6 dB Bandwidth	Compliance
15.203	Antenna Requirement	Compliance

NOTE:

1. Except the data of RSE and Band Edge Measurement, other data please refer to the appendix.
2. This report refers to the data of W7L-P23030003RF03 (FCC ID: 2AFZZRN02L, model: 23053RN02L), the difference between 23053RN02L and 23053RN02A is model, FCC ID and supporting bands. 23053RN02A remove WCDMA B2<E B2& LTE B2& LTE B4& LTE B12& LTE B13& LTE B17& LTE B26& LTE B66, The new sample only Spot-Check worst case for RSE and conducted power, and the Spot-Check results of conducted power are similar or lower. So this report only updates the Spot-Check data of RSE(802.11ac (80MHz) CH 58). add Spot-Check data of conducted power.



1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	±2.70dB
Radiated emissions (9KHz~30MHz)	±2.68dB
Radiated emissions (30MHz~1GHz)	±4.98dB
Radiated emissions (1GHz ~6GHz)	±4.70dB
Radiated emissions (6GHz ~18GHz)	±4.60dB
Radiated emissions (18GHz ~40GHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Power Spectral Density	±0.85 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

**2 GENERAL INFORMATION****2.1 GENERAL DESCRIPTION OF EUT**

PRODUCT	Mobile Phone
BRAND NAME	Redmi
MODEL NAME	23053RN02A
NOMINAL VOLTAGE	5V/9V/10V/12Vdc(adapter or host equipment) 3.8Vdc (Li-ion, battery)
MODULATION	OFDM
TRANSFER RATE	802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 300.0Mbps 802.11ac: up to 866.6Mbps
OPERATING FREQUENCY	5180 ~ 5240MHz, 5260 ~ 5320MHz, 5500 ~ 5720MHz, 5745 ~ 5825MHz
NUMBER OF CHANNEL	5180 ~ 5240MHz: 4 for 802.11a, 802.11n, 802.11ac (20MHz) 2 for 802.11n, 802.11ac (40MHz) 1 for 802.11ac (80MHz) 5260 ~ 5320MHz: 4 for 802.11a, 802.11n, 802.11ac (20MHz) 2 for 802.11n, 802.11ac (40MHz) 1 for 802.11ac (80MHz) 5500 ~ 5720MHz: 11 for 802.11a, 802.11n, 802.11ac(20MHz) 5 for 802.11n, 802.11ac (40MHz) 2 for 802.11ac (80MHz) 5745 ~ 5825MHz: 4 for 802.11a, 802.11n, 802.11ac (20MHz) 2 for 802.11n, 802.11ac (40MHz) 1 for 802.11ac (80MHz)
AVERAGE POWER	51.40 mW for 5180 ~ 5240MHz 53.70 mW for 5260 ~ 5320MHz 51.88 mW for 5500 ~ 5720MHz 52.00 mW for 5745 ~ 5825MHz
ANTENNA TYPE	IFA Antenna
ANTENNA GAIN	-3.6dBi for 5180 ~ 5240MHz -3.9dBi for 5260 ~ 5320MHz -3.8dBi for 5500 ~ 5720MHz -4.3dBi for 5745 ~ 5825MHz
HW VERSION	P1.1
SW VERSION	MIUI14
IMEI	861065060020543 861065060023927 861065060023935
I/O PORTS	Refer to user's manual



CABLE SUPPLIED	USB cable1: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable2: non-shielded cable, with w/o ferrite core, 1.0 meter
-----------------------	--

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receiver.

MODULATION MODE	TX FUNCTION
802.11a	1TX/1RX
802.11n/802.11ac (20MHz)	1TX/1RX
802.11n/802.11ac (40MHz)	1TX/1RX
802.11ac (80MHz)	1TX/1RX

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



2.2 DESCRIPTION OF TEST MODES

FOR 5180 ~ 5240MHz

4 channels are provided for 802.11a, 802.11n, 802.11ac (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n, 802.11ac (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
38	5190 MHz	46	5230 MHz

1 channel is provided for 802.11ac (80MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
42	5210 MHz		

FOR 5260 ~ 5320MHz

4 channels are provided for 802.11a, 802.11n, 802.11ac (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
52	5260 MHz	60	5300 MHz
56	5280 MHz	64	5320 MHz

2 channels are provided for 802.11n, 802.11ac (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
54	5270 MHz	62	5310 MHz

1 channel is provided for 802.11ac (80MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
58	5290 MHz		



FOR 5500 ~ 5720MHz

12 channels are provided for 802.11a, 802.11n, 802.11ac (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
100	5500 MHz	124	5620MHz
104	5520 MHz	128	5640MHz
108	5540 MHz	132	5660 MHz
112	5560 MHz	136	5680 MHz
116	5580 MHz	140	5700 MHz
120	5600 MHz	144	5720 MHz

6 channels are provided for 802.11n, 802.11ac (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
102	5510 MHz	126	5630MHz
110	5550 MHz	134	5670 MHz
118	5590 MHz	142	5710 MHz

3 channel is provided for 802.11ac (80MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
106	5530 MHz	138	5690 MHz
122	5610 MHz		



FOR 5745 ~ 5825MHz

5 channels are provided for 802.11a, 802.11n, 802.11ac (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745 MHz	161	5805 MHz
153	5765 MHz	165	5825 MHz
157	5785 MHz		

2 channels are provided for 802.11n, 802.11ac (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
142	5710 MHz	159	5795 MHz
151	5755 MHz		

1 channel is provided for 802.11ac (80MHz):

CHANNEL	FREQUENCY
155	5775 MHz



2.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
A	√	√	√	-	Powered by Adapter with wifi(5G) link
B	-	-	-	√	Powered by Battery with wifi(5G) link
C	-	-	-	-	Powered by USB with wifi(5G) link

Where **RE≥1G**: Radiated Emission above 1GHz **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE:

The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

NOTE: "-" means no effect

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
A	802.11ac (20MHz)	5500-5720	100 to 144	140	OFDM	MCS0



RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
A	802.11a	5180-5240	36 to 48	36, 48	OFDM	6.0
A	802.11an/ac (20MHz)		36 to 48	36, 48	OFDM	MCS0
A	802.11an/ac (40MHz)		38 to 46	38, 46	OFDM	MCS0
A	802.11ac (80MHz)		42	42	OFDM	MCS0
A	802.11a	5260-5320	52 to 64	52, 60, 64	OFDM	6.0
A	802.11an/ac (20MHz)		52 to 64	52, 60, 64	OFDM	MCS0
A	802.11an/ac (40MHz)		54 to 62	54, 62	OFDM	MCS0
A	802.11ac (80MHz)		58	58	OFDM	MCS0
A	802.11a	5500-5720	100 to 144	100, 116, 140, 144	OFDM	6.0
A	802.11an/ac (20MHz)		100 to 144	100, 116, 140, 144	OFDM	MCS0
A	802.11an/ac (40MHz)		102 to 142	102, 110, 134, 142	OFDM	MCS0
A	802.11ac (80MHz)		106 to 138	106, 138	OFDM	MCS0
A	802.11a	5745-5825	144 to 165	144,149, 157,165	OFDM	6.0
A	802.11an/ac (20MHz)		144 to 165	144,149, 157,165	OFDM	MCS0
A	802.11an/ac (40MHz)		142 to 159	142,151, 159	OFDM	MCS0
A	802.11ac (80MHz)		138 to 155	138,155	OFDM	MCS0



POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
A	802.11ac (80MHz)	5260-5320	58	58	OFDM	MCS0

BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
A	802.11a	5180-5240	36 to 48	36, 48	OFDM	6.0
A	802.11an/ac (20MHz)		36 to 48	36, 48	OFDM	MCS0
A	802.11an/ac (40MHz)		38 to 46	38, 46	OFDM	MCS0
A	802.11ac (80MHz)		42	42	OFDM	MCS0
A	802.11a	5260-5320	52 to 64	52, 60, 64	OFDM	6.0
A	802.11an/ac (20MHz)		52 to 64	52, 60, 64	OFDM	MCS0
A	802.11an/ac (40MHz)		54 to 62	54, 62	OFDM	MCS0
A	802.11ac (80MHz)		58	58	OFDM	MCS0
A	802.11a	5500-5720	100 to 144	100, 116, 140, 144	OFDM	6.0
A	802.11an/ac (20MHz)		100 to 144	100, 116, 140, 144	OFDM	MCS0
A	802.11an/ac/ (40MHz)		102 to 142	102, 110, 134, 142	OFDM	MCS0
A	802.11ac (80MHz)		106 to 138	106, 138	OFDM	MCS0
A	802.11a	5745-5825	144 to 165	144, 149, 157,165	OFDM	6.0
A	802.11an/ac (20MHz)		144 to 165	144, 149, 157,165	OFDM	MCS0
A	802.11an/ac (40MHz)		142 to 159	142, 151, 159	OFDM	MCS0
A	802.11ac (80MHz)		138,155	138, 155	OFDM	MCS0



ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
A	802.11a	5180-5240	36 to 48	36, 48	OFDM	6.0
A	802.11an/ac (20MHz)		36 to 48	36, 48	OFDM	MCS0
A	802.11an/ac (40MHz)		38 to 46	38, 46	OFDM	MCS0
A	802.11ac (80MHz)		42	42	OFDM	MCS0
A	802.11a	5260-5320	52 to 64	52, 60, 64	OFDM	6.0
A	802.11an/ac (20MHz)		52 to 64	52, 60, 64	OFDM	MCS0
A	802.11an/ac (40MHz)		54 to 62	54, 62	OFDM	MCS0
A	802.11ac (80MHz)		58	58	OFDM	MCS0
A	802.11a	5500-5720	100 to 144	100, 116, 140, 144	OFDM	6.0
A	802.11an/ac (20MHz)		100 to 144	100, 116, 140, 144	OFDM	MCS0
A	802.11an/ac (40MHz)		102 to 142	102, 110, 134, 142	OFDM	MCS0
A	802.11ac (80MHz)		106 to 138	106, 138	OFDM	MCS0
A	802.11a	5745-5825	144 to 165	144, 149, 157,165	OFDM	6.0
A	802.11an/ac (20MHz)		144 to 165	144, 149, 157,165	OFDM	MCS0
A	802.11an/ac (40MHz)		142 to 159	142, 151, 159	OFDM	MCS0
A	802.11ac (80MHz)		138,155	138, 155	OFDM	MCS0



TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE<1G	23deg. C, 70%RH	DC 5V/9V/10V/12V By Adapter	Jace Hu
RE≥1G	23deg. C, 70%RH	DC 5V/9V/10V/12V By Adapter	Jace Hu
PLC	25deg. C, 52%RH	DC 5V/9V/10V/12V By Adapter	James Fu
APCM	25deg. C, 60%RH	DC 3.8 By Battery	James Fu



2.3 DUTY CYCLE OF TEST SIGNAL

Please Refer to Appendix A Of this test report.

WORST-CASE DATA:

Measured Duty Cycle		
Mode		Duty Cycle [%]
		ANT1
5GHZ	11a	97.22
	11n20	97.01
	11n40	94.20
	11ac20	97.06
	11ac40	94.29
	11ac80	89.19

Note:

Duty cycle of test signal is < 98%, duty factor shall be considered.



2.4 DESCRIPTION OF SUPPORT UNITS




The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Desktop	Lenovo	M73 SFF	PC04GRQV	N/A
2	Desktop	Lenovo	M73 SFF	PC06CS27	N/A
3	Laptop	Lenovo	ThinkpadL440	R90FTFKN	N/A
4	DC source	Kikusui/JP	PMX18-5A	0000001	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	AC Line: Unshielded, Detachable 1.5m
3	AC Line: Unshielded, Detachable 1.5m
4	DC Line: Unshielded, Detachable 1.0m



2.4.1 CONFIGURATION OF SYSTEM UNDER TEST





2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart E (15.407)

KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.



3 TEST TYPES AND RESULTS

3.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

3.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

3.1.2 LIMITS OF UNWANTED EMISSION

RESTRICTED BANDS	APPLICABLE TO	LIMIT	
	789033 D02 General UNII Test Procedures New Rules v02r01	FIELD STRENGTH AT 3m (dBµV/m)	
	PK : 74	AV : 54	
OUT OF THE RESTRICTED BANDS	APPLICABLE TO	EIRP LIMIT (dBm/MHz)	EQUIVALENT FIELD STRENGTH AT 3m (dBµV/m)
	15.407(b)(1)	PK : -27	PK : 68.2
	15.407(b)(2)		
	15.407(b)(3)		
15.407(b)(4)	See note 2 (FCC 16-24)		



NOTE: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts).}$$

2. All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

3.1.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 19,20	May. 18,23
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Mar. 05,23	Mar. 04,24
Horn Antenna	ETS-LINDGREN	3117	00168692	Mar. 05,23	Mar. 04,24
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Sep.04, 22	Sep.03, 23
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	JS1120-3	3.2.06	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	N/A	May. 12,22	May. 11,23
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 20,23	Feb. 19,24
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May.12,22	May.11,23
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.12,22	May.11,23
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 17,23	Feb. 16,24
DC Source	Kikusui/JP	PMX18-5A	0000001	Aug. 12,22	Aug. 11,23
Power Meter	Anritsu	ML2495A	1506002	Feb. 14,23	Feb. 13,24
Power Sensor	Anritsu	MA2411B	1339352	Feb. 14,23	Feb. 13,24
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.03,22	Sep.02,23

NOTE:

1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.
3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



3.1.4 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle \geq 98%) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


3.1.5 DEVIATION FROM TEST STANDARD

No deviation.




3.1.6 TEST SETUP


<Frequency Range 9KHz~30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.7 EUT OPERATING CONDITION

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.



3.1.8 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

30 MHz – 1GHz data:

Band 2


802.11ac (80MHz):

CHANNEL	TX Channel 58	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
52.31	25.41	52.02	40	-14.59	9.97	0.41	36.99	160	349	QP
84.32	28.11	56.34	40	-11.89	8.22	0.5	36.95	131	37	QP
171.62	39.53	64.09	43.5	-3.97	11.19	0.69	36.44	111	242	QP
251.16	42.04	63.96	46	-3.96	13.51	0.84	36.27	151	271	QP
320.03	35.09	56	46	-10.91	14.44	0.94	36.29	103	96	QP
422.85	24.97	43.7	46	-21.03	16.63	1.11	36.47	197	94	QP

REMARKS:

1. Emission level (dBuV/m) = Read level (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






CHANNEL	Channel 58	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
41.64	26.42	51.26	40	-13.58	11.97	0.37	37.18	110	310	QP
84.32	26.53	54.95	40	-13.47	8.03	0.5	36.95	149	63	QP
166.77	39.2	63.98	43.5	-4.3	11	0.69	36.47	148	189	QP
256.98	35.09	57.72	46	-10.91	12.8	0.84	36.27	156	275	QP
320.03	33.72	54.61	46	-12.28	14.46	0.94	36.29	145	271	QP
422.85	27.14	45.9	46	-18.86	16.6	1.11	36.47	187	197	QP

REMARKS:

1. Emission level (dBuV/m) = Read level (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.





ABOVE 1GHz WORST-CASE DATA:

Note: For higher frequency, the emission is too low to be detected.

Band 1

802.11a

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	61.14	62.21	74	-12.86	34.52	9.92	45.51	200	325	Peak
5150	50.21	51.28	54	-3.79	34.52	9.92	45.51	200	325	Average
5180	108.71	109.77	/	/	34.54	9.91	45.51	200	325	Peak
5180	100.85	101.91	/	/	34.54	9.91	45.51	200	325	Average
5350	55.99	56.97	74	-18.01	34.68	9.85	45.51	200	325	Peak
5350	47.6	48.58	54	-6.4	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.54	57.53	74	-17.46	34.6	9.92	45.51	100	170	Peak
5150	48.17	49.16	54	-5.83	34.6	9.92	45.51	100	170	Average
5180	99.75	100.75	/	/	34.6	9.91	45.51	100	170	Peak
5180	91.82	92.82	/	/	34.6	9.91	45.51	100	170	Average
5350	57.02	58.08	74	-16.98	34.6	9.85	45.51	100	170	Peak
5350	47.41	48.47	54	-6.59	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5180MHz: Fundamental frequency.



CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.98	57.05	74	-18.02	34.52	9.92	45.51	200	325	Peak
5150	48.7	49.77	54	-5.3	34.52	9.92	45.51	200	325	Average
5200	108.04	109.09	/	/	34.56	9.9	45.51	200	325	Peak
5200	100.01	101.06	/	/	34.56	9.9	45.51	200	325	Average
5350	56.36	57.34	74	-17.64	34.68	9.85	45.51	200	325	Peak
5350	47.99	48.97	54	-6.01	34.68	9.85	45.51	200	325	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.58	56.57	74	-18.42	34.6	9.92	45.51	100	170	Peak
5150	48.06	49.05	54	-5.94	34.6	9.92	45.51	100	170	Average
5200	99.28	100.29	/	/	34.6	9.9	45.51	100	170	Peak
5200	91.76	92.77	/	/	34.6	9.9	45.51	100	170	Average
5350	55.76	56.82	74	-18.24	34.6	9.85	45.51	100	170	Peak
5350	47.91	48.97	54	-6.09	34.6	9.85	45.51	100	170	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 5200MHz: Fundamental frequency.



CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.13	57.2	74	-17.87	34.52	9.92	45.51	200	325	Peak
5150	48.11	49.18	54	-5.89	34.52	9.92	45.51	200	325	Average
5240	107.3	108.33	/	/	34.59	9.89	45.51	200	325	Peak
5240	99.29	100.32	/	/	34.59	9.89	45.51	200	325	Average
5350	55.42	56.4	74	-18.58	34.68	9.85	45.51	200	325	Peak
5350	47.99	48.97	54	-6.01	34.68	9.85	45.51	200	325	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.58	56.57	74	-18.42	34.6	9.92	45.51	100	170	Peak
5150	47.3	48.29	54	-6.7	34.6	9.92	45.51	100	170	Average
5240	100.28	101.3	/	/	34.6	9.89	45.51	100	170	Peak
5240	92.19	93.21	/	/	34.6	9.89	45.51	100	170	Average
5350	56.39	57.45	74	-17.61	34.6	9.85	45.51	100	170	Peak
5350	47.55	48.61	54	-6.45	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5240MHz: Fundamental frequency.



802.11n (20MHz)

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	59.3	60.37	74	-14.7	34.52	9.92	45.51	200	325	Peak
5150	49.28	50.35	54	-4.72	34.52	9.92	45.51	200	325	Average
5180	107.78	108.84	/	/	34.54	9.91	45.51	200	325	Peak
5180	99.63	100.69	/	/	34.54	9.91	45.51	200	325	Average
5350	55.99	56.97	74	-18.01	34.68	9.85	45.51	200	325	Peak
5350	48.45	49.43	54	-5.55	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.19	57.18	74	-17.81	34.6	9.92	45.51	100	170	Peak
5150	47.63	48.62	54	-6.37	34.6	9.92	45.51	100	170	Average
5180	98.9	99.9	/	/	34.6	9.91	45.51	100	170	Peak
5180	90.94	91.94	/	/	34.6	9.91	45.51	100	170	Average
5350	54.96	56.02	74	-19.04	34.6	9.85	45.51	100	170	Peak
5350	47.52	48.58	54	-6.48	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5180MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P23030005RF03

CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	59.15	60.22	74	-14.85	34.52	9.92	45.51	200	325	Peak
5150	49.34	50.41	54	-4.66	34.52	9.92	45.51	200	325	Average
5200	108.17	109.22	/	/	34.56	9.9	45.51	200	325	Peak
5200	99.87	100.92	/	/	34.56	9.9	45.51	200	325	Average
5350	55.49	56.47	74	-18.51	34.68	9.85	45.51	200	325	Peak
5350	47.77	48.75	54	-6.23	34.68	9.85	45.51	200	325	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.76	56.75	74	-18.24	34.6	9.92	45.51	100	170	Peak
5150	47.62	48.61	54	-6.38	34.6	9.92	45.51	100	170	Average
5200	99.67	100.68	/	/	34.6	9.9	45.51	100	170	Peak
5200	91.42	92.43	/	/	34.6	9.9	45.51	100	170	Average
5350	56.21	57.27	74	-17.79	34.6	9.85	45.51	100	170	Peak
5350	47.77	48.83	54	-6.23	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5200MHz: Fundamental frequency.



CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.34	57.41	74	-17.66	34.52	9.92	45.51	200	325	Peak
5150	47.75	48.82	54	-6.25	34.52	9.92	45.51	200	325	Average
5240	106.07	107.1	/	/	34.59	9.89	45.51	200	325	Peak
5240	97.87	98.9	/	/	34.59	9.89	45.51	200	325	Average
5350	55.98	56.96	74	-18.02	34.68	9.85	45.51	200	325	Peak
5350	47.81	48.79	54	-6.19	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.62	56.61	74	-18.38	34.6	9.92	45.51	100	70	Peak
5150	47.86	48.85	54	-6.14	34.6	9.92	45.51	100	70	Average
5240	98.57	99.59	/	/	34.6	9.89	45.51	100	70	Peak
5240	90.85	91.87	/	/	34.6	9.89	45.51	100	70	Average
5350	55.53	56.59	74	-18.47	34.6	9.85	45.51	100	70	Peak
5350	47.33	48.39	54	-6.67	34.6	9.85	45.51	100	70	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5240MHz: Fundamental frequency.



802.11n (40MHz)

CHANNEL	TX Channel 38	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	60.85	61.92	74	-13.15	34.52	9.92	45.51	200	325	Peak
5150	50.46	51.53	54	-3.54	34.52	9.92	45.51	200	325	Average
5190	103.75	104.8	/	/	34.55	9.91	45.51	200	325	Peak
5190	96.02	97.07	/	/	34.55	9.91	45.51	200	325	Average
5350	56.38	57.36	74	-17.62	34.68	9.85	45.51	200	325	Peak
5350	47.57	48.55	54	-6.43	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.91	56.9	74	-18.09	34.6	9.92	45.51	100	170	Peak
5150	47.99	48.98	54	-6.01	34.6	9.92	45.51	100	170	Average
5190	94.86	95.86	/	/	34.6	9.91	45.51	100	170	Peak
5190	86.78	87.78	/	/	34.6	9.91	45.51	100	170	Average
5350	54.91	55.97	74	-19.09	34.6	9.85	45.51	100	170	Peak
5350	47.73	48.79	54	-6.27	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5190MHz: Fundamental frequency.



CHANNEL	TX Channel 46	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.1	57.17	74	-17.9	34.52	9.92	45.51	200	325	Peak
5150	48.02	49.09	54	-5.98	34.52	9.92	45.51	200	325	Average
5230	103.2	104.24	/	/	34.58	9.89	45.51	200	325	Peak
5230	95.15	96.19	/	/	34.58	9.89	45.51	200	325	Average
5350	54.97	55.95	74	-19.03	34.68	9.85	45.51	200	325	Peak
5350	48.03	49.01	54	-5.97	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.36	56.35	74	-18.64	34.6	9.92	45.51	100	170	Peak
5150	47.79	48.78	54	-6.21	34.6	9.92	45.51	100	170	Average
5230	95.29	96.31	/	/	34.6	9.89	45.51	100	170	Peak
5230	87.31	88.33	/	/	34.6	9.89	45.51	100	170	Average
5350	55.27	56.33	74	-18.73	34.6	9.85	45.51	100	170	Peak
5350	48.11	49.17	54	-5.89	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5230MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P23030005RF03

802.11ac (20MHz)

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	57.94	59.01	74	-16.06	34.52	9.92	45.51	200	325	Peak
5150	50.16	51.23	54	-3.84	34.52	9.92	45.51	200	325	Average
5180	107.71	108.77	/	/	34.54	9.91	45.51	200	325	Peak
5180	99.73	100.79	/	/	34.54	9.91	45.51	200	325	Average
5350	55.75	56.73	74	-18.25	34.68	9.85	45.51	200	325	Peak
5350	47.53	48.51	54	-6.47	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.07	57.06	74	-17.93	34.6	9.92	45.51	100	170	Peak
5150	47.65	48.64	54	-6.35	34.6	9.92	45.51	100	170	Average
5180	98.65	99.65	/	/	34.6	9.91	45.51	100	170	Peak
5180	90.64	91.64	/	/	34.6	9.91	45.51	100	170	Average
5350	55.89	56.95	74	-18.11	34.6	9.85	45.51	100	170	Peak
5350	48	49.06	54	-6	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5180MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P23030005RF03

CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	57	58.07	74	-17	34.52	9.92	45.51	190	50	Peak
5150	48.71	49.78	54	-5.29	34.52	9.92	45.51	190	50	Average
5200	107.22	108.27	/	/	34.56	9.9	45.51	200	325	Peak
5200	99	100.05	/	/	34.56	9.9	45.51	200	325	Average
5350	56.67	57.65	74	-17.33	34.68	9.85	45.51	200	120	Peak
5350	48.98	49.96	54	-5.02	34.68	9.85	45.51	200	120	Average
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.17	57.16	74	-17.83	34.6	9.92	45.51	120	50	Peak
5150	48.19	49.18	54	-5.81	34.6	9.92	45.51	120	50	Average
5200	99.46	100.47	/	/	34.6	9.9	45.51	100	170	Peak
5200	91.69	92.7	/	/	34.6	9.9	45.51	100	170	Average
5350	56.09	57.15	74	-17.91	34.6	9.85	45.51	155	85	Peak
5350	49.11	50.17	54	-4.89	34.6	9.85	45.51	155	85	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 5200MHz: Fundamental frequency.



CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.87	56.94	74	-18.13	34.52	9.92	45.51	100	95	Peak
5150	47.64	48.71	54	-6.36	34.52	9.92	45.51	100	95	Average
5240	107.43	108.46	/	/	34.59	9.89	45.51	200	325	Peak
5240	98.44	99.47	/	/	34.59	9.89	45.51	200	325	Average
5350	56.37	57.35	74	-17.63	34.68	9.85	45.51	170	81	Peak
5350	47.87	48.85	54	-6.13	34.68	9.85	45.51	170	81	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.53	56.52	74	-18.47	34.6	9.92	45.51	100	170	Peak
5150	47.65	48.64	54	-6.35	34.6	9.92	45.51	100	170	Average
5240	99.51	100.53	/	/	34.6	9.89	45.51	100	170	Peak
5240	91.28	92.3	/	/	34.6	9.89	45.51	100	170	Average
5350	55.64	56.7	74	-18.36	34.6	9.85	45.51	100	170	Peak
5350	48.3	49.36	54	-5.7	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5240MHz: Fundamental frequency.



802.11ac (40MHz)

CHANNEL	TX Channel 38	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	61.43	62.5	74	-12.57	34.52	9.92	45.51	200	325	Peak
5150	50.26	51.33	54	-3.74	34.52	9.92	45.51	200	325	Average
5190	104.06	105.11	/	/	34.55	9.91	45.51	200	325	Peak
5190	96.14	97.19	/	/	34.55	9.91	45.51	200	325	Average
5350	56.53	57.51	74	-17.47	34.68	9.85	45.51	200	325	Peak
5350	47.75	48.73	54	-6.25	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.85	57.84	74	-17.15	34.6	9.92	45.51	100	170	Peak
5150	48.4	49.39	54	-5.6	34.6	9.92	45.51	100	170	Average
5190	94.61	95.61	/	/	34.6	9.91	45.51	100	170	Peak
5190	86.92	87.92	/	/	34.6	9.91	45.51	100	170	Average
5350	58.62	59.68	74	-15.38	34.6	9.85	45.51	100	170	Peak
5350	47.92	48.98	54	-6.08	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5190MHz: Fundamental frequency.



CHANNEL	TX Channel 46	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.24	57.31	74	-17.76	34.52	9.92	45.51	200	325	Peak
5150	48.11	49.18	54	-5.89	34.52	9.92	45.51	200	325	Average
5230	103.78	104.82	/	/	34.58	9.89	45.51	200	325	Peak
5230	95.29	96.33	/	/	34.58	9.89	45.51	200	325	Average
5350	55.51	56.49	74	-18.49	34.68	9.85	45.51	200	325	Peak
5350	48.57	49.55	54	-5.43	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.63	56.62	74	-18.37	34.6	9.92	45.51	100	170	Peak
5150	47.99	48.98	54	-6.01	34.6	9.92	45.51	100	170	Average
5230	95.41	96.43	/	/	34.6	9.89	45.51	100	170	Peak
5230	86.99	88.01	/	/	34.6	9.89	45.51	100	170	Average
5350	56.92	57.98	74	-17.08	34.6	9.85	45.51	100	170	Peak
5350	47.73	48.79	54	-6.27	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5230MHz: Fundamental frequency.



802.11ac (80MHz)

CHANNEL	TX Channel 42	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	59.33	60.4	74	-14.67	34.52	9.92	45.51	200	325	Peak
5150	50.65	51.72	54	-3.35	34.52	9.92	45.51	200	325	Average
5210	99.56	100.6	/	/	34.57	9.9	45.51	200	325	Peak
5210	90.73	91.77	/	/	34.57	9.9	45.51	200	325	Average
5350	55.26	56.24	74	-18.74	34.68	9.85	45.51	200	325	Peak
5350	48.05	49.03	54	-5.95	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.46	57.45	74	-17.54	34.6	9.92	45.51	100	170	Peak
5150	48.45	49.44	54	-5.55	34.6	9.92	45.51	100	170	Average
5210	91.37	92.38	/	/	34.6	9.9	45.51	100	170	Peak
5210	82.95	83.96	/	/	34.6	9.9	45.51	100	170	Average
5350	54.44	55.5	74	-19.56	34.6	9.85	45.51	100	170	Peak
5350	47.24	48.3	54	-6.76	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5210MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P23030005RF03


802.11ac (80MHz)

Worst case harmonic:

CHANNEL	TX Channel 42	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m		
1	10420.000	54.05	47.15	74.00	-19.95	6.90	Peak	Horizontal
2	10420.000	42.97	36.07	54.00	-11.03	6.90	Average	Horizontal
3	PK15637.000	58.49	45.36	74.00	-15.51	13.13	Peak	Horizontal
4	PP15637.000	48.74	35.61	54.00	-5.26	13.13	Average	Horizontal





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBuV/m	dBuV	dBuV/m	dB	dB/m		
1	10418.000	54.50	46.38	74.00	-19.50	8.12	Peak	Vertical
2	10418.000	43.40	35.28	54.00	-10.60	8.12	Average	Vertical
3	PK15630.000	57.74	45.73	74.00	-16.26	12.01	Peak	Vertical
4	PP15630.000	46.60	34.59	54.00	-7.40	12.01	Average	Vertical



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
2. 5210MHz: Fundamental frequency.
3. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.



Band 2
802.11a

CHANNEL	TX Channel 52	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.93	57	74	-18.07	34.52	9.92	45.51	200	325	Peak
5150	47.74	48.81	54	-6.26	34.52	9.92	45.51	200	325	Average
5260	108.34	109.36	/	/	34.61	9.88	45.51	200	325	Peak
5260	100.25	101.27	/	/	34.61	9.88	45.51	200	325	Average
5350	55.34	56.32	74	-18.66	34.68	9.85	45.51	200	325	Peak
5350	48.1	49.08	54	-5.9	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.58	56.57	74	-18.42	34.6	9.92	45.51	100	170	Peak
5150	47.74	48.73	54	-6.26	34.6	9.92	45.51	100	170	Average
5260	100.02	101.05	/	/	34.6	9.88	45.51	100	170	Peak
5260	91.97	93	/	/	34.6	9.88	45.51	100	170	Average
5350	57.4	58.46	74	-16.6	34.6	9.85	45.51	100	170	Peak
5350	47.2	48.26	54	-6.8	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5260MHz: Fundamental frequency.



CHANNEL	TX Channel 60	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	54.12	55.19	74	-19.88	34.52	9.92	45.51	200	325	Peak
5150	47.36	48.43	54	-6.64	34.52	9.92	45.51	200	325	Average
5300	106.58	107.58	/	/	34.64	9.87	45.51	200	325	Peak
5300	99.86	100.86	/	/	34.64	9.87	45.51	200	325	Average
5350	55.27	56.25	74	-18.73	34.68	9.85	45.51	200	325	Peak
5350	48.37	49.35	54	-5.63	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.29	57.28	74	-17.71	34.6	9.92	45.51	100	170	Peak
5150	47.49	48.48	54	-6.51	34.6	9.92	45.51	100	170	Average
5300	99.95	100.99	/	/	34.6	9.87	45.51	100	170	Peak
5300	90.5	91.54	/	/	34.6	9.87	45.51	100	170	Average
5350	55.07	56.13	74	-18.93	34.6	9.85	45.51	100	170	Peak
5350	47.61	48.67	54	-6.39	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5300MHz: Fundamental frequency.



CHANNEL	TX Channel 64	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.26	57.33	74	-17.74	34.52	9.92	45.51	200	325	Peak
5150	48.17	49.24	54	-5.83	34.52	9.92	45.51	200	325	Average
5320	107.11	108.1	/	/	34.66	9.86	45.51	200	325	Peak
5320	99	99.99	/	/	34.66	9.86	45.51	200	325	Average
5350	57.69	58.67	74	-16.31	34.68	9.85	45.51	200	325	Peak
5350	49.1	50.08	54	-4.9	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.7	56.69	74	-18.3	34.6	9.92	45.51	100	170	Peak
5150	47.29	48.28	54	-6.71	34.6	9.92	45.51	100	170	Average
5320	98.36	99.41	/	/	34.6	9.86	45.51	100	170	Peak
5320	91.15	92.2	/	/	34.6	9.86	45.51	100	170	Average
5350	56.75	57.81	74	-17.25	34.6	9.85	45.51	100	170	Peak
5350	47.86	48.92	54	-6.14	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5320MHz: Fundamental frequency.



802.11n (20MHz)

CHANNEL	TX Channel 52	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.74	57.81	74	-17.26	34.52	9.92	45.51	200	325	Peak
5150	48.25	49.32	54	-5.75	34.52	9.92	45.51	200	325	Average
5260	106.67	107.69	/	/	34.61	9.88	45.51	200	325	Peak
5260	98.71	99.73	/	/	34.61	9.88	45.51	200	325	Average
5350	56.14	57.12	74	-17.86	34.68	9.85	45.51	200	325	Peak
5350	48.29	49.27	54	-5.71	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.58	57.57	74	-17.42	34.6	9.92	45.51	100	170	Peak
5150	47.29	48.28	54	-6.71	34.6	9.92	45.51	100	170	Average
5260	99.55	100.58	/	/	34.6	9.88	45.51	100	170	Peak
5260	90.05	91.08	/	/	34.6	9.88	45.51	100	170	Average
5350	55.52	56.58	74	-18.48	34.6	9.85	45.51	100	170	Peak
5350	48.81	49.87	54	-5.19	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5260MHz: Fundamental frequency.



CHANNEL	TX Channel 60	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.16	56.23	74	-18.84	34.52	9.92	45.51	200	325	Peak
5150	47.47	48.54	54	-6.53	34.52	9.92	45.51	200	325	Average
5300	106.28	107.28	/	/	34.64	9.87	45.51	200	325	Peak
5300	98.01	99.01	/	/	34.64	9.87	45.51	200	325	Average
5350	57.76	58.74	74	-16.24	34.68	9.85	45.51	200	325	Peak
5350	48.2	49.18	54	-5.8	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.31	56.3	74	-18.69	34.6	9.92	45.51	100	170	Peak
5150	47.68	48.67	54	-6.32	34.6	9.92	45.51	100	170	Average
5300	97.08	98.12	/	/	34.6	9.87	45.51	100	170	Peak
5300	90.49	91.53	/	/	34.6	9.87	45.51	100	170	Average
5350	55.16	56.22	74	-18.84	34.6	9.85	45.51	100	170	Peak
5350	47.43	48.49	54	-6.57	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5300MHz: Fundamental frequency.



BUREAU
VERITAS

Test Report No.: W7L-P23030005RF03

CHANNEL	TX Channel 64	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.14	56.21	74	-18.86	34.52	9.92	45.51	200	325	Peak
5150	47.74	48.81	54	-6.26	34.52	9.92	45.51	200	325	Average
5320	106.05	107.04	/	/	34.66	9.86	45.51	200	325	Peak
5320	97.88	98.87	/	/	34.66	9.86	45.51	200	325	Average
5350	58.19	59.17	74	-15.81	34.68	9.85	45.51	200	325	Peak
5350	48.75	49.73	54	-5.25	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.93	56.92	74	-18.07	34.6	9.92	45.51	100	170	Peak
5150	47.76	48.75	54	-6.24	34.6	9.92	45.51	100	170	Average
5320	97.78	98.83	/	/	34.6	9.86	45.51	100	170	Peak
5320	90.79	91.84	/	/	34.6	9.86	45.51	100	170	Average
5350	56.76	57.82	74	-17.24	34.6	9.85	45.51	100	170	Peak
5350	47.99	49.05	54	-6.01	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5320MHz: Fundamental frequency.



802.11n (40MHz)

CHANNEL	TX Channel 54	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.46	57.53	74	-17.54	34.52	9.92	45.51	200	325	Peak
5150	48.2	49.27	54	-5.8	34.52	9.92	45.51	200	325	Average
5270	104.08	105.09	/	/	34.62	9.88	45.51	200	325	Peak
5270	95.34	96.35	/	/	34.62	9.88	45.51	200	325	Average
5350	57.68	58.66	74	-16.32	34.68	9.85	45.51	200	325	Peak
5350	47.27	48.25	54	-6.73	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.12	57.11	74	-17.88	34.6	9.92	45.51	100	170	Peak
5150	47.85	48.84	54	-6.15	34.6	9.92	45.51	100	170	Average
5270	94.56	95.59	/	/	34.6	9.88	45.51	100	170	Peak
5270	86.96	87.99	/	/	34.6	9.88	45.51	100	170	Average
5350	55.73	56.79	74	-18.27	34.6	9.85	45.51	100	170	Peak
5350	47.38	48.44	54	-6.62	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5270MHz: Fundamental frequency.



CHANNEL	TX Channel 62	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.96	57.03	74	-18.04	34.52	9.92	45.51	200	325	Peak
5150	47.83	48.9	54	-6.17	34.52	9.92	45.51	200	325	Average
5310	102.79	103.79	/	/	34.65	9.86	45.51	200	325	Peak
5310	94.99	95.99	/	/	34.65	9.86	45.51	200	325	Average
5350	57.08	58.06	74	-16.92	34.68	9.85	45.51	200	325	Peak
5350	50.44	51.42	54	-3.56	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.64	56.63	74	-18.36	34.6	9.92	45.51	100	170	Peak
5150	47.87	48.86	54	-6.13	34.6	9.92	45.51	100	170	Average
5310	94.02	95.07	/	/	34.6	9.86	45.51	100	170	Peak
5310	86.43	87.48	/	/	34.6	9.86	45.51	100	170	Average
5350	54.98	56.04	74	-19.02	34.6	9.85	45.51	100	170	Peak
5350	47.4	48.46	54	-6.6	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5310MHz: Fundamental frequency.



802.11ac (20MHz)

CHANNEL	TX Channel 52	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.84	56.91	74	-18.16	34.52	9.92	45.51	200	325	Peak
5150	48.48	49.55	54	-5.52	34.52	9.92	45.51	200	325	Average
5260	107.65	108.67	/	/	34.61	9.88	45.51	200	325	Peak
5260	100.04	101.06	/	/	34.61	9.88	45.51	200	325	Average
5350	55.69	56.67	74	-18.31	34.68	9.85	45.51	200	325	Peak
5350	48.77	49.75	54	-5.23	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.57	56.56	74	-18.43	34.6	9.92	45.51	100	170	Peak
5150	47.73	48.72	54	-6.27	34.6	9.92	45.51	100	170	Average
5260	99.41	100.44	/	/	34.6	9.88	45.51	100	170	Peak
5260	91.88	92.91	/	/	34.6	9.88	45.51	100	170	Average
5350	55.27	56.33	74	-18.73	34.6	9.85	45.51	100	170	Peak
5350	47.91	48.97	54	-6.09	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5260MHz: Fundamental frequency.



CHANNEL	TX Channel 60	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.39	57.46	74	-17.61	34.52	9.92	45.51	200	325	Peak
5150	47.87	48.94	54	-6.13	34.52	9.92	45.51	200	325	Average
5300	106.05	107.05	/	/	34.64	9.87	45.51	200	325	Peak
5300	98.58	99.58	/	/	34.64	9.87	45.51	200	325	Average
5350	57.67	58.65	74	-16.33	34.68	9.85	45.51	200	325	Peak
5350	48.04	49.02	54	-5.96	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.22	57.21	74	-17.78	34.6	9.92	45.51	100	170	Peak
5150	47.91	48.9	54	-6.09	34.6	9.92	45.51	100	170	Average
5300	99.85	100.89	/	/	34.6	9.87	45.51	100	170	Peak
5300	89.68	90.72	/	/	34.6	9.87	45.51	100	170	Average
5350	57.59	58.65	74	-16.41	34.6	9.85	45.51	100	170	Peak
5350	47.36	48.42	54	-6.64	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5300MHz: Fundamental frequency.



CHANNEL	TX Channel 64	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.84	57.91	74	-17.16	34.52	9.92	45.51	200	325	Peak
5150	48.32	49.39	54	-5.68	34.52	9.92	45.51	200	325	Average
5320	106.08	107.07	/	/	34.66	9.86	45.51	200	325	Peak
5320	98.21	99.2	/	/	34.66	9.86	45.51	200	325	Average
5350	58.52	59.5	74	-15.48	34.68	9.85	45.51	200	325	Peak
5350	49.58	50.56	54	-4.42	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.27	57.26	74	-17.73	34.6	9.92	45.51	100	170	Peak
5150	47.25	48.24	54	-6.75	34.6	9.92	45.51	100	170	Average
5320	98.02	99.07	/	/	34.6	9.86	45.51	100	170	Peak
5320	90.34	91.39	/	/	34.6	9.86	45.51	100	170	Average
5350	56.43	57.49	74	-17.57	34.6	9.85	45.51	100	170	Peak
5350	47.98	49.04	54	-6.02	34.6	9.85	45.51	100	170	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5320MHz: Fundamental frequency.



802.11ac (40MHz)

CHANNEL	TX Channel 54	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	56.79	57.86	74	-17.21	34.52	9.92	45.51	200	325	Peak
5150	48.05	49.12	54	-5.95	34.52	9.92	45.51	200	325	Average
5270	103.87	104.88	/	/	34.62	9.88	45.51	200	325	Peak
5270	95.41	96.42	/	/	34.62	9.88	45.51	200	325	Average
5350	56.36	57.34	74	-17.64	34.68	9.85	45.51	200	325	Peak
5350	48.37	49.35	54	-5.63	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	55.17	56.16	74	-18.83	34.6	9.92	45.51	100	185	Peak
5150	47.43	48.42	54	-6.57	34.6	9.92	45.51	100	185	Average
5270	96.17	97.2	/	/	34.6	9.88	45.51	100	185	Peak
5270	88.62	89.65	/	/	34.6	9.88	45.51	100	185	Average
5350	55.11	56.17	74	-18.89	34.6	9.85	45.51	100	185	Peak
5350	47.86	48.92	54	-6.14	34.6	9.85	45.51	100	185	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5270MHz: Fundamental frequency.



CHANNEL	TX Channel 62	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	57.05	58.12	74	-16.95	34.52	9.92	45.51	200	325	Peak
5150	48.08	49.15	54	-5.92	34.52	9.92	45.51	200	325	Average
5310	103.19	104.19	/	/	34.65	9.86	45.51	200	325	Peak
5310	94.5	95.5	/	/	34.65	9.86	45.51	200	325	Average
5350	57.1	58.08	74	-16.9	34.68	9.85	45.51	200	325	Peak
5350	49.51	50.49	54	-4.49	34.68	9.85	45.51	200	325	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	54	54.99	74	-20	34.6	9.92	45.51	100	185	Peak
5150	47.85	48.84	54	-6.15	34.6	9.92	45.51	100	185	Average
5310	95.12	96.17	/	/	34.6	9.86	45.51	100	185	Peak
5310	88.68	89.73	/	/	34.6	9.86	45.51	100	185	Average
5350	55.25	56.31	74	-18.75	34.6	9.85	45.51	100	185	Peak
5350	48.73	49.79	54	-5.27	34.6	9.85	45.51	100	185	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5310MHz: Fundamental frequency.



802.11ac (80MHz)

CHANNEL	TX Channel 58	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	53.36	54.43	74	-20.64	34.52	9.92	45.51	200	320	Peak
5150	47.18	48.25	54	-6.82	34.52	9.92	45.51	200	320	Average
5290	99.3	100.31	/	/	34.63	9.87	45.51	200	320	Peak
5290	91.77	92.78	/	/	34.63	9.87	45.51	200	320	Average
5350	56.61	57.59	74	-17.39	34.68	9.85	45.51	200	320	Peak
5350	50.57	51.55	54	-3.43	34.68	9.85	45.51	200	320	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5150	53.12	54.11	74	-20.88	34.6	9.92	45.51	100	235	Peak
5150	47.22	48.21	54	-6.78	34.6	9.92	45.51	100	235	Average
5290	90.66	91.7	/	/	34.6	9.87	45.51	100	235	Peak
5290	83.38	84.42	/	/	34.6	9.87	45.51	100	235	Average
5350	53.43	54.49	74	-20.57	34.6	9.85	45.51	100	235	Peak
5350	47.5	48.56	54	-6.5	34.6	9.85	45.51	100	235	Average

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Emission level – Limit value.
- 5290MHz: Fundamental frequency.