

VARIANT FCC TEST REPORT

(PART 27)


Applicant:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

Manufacturer or Supplier:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Product:	Mobile Phone
Brand Name:	Redmi
Model Name:	2409BRN2CL
FCC ID:	2AFZZRN2CL
Date of tests:	May. 11, 2024 ~ Jul. 05, 2024 Oct. 16, 2024 ~ Oct. 29, 2024

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 27** ☒ **ANSI/TIA/EIA-603-D**
☒ **FCC Part 2** ☒ **ANSI/TIA/EIA-603-E** ☒ **ANSI C63.26-2015**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
 Date: Oct. 29, 2024	 Date: Oct. 29, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS	5
1.1 MEASUREMENT UNCERTAINTY	6
1.2 TEST SITE AND INSTRUMENTS	7
2 GENERAL INFORMATION	9
2.1 GENERAL DESCRIPTION OF EUT	9
2.2 CONFIGURATION OF SYSTEM UNDER TEST	12
2.3 DESCRIPTION OF SUPPORT UNITS	13
2.4 TEST ITEM AND TEST CONFIGURATION	13
2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	17
3 TEST TYPES AND RESULTS	18
3.1 OUTPUT POWER MEASUREMENT	18
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	18
3.1.2 TEST PROCEDURES	18
3.1.3 TEST SETUP	19
3.1.4 TEST RESULTS	20
3.2 FREQUENCY STABILITY MEASUREMENT	46
3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	46
3.2.2 TEST PROCEDURE	46
3.2.3 TEST SETUP	46
3.2.4 TEST RESULTS	47
3.3 OCCUPIED BANDWIDTH MEASUREMENT	48
3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT	48
3.3.2 TEST SETUP	48
3.3.3 TEST PROCEDURES	48
3.3.4 TEST RESULTS	49
3.4 BAND EDGE MEASUREMENT	50
3.4.1 LIMITS OF BAND EDGE MEASUREMENT	50
3.4.2 TEST SETUP	51
3.4.3 TEST PROCEDURES	52
3.4.4 TEST RESULTS	53
3.5 CONDUCTED SPURIOUS EMISSIONS	54
3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	54
3.5.2 TEST PROCEDURE	54
3.5.3 TEST SETUP	54
3.5.4 TEST RESULTS	55
3.6 RADIATED EMISSION MEASUREMENT	56
3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT	56
3.6.2 TEST PROCEDURES	56
3.6.3 DEVIATION FROM TEST STANDARD	56
3.6.4 TEST SETUP	57
3.6.5 TEST RESULTS	59
3.7 PEAK TO AVERAGE RATIO	87
3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT	87
3.7.2 TEST SETUP	87
3.7.3 TEST PROCEDURES	87
3.7.4 TEST RESULTS	88
4 PHOTOGRAPHS OF THE TEST CONFIGURATION	89



Test Report No.: W7L-P24100002RF07

5 INFORMATION ON THE TESTING LABORATORIES	90
6 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB...	91
7 APPENDIX	92
WCDMA BAND4	92
LTE BAND7	104
LTE BAND13	138



Test Report No.: W7L-P24100002RF07

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P24050014RF07	Original release	Jul. 05, 2024
W7L-P24100002RF07	Based on the original report product add 2 nd materials and 5 nd and 6 nd screens. This report only verify EIRP and RSE worst case and verify results of EIRP are similar or lower, So this report only replaces the RSE data of LTE Band 13.	Oct. 29, 2024

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 27 & PART 2		
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT
§2.1046	Conducted Output Power	Compliance
§27.50(b)(10)	Effective Radiated Power (Band 13)	Compliance
§27.50(d)(4) §27.50(h)(2)	Equivalent Isotropically Radiated Power (WCMDA Band 4)(Band 7)	Compliance
§2.1055 §27.54	Frequency Stability	Compliance
§2.1049	Occupied Bandwidth	Compliance
§2.1051 §27.53(c)(2)(4) §27.53(h) §27.53(m)(4)	Conducted Band Edge Measurements (WCMDA Band 4) (Band 7) (Band 13)	Compliance
§2.1051 §27.53(c)(2)(4) §27.53(h) §27.53(m)(4)	Conducted Spurious Emissions (WCMDA Band 4)(Band 7) (Band 13)	Compliance
§2.1053 §27.53(c)(2)(4) §27.53(h) §27.53(m)(4)	Radiated Spurious Emissions (WCMDA Band 4)(Band 7) (Band 13)	Compliance
NA	Peak to average ratio	Compliance

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Frequency Stability	$\pm 76.97\text{Hz}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions & Radiated Power (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions & Radiated Power (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Band Edge Measurements	$\pm 4.70\text{dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

1.2 TEST SITE AND INSTRUMENTS

#1

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 28,24	Mar. 27,25
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	May.10,24	May.09,25
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.03,23	Sep.02,24
Bilog Antenna	ETS-LINDGRE N	3143B	00161965	Feb. 18,24	Feb. 17,25
Horn Antenna	ETS-LINDGRE N	3117	00168692	Feb. 18,24	Feb. 17,25
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K- SG/QMS-00361	15433	Sep.04, 23	Sep.03, 24
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 14,24	Feb. 13,25
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May. 06,24	May. 05,25
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.10,24	May.09,25
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 17,24	Feb.16,25
3m Semi-anechoic Chamber	ETS-LINDGRE N	9m*6m*6m	Euroshieldpn- CT0001143-121 6	Nov. 14,23	Nov. 13,26
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	JS1120	3.1.36	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	50HF-010-SMA	May. 06,24	May. 05,25
Power Meter	Anritsu	ML2495A	1506002	Feb. 14,24	Feb. 13,25
Power Sensor	Anritsu	MA2411B	1339352	Feb. 14,24	Feb. 13,25
Temperature Chamber	ESPEC	SH-242	93000855	May. 06,24	May. 05,25
MXG Analog Microvave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 14,24	Feb. 13,25
Base station R&S CMW500	Rohde&Schwa rz	CMW500	153085	May.10,24	May.09,25
DC Source	Kikusui/JP	PMX18-5A	N/A	Aug. 11,23	Aug. 10,24

#2

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 28,24	Mar. 27,25
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	May.10,24	May.09,25
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.03,24	Sep.02,25
Bilog Antenna	ETS-LINDGRE N	3143B	00161965	Feb. 18,24	Feb. 17,25
Horn Antenna	ETS-LINDGRE N	3117	00168692	Feb. 18,24	Feb. 17,25
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Sep.04, 24	Sep.03, 25
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 14,24	Feb. 13,25
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May. 06,24	May. 05,25
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.10,24	May.09,25
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 17,24	Feb.16,25
3m Semi-anechoic Chamber	ETS-LINDGRE N	9m*6m*6m	Euroshieldpn-CT0001143-1216	Nov. 14,23	Nov. 13,26
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	JS1120	3.1.36	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	50HF-010-SMA	May. 06,24	May. 05,25
Power Meter	Anritsu	ML2495A	1506002	Feb. 14,24	Feb. 13,25
Power Sensor	Anritsu	MA2411B	1339352	Feb. 14,24	Feb. 13,25
Temperature Chamber	ESPEC	SH-242	93000855	May. 06,24	May. 05,25
MXG Analog Microwave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 14,24	Feb. 13,25
Base station R&S CMW500	Rohde&Schwarz	CMW500	153085	May.10,24	May.09,25
DC Source	Kikusui/JP	PMX18-5A	N/A	Aug. 11,24	Aug. 10,25

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
 3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Mobile Phone	
BRAND NAME	Redmi	
MODEL NAME	2409BRN2CL	
NOMINAL VOLTAGE	5/3.6~11Vdc(adapter or host equipment) 3.84Vdc (Li-ion, battery)	
MODULATION TECHNOLOGY	WCDMA IV	BPSK, QPSK
	LTE	QPSK, 16QAM, 64QAM
FREQUENCY RANGE	WCDMA IV	1712.4MHz ~ 1752.6MHz
	LTE Band 7 Channel Bandwidth: 5MHz	2502.5MHz ~ 2567.5MHz
	LTE Band 7 Channel Bandwidth: 10MHz	2505MHz ~ 2565MHz
	LTE Band 7 Channel Bandwidth: 15MHz	2507.5MHz ~ 2562.5MHz
	LTE Band 7 Channel Bandwidth: 20MHz	2510MHz ~ 2560MHz
	LTE Band 13 Channel Bandwidth: 5MHz	779.5MHz ~ 784.5MHz
	LTE Band 13 Channel Bandwidth: 10MHz	782MHz
MAX. EIRP POWER	WCDMA IV	208.45mW
	LTE Band 7 Channel Bandwidth: 5MHz	233.35mW
	LTE Band 7 Channel Bandwidth: 10MHz	237.14mW
	LTE Band 7 Channel Bandwidth: 15MHz	236.05mW
	LTE Band 7 Channel Bandwidth: 20MHz	241.55mW
	LTE Band 13 Channel Bandwidth: 5MHz	54.7mW
	LTE Band 13 Channel Bandwidth: 10MHz	54.83mW
EMISSION DESIGNATOR	WCDMA IV	4M17F9W
	LTE Band 7 Channel Bandwidth: 5MHz	QPSK: 4M50G7D
		16QAM: 4M51W7D
	LTE Band 7	QPSK:8M99G7D



**BUREAU
VERITAS**

Test Report No.: W7L-P24100002RF07

	Channel Bandwidth: 10MHz	16QAM: 9M00W7D
	LTE Band 7	QPSK: 13M5G7D
	Channel Bandwidth: 15MHz	16QAM: 13M5W7D
	LTE Band 7	QPSK: 18M0G7D
	Channel Bandwidth: 20MHz	16QAM: 17M9W7D
	LTE Band 13	QPSK: 4M54G7D
	Channel Bandwidth: 5MHz	16QAM: 4M52W7D
	LTE Band 13	QPSK: 9M03G7D
	Channel Bandwidth: 10MHz	16QAM: 9M00W7D
ANTENNA TYPE	ANT 0(UP): PIFA Antenna with -1.5dBi gain for WCDMA IV PIFA Antenna with -1dBi gain for LTE7 PIFA Antenna with -6.5dBi gain for LTE13 ANT 1(DOWN): PIFA Antenna with -1.5dBi gain for WCDMA IV PIFA Antenna with -0.5dBi gain for LTE7 PIFA Antenna with -5dBi gain for LTE13	
HW VERSION	135100C3N	
SW VERSION	Xiaomi HyperOS 1.0	
IMEI	867957070066520	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	USB cable1: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable2: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable3: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable4: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable5: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable6: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable7: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable8: non-shielded cable, with w/o ferrite core, 1.0 meter	
EXTREME TEMPERATURE	0-40 °C	
EXTREME VOLTAGE	3.6V - 4.4V	

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- Physically, the EUT provides two completed transmitters and two receivers.

MODULATION MODE	TX FUNCTION
LTE	2TX/2RX

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in the test report.




Test Report No.: W7L-P24100002RF07

4. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.

2.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.8m

2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Y-plane for EIRP and X-axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter + USB Cable with WCDMA or LTE link
B	EUT + DC source with GSM or WCDMA or LTE link

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	1312 to 1513	1312, 1413, 1513	WCDMA
B	FREQUENCY STABILITY	1312 to 1513	1312, 1413, 1513	WCDMA
A	OCCUPIED BANDWIDTH	1312 to 1513	1312, 1413, 1513	WCDMA
A	BAND EDGE	1312 to 1513	1312, 1513	WCDMA
A	PEAK TO AVERAGE RATIO	1312 to 1513	1312, 1413, 1513	WCDMA
A	CONDUCTED EMISSION	1312 to 1513	1312, 1413, 1513	WCDMA
A	RADIATED EMISSION	1312 to 1513	1312, 1413, 1513	WCDMA

LTE BAND 7 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDT H	MODULATION	MODE
A	EIRP	20775 to 21425	20775, 21100, 21425	5MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10MHz	QPSK, 16QAM, 64QAM	1 RB / 0RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		20850 to 21350	20850, 21100, 21350	20MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	20850 to 21350	20850, 21100, 21350	20MHz	QPSK	100 RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	20775 to 21425	20775, 21100, 21425	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20850 to 21350	20850, 21100, 21350	20MHz	QPSK, 16QAM	100 RB / 0 RB Offset
A	PEAK TO AVERAGE RATIO	20850 to 21350	20850, 21100, 21350	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset 100 RB / 0 RB Offset
A	BAND EDGE	20775 to 21425	20775	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset 25 RB / 0 RB Offset
			21425	5MHz	QPSK, 16QAM	1 RB / 24 RB Offset 25 RB / 0 RB Offset
		20800 to 21400	20800	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset 50 RB / 0 RB Offset
			21400	10MHz	QPSK, 16QAM	1 RB / 49 RB Offset 50 RB / 0 RB Offset
		20825 to 21375	20825	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset 75 RB / 0 RB Offset
			21375	15MHz	QPSK, 16QAM	1 RB / 74 RB Offset 75 RB / 0 RB Offset
		20850 to 21350	20850	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset 100 RB / 0 RB Offset
			21350	20MHz	QPSK, 16QAM	1 RB / 99 RB Offset 100 RB / 0 RB Offset
A	CONDCUDE TED EMISSION	20775 to 21425	20775, 21100, 21425	5MHz	QPSK	1 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10MHz	QPSK	1 RB / 0RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK	1 RB / 0 RB Offset
		20850 to 21350	20850, 21100, 21350	20MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	20775 to 21425	21100	5MHz	QPSK	1 RB / 0 RB Offset
		20800 to 21400	21100	10MHz	QPSK	1 RB / 0 RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK	1 RB / 0 RB Offset
		20850 to 21350	21100	20MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE BAND 13 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	ERP	23205 to 23255	23205, 23230, 23255	5MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	23230	23230	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	23205 to 23255	23205, 23230, 23255	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
A	PEAK TO AVERAGE RATIO	23230	23230	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset 50 RB / 0 RB Offset
A	BAND EDGE	23205 to 23255	23205	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset 25 RB / 0 RB Offset
						1 RB / 24 RB Offset 25 RB / 0 RB Offset
			23255	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset 1 RB / 49 RB Offset
						50 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset 1 RB / 49 RB Offset
						50 RB / 0 RB Offset
A	CONDUCTED EMISSION	23205 to 23255	23205, 23230, 23255	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
A	RADIATED EMISSION	23205 to 23255	23230	5MHz	QPSK	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.



Test Report No.: W7L-P24100002RF07

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP&EIRP	23deg. C, 70%RH	DC 5/3.6~11V By Adapter	Jace Hu
FREQUENCY STABILITY	See Note	DC 3.6/3.84/4.4 By DC Source	James Fu
OCCUPIED BANDWIDTH	23deg. C, 70%RH	DC 5/3.6~11V By Adapter	James Fu
BAND EDGE	23deg. C, 70%RH	DC 5/3.6~11V By Adapter	James Fu
CONDCUDED EMISSION	23deg. C, 70%RH	DC 5/3.6~11V By Adapter	James Fu
RADIATED EMISSION	23deg. C, 70%RH	DC 5/3.6~11V By Adapter	Jace Hu
PEAK TO AVERAGE RATIO	23deg. C, 70%RH	DC 5/3.6~11V By Adapter	James Fu



Test Report No.: W7L-P24100002RF07

2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

The radiated peak output power shall be according to the specific rule Part 27.50(h)(2) that “User stations are limited to 2 watts” and 27.50(i) specific that “Peak transmit power must be measure over any interval of continuous transmission using instrumentation calibration in terms of rms-equivalent voltage.”

Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1-watt EIRP

According to the specific rule Part 27.50(b)(10) Fixed, mobile, and Portable stations (hand-held devices) transmitting in the 698-746 MHz, 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP.

3.1.2 TEST PROCEDURES

EIRP MEASUREMENT:

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T - L_C$$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively
(expressed in the same units as P_{Meas} , typically dBW or dBm).

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW.

G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP).

L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

CONDUCTED POWER MEASUREMENT:

- The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- Set the EUT to transmit under low, middle, and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

ANT0(UP):

Band	WCDMA IV		
Channel	1312	1413	1513
Frequency (MHz)	1712.4	1732.6	1752.6
RMC 12.2K	24.67	24.76	24.79
HSDPA Subtest-1	23.85	23.86	23.92
HSDPA Subtest-2	23.78	23.90	23.94
HSDPA Subtest-3	23.34	23.35	23.40
HSDPA Subtest-4	23.36	23.43	23.43
DC-HSDPA Subtest-1	23.79	23.94	23.98
DC-HSDPA Subtest-2	23.85	23.88	23.91
DC-HSDPA Subtest-3	23.33	23.38	23.48
DC-HSDPA Subtest-4	23.32	23.40	23.47
HSUPA Subtest-1	22.05	22.07	22.10
HSUPA Subtest-2	21.69	21.76	21.86
HSUPA Subtest-3	22.60	22.68	22.76
HSUPA Subtest-4	21.36	21.39	21.49
HSUPA Subtest-5	22.57	22.65	22.70
HSPA+ Subtest-1	21.88	22.03	22.02

LTE Band 7

Band/BW	Modulation	RB Size	RB Offset	Low CH 20775	Mid CH 21100	High CH 21425
				Frequency 2502.5 MHz	Frequency 2535 MHz	Frequency 2567.5 MHz
7/ 5	QPSK	1	0	23.38	23.19	23.06
		1	12	23.70	23.32	23.42
		1	24	23.20	23.08	23.15
		12	0	22.63	22.42	22.27
		12	6	22.71	22.40	22.43
		12	13	22.60	22.35	22.26
		25	0	22.67	22.32	22.22
	16QAM	1	0	22.59	22.43	22.29
		1	12	22.90	22.49	22.62
		1	24	22.41	22.20	22.25
		12	0	21.59	21.39	21.25
		12	6	21.70	21.44	21.31
		12	13	21.69	21.33	21.15
		25	0	21.49	21.35	21.27
	64QAM	1	0	21.54	21.22	21.26
		1	12	21.85	21.52	21.43
		1	24	21.34	21.17	21.31
		12	0	20.43	20.46	20.20
		12	6	20.59	20.30	20.21
		12	13	20.57	20.16	20.21
		25	0	20.48	20.25	20.26

Band/BW	Modulation	RB Size	RB Offset	Low CH 20800	Mid CH 21100	High CH 21400
				Frequency 2505 MHz	Frequency 2535 MHz	Frequency 2565 MHz
7/ 10	QPSK	1	0	23.42	23.09	22.97
		1	24	23.59	23.39	23.38
		1	49	23.17	23.21	23.14
		25	0	22.64	22.41	22.36
		25	12	22.69	22.42	22.30
		25	25	22.68	22.26	22.26
		50	0	22.57	22.36	22.31
	16QAM	1	0	22.64	22.30	22.22
		1	24	22.88	22.52	22.61
		1	49	22.41	22.18	22.14
		25	0	21.61	21.47	21.29
		25	12	21.57	21.35	21.35
		25	25	21.65	21.31	21.13
		50	0	21.60	21.28	21.22
	64QAM	1	0	21.54	21.29	21.30
		1	24	21.86	21.46	21.44
		1	49	21.33	21.30	21.28
		25	0	20.47	20.43	20.20
		25	12	20.55	20.28	20.28
		25	25	20.62	20.17	20.32
		50	0	20.55	20.31	20.21

Band/BW	Modulation	RB Size	RB Offset	Low CH 20825	Mid CH 21100	High CH 21375
				Frequency 2507.5 MHz	Frequency 2535 MHz	Frequency 2562.5 MHz
7/ 15	QPSK	1	0	23.44	23.14	23.07
		1	37	23.62	23.44	23.40
		1	74	23.18	22.87	23.08
		36	0	22.56	22.47	22.34
		36	19	22.67	22.40	22.38
		36	39	22.58	22.32	22.26
		75	0	22.67	22.31	22.24
	16QAM	1	0	22.59	22.36	22.22
		1	37	22.90	22.59	22.58
		1	74	22.38	22.18	22.21
		36	0	21.47	21.35	21.25
		36	19	21.70	21.31	21.26
		36	39	21.56	21.24	21.19
		75	0	21.52	21.39	21.25
	64QAM	1	0	21.46	21.26	21.29
		1	37	21.86	21.42	21.46
		1	74	21.29	21.22	21.27
		36	0	20.43	20.34	20.22
		36	19	20.61	20.37	20.30
		36	39	20.63	20.27	20.29
		75	0	20.57	20.35	20.23

Band/BW	Modulation	RB Size	RB Offset	Low CH 20850	Mid CH 21100	High CH 21350
				Frequency 2510 MHz	Frequency 2535 MHz	Frequency 2560 MHz
7/ 20	QPSK	1	0	23.48	23.21	23.12
		1	50	23.72	23.47	23.45
		1	99	23.23	23.00	23.09
		50	0	22.66	22.51	22.40
		50	25	22.73	22.55	22.44
		50	50	22.72	22.38	22.28
		100	0	22.68	22.43	22.33
	16QAM	1	0	22.70	22.44	22.32
		1	50	22.93	22.64	22.65
		1	99	22.51	22.22	22.26
		50	0	21.62	21.50	21.35
		50	25	21.72	21.45	21.40
		50	50	21.71	21.36	21.28
		100	0	21.64	21.41	21.29
	64QAM	1	0	21.55	21.35	21.31
		1	50	21.88	21.57	21.58
		1	99	21.41	21.32	21.35
		50	0	20.57	20.47	20.32
		50	25	20.70	20.41	20.36
		50	50	20.69	20.31	20.33
		100	0	20.62	20.40	20.35

LTE Band 13

Band/BW	Modulation	RB Size	RB Offset	Low CH 23205	Mid CH 23230	High CH 23255
				Frequency 779.5 MHz	Frequency 782.0 MHz	Frequency 784.5 MHz
13/ 5	QPSK	1	0	24.32	24.22	24.27
		1	12	24.40	24.42	24.35
		1	24	24.28	24.24	24.23
		12	0	23.35	23.32	23.23
		12	6	23.30	23.23	23.30
		12	13	23.27	23.32	23.36
		25	0	23.37	23.39	23.29
	16QAM	1	0	23.52	23.59	23.59
		1	12	23.81	23.79	23.72
		1	24	23.49	23.58	23.60
		12	0	22.48	22.44	22.39
		12	6	22.39	22.42	22.42
		12	13	22.34	22.46	22.42
		25	0	22.47	22.35	22.37
	64QAM	1	0	22.43	22.42	22.50
		1	12	22.69	22.73	22.75
		1	24	22.41	22.40	22.46
		12	0	21.29	21.22	21.32
		12	6	21.23	21.31	21.22
		12	13	21.23	21.18	21.16
		25	0	21.21	21.25	21.25

Band/BW	Modulation	RB Size	RB Offset	/	Mid CH 23230	/
				/	Frequency 782.0 MHz	/
13/ 10	QPSK	1	0	/	24.33	/
		1	24	/	24.46	/
		1	49	/	24.31	/
		25	0	/	23.38	/
		25	12	/	23.42	/
		25	25	/	23.39	/
		50	0	/	23.41	/
	16QAM	1	0	/	23.64	/
		1	24	/	23.86	/
		1	49	/	23.62	/
		25	0	/	22.51	/
		25	12	/	22.48	/
		25	25	/	22.47	/
		50	0	/	22.50	/
	64QAM	1	0	/	22.55	/
		1	24	/	22.77	/
		1	49	/	22.55	/
		25	0	/	21.37	/
		25	12	/	21.33	/
		25	25	/	21.31	/
		50	0	/	21.35	/

ANT1(DOWN):

Band	WCDMA IV		
Channel	1312	1413	1513
Frequency (MHz)	1712.4	1732.6	1752.6
RMC 12.2K	24.61	24.63	24.69
HSDPA Subtest-1	23.72	23.81	23.75
HSDPA Subtest-2	23.79	23.77	23.70
HSDPA Subtest-3	23.24	23.30	23.29
HSDPA Subtest-4	23.32	23.35	23.37
DC-HSDPA Subtest-1	23.82	23.78	23.78
DC-HSDPA Subtest-2	23.80	23.83	23.88
DC-HSDPA Subtest-3	23.30	23.30	23.33
DC-HSDPA Subtest-4	23.30	23.28	23.38
HSUPA Subtest-1	21.93	21.97	22.09
HSUPA Subtest-2	21.63	21.66	21.74
HSUPA Subtest-3	22.54	22.61	22.65
HSUPA Subtest-4	21.28	21.32	21.28
HSUPA Subtest-5	22.59	22.56	22.66
HSPA+ Subtest-1	21.91	21.87	21.94

LTE Band 7

Band/BW	Modulation	RB Size	RB Offset	Low CH 20775	Mid CH 21100	High CH 21425
				Frequency 2502.5 MHz	Frequency 2535 MHz	Frequency 2567.5 MHz
7/ 5	QPSK	1	0	23.94	23.56	23.70
		1	12	24.18	23.95	24.07
		1	24	23.86	23.61	23.86
		12	0	23.02	22.71	22.87
		12	6	23.08	22.85	22.74
		12	13	22.99	22.77	23.03
		25	0	23.06	22.64	23.00
	16QAM	1	0	22.99	22.69	23.20
		1	12	23.30	23.02	23.59
		1	24	22.87	22.64	23.10
		12	0	22.02	21.64	21.90
		12	6	22.07	21.70	21.84
		12	13	22.02	21.57	21.89
		25	0	21.99	21.63	21.82
	64QAM	1	0	22.09	21.98	21.56
		1	12	22.44	22.25	21.84
		1	24	22.05	21.87	21.59
		12	0	21.01	21.03	20.97
		12	6	21.00	21.02	20.94
		12	13	20.99	20.99	20.87
		25	0	21.02	20.96	20.96

Band/BW	Modulation	RB Size	RB Offset	Low CH 20800	Mid CH 21100	High CH 21400
				Frequency 2505 MHz	Frequency 2535 MHz	Frequency 2565 MHz
7/ 10	QPSK	1	0	23.88	23.53	23.67
		1	24	24.25	23.99	24.14
		1	49	23.76	23.54	23.72
		25	0	22.97	22.78	22.89
		25	12	23.13	22.84	22.78
		25	25	23.05	22.79	23.02
		50	0	22.96	22.68	23.05
	16QAM	1	0	22.91	22.63	23.23
		1	24	23.33	23.02	23.48
		1	49	22.93	22.56	23.13
		25	0	21.97	21.59	21.89
		25	12	22.11	21.69	21.88
		25	25	21.98	21.50	21.85
		50	0	21.95	21.54	21.86
	64QAM	1	0	21.98	21.91	21.52
		1	24	22.45	22.34	21.96
		1	49	21.93	21.85	21.56
		25	0	20.92	20.99	20.86
		25	12	21.14	21.03	20.91
		25	25	21.09	20.94	20.87
		50	0	20.92	21.02	21.01

Band/BW	Modulation	RB Size	RB Offset	Low CH 20825	Mid CH 21100	High CH 21375
				Frequency 2507.5 MHz	Frequency 2535 MHz	Frequency 2562.5 MHz
7/ 15	QPSK	1	0	23.84	23.54	23.69
		1	37	24.23	23.99	24.10
		1	74	23.86	23.53	23.86
		36	0	23.02	22.70	22.88
		36	19	23.07	22.81	22.83
		36	39	23.11	22.69	23.06
		75	0	22.97	22.62	22.96
	16QAM	1	0	22.93	22.58	23.22
		1	37	23.30	22.88	23.57
		1	74	22.86	22.63	23.20
		36	0	22.04	21.62	21.87
		36	19	21.97	21.74	21.97
		36	39	22.01	21.59	21.78
		75	0	22.00	21.58	21.92
	64QAM	1	0	22.06	21.89	21.52
		1	37	22.42	22.28	21.89
		1	74	22.00	21.95	21.60
		36	0	20.99	21.05	20.84
		36	19	21.00	21.04	21.04
		36	39	21.02	20.96	20.86
		75	0	20.90	21.02	21.02

Band/BW	Modulation	RB Size	RB Offset	Low CH 20850	Mid CH 21100	High CH 21350
				Frequency 2510 MHz	Frequency 2535 MHz	Frequency 2560 MHz
7/ 20	QPSK	1	0	23.95	23.67	23.79
		1	50	24.33	24.02	24.19
		1	99	23.91	23.58	23.87
		50	0	23.07	22.83	23.02
		50	25	23.14	22.91	23.08
		50	50	23.12	22.82	22.97
		100	0	23.10	22.75	23.09
	16QAM	1	0	23.02	22.72	23.35
		1	50	23.39	23.03	23.60
		1	99	23.01	22.67	23.21
		50	0	22.06	21.67	21.93
		50	25	22.12	21.75	21.98
		50	50	22.09	21.62	21.90
		100	0	22.05	21.68	21.93
	64QAM	1	0	22.13	22.02	21.58
		1	50	22.49	22.35	21.97
		1	99	22.06	21.96	21.62
		50	0	21.05	21.08	20.98
		50	25	21.15	21.17	21.05
		50	50	21.13	21.04	20.97
		100	0	21.04	21.06	21.03



**BUREAU
VERITAS**

Test Report No.: W7L-P24100002RF07

LTE Band 13

Band/BW	Modulation	RB Size	RB Offset	Low CH 23205	Mid CH 23230	High CH 23255
				Frequency 779.5 MHz	Frequency 782.0 MHz	Frequency 784.5 MHz
13/ 5	QPSK	1	0	24.35	24.30	24.42
		1	12	24.53	24.42	24.48
		1	24	24.37	24.35	24.26
		12	0	23.37	23.40	23.41
		12	6	23.50	23.51	23.49
		12	13	23.54	23.45	23.50
		25	0	23.48	23.51	23.42
	16QAM	1	0	23.36	23.35	23.44
		1	12	23.73	23.73	23.70
		1	24	23.45	23.42	23.44
		12	0	22.41	22.49	22.45
		12	6	22.45	22.44	22.39
		12	13	22.38	22.37	22.41
		25	0	22.49	22.40	22.53
	64QAM	1	0	22.45	22.54	22.43
		1	12	22.73	22.67	22.72
		1	24	22.45	22.48	22.50
		12	0	21.40	21.38	21.44
		12	6	21.39	21.44	21.38
		12	13	21.39	21.44	21.36
		25	0	21.39	21.47	21.47

Band/BW	Modulation	RB Size	RB Offset	/	Mid CH 23230	/
				/	Frequency 782.0 MHz	/
13/ 10	QPSK	1	0	/	24.45	/
		1	24	/	24.54	/
		1	49	/	24.40	/
		25	0	/	23.51	/
		25	12	/	23.63	/
		25	25	/	23.56	/
		50	0	/	23.53	/
	16QAM	1	0	/	23.46	/
		1	24	/	23.74	/
		1	49	/	23.56	/
		25	0	/	22.51	/
		25	12	/	22.52	/
		25	25	/	22.49	/
		50	0	/	22.55	/
	64QAM	1	0	/	22.56	/
		1	24	/	22.78	/
		1	49	/	22.59	/
		25	0	/	21.49	/
		25	12	/	21.48	/
		25	25	/	21.47	/
		50	0	/	21.51	/

**EIRP
ANT0(UP):**

WCDMA IV

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
1312	1712.4	24.67	-1.5	23.17	207.49	1
1413	1732.6	24.76	-1.5	23.26	211.84	1
1513	1752.6	24.79	-1.5	23.29	213.3	1

LTE BAND 7

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20775	2502.5	23.7	-1	22.7	186.21	2
21100	2535.0	23.32	-1	22.32	170.61	2
21425	2567.5	23.42	-1	22.42	174.58	2

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20775	2502.5	22.9	-1	21.9	154.88	2
21100	2535.0	22.49	-1	21.49	140.93	2
21425	2567.5	22.62	-1	21.62	145.21	2

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20775	2502.5	21.85	-1	20.85	121.62	2
21100	2535	21.52	-1	20.52	112.72	2
21425	2567.5	21.43	-1	20.43	110.41	2

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20800	2505.0	23.59	-1	22.59	181.55	2
21100	2535.0	23.39	-1	22.39	173.38	2
21400	2565.0	23.38	-1	22.38	172.98	2

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20800	2505.0	22.88	-1	21.88	154.17	2
21100	2535.0	22.52	-1	21.52	141.91	2
21400	2565.0	22.61	-1	21.61	144.88	2

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20800	2505	21.86	-1	20.86	121.9	2
21100	2535	21.46	-1	20.46	111.17	2
21400	2565	21.44	-1	20.44	110.66	2

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	23.62	-1	22.62	182.81	2
21100	2535.0	23.44	-1	22.44	175.39	2
21375	2562.5	23.4	-1	22.4	173.78	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	22.9	-1	21.9	154.88	2
21100	2535.0	22.59	-1	21.59	144.21	2
21375	2562.5	22.58	-1	21.58	143.88	2

CHANNEL BANDWIDTH: 15MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	21.86	-1	20.86	121.9	2
21100	2535	21.42	-1	20.42	110.15	2
21375	2562.5	21.46	-1	20.46	111.17	2



**BUREAU
VERITAS**

Test Report No.: W7L-P24100002RF07

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510.0	23.72	-1	22.72	187.07	2
21100	2535.0	23.47	-1	22.47	176.6	2
21350	2560.0	23.45	-1	22.45	175.79	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510.0	22.93	-1	21.93	155.96	2
21100	2535.0	22.64	-1	21.64	145.88	2
21350	2560.0	22.65	-1	21.65	146.22	2

CHANNEL BANDWIDTH: 20MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510	21.88	-1	20.88	122.46	2
21100	2535	21.57	-1	20.57	114.02	2
21350	2560	21.58	-1	20.58	114.29	2



**BUREAU
VERITAS**

Test Report No.: W7L-P24100002RF07

LTE BAND 13

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	24.4	-6.5	15.75	37.58	3
23230	782	24.42	-6.5	15.77	37.76	3
23255	784.5	24.35	-6.5	15.7	37.15	3

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	23.81	-6.5	15.16	32.81	3
23230	782	23.79	-6.5	15.14	32.66	3
23255	784.5	23.72	-6.5	15.07	32.14	3

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	22.69	-6.5	14.04	25.35	3
23230	782	22.73	-6.5	14.08	25.59	3
23255	784.5	22.75	-6.5	14.1	25.7	3

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	24.46	-6.5	15.81	38.11	3
-	-	-	-	-	-	-

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	23.86	-6.5	15.21	33.19	3
-	-	-	-	-	-	-

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	22.77	-6.5	14.12	25.82	3
-	-	-	-	-	-	-

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).

ANT1(DOWN):

WCDMA IV

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
1312	1712.4	24.61	-1.5	23.11	204.64	1
1413	1732.6	24.63	-1.5	23.13	205.59	1
1513	1752.6	24.69	-1.5	23.19	208.45	1

LTE BAND 7

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20775	2502.5	24.18	-0.5	23.68	233.35	2
21100	2535.0	23.95	-0.5	23.45	221.31	2
21425	2567.5	24.07	-0.5	23.57	227.51	2

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20775	2502.5	23.3	-0.5	22.8	190.55	2
21100	2535.0	23.02	-0.5	22.52	178.65	2
21425	2567.5	23.59	-0.5	23.09	203.7	2

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20775	2502.5	22.44	-0.5	21.94	156.31	2
21100	2535	22.25	-0.5	21.75	149.62	2
21425	2567.5	21.84	-0.5	21.34	136.14	2

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20800	2505.0	24.25	-0.5	23.75	237.14	2
21100	2535.0	23.99	-0.5	23.49	223.36	2
21400	2565.0	24.14	-0.5	23.64	231.21	2

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20800	2505.0	23.33	-0.5	22.83	191.87	2
21100	2535.0	23.02	-0.5	22.52	178.65	2
21400	2565.0	23.48	-0.5	22.98	198.61	2

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20800	2505	22.45	-0.5	21.95	156.68	2
21100	2535	22.34	-0.5	21.84	152.76	2
21400	2565	21.96	-0.5	21.46	139.96	2

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	24.23	-0.5	23.73	236.05	2
21100	2535.0	23.99	-0.5	23.49	223.36	2
21375	2562.5	24.1	-0.5	23.6	229.09	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	23.3	-0.5	22.8	190.55	2
21100	2535.0	22.88	-0.5	22.38	172.98	2
21375	2562.5	23.57	-0.5	23.07	202.77	2

CHANNEL BANDWIDTH: 15MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20825	2507.5	22.42	-0.5	21.92	155.6	2
21100	2535	22.28	-0.5	21.78	150.66	2
21375	2562.5	21.89	-0.5	21.39	137.72	2



**BUREAU
VERITAS**

Test Report No.: W7L-P24100002RF07

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510.0	24.33	-0.5	23.83	241.55	2
21100	2535.0	24.02	-0.5	23.52	224.91	2
21350	2560.0	24.19	-0.5	23.69	233.88	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510.0	23.39	-0.5	22.89	194.54	2
21100	2535.0	23.03	-0.5	22.53	179.06	2
21350	2560.0	23.6	-0.5	23.1	204.17	2

CHANNEL BANDWIDTH: 20MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20850	2510	22.49	-0.5	21.99	158.12	2
21100	2535	22.35	-0.5	21.85	153.11	2
21350	2560	21.97	-0.5	21.47	140.28	2



**BUREAU
VERITAS**

Test Report No.: W7L-P24100002RF07

LTE BAND 13

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	24.53	-5	17.38	54.7	3
23230	782	24.42	-5	17.27	53.33	3
23255	784.5	24.48	-5	17.33	54.08	3

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	23.73	-5	16.58	45.5	3
23230	782	23.73	-5	16.58	45.5	3
23255	784.5	23.7	-5	16.55	45.19	3

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
23205	779.5	22.73	-5	15.58	36.14	3
23230	782	22.67	-5	15.52	35.65	3
23255	784.5	22.72	-5	15.57	36.06	3

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	24.54	-5	17.39	54.83	3
-	-	-	-	-	-	-

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	23.74	-5	16.59	45.6	3
-	-	-	-	-	-	-

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	ERP (dBm)	ERP (mW)	Limit (W)
-	-	-	-	-	-	-
23230	782	22.78	-5	15.63	36.56	3
-	-	-	-	-	-	-

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).

3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

3.2.2 TEST PROCEDURE

- The device is placed at the oven room. The oven room could control the temperatures and humidity. Power warms up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be recording the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be holding $\pm 0.5^{\circ}\text{C}$ during the measurement testing. Each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP





Test Report No.: W7L-P24100002RF07

3.2.4 TEST RESULTS

Please Refer to Appendix Of this test report.


Note: LV = Low voltage (3.6V); NV = Normal voltage (3.84V); HV= High voltage (4.4V).
NT = Normal temperature (25°C)

3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band is such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage. 0.5 % of the total mean power of a given emission.

3.3.2 TEST SETUP



3.3.3 TEST PROCEDURES

- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.



Test Report No.: W7L-P24100002RF07

3.3.4 TEST RESULTS

Please Refer to Appendix Of this test report.

3.4 BAND EDGE MEASUREMENT

3.4.1 LIMITS OF BAND EDGE MEASUREMENT

According to FCC 27.53(c) specified that For operations in the 746-758 MHz band and the 776-788 MHz band , the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed. In addition, the power of any unwanted emission in an 6.25kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P(dBW), by at least $65 + 10 \log 10p(P)$, dB, for mobile and portable equipment.

According to FCC 27.53(h) specified that For operations in the 1710-1755 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. However, in the 1-megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

According to FCC 27.53(m)(4) specified that For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees. For mobile digital stations, in the 1-megahertz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least two percent may be employed.