

TEST REPORT

Reference No...... : WTS17S1298632-1E
FCC ID : 2AG32EG7010C
Applicant..... : Baicells Technologies Co., Ltd.
Address..... : 3F, Hui Yuan Development Building, No.1 Shangdi Information Industry Base, Haidian Dist., Beijing, China
Manufacturer : The same as above
Address..... : The same as above
Product..... : LTE Outdoor CPE
Model(s) : EG7010C
Brand Name..... : BaiCells
Standards..... : FCC CFR Title 47 Part 2
: FCC CFR Title 47 Part 90 Subpart Z: 2017
Date of Receipt sample : 2017-12-19
Date of Test : 2017-12-20 to 2018-02-01
Date of Issue..... : 2018-02-02
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Ford Wang

Ford Wang / Project Engineer

Approved by:



Philo Zhong

Philo Zhong / Manager

2 Laboratories Introduction

Waltek Services (Shenzhen) Co., Ltd is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation) of USA, Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CEC(California energy efficiency), IC(Industry Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek(ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.



Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. Electro Magnetic Compatibility (EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

Test Facility:**A. Accreditations for Conformity Assessment (International)**

Country/Region	Accreditation Body	Scope	Note
USA	A2LA (Certificate No.: 4243.01)	FCC ID \ DOC \ VOC	1
Canada		IC ID \ VOC	2
Japan		MIC-T \ MIC-R	-
Europe		EMCD \ RED	-
Taiwan		NCC	-
Hong Kong		OFCA	-
Australia		RCM	-
India	International Services	WPC	-
Thailand		NTC	-
Singapore		IDA	-
Note:			
1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476.			
2. IC Canada Registration No.: 7760A			

B. TCBs and Notify Bodies Recognized Testing Laboratory.

Recognized Testing Laboratory of ...	Notify body number
TUV Rheinland	Optional.
Intertek	
TUV SUD	
SGS	
Phoenix Testlab GmbH	0700
Element Materials Technology Warwick Ltd	0891
Timco Engineering, Inc.	1177
Eurofins Product Service GmbH	0681

3 Contents

	Page
1 COVER PAGE.....	1
2 LABORATORIES INTRODUCTION.....	2
3 CONTENTS.....	4
4 REVISION HISTORY.....	6
5 GENERAL INFORMATION.....	7
5.1 GENERAL DESCRIPTION OF E.U.T.	7
5.2 DETAILS OF E.U.T.	7
5.3 CHANNEL LIST.....	8
5.4 TEST MODE.....	8
5.5 SUBCONTRACTED.....	8
6 TEST SUMMARY.....	9
7 EQUIPMENT USED DURING TEST.....	10
7.1 EQUIPMENTS LIST.....	10
7.2 MEASUREMENT UNCERTAINTY.....	11
7.3 TEST EQUIPMENT CALIBRATION.....	11
8 TRANSMIT OUTPUT POWER AND PSD.....	12
8.1 EUT OPERATION.....	12
8.2 TEST PROCEDURE.....	12
8.3 TEST RESULT.....	13
9 OCCUPY BANDWIDTH.....	27
9.1 EUT OPERATION.....	27
9.2 TEST PROCEDURE.....	27
9.3 TEST RESULT.....	28
10 EMISSION MASK.....	38
10.1 EUT OPERATION.....	38
10.2 TEST PROCEDURE.....	38
10.3 TEST RESULT.....	39
11 OUT OF BAND EMISSION AT ANTENNA TERMINALS.....	47
11.1 EUT OPERATION.....	47
11.2 TEST PROCEDURE.....	47
11.3 TEST RESULT.....	47
12 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT.....	70
12.1 EUT OPERATION.....	70
12.2 TEST SETUP.....	70
12.3 SPECTRUM ANALYZER SETUP.....	71
12.4 TEST PROCEDURE.....	72
12.5 TEST RESULT.....	73
13 FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT.....	74
13.1 EUT OPERATION.....	74
13.2 TEST PROCEDURE.....	74
13.3 TEST RESULT.....	76
14 FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT.....	80
14.1 EUT OPERATION.....	80

14.2	TEST PROCEDURE.....	80
14.3	TEST RESULT	82
15	PHOTOGRAPHS OF TEST SETUP AND EUT.....	84

4 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS17S12986 32-1E	2017-12-19	2017-12-20 to 2018-02-01	2018-02-02	original	-	Valid

5 General Information

5.1 General Description of E.U.T.

Product:	LTE Outdoor CPE
Model(s):	EG7010C
Model Description:	N/A
Storage Location:	Internal Storage
Note:	N/A

5.2 Details of E.U.T.

Operation Frequency:	LTE Band 43: 3652.5~3697.5MHz WiFi 802.11b/g/n HT20: 2412~2462MHz
Type of Modulation:	LTE: QPSK, 16QAM WiFi: CCK, OFDM
Antenna installation:	LTE: Internal antenna WiFi: Internal antenna
Antenna Gain:	LTE: 10.0dBi WiFi: 0dBi
Ratings:	DC 24V, 0.5A
Number of transmitter chains:	LTE: 2TX*4RX (MIMO)

The device supports MIMO 2TX*4RX, and the MIMO works with STBC(Space-Time Block Coding).The antenna is omnidirectional, does not support any directional gain in any modes.

MIMO rate, antennas use two different streams, from this side, if RX side need to decode MIMO, data between the two stream should be correlated. The device transmits simultaneously in multiple channels in single frequency bands and uses carrier aggregation techniques.

Directional gain =GANT + 10 log (ANT_N) dBi

5.3 Channel List

Normal

5MHz		10MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
Low	3652.5	Low	3655
Middle	3675	Middle	3675
High	3697.5	High	3695
15MHz		20MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
Low	3657.5	Low	3660
Middle	3675	Middle	3675
High	3692.5	High	3690

5.4 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test Mode	Description
Data Mode (QPSK)	Keep the EUT in data communicating mode (QPSK). (5MHz, 10MHz, 15MHz, 20MHz)
Data Mode (16QAM)	Keep the EUT in data communicating mode (16QAM). (5MHz, 10MHz, 15MHz, 20MHz)

5.5 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

Yes No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

6 Test Summary

Test Items	Test Requirement	Result
	FCC	
RF Output Power	Part 2.1046 Part 90.1321	PASS
Modulation Characteristics	Part 2.1047	PASS
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 90.209	PASS
Emission Mask	Part 90.210(b)	PASS
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 90.1323	PASS
Field Strength of Spurious Radiation	Part 2.1053 Part 90.1323	PASS
Frequency stability vs. temperature	Part 2.1055(a)(1)(b) Part 90.213(a)	PASS
Frequency stability vs. voltage	Part 2.1055(d)(1)(2) Part 90.213(a)	PASS

Pass: The EUT complies with the essential requirements in the standard.

Note 1: According to FCC KDB 662911 D01 Multiple Transmitter Output v02r01 & KDB 971168 D01 Power Means License Digital Systems v03.

Note 2: EUT was on continue transmit mode, the duty cycle was 100%.

7 Equipment Used during Test

7.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	2017-09-12	2018-09-11
2.	LISN	R&S	ENV216	101215	2017-09-12	2018-09-11
3.	Cable	Top	TYPE16(3.5M)	-	2017-09-12	2018-09-11
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	2017-09-12	2018-09-11
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	2017-09-12	2018-09-11
3.	Limiter	York	MTS-IMP-136	261115-001-0024	2017-09-12	2018-09-11
4.	Cable	LARGE	RF300	-	2017-09-12	2018-09-11
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP	100091	2017-04-29	2018-04-28
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	2017-04-09	2018-04-08
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2017-04-09	2018-04-08
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2017-09-12	2018-09-11
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2017-04-09	2018-04-08
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2017-04-09	2018-04-08
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2017-04-13	2018-04-12
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	2017-04-13	2018-04-12
9	Universal Radio Communication Tester	R&S	CMU 200	112461	2017-04-13	2018-04-12
10	Signal Generator	R&S	SMR20	100046	2017-09-12	2018-09-11
11	Smart Antenna	SCHWARZBECK	HA08	-	2017-04-09	2018-04-08
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date

1	Test Receiver	R&S	ESCI	101296	2017-04-13	2018-04-12
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2017-04-09	2018-04-08
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	2017-04-13	2018-04-12
4	Cable	HUBER+SUHNER	CBL2	525178	2017-04-13	2018-04-12
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	2017-09-12	2018-09-11
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	2017-09-12	2018-09-11
3.	Universal Radio Communication Tester	R&S	CMU 200	112461	2017-04-13	2018-04-12
4	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	2017-09-12	2018-09-11

7.2 Measurement Uncertainty

Parameter	Uncertainty
Conducted Emission	± 3.64 dB(AC mains 150KHz~30MHz)
Radiated Spurious Emissions	± 5.08 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Radio Frequency	± 1 x 10 ⁻⁷ Hz
RF Power	± 0.42 dB
RF Power Density	± 0.7dB
Conducted Spurious Emissions	± 2.76 dB (9kHz~26500MHz)
Confidence interval: 95%. Confidence factor:k=2	

7.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

8 Transmit Output Power and PSD

Test Requirement:	FCC part90.1321(a)
Test Method:	FCC part2.1046 ANSI/TIA-603-E-2016
Test Mode:	Data communicating mode
Limit:	FCC: (a) Base and fixed stations are limited to 25 watts/25 MHz equivalent isotropically radiated power (EIRP). In any event, the peak EIRP powerdensity shall not exceed 1 Watt in any one-megahertz slice of spectrum. (b) In addition to the provisions in paragraph (a) of this section, transmitters operating in the 3650-3700 MHz band that emit multipledirectional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided theemissions comply with the following: (1) Different information must be transmitted to each receiver. (2) If the transmitter employs an antenna system that emits multiple directional beams but does not emit multiple directional beamssimultaneously, the total output power conducted to the array or arrays that comprise the device, <i>i.e.</i> , the sum of the power supplied to allantennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph(a) of this section, as applicable. The directional antenna gain shall be computed as follows: (i) The directional gain, in dBi, shall be calculated as the sum of 10 log (number of array elements or staves) plus the directional gain, in dBi,of the individual element or stave having the highest gain. (ii) A lower value for the directional gain than that calculated in paragraph (b)(2)(i) of this section will be accepted if sufficient evidence ispresented, <i>e.g.</i> , due to shading of the array or coherence loss in the beam-forming. (3) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequencychannels and if transmitted beams overlap, the power shall be reduced to ensure that the aggregate power from the overlapping beams does notexceed the limit specified in paragraph (b)(2) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall notexceed the limit specified in paragraph (b)(2) of this section by more than 8 dB. (4) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (b)(2) of this section.


8.1 EUT Operation

Operating Environment :

Temperature:	22.5 °C
Humidity:	52.1 % RH
Atmospheric Pressure:	101.2kPa

8.2 Test Procedure

Conducted method: The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



8.3 Test Result

Transmit Output Power								
5MHz Bandwidth								
Modulation	Test Channel	RB Size/ RB Offset	Chain 0 Output Power (dBm/5MHz)	Chain 1 Output Power (dBm/5MHz)	Total Power (dBm/5MHz)	Antenna Gain (dBi)	EIRP (dBm/5MHz)	EIRP Limit (dBm/5MHz)
QPSK	Low	1/0	18.48	18.91	21.71	13	34.71	37.01
		1/12	18.93	19.22	22.09	13	35.09	
		1/24	18.73	18.79	21.77	13	34.77	
		12/0	18.81	18.96	21.90	13	34.90	
		12/6	19.02	19.11	22.08	13	35.08	
		12/11	18.74	18.93	21.85	13	34.85	
		25/0	18.67	18.92	21.81	13	34.81	
	Middle	1/0	19.18	19.16	22.18	13	35.18	37.01
		1/12	19.26	19.48	22.38	13	35.38	
		1/24	19.5	19.22	22.37	13	35.37	
		12/0	19.38	19.33	22.37	13	35.37	
		12/6	19.33	19.43	22.39	13	35.39	
		12/11	19.36	19.32	22.35	13	35.35	
		25/0	19.21	19.36	22.30	13	35.30	
	High	1/0	18.69	19.11	21.92	13	34.92	37.01
		1/12	18.91	19.36	22.15	13	35.15	
		1/24	18.74	19.03	21.90	13	34.90	
		12/0	18.8	19.22	22.03	13	35.03	
		12/6	19.03	19.29	22.17	13	35.17	
		12/11	18.87	19.18	22.04	13	35.04	
		25/0	19	19.14	22.08	13	35.08	
16QAM	Low	1/0	18.77	19	21.90	13	34.90	37.01
		1/12	18.81	19.05	21.94	13	34.94	
		1/24	18.69	18.99	21.85	13	34.85	
		12/0	18.74	19.04	21.90	13	34.90	
		12/6	18.78	19.07	21.94	13	34.94	
		12/11	18.64	18.91	21.79	13	34.79	
		25/0	18.62	19.04	21.85	13	34.85	
	Middle	1/0	19.2	19.07	22.15	13	35.15	37.01
		1/12	19.34	19.32	22.34	13	35.34	
		1/24	18.89	19.01	21.96	13	34.96	
		12/0	19	19.13	22.08	13	35.08	
		12/6	19.17	19.22	22.21	13	35.21	
		12/11	19.15	19.15	22.16	13	35.16	
		25/0	19.24	19.15	22.21	13	35.21	
High	1/0	19.04	19.1	22.08	13	35.08	37.01	

		1/12	19.39	19.2	22.31	13	35.31	
		1/24	19.06	19.18	22.13	13	35.13	
		12/0	18.92	18.93	21.94	13	34.94	
		12/6	19.08	19.05	22.08	13	35.08	
		12/11	18.92	18.9	21.92	13	34.92	
		25/0	18.92	18.88	21.91	13	34.91	
10MHz Bandwidth								
Modulation	Test Channel	RB Size/ RB Offset	Chain 0 Output Power (dBm/10MHz)	Chain 1 Output Power (dBm/10MHz)	Total Power (dBm/10MHz)	Antenna Gain (dBi)	EIRP (dBm/10MHz)	EIRP Limit (dBm/10MHz)
QPSK	Low	1/0	18.57	18.81	21.70	13	34.70	40.02
		1/24	18.86	19.03	21.96	13	34.96	
		1/49	18.62	18.6	21.62	13	34.62	
		25/0	18.88	19.11	22.01	13	35.01	
		25/12	19.03	19.24	22.15	13	35.15	
		25/24	19.21	19.16	22.20	13	35.20	
		50/0	18.87	18.98	21.94	13	34.94	
	Middle	1/0	18.59	18.97	21.79	13	34.79	40.02
		1/24	19.36	19.74	22.56	13	35.56	
		1/49	18.7	18.99	21.86	13	34.86	
		25/0	19.09	19.26	22.19	13	35.19	
		25/12	19.38	19.54	22.47	13	35.47	
		25/24	19.21	19.38	22.31	13	35.31	
		50/0	19.16	19.25	22.22	13	35.22	
	High	1/0	18.57	18.98	21.79	13	34.79	40.02
		1/24	18.8	19.04	21.93	13	34.93	
		1/49	18.57	18.73	21.66	13	34.66	
		25/0	18.76	18.94	21.86	13	34.86	
		25/12	18.79	18.96	21.89	13	34.89	
		25/24	18.84	18.92	21.89	13	34.89	
		50/0	18.81	18.94	21.89	13	34.89	
16QAM	Low	1/0	18.27	18.67	21.48	13	34.48	40.02
		1/24	19.06	19.51	22.30	13	35.30	
		1/49	18.38	18.82	21.62	13	34.62	
		25/0	18.68	18.92	21.81	13	34.81	
		25/12	18.71	19.21	21.98	13	34.98	
		25/24	18.72	18.98	21.86	13	34.86	
		50/0	18.78	19.01	21.91	13	34.91	
	Middle	1/0	19.3	19.09	22.21	13	35.21	
		1/24	19.52	19.43	22.49	13	35.49	
		1/49	18.95	18.89	21.93	13	34.93	
		25/0	19.22	19.29	22.27	13	35.27	
		25/12	19.39	19.38	22.40	13	35.40	

		25/24	19.27	19.19	22.24	13	35.24	
		50/0	19.21	19.18	22.21	13	35.21	
	High	1/0	18.5	18.43	21.48	13	34.48	40.02
		1/24	19.28	19.19	22.25	13	35.25	
		1/49	18.62	18.61	21.63	13	34.63	
		25/0	18.79	18.82	21.82	13	34.82	
		25/12	19.02	19.16	22.10	13	35.10	
		25/24	18.86	18.98	21.93	13	34.93	
		50/0	18.85	18.96	21.92	13	34.92	
15MHz Bandwidth								
Modulation	Test Channel	RB Size/ RB Offset	Chain 0 Output Power (dBm/15MHz)	Chain 1 Output Power (dBm/15MHz)	Total Power (dBm/15MHz)	Antenna Gain (dBi)	EIRP (dBm/15MHz)	EIRP Limit (dBm/15MHz)
QPSK	Low	1/0	19.01	19.16	22.10	13	35.10	41.78
		1/37	19.23	19.3	22.28	13	35.28	
		1/74	18.95	19.2	22.09	13	35.09	
		36/0	18.78	19	21.90	13	34.90	
		36/16	19.12	19.19	22.17	13	35.17	
		36/35	18.81	18.95	21.89	13	34.89	
		75/0	18.98	19.06	22.03	13	35.03	
	Middle	1/0	19.03	19.22	22.14	13	35.14	41.78
		1/37	19.35	19.64	22.51	13	35.51	
		1/74	18.16	18.41	21.30	13	34.30	
		36/0	19.24	19.2	22.23	13	35.23	
		36/16	19.09	19.34	22.23	13	35.23	
		36/35	19.07	19.28	22.19	13	35.19	
		75/0	19.2	19.26	22.24	13	35.24	
	High	1/0	18.95	19.1	22.04	13	35.04	41.78
		1/37	19.2	19.2	22.21	13	35.21	
		1/74	19	19.08	22.05	13	35.05	
		36/0	18.97	18.91	21.95	13	34.95	
		36/16	19.14	19.1	22.13	13	35.13	
		36/35	18.87	18.98	21.94	13	34.94	
		75/0	18.94	18.88	21.92	13	34.92	
16QAM	Low	1/0	19.11	18.83	21.98	13	34.98	41.78
		1/37	19.4	19.16	22.29	13	35.29	
		1/74	18.91	18.82	21.88	13	34.88	
		36/0	18.97	18.86	21.93	13	34.93	
		36/16	19.18	18.92	22.06	13	35.06	
		36/35	19.19	18.92	22.07	13	35.07	
		75/0	19.03	18.97	22.01	13	35.01	
	Middle	1/0	19.03	19.25	22.15	13	35.15	41.78
		1/37	19.3	19.48	22.40	13	35.40	

		1/74	19.2	19.25	22.24	13	35.24	41.78
		36/0	19.24	19.35	22.31	13	35.31	
		36/16	19.23	19.23	22.24	13	35.24	
		36/35	19.29	19.34	22.33	13	35.33	
		75/0	19.26	19.18	22.23	13	35.23	
	High	1/0	18.73	18.65	21.70	13	34.70	
		1/37	19.46	18.92	22.21	13	35.21	
		1/74	18.92	18.6	21.77	13	34.77	
		36/0	18.95	18.81	21.89	13	34.89	
		36/16	19.3	18.96	22.14	13	35.14	
		36/35	19.11	18.92	22.03	13	35.03	
	75/0	19.05	18.89	21.98	13	34.98		
	20MHz Bandwidth							
Modulation	Test Channel	RB Size/ RB Offset	Chain 0 Output Power (dBm/20MHz)	Chain 1 Output Power (dBm/20MHz)	Total Power (dBm/20MHz)	Antenna Gain (dBi)	EIRP (dBm/20MHz)	EIRP Limit (dBm/20MHz)
QPSK	Low	1/0	19.11	19.29	22.21	13	35.21	43.03
		1/49	19.17	19.11	22.15	13	35.15	
		1/99	19.1	19.3	22.21	13	35.21	
		50/0	19.14	19.21	22.19	13	35.19	
		50/24	19.13	19.14	22.15	13	35.15	
		50/49	19.19	19.08	22.15	13	35.15	
	Middle	100/0	19.21	19.25	22.24	13	35.24	
		1/0	19.22	19.01	22.13	13	35.13	43.03
		1/49	19.02	19.07	22.06	13	35.06	
		1/99	19.07	18.97	22.03	13	35.03	
		50/0	19.06	18.99	22.04	13	35.04	
		50/24	19.02	18.9	21.97	13	34.97	
	50/49	19.07	18.83	21.96	13	34.96		
	High	100/0	18.93	18.89	21.92	13	34.92	
		1/0	19.13	19.19	22.17	13	35.17	43.03
		1/49	19.19	19.01	22.11	13	35.11	
		1/99	19.12	19.2	22.17	13	35.17	
		50/0	19.16	19.11	22.15	13	35.15	
		50/24	19.15	19.04	22.11	13	35.11	
	50/49	19.21	18.98	22.11	13	35.11		
	16QAM	Low	100/0	19.23	19.15	22.20	13	35.20
1/0			19.52	19.36	22.45	13	35.45	43.03
1/49			19.35	19.26	22.32	13	35.32	
1/99			19.61	19.37	22.50	13	35.50	
50/0			19.28	19.23	22.27	13	35.27	
50/24			19.12	19.07	22.11	13	35.11	
50/49	19.19	18.97	22.09	13	35.09			

		100/0	19.24	19.06	22.16	13	35.16	
	Middle	1/0	19.19	19.24	22.23	13	35.23	43.03
		1/49	19.25	19.11	22.19	13	35.19	
		1/99	19.11	19.18	22.16	13	35.16	
		50/0	19.05	18.89	21.98	13	34.98	
		50/24	19.28	19.09	22.20	13	35.20	
		50/49	18.94	18.9	21.93	13	34.93	
		100/0	19.01	18.92	21.98	13	34.98	
	High	1/0	19.33	19.25	22.30	13	35.30	43.03
		1/49	19.15	19.19	22.18	13	35.18	
		1/99	19.08	19.14	22.12	13	35.12	
		50/0	19.26	19.13	22.21	13	35.21	
		50/24	19.21	19.06	22.15	13	35.15	
		50/49	19.26	19.1	22.19	13	35.19	
		100/0	19.28	19.12	22.21	13	35.21	


Note: Limit=30dBm+10log(bandwidth/25MHz)


Remark: Directional antenna Gain = Antenna Gain + 10 lg (ANT_N) = 10.0+10 lg (2)=13.0dBi

PSD (Full RB Size)								
Bandwidth (MHz)	Modulation	Test Channel	Chain 0 PSD (dBm/MHz)	Chain 1 PSD (dBm/MHz)	Total PSD (dBm/MHz)	Antenna Gain (dBi)	EIRP density (dBm/MHz)	EIRP density Limit (dBm/MHz)
5	QPSK	Low	11.673	11.836	14.77	13.0	27.77	30.0
		Middle	11.898	11.797	14.86	13.0	27.86	
		High	11.520	11.437	14.49	13.0	27.49	
	16QAM	Low	11.193	11.505	14.36	13.0	27.36	
		Middle	11.990	12.014	15.01	13.0	28.01	
		High	11.274	11.338	14.32	13.0	27.32	
Bandwidth (MHz)	Modulation	Test Channel	Chain 0 PSD (dBm/MHz)	Chain 1 PSD (dBm/MHz)	Total PSD (dBm/MHz)	Antenna Gain (dBi)	EIRP density (dBm/MHz)	EIRP density Limit (dBm/MHz)
10	QPSK	Low	8.970	8.512	11.76	13.0	24.76	30.0
		Middle	8.751	8.625	11.70	13.0	24.70	
		High	8.446	8.563	11.52	13.0	24.52	
	16QAM	Low	8.744	8.893	11.83	13.0	24.83	
		Middle	8.559	8.611	11.60	13.0	24.60	
		High	8.373	8.391	11.39	13.0	24.39	
Bandwidth (MHz)	Modulation	Test Channel	Chain 0 PSD (dBm/MHz)	Chain 1 PSD (dBm/MHz)	Total PSD (dBm/MHz)	Antenna Gain (dBi)	EIRP density (dBm/MHz)	EIRP density Limit (dBm/MHz)
15	QPSK	Low	7.116	7.236	10.19	13.0	23.19	30.0
		Middle	7.486	7.034	10.28	13.0	23.28	
		High	7.402	6.967	10.20	13.0	23.20	
	16QAM	Low	7.344	7.127	10.25	13.0	23.25	
		Middle	7.274	6.755	10.03	13.0	23.03	
		High	7.188	6.947	10.08	13.0	23.08	
Bandwidth (MHz)	Modulation	Test Channel	Chain 0 PSD (dBm/MHz)	Chain 1 PSD (dBm/MHz)	Total PSD (dBm/MHz)	Antenna Gain (dBi)	EIRP density (dBm/MHz)	EIRP density Limit (dBm/MHz)
20	QPSK	Low	5.737	5.762	8.76	13.0	21.76	30.0
		Middle	5.685	5.780	8.74	13.0	21.74	
		High	5.517	5.733	8.64	13.0	21.64	
	16QAM	Low	6.004	5.796	8.91	13.0	21.91	
		Middle	5.899	6.035	8.98	13.0	21.98	
		High	6.094	5.907	9.01	13.0	22.01	

Remark: Directional antenna Gain = Antenna Gain + 10 lg (ANT_N) = 10.0+10 lg (2)=13.0dBi

Test Plots for PSD
Chain 0






10MHz - Low CH QPSK



10MHz - Low CH 16QAM




10MHz - Middle CH QPSK




10MHz - Middle CH 16QAM




10MHz - High CH QPSK




10MHz - High CH 16QAM




15MHz - Low CH QPSK




15MHz - Low CH 16QAM




15MHz - Middle CH QPSK




15MHz - Middle CH 16QAM




15MHz - High CH QPSK



15MHz - High CH 16QAM



20MHz - Low CH QPSK




20MHz - Low CH 16QAM




20MHz - Middle CH QPSK



20MHz - Middle CH 16QAM





20MHz - High CH QPSK




20MHz - High CH 16QAM

Chain 1







10MHz - Low CH QPSK




10MHz - Low CH 16QAM




10MHz - Middle CH QPSK




10MHz - Middle CH 16QAM




10MHz - High CH QPSK




10MHz - High CH 16QAM



15MHz - Low CH QPSK




15MHz - Low CH 16QAM




15MHz - Middle CH QPSK




15MHz - Middle CH 16QAM




15MHz - High CH QPSK




15MHz - High CH 16QAM



20MHz - Low CH QPSK




20MHz - Low CH 16QAM




20MHz - Middle CH QPSK



20MHz - Middle CH 16QAM



20MHz - High CH QPSK



20MHz - High CH 16QAM

9 Occupy Bandwidth

Test Requirement:	FCC part 90.209
Test Method:	FCC part 2.1049 ANSI/TIA-603-E-2016
Test Mode:	Data communicating mode

9.1 EUT Operation

Operating Environment :

Temperature:	22.5 °C
Humidity:	52.3% RH
Atmospheric Pressure:	101.2kPa

9.2 Test Procedure

1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer.
2. The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
3. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
4. The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

9.3 Test Result


Chain 0


Bandwidth (MHz)	Modulation	Test Channel	26dB Occupy bandwidth (MHz)	99% Occupy bandwidth (MHz)
5	QPSK	Low	4.838	4.489
		Middle	4.830	4.487
		High	4.849	4.484
	16QAM	Low	4.809	4.492
		Middle	4.874	4.494
		High	4.823	4.497
Bandwidth (MHz)	Modulation	Test Channel	26dB Occupy bandwidth (MHz)	99% Occupy bandwidth (MHz)
10	QPSK	Low	9.348	8.913
		Middle	9.376	8.920
		High	9.331	8.914
	16QAM	Low	9.331	8.927
		Middle	8.349	8.912
		High	9.328	8.916
Bandwidth (MHz)	Modulation	Test Channel	26dB Occupy bandwidth (MHz)	99% Occupy bandwidth (MHz)
15	QPSK	Low	14.030	13.403
		Middle	14.030	13.393
		High	14.040	13.395
	16QAM	Low	14.000	13.401
		Middle	14.030	13.399
		High	14.030	13.387
Bandwidth (MHz)	Modulation	Test Channel	26dB Occupy bandwidth (MHz)	99% Occupy bandwidth (MHz)
20	QPSK	Low	18.530	17.833
		Middle	18.540	17.826
		High	18.520	17.832
	16QAM	Low	18.510	17.838
		Middle	18.510	17.833
		High	18.540	17.838

Chain 1


Bandwidth (MHz)	Modulation	Test Channel	26dB Occupy bandwidth (MHz)	99% Occupy bandwidth (MHz)
5	QPSK	Low	4.864	4.491
		Middle	4.810	4.491
		High	4.861	4.495
	16QAM	Low	4.915	4.487
		Middle	4.886	4.495
		High	4.864	4.491
Bandwidth (MHz)	Modulation	Test Channel	26dB Occupy bandwidth (MHz)	99% Occupy bandwidth (MHz)
10	QPSK	Low	9.309	8.921
		Middle	9.309	8.914
		High	9.291	8.914
	16QAM	Low	9.332	8.919
		Middle	9.313	8.914
		High	9.325	8.915
Bandwidth (MHz)	Modulation	Test Channel	26dB Occupy bandwidth (MHz)	99% Occupy bandwidth (MHz)
15	QPSK	Low	14.040	13.400
		Middle	14.010	13.383
		High	14.010	13.397
	16QAM	Low	14.020	13.397
		Middle	14.000	13.401
		High	14.040	13.390
Bandwidth (MHz)	Modulation	Test Channel	26dB Occupy bandwidth (MHz)	99% Occupy bandwidth (MHz)
20	QPSK	Low	18.530	17.833
		Middle	18.540	17.826
		High	18.520	17.832
	16QAM	Low	18.530	17.837
		Middle	18.520	17.839
		High	18.510	17.830

Test Plots
Chain 0







10MHz - Low CH QPSK




10MHz - Low CH 16QAM




10MHz - Middle CH QPSK




10MHz - Middle CH 16QAM




10MHz - High CH QPSK




10MHz - High CH 16QAM




15MHz - Low CH QPSK




15MHz - Low CH 16QAM




15MHz - Middle CH QPSK




15MHz - Middle CH 16QAM




15MHz - High CH QPSK




15MHz - High CH 16QAM




20MHz - Low CH QPSK




20MHz - Low CH 16QAM




20MHz - Middle CH QPSK



20MHz - Middle CH 16QAM




20MHz - High CH QPSK




20MHz - High CH 16QAM


Chain 1




5MHz - Low CH QPSK




5MHz - Low CH 16QAM




5MHz - Middle CH QPSK




5MHz - Middle CH 16QAM




5MHz - High CH QPSK




5MHz - High CH 16QAM




10MHz - Low CH QPSK




10MHz - Low CH 16QAM




10MHz - Middle CH QPSK




10MHz - Middle CH 16QAM




10MHz - High CH QPSK




10MHz - High CH 16QAM




15MHz - Low CH QPSK




15MHz - Low CH 16QAM




15MHz - Middle CH QPSK




15MHz - Middle CH 16QAM




15MHz - High CH QPSK




15MHz - High CH 16QAM




20MHz - Low CH QPSK




20MHz - Low CH 16QAM




20MHz - Middle CH QPSK



20MHz - Middle CH 16QAM



20MHz - High CH QPSK



20MHz - High CH 16QAM

10 Emission Mask

Test Requirement:	FCC part 90.210(b)
Test Method:	ANSI/TIA-603-E-2016
Test Mode:	Data communicating mode
Limit:	Emission Mask B. For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows: (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB. (2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB. (3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log (P)$ dB

10.1 EUT Operation

Operating Environment :	
Temperature:	22.5 °C
Humidity:	52.3% RH
Atmospheric Pressure:	101.2kPa

10.2 Test Procedure

1. The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation.
2. RBW=100kHz, VBW=1MHz, Detector mode= RMS,
Trace mode: Power averaging over 100 sweeps

Note: For FCC part 90.210(b) 3, more than 250 percent emission was considered in radiated emission test items.

10.3 Test Result

Test Plots Chain 0




5MHz - Low CH QPSK

5MHz - Low CH 16QAM




5MHz - Middle CH QPSK




5MHz - Middle CH 16QAM




5MHz - High CH QPSK




5MHz - High CH 16QAM




10MHz - Low CH QPSK



10MHz - Low CH 16QAM




10MHz - Middle CH QPSK




10MHz - Middle CH 16QAM




10MHz - High CH QPSK




10MHz - High CH 16QAM




15MHz - Low CH QPSK



15MHz - Low CH 16QAM



15MHz - Middle CH QPSK




15MHz - Middle CH 16QAM



15MHz - High CH QPSK




15MHz - High CH 16QAM




20MHz - Low CH QPSK




20MHz - Low CH 16QAM




20MHz - Middle CH QPSK



20MHz - Middle CH 16QAM




20MHz - High CH QPSK




20MHz - High CH 16QAM


Chain 1




5MHz - Low CH QPSK



5MHz - Low CH 16QAM




5MHz - Middle CH QPSK




5MHz - Middle CH 16QAM



5MHz - High CH QPSK




5MHz - High CH 16QAM




10MHz - Low CH QPSK



10MHz - Low CH 16QAM




10MHz - Middle CH QPSK




10MHz - Middle CH 16QAM



10MHz - High CH QPSK




10MHz - High CH 16QAM




15MHz - Low CH QPSK



15MHz - Low CH 16QAM




15MHz - Middle CH QPSK




15MHz - Middle CH 16QAM




15MHz - High CH QPSK




15MHz - High CH 16QAM




20MHz - Low CH QPSK



20MHz - Low CH 16QAM



20MHz - Middle CH QPSK



20MHz - Middle CH 16QAM



20MHz - High CH QPSK



20MHz - High CH 16QAM

11 Out of band emission at antenna terminals

Test Requirement:	FCC part90.1323
Test Method:	FCC part2.1051 ANSI/TIA-603-E-2016
Test Mode:	Data communicating mode
Limit:	-13dBm

11.1 EUT Operation

Operating Environment :

Temperature:	23.5 °C
Humidity:	52.1 % RH
Atmospheric Pressure:	101.3kPa

11.2 Test Procedure

1. The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation.
2. The resolution bandwidth of the spectrum analyzer was set at 100 kHz when below 1GHz, 1MHz when above 1 GHz; sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic.
3. For the out of band: Set the RBW=100 kHz, VBW=300 kHz when below 1 GHz, RBW =1 MHz, VBW=3 MHz when above 1 GHz, Start=30MHz, Stop= 10th harmonic.
4. Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.

11.3 Test Result

Remark: During the test, pre-scan the QPSK, 64QAM modulation, and found the QPSK modulation(10MHz/20MHz middle channel) is the worst case.

The permit frequency range of Part 90Z is from 3650-3700MHz. according the frequency table of the device on page 7. Notes as below:

1. The frequency star and stop for band edge test instruction as below:

bandwidth	Left > 1MHz	Left 1MHz immediately	Low channel	Middle Channel	High channel	Right 1MHz immediately	Right > 1MHz
5MHz	3646.5-3649	3649-3650	3652.5	3675	3697.5	3700-3701	3701-3703.5
10MHz	3644-3649	3649-3650	3655	3675	3695	3700-3701	3701-3706
15MHz	3641.5-3649	3649-3650	3657.5	3675	3692.5	3700-3701	3701-3708.5
20MHz	3639-3649	3649-3650	3660	3675	3690	3700-3701	3701-3711

Note 1:

For **low** channel, we test left 1 MHz immediately and more than 1MHz away (5 MHz for 10 MHz bandwidth & 10MHz for 20MHz bandwidth) from the permit left band 3650 MHz; the emission above right of 3700MHz has no intentional.

For **high** channel, we test right 1 MHz immediately and more than 1MHz away (5 MHz for 10 MHz bandwidth & 10MHz for 20MHz bandwidth) from the permit right band 3700 MHz; the emission below left of 3650MHz has no intentional.


For **middle** channel, we both test left and right 1 MHz immediately and more than 1MHz away (5 MHz for 10 MHz bandwidth & 10MHz for 20MHz bandwidth) from the permit band 3650 MHz to 3700 MHz; see above table.

2. The RBW and the limit instruction as below: (The general limit = -13dBm)


1. For 2x4 MIMO, the limit=-13dBm -10 log 2=-16dBm.
2. For RBW=100kHz, the limit = -16dBm - 10log(1MHz/100kHz)= -26dBm
3. For RBW=50kHz, the limit= -16dBm - 10log(1MHz/50kHz)= -29dBm
(The spectrum of N9020A only display the RBW=51kHz, and RBW=50kHz limit is lower than RBW=51kHz.)
4. For RBW=200kHz, the limit= -16dBm - 10log(1MHz/200kHz)= -23dBm

Test Plots

Spurious emission
Chain 0




5MHz - Low CH 30MHz~26.5GHz




Date: 4.JAN.2018 04:41:16

5MHz - Low CH 26.5GHz~40GHz




5MHz - Middle CH 30MHz~26.5GHz




Date: 4.JAN.2018 04:41:44

5MHz - Middle CH 26.5GHz~40GHz



5MHz - High CH 30MHz~26.5GHz



5MHz - High CH 26.5GHz~40GHz