RF Exposure

FCC ID: 2AG32ER2820

Applicant: Chongqing Century Technology Service Co., LTD

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit Device Type: Wi-Fi 6 Router

Refer Standard: FCC Part 2.1091: Radio Frequency (RF) Exposure Compliance of Radio

communication Apparatus (All Frequency Bands)

FCC MPE Limited:

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm2)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f2)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Test Data

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Antenna Gain information:

Antenna type	Chain	Gain(dBi)
	0	3
Internal	1	3
	0+1	6

Worst-Case mode Conducted Output Power Results for 2.4G WIFI

802.11n40MHz mode

Channel	Frequency (MHz)	Output Power(dBm)	Tune Up tolerance(dBm)
1	2422	21.19	22±1

Worst-Case mode Conducted Power Test results of band U-NII-1/U-NII-3

802.11ax(40MHz) MIMO

Frequency (MHz)	Conducted Output Power (dBm)	Tune Up tolerance(dBm)
5755	15.96	16±1

Calculation results (for 2.4G WIFI): Worst-case mode

Frequency	Maximum tune	RF	Result	Limit
(MHz)	up power(dBm)	distance(cm)	(mW/cm2)	(mW/cm2)
2412	23	20	0.158	1.0

Calculation results (for 5G WIFI): Worst-Case mode

ſ	Frequency	Maximum tune	RF	Result	Limit
	(MHz)	up power(dBm)	distance(cm)	(mW/cm2)	(mW/cm2)
Ī	5745	17	20	0.040	1.0

Simultaneous Transmission Calculation

No.	Transmitter Combinations	Scenario Supported or not	
1	2.4G WLAN+5G WLAN	Yes	

Max Simultaneous Transmission Calculation (Worst-case mode)

No.	Worst Mode	MPE Ratio	Results
1	2.4G WLAN+5G WLAN	0.158+0.04=0.198	<1.0(pass)