

## RF exposure evaluation

The RF exposure evaluation was calculated as below:

1) The maximum conducted output power is -1.34dBm (0.73mW) at 2402MHz of Pi/4DQPSK mode. (0dBi antenna gain, with 1 numeric antenna gain.)

2) For Bluetooth device or fixed location transmitters, no SAR consideration applied.

3) Per KDB 447498 D01v05r02, the 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- 
- The result is rounded to one decimal place for comparison

Channel	Frequency (GHz)	Power (dBm)	Max. Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 00	2.402	-1.34	0.73	5	0.23	3.0

- Base on the calculation value, SAR evaluation is not required.
- The public is not exposed to radio frequency energy level in excess of the Commission's guideline.