

Three Panel Lamp Differential Explanation

The Panel Lamps contains three similar shapes. The dimensions are 1200*600mm 、 600*600mm and 1200*300mm. The Panel Lamps use the same Power Supply and Wireless Module, and the driver has the same schematic, Only the output current parameters are adjusted. The difference chart is as follows:

Model	LP60L12060Q01	LP60L12060D01	LP40L6060Q01	LP40L6060D01	LP40L12030Q01	LP40L12030D01
Installation	Embedded Installation	Hoisting Installation	Embedded Installation	Hoisting Installation	Embedded Installation	Hoisting Installation
Dimensions	1200*600mm 60W		600*600mm 40W		1200*300mm 40W	
Power Supply	Model: ELG-75-48 (Output: 48V/1.6A) Model: ELG-75-42 (Output: 42V/1.8A)		Model: ELG-75-48 (Output: 48V/1.6A) Model: ELG-75-42 (Output: 42V/1.8A)		Model: ELG-75-48 (Output: 48V/1.6A) Model: ELG-75-42 (Output: 42V/1.8A)	
Driver	Output: 36V/1.45A		Output: 38V/0.95A		Output: 36V/0.95A	
	R26=R27=R27=0.51R		R26=R27=0.51R		R26=R27=0.51R	
	R29=0.51R		R27=0.82R R29=NC		R27=0.82R R29=NC	
Communication Protocol	802.15.4(Zigbee)		802.15.4(Zigbee)		802.15.4(Zigbee)	
LED	Cold light LED: 336 PCS Warm light LED: 336 PCS		Cold light LED: 182 PCS Warm light LED: 182 PCS		Cold light LED: 168 PCS Warm light LED: 168 PCS	

Zhen Wang