





LTE Band 5 16QAM 1.4MHz CH-Low 1RB



LTE Band 5 16QAM 1.4MHz CH-High 1RB




LTE Band 5 16QAM 1.4MHz CH-Low 100%RB




LTE Band 5 16QAM 1.4MHz CH-High 100%RB



LTE Band 5 16QAM 3MHz CH-Low 1RB




LTE Band 5 16QAM 3MHz CH-High 1RB






LTE Band 5 16QAM 3MHz CH-Low 100%RB




LTE Band 5 16QAM 3MHz CH-High 100%RB




LTE Band 5 16QAM 5MHz CH-Low 1RB




LTE Band 5 16QAM 5MHz CH-High 1RB



LTE Band 5 16QAM 5MHz CH-Low 100%RB




LTE Band 5 16QAM 5MHz CH-High 100%RB







LTE Band 5 16QAM 10MHz CH-Low 1RB



LTE Band 5 16QAM 10MHz CH-High 1RB



LTE Band 5 16QAM 10MHz CH-Low 100%RB



LTE Band 5 16QAM 10MHz CH-High 100%RB



5.4. Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as P_{Pk} . And measure the total average power and record as P_{Avg} . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = P_{Pk} (\text{dBm}) - P_{Avg} (\text{dBm}).$$

Test Setup



Limits

According to the Sec. 22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.



Test Results

Mode	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
GSM 850 (GSM)	128	824.2	34.65	33.67	0.98	≤13	PASS
	190	836.6	34.35	33.48	0.87	≤13	PASS
	251	848.8	34.58	33.65	0.93	≤13	PASS
GPRS 850 (GMSK)	128	824.2	30.62	29.60	1.02	≤13	PASS
	190	836.6	30.59	29.54	1.05	≤13	PASS
	251	848.8	30.62	29.61	1.01	≤13	PASS
EGPRS 850 (8-PSK)	128	824.2	30.55	29.43	1.12	≤13	PASS
	190	836.6	30.52	29.46	1.06	≤13	PASS
	251	848.8	30.72	29.61	1.11	≤13	PASS
WCDMA Band V (RMC)	4132	826.4	26.68	23.80	2.88	≤13	PASS
	4183	836.6	26.87	23.98	2.89	≤13	PASS
	4233	846.6	26.82	23.89	2.93	≤13	PASS



LTE Band 5								
Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
QPSK	1.4	20407	824.7	28.17	23.07	5.10	≤13	PASS
		20525	836.5	28.03	23.03	5.00	≤13	PASS
		20643	848.3	28.10	23.07	5.03	≤13	PASS
	3	20415	825.5	28.38	23.16	5.22	≤13	PASS
		20525	836.5	28.23	23.08	5.15	≤13	PASS
		20635	847.5	28.29	23.12	5.17	≤13	PASS
	5	20425	826.5	28.34	23.14	5.20	≤13	PASS
		20525	836.5	28.19	23.04	5.15	≤13	PASS
		20625	846.5	28.21	23.07	5.14	≤13	PASS
	10	20450	829	28.31	23.11	5.20	≤13	PASS
		20525	836.5	28.13	22.99	5.14	≤13	PASS
		20600	844	28.14	23.03	5.11	≤13	PASS
16QAM	1.4	20407	824.7	27.41	21.52	5.89	≤13	PASS
		20525	836.5	27.52	21.72	5.80	≤13	PASS
		20643	848.3	27.64	21.77	5.87	≤13	PASS
	3	20415	825.5	27.58	21.56	6.02	≤13	PASS
		20525	836.5	27.75	21.77	5.98	≤13	PASS
		20635	847.5	27.76	21.79	5.97	≤13	PASS
	5	20425	826.5	27.51	21.53	5.98	≤13	PASS
		20525	836.5	27.66	21.72	5.94	≤13	PASS
		20625	846.5	27.64	21.75	5.89	≤13	PASS
	10	20450	829	27.51	21.51	6.00	≤13	PASS
		20525	836.5	27.61	21.68	5.93	≤13	PASS
		20600	844	27.62	21.72	5.90	≤13	PASS

5.5. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -40°C to +85°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -40°C to +85°. Allow at least 1.5 hours at each temperature, un-powered, before making measurements. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.3 V and 4.3 V, with a nominal voltage of 3.8V.

Test setup





Limits

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

Limits	$\leq 2.5 \text{ ppm}$
--------	------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01\text{ppm}$.



Test Result

GSM850						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
Temperature	Voltage	GMSK	8PSK	GMSK	8PSK	
Normal (25°C)	Normal	6.30	12.29	0.00335	0.00654	PASS
Extreme (85°C)		1.80	3.15	0.00096	0.00168	PASS
Extreme (80°C)		11.83	5.44	0.00629	0.00289	PASS
Extreme (70°C)		4.46	4.77	0.00237	0.00254	PASS
Extreme (60°C)		2.46	9.47	0.00131	0.00504	PASS
Extreme (50°C)		2.42	7.83	0.00129	0.00417	PASS
Extreme (40°C)		17.43	4.25	0.00927	0.00226	PASS
Extreme (30°C)		6.74	14.26	0.00359	0.00759	PASS
Extreme (20°C)		15.39	12.08	0.00819	0.00643	PASS
Extreme (10°C)		15.50	13.01	0.00825	0.00692	PASS
Extreme (0°C)		10.94	13.47	0.00582	0.00716	PASS
Extreme (-10°C)		15.80	6.73	0.00840	0.00358	PASS
Extreme (-20°C)		17.69	13.27	0.00941	0.00706	PASS
Extreme (-30°C)		1.25	14.10	0.00066	0.00750	PASS
Extreme (-40°C)		2.27	9.59	0.00121	0.00510	PASS
25°C	LV	14.54	4.61	0.00774	0.00245	PASS
	HV	10.55	2.95	0.00561	0.00157	PASS



WCDMA Band 5						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
Temperature	Voltage	BPSK	QPSK	BPSK	QPSK	
Normal (25°C)	Normal	10.54	13.49	0.00561	0.00717	PASS
Extreme (85°C)		11.20	11.74	0.00596	0.00624	PASS
Extreme (80°C)		9.39	10.15	0.00500	0.00540	PASS
Extreme (70°C)		16.43	2.75	0.00874	0.00146	PASS
Extreme (60°C)		1.64	9.08	0.00087	0.00483	PASS
Extreme (50°C)		9.39	12.90	0.00499	0.00686	PASS
Extreme (40°C)		8.18	11.06	0.00435	0.00588	PASS
Extreme (30°C)		6.90	6.60	0.00367	0.00351	PASS
Extreme (20°C)		6.97	16.30	0.00371	0.00867	PASS
Extreme (10°C)		13.79	15.86	0.00734	0.00843	PASS
Extreme (0°C)		13.25	10.27	0.00705	0.00547	PASS
Extreme (-10°C)		17.11	11.28	0.00910	0.00600	PASS
Extreme (-20°C)		17.77	4.51	0.00945	0.00240	PASS
Extreme (-30°C)		15.33	1.04	0.00815	0.00055	PASS
Extreme (-40°C)		1.48	4.12	0.00079	0.00219	PASS
25°C	LV	13.15	1.98	0.00699	0.00105	PASS
	HV	11.70	8.88	0.00622	0.00472	PASS

LTE Band 5						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	1.4MHz	16QAM	QPSK	16QAM	QPSK	
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	Normal
Normal (25°C)	3.96	9.13	0.00211	0.00485		
Extreme (85°C)	14.06	16.22	0.00748	0.00863		
Extreme (80°C)	8.99	17.77	0.00478	0.00945		
Extreme (70°C)	5.11	5.47	0.00272	0.00291		
Extreme (60°C)	7.72	10.17	0.00411	0.00541		
Extreme (50°C)	13.38	11.00	0.00712	0.00585		
Extreme (40°C)	15.05	10.40	0.00800	0.00553		
Extreme (30°C)	11.66	13.50	0.00620	0.00718		
Extreme (20°C)	2.65	10.83	0.00141	0.00576		
Extreme (10°C)	1.25	9.01	0.00067	0.00479		
Extreme (0°C)	5.94	11.65	0.00316	0.00620		



Extreme (-10°C)		13.56	9.40	0.00722	0.00500	PASS
Extreme (-20°C)		9.60	11.12	0.00511	0.00591	PASS
Extreme (-30°C)		1.63	2.25	0.00086	0.00120	PASS
Extreme (-40°C)		12.37	2.65	0.00658	0.00141	PASS
25°C	LV	11.75	14.48	0.00625	0.00770	PASS
	HV	10.00	15.41	0.00532	0.00820	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	3MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25°C)	Normal	7.11	17.16	0.00378	0.00913	PASS
Extreme (85°C)		15.75	17.62	0.00838	0.00937	PASS
Extreme (80°C)		4.39	7.71	0.00234	0.00410	PASS
Extreme (70°C)		8.92	14.00	0.00474	0.00745	PASS
Extreme (60°C)		6.68	9.08	0.00356	0.00483	PASS
Extreme (50°C)		1.99	2.32	0.00106	0.00124	PASS
Extreme (40°C)		7.72	15.11	0.00411	0.00804	PASS
Extreme (30°C)		13.00	15.63	0.00691	0.00831	PASS
Extreme (20°C)		6.03	8.32	0.00321	0.00443	PASS
Extreme (10°C)		2.28	15.86	0.00121	0.00843	PASS
Extreme (0°C)		3.22	15.15	0.00171	0.00806	PASS
Extreme (-10°C)		14.64	13.52	0.00779	0.00719	PASS
Extreme (-20°C)		12.45	6.25	0.00662	0.00332	PASS
Extreme (-30°C)		10.29	6.14	0.00547	0.00327	PASS
Extreme (-40°C)		13.41	8.99	0.00713	0.00478	PASS
25°C	LV	2.01	11.68	0.00107	0.00621	PASS
	HV	11.23	13.58	0.00597	0.00723	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	5MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25°C)	Normal	9.30	10.33	0.00495	0.00550	PASS
Extreme (85°C)		15.63	3.23	0.00832	0.00172	PASS
Extreme (80°C)		3.88	8.75	0.00206	0.00466	PASS
Extreme (70°C)		1.55	14.73	0.00082	0.00784	PASS
Extreme (60°C)		3.67	17.11	0.00195	0.00910	PASS
Extreme (50°C)		17.51	1.06	0.00931	0.00056	PASS
Extreme (40°C)		17.45	1.17	0.00928	0.00062	PASS
Extreme (30°C)		16.14	16.29	0.00859	0.00866	PASS
Extreme (20°C)		9.30	9.97	0.00495	0.00530	PASS
Extreme (10°C)		12.95	2.01	0.00689	0.00107	PASS



Extreme (0°C)		14.92	3.22	0.00794	0.00171	PASS
Extreme (-10°C)		14.99	4.57	0.00797	0.00243	PASS
Extreme (-20°C)		8.65	16.15	0.00460	0.00859	PASS
Extreme (-30°C)		9.63	15.01	0.00512	0.00798	PASS
Extreme (-40°C)		17.51	14.61	0.00931	0.00777	PASS
25°C	LV	14.66	13.08	0.00780	0.00696	PASS
	HV	4.39	8.86	0.00233	0.00471	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	10MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25°C)	Normal	15.11	15.55	0.00804	0.00827	PASS
Extreme (85°C)		2.28	6.92	0.00122	0.00368	PASS
Extreme (80°C)		6.45	16.38	0.00343	0.00871	PASS
Extreme (70°C)		9.36	11.32	0.00498	0.00602	PASS
Extreme (60°C)		14.55	10.83	0.00774	0.00576	PASS
Extreme (50°C)		17.30	1.71	0.00920	0.00091	PASS
Extreme (40°C)		1.96	3.65	0.00104	0.00194	PASS
Extreme (30°C)		2.30	7.46	0.00122	0.00397	PASS
Extreme (20°C)		14.01	8.94	0.00745	0.00476	PASS
Extreme (10°C)		17.21	5.60	0.00915	0.00298	PASS
Extreme (0°C)		8.25	13.53	0.00439	0.00720	PASS
Extreme (-10°C)		16.50	1.84	0.00877	0.00098	PASS
Extreme (-20°C)		4.27	5.22	0.00227	0.00278	PASS
Extreme (-30°C)		1.75	3.90	0.00093	0.00207	PASS
Extreme (-40°C)		12.38	9.48	0.00658	0.00504	PASS
25°C	LV	3.36	9.28	0.00179	0.00494	PASS
	HV	5.08	11.32	0.00270	0.00602	PASS

5.6. Spurious Emissions at Antenna Terminals

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier.

The peak detector is used. RBW are set to 100 kHz and VBW are set to 300 kHz for below 1G, RBW are set to 1MHz and VBW are set to 3MHz for above 1G, Sweep is set to ATUO.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 22.917(a) specifies that "The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB."

Limit	-13 dBm

Measurement Uncertainty


The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
9kHz-1GHz	0.684 dB
1GHz-18GHz	1.407 dB

Test Result


Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported.

The signal beyond the limit is carrier.







WCDMA Band V CH-Low 30MHz ~ 1GHz




WCDMA Band V CH-Low 1GHz ~ 9GHz




WCDMA Band V CH-Middle 30MHz ~ 1GHz




WCDMA Band V CH-Middle 1GHz ~ 9GHz



WCDMA Band V CH-High 30MHz ~ 1GHz




WCDMA Band V CH-High 1GHz ~ 9GHz







LTE Band 5 1.4MHz CH-Low 30MHz~1GHz




LTE Band 5 1.4MHz CH-Low 1GHz~9GHz




LTE Band 5 1.4MHz CH-Middle 30MHz~1GHz




LTE Band 5 1.4MHz CH-Middle 1GHz~9GHz



LTE Band 5 1.4MHz CH-High 30MHz~1GHz




LTE Band 5 1.4MHz CH-High 1GHz~9GHz







LTE Band 5 3MHz CH-Low 30MHz~1GHz




LTE Band 5 3MHz CH-Low 1GHz~9GHz




LTE Band 5 3MHz CH-Middle 30MHz~1GHz




LTE Band 5 3MHz CH-Middle 1GHz~9GHz



LTE Band 5 3MHz CH-High 30MHz~1GHz




LTE Band 5 3MHz CH-High 1GHz~9GHz







LTE Band 5 5MHz CH-Low 30MHz~1GHz




LTE Band 5 5MHz CH-Low 1GHz~9GHz




LTE Band 5 5MHz CH-Middle 30MHz~1GHz




LTE Band 5 5MHz CH-Middle 1GHz~9GHz



LTE Band 5 5MHz CH-High 30MHz~1GHz




LTE Band 5 5MHz CH-High 1GHz~9GHz







LTE Band 5 10MHz CH-Low 30MHz~1GHz




LTE Band 5 10MHz CH-Low 1GHz~9GHz




LTE Band 5 10MHz CH-Middle 30MHz~1GHz




LTE Band 5 10MHz CH-Middle 1GHz~9GHz



LTE Band 5 10MHz CH-High 30MHz~1GHz



LTE Band 5 10MHz CH-High 1GHz~9GHz





5.7. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement


1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26 (2015).
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=100kHz,VBW=300kHz, and the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl),the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$
The measurement results are amend as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP

= EIRP-2.15dBi.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup


9KHz ~ 30MHz



30MHz ~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m



Limits

Rule Part 22.917(a) specifies that "The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB."

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.



Test Result

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

GSM 850 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1672.9	-45.05	1.70	8.70	Horizontal	-40.20	-13.00	27.20	270
3	2509.8	-52.46	2.30	12.00	Horizontal	-44.91	-13.00	31.91	90
4	3346.4	-61.71	2.70	12.70	Horizontal	-53.86	-13.00	40.86	135
5	4183.0	-58.95	3.00	12.50	Horizontal	-51.60	-13.00	38.60	225
6	5019.6	-56.05	3.40	12.50	Horizontal	-49.10	-13.00	36.10	180
7	5856.2	-58.24	3.40	12.80	Horizontal	-50.99	-13.00	37.99	315
8	6692.8	-57.73	4.10	11.50	Horizontal	-52.48	-13.00	39.48	135
9	7529.4	-54.36	4.20	12.20	Horizontal	-48.51	-13.00	35.51	0
10	8366.0	-55.58	4.30	12.50	Horizontal	-49.53	-13.00	36.53	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

WCDMA Band V CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.2	-64.39	1.70	8.70	Horizontal	-59.54	-13.00	46.54	90
3	2509.8	-63.36	2.30	12.00	Horizontal	-55.81	-13.00	42.81	135
4	3346.4	-61.34	2.70	12.70	Horizontal	-53.49	-13.00	40.49	45
5	4183.0	-59.45	3.00	12.50	Horizontal	-52.10	-13.00	39.10	180
6	5019.6	-57.17	3.40	12.50	Horizontal	-50.22	-13.00	37.22	315
7	5856.2	-58.06	3.40	12.80	Horizontal	-50.81	-13.00	37.81	225
8	6692.8	-57.67	4.10	11.50	Horizontal	-52.42	-13.00	39.42	45
9	7529.4	-53.66	4.20	12.20	Horizontal	-47.81	-13.00	34.81	270
10	8366.0	-55.11	4.30	12.50	Horizontal	-49.06	-13.00	36.06	180

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 5 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1671.9	-65.08	1.70	8.70	Horizontal	-60.23	-13.00	47.23	135
3	2507.9	-50.02	2.30	12.00	Horizontal	-42.47	-13.00	29.47	45
4	3343.9	-50.36	2.70	12.70	Horizontal	-42.51	-13.00	29.51	270
5	4180.1	-55.66	3.00	12.50	Horizontal	-48.31	-13.00	35.31	180
6	5016.4	-57.52	3.40	12.50	Horizontal	-50.57	-13.00	37.57	90
7	5852.6	-58.68	3.40	12.80	Horizontal	-51.43	-13.00	38.43	315
8	6688.9	-58.31	4.10	11.50	Horizontal	-53.06	-13.00	40.06	225
9	7525.1	-54.14	4.20	12.20	Horizontal	-48.29	-13.00	35.29	135
10	8361.4	-55.05	4.30	12.50	Horizontal	-49.00	-13.00	36.00	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 5 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.0	-64.07	1.70	8.70	Horizontal	-59.22	-13.00	46.22	270
3	2509.5	-60.91	2.30	12.00	Horizontal	-53.36	-13.00	40.36	135
4	3346.0	-65.81	2.70	12.70	Horizontal	-57.96	-13.00	44.96	180
5	4182.5	-65.97	3.00	12.50	Horizontal	-58.62	-13.00	45.62	90
6	5019.0	-63.45	3.40	12.50	Horizontal	-56.50	-13.00	43.50	270
7	5855.5	-64.29	3.40	12.80	Horizontal	-57.04	-13.00	44.04	135
8	6692.0	-57.54	4.10	11.50	Horizontal	-52.29	-13.00	39.29	90
9	7528.5	-61.28	4.20	12.20	Horizontal	-55.43	-13.00	42.43	315
10	8365.0	-59.40	4.30	12.50	Horizontal	-53.35	-13.00	40.35	180

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 5 5MHz CH-High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1668.6	-64.53	1.70	8.70	Horizontal	-59.68	-13.00	46.68	90
3	2502.8	-51.39	2.30	12.00	Horizontal	-43.84	-13.00	30.84	315
4	3337.1	-50.90	2.70	12.70	Horizontal	-43.05	-13.00	30.05	90
5	4171.9	-54.77	3.00	12.50	Horizontal	-47.42	-13.00	34.42	135
6	5006.6	-57.46	3.40	12.50	Horizontal	-50.51	-13.00	37.51	270
7	5841.4	-58.87	3.40	12.80	Horizontal	-51.62	-13.00	38.62	180
8	6676.1	-58.18	4.10	11.50	Horizontal	-52.93	-13.00	39.93	90
9	7510.9	-55.02	4.20	12.20	Horizontal	-49.17	-13.00	36.17	315
10	8345.6	-55.55	4.30	12.50	Horizontal	-49.50	-13.00	36.50	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 5 10MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1664.3	-64.01	1.70	8.70	Horizontal	-59.16	-13.00	46.16	180
3	2496.2	-54.81	2.30	12.00	Horizontal	-47.26	-13.00	34.26	135
4	3328.1	-53.83	2.70	12.70	Horizontal	-45.98	-13.00	32.98	135
5	4160.3	-53.08	3.00	12.50	Horizontal	-45.73	-13.00	32.73	315
6	4992.4	-57.62	3.40	12.50	Horizontal	-50.67	-13.00	37.67	180
7	5824.5	-57.79	3.40	12.80	Horizontal	-50.54	-13.00	37.54	90
8	6656.6	-57.99	4.10	11.50	Horizontal	-52.74	-13.00	39.74	0
9	7488.8	-54.14	4.20	12.20	Horizontal	-48.29	-13.00	35.29	45
10	8320.9	-55.74	4.30	12.50	Horizontal	-49.69	-13.00	36.69	315

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	113824	2017-05-21	2018-05-20
Base Station Simulator	R&S	CMW500	113824	2018-05-20	2019-05-19
Base Station Simulator	R&S	CMW500	113824	2019-05-19	2020-05-18
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	/	/
Spectrum Analyzer	Key sight	N9010A	MY50210259	2017-05-21	2018-05-20
Spectrum Analyzer	Key sight	N9010A	MY50210259	2018-05-20	2019-05-19
Spectrum Analyzer	Key sight	N9010A	MY50210259	2019-05-19	2020-05-18
Universal Radio Communication Tester	Key sight	E5515C	MY48367192	2017-05-21	2018-05-20
Universal Radio Communication Tester	Key sight	E5515C	MY48367192	2018-05-20	2019-05-19
Universal Radio Communication Tester	Key sight	E5515C	MY48367192	2019-05-19	2020-05-18
Signal Analyzer	R&S	FSV30	100815	2017-12-17	2018-12-16
Signal Analyzer	R&S	FSV30	100815	2018-12-16	2019-12-15
Signal Analyzer	R&S	FSV30	100815	2019-12-15	2020-12-14
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2017-09-26	2020-09-25
Trilog Antenna	SCHWARZBECK	VUBL 9163	9163-201	2017-11-18	2020-11-17
Horn Antenna	R&S	HF907	100126	2016-07-08	2018-07-07
Horn Antenna	R&S	HF907	100126	2018-07-07	2020-07-06
Horn Antenna	ETS-Lindgren	3160-09	00102643	2016-06-21	2018-06-20
Horn Antenna	ETS-Lindgren	3160-09	00102643	2018-06-20	2020-06-19
Signal generator	R&S	SMB 100A	102594	2017-05-21	2018-05-20



Signal generator	R&S	SMB 100A	102594	2018-05-20	2019-05-19
Signal generator	R&S	SMB 100A	102594	2019-05-19	2020-05-18
Climatic Chamber	ESPEC	SU-242	93000506	2017-12-17	2020-12-16
Preampflier	R&S	SCU18	102327	2017-05-21	2018-05-20
Preampflier	R&S	SCU18	102327	2018-05-20	2019-05-19
Preampflier	R&S	SCU18	102327	2019-05-19	2020-05-18
MOB COMMS DC SUPPLY	Keysight	66319D	MY43004105	2017-05-21	2018-05-20
MOB COMMS DC SUPPLY	Keysight	66319D	MY43004105	2018-05-20	2019-05-19
MOB COMMS DC SUPPLY	Keysight	66319D	MY43004105	2019-05-19	2020-05-18
RF Cable	Agilent	SMA 15cm	0001	2017-12-17	2018-06-16
RF Cable	Agilent	SMA 15cm	0001	2018-06-16	2018-12-15
RF Cable	Agilent	SMA 15cm	0001	2018-12-15	2019-06-14
RF Cable	Agilent	SMA 15cm	0001	2019-06-14	2019-12-13
RF Cable	Agilent	SMA 15cm	0001	2019-12-13	2020-06-12
Software	R&S	EMC32	9.26.0	/	/

*****END OF REPORT*****



ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.



ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.



ANNEX C: Product Change Description

The Product Change Description are submitted separately.



ANNEX D: Verify data

The Verify data are submitted separately.