



# Test Report

## FCC Part15 Subpart C & RSS 247 Issue2

Product Name : Parrot Camera FPV  
Model No. : Camera FPV  
FCC ID : 2AG6ICAMFPV  
IC : 21053-CAMFPV

Applicant : PARROT DRONE SAS

Address : 174 Quai de Jemmapes Paris France 75010

Date of Receipt : Jul. 13th, 2017  
Test Date : Jun. 13th, 2017~ Jul. 13th, 2017  
Issued Date : Sep. 01st, 2017  
Report No. : 1772069R-RF-US-P06V01  
Report Version : V1.3

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.

# Test Report Certification

Issued Date : Sep. 01st, 2017

Report No. : 1772069R-RF-US-P06V01



Product Name : Parrot Camera FPV  
 Applicant : PARROT DRONE SAS  
 Address : 174 Quai de Jemmapes Paris France 75010  
 Manufacturer : GoerTek Inc.  
 Address : NO 268 DONGFANG NEW&HIGH-TECH INDUSTRY  
 DEVELOPMENT ZONE WEIFANG,SHANDONG 261031

Model No. : Camera FPV  
 FCC ID : 2AG6ICAMFPV  
 IC : 21053-CAMFPV  
 EUT Voltage : DC 3.3V  
 Test Voltage : AC120V/60Hz  
 Brand Name : Parrot  
 Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2015  
 ANSI C63.4:2014; ANSI C63.10:2013;  
 KDB 558074 D01v04  
 RSS GEN: Issue 4  
 RSS247: Issue 2

Test Result : Complied  
 Performed Location : DEKRA Testing and Certification (Suzhou) Co., Ltd.  
 No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006,  
 Jiangsu, China  
 TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098  
 FCC Registration Number: 800392; IC Lab Code: 4075B

Documented By : Kathy Feng  
 (Adm. Specialist: Kathy Feng)

Reviewed By : Frank He  
 (Senior Engineer: Frank He )

Approved By : Harry Zhao  
 (Engineering Manager: Harry Zhao )

## TABLE OF CONTENTS

Description	Page
1. General Information.....	6
1.1. EUT Description .....	6
1.2. Working Frequency of Each Channel: .....	6
1.3. Antenna information .....	7
1.4. Mode of Operation.....	8
1.5. Tested System Details .....	8
1.6. Configuration of Tested System.....	9
2. Technical Test.....	11
2.1. Summary of Test Result.....	11
2.2. Test Frequency configuration:.....	12
2.3. Power setting parameter.....	13
2.4. Power vs Data Rate.....	14
2.5. Test Environment.....	15
2.6. Measurement Uncertainty.....	15
3. AC Power Line Conducted Emission.....	16
3.1. Test Equipment.....	16
3.2. Test Setup.....	16
3.3. Limit.....	17
3.4. Test Procedure .....	17
3.5. Test Result.....	18
4. Emissions in restricted frequency bands .....	19
4.1. Test Equipment.....	19
4.2. Test Setup.....	20
4.3. Limit.....	21
4.4. Test Procedure .....	24
4.5. EUT test Axis definition.....	25
4.6. Test Result.....	26
5. Emissions in non-restricted frequency bands .....	40
5.1. Test Equipment.....	40
5.2. Test Setup.....	41
5.3. Limit.....	42
5.4. Test Procedure .....	43
5.5. EUT test Axis definition.....	44
5.6. Test Result.....	45
6. Radiated Emission Band Edge .....	46
6.1. Test Equipment.....	46
6.2. Test Setup.....	47

- 6.3. Limit.....47
- 6.4. Test Procedure .....48
- 6.5. EUT test definition .....49
- 6.6. Duty Cycle .....50
- 6.7. Test Result.....51
- 7. Occupied Bandwidth.....83
- 7.1. Test Equipment.....83
- 7.2. Test Setup.....83
- 7.3. Limit.....84
- 7.4. Test Procedure .....84
- 7.5. EUT test definition .....85
- 7.6. Test Result.....86
- 8. Fundamental emission output power .....87
- 8.1. Test Equipment.....87
- 8.2. Test Setup.....87
- 8.3. Limit.....88
- 8.4. Test Procedure .....89
- 8.5. EUT test definition .....90
- 8.6. Test Result.....91
- 9. Power Spectral Density .....92
- 9.1. Test Equipment.....92
- 9.2. Test Setup.....92
- 9.3. Limit.....92
- 9.4. Test Procedure .....93
- 9.5. EUT test definition .....94
- 9.6. Test Result.....95

## History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
1772069R-RF-US-P06V01	V1.0	Initial Issued Report	Aug. 04th, 2017
1772069R-RF-US-P06V01	V1.1	Add the data about power band edge for CH2 & CH10	Aug. 28th, 2017
1772069R-RF-US-P06V01	V1.2	Change the antenna gain from 0.42dBi to -0.2dBi	Aug. 29th, 2017
1772069R-RF-US-P06V01	V1.3	Update test method and description at P88, P89.	Sep. 01st, 2017

## 1. General Information

### 1.1. EUT Description

Product Name	Parrot Camera FPV
Model No.	Camera FPV
EUT Voltage	DC 3.3V
Test Voltage	AC120V/60Hz
Frequency Range	For 2.4GHz Band 802.11b/g: 2412~2462MHz
Channel Number	For 2.4GHz Band 802.11b/g: 11
Type of Modulation	802.11b: DSSS 802.11g: OFDM
Data Rate	802.11g: 6/9/12/18/24/36/48/54 Mbps 802.11b: 1/2/5.5/11 Mbps
Channel Control	Auto

### 1.2. Working Frequency of Each Channel:

802.11b/g Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz	04	2427 MHz
05	2432 MHz	06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	10	2457 MHz	11	2462 MHz	N/A	N/A

**1.3. Antenna information**

Antenna manufacturer	N/A		
Antenna Delivery	<input checked="" type="checkbox"/> 1*TX+1*RX	<input type="checkbox"/> 2*TX+2*RX	<input type="checkbox"/> 3*TX+3*RX
Antenna technology	<input checked="" type="checkbox"/> SISO		
	<input type="checkbox"/> MIMO	<input type="checkbox"/> Basic	
		<input type="checkbox"/> Sectorized antenna systems	
		<input type="checkbox"/> Cross-polarized antennas	
		<input type="checkbox"/> Unequal antenna gains, with equal transmit powers	
		<input type="checkbox"/> Spatial Multiplexing	
		<input type="checkbox"/> CDD	
Antenna Type	<input type="checkbox"/> External	<input type="checkbox"/> Dipole	
		<input checked="" type="checkbox"/> Internal	
		<input checked="" type="checkbox"/> PIFA	
		<input type="checkbox"/> PCB	
		<input type="checkbox"/> Ceramic Chip Antenna	
		<input type="checkbox"/> Metal plate type F antenna	
	<input type="checkbox"/> Cross-polarize Antenna		
Antenna Gain	-0.2dBi		

#### 1.4. Mode of Operation

Test Modes List
Mode 1: Transmit by 802.11b
Mode 2: Transmit by 802.11g


#### 1.5. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

No.	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook	Lenovo	Think pad x220	SUA0600195	Non-shielded
A	LAN cable	N/A	N/A	N/A	Non-shielded, 1.5m
B	LAN cable	N/A	N/A	N/A	Non-shielded, 10m



### 1.6. Configuration of Tested System



### 1.7. EUT Exercise Software

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of all equipment.
3	Run the RF test software, and set the test mode and channel, then press OK to start continue Transmit.

## 2. Technical Test

### 2.1. Summary of Test Result

#### For FCC:

Performed Test Item	Normative References	Limit	Result
AC Power Line Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.207	FCC 15.207	N/A
Emissions in restricted frequency bands	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.209	FCC 15.209	PASS
Emissions in non-restricted frequency bands	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(d)	$\geq 20\text{dBc}$	PASS
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2015 15.247(d)	FCC 15.209	PASS
Occupied Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(2)	$\geq 500\text{kHz}$	PASS
Fundamental emission output power	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(b)(3)	$\leq 30\text{dBm}$	PASS
Power Spectral Density	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(e)	$\leq 8\text{dBm}/3\text{kHz}$	PASS
Antenna Requirement	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.203	FCC 15.203	PASS

**For IC:**

Performed Test Item	Normative References	Limit	Result
AC Power Line Conducted Emission	RSS-Gen Issue 4 November 2014 Section 8.8	RSS-Gen	N/A
Emissions in restricted frequency bands	RSS-247 Issue 2 Feb 2017 Section 5.5	RSS-247	PASS
Emissions in non-restricted frequency bands	RSS-247 Issue 2 Feb 2017 Section 5.5	$\geq 20\text{dBc}$	PASS
Radiated Emission Band Edge	RSS-Gen Issue 4 November 2014 Section 8.10	RSS-Gen	PASS
Occupied Bandwidth	RSS-Gen Issue 4 November 2014 Section 6.6 RSS-247 Issue 2 Feb 2017 Section 5.2	$\geq 500\text{kHz}$	PASS
Fundamental emission output power	RSS-247 Issue 2 Feb 2017 Section 5.4	$\leq 30\text{dBm}$	PASS
Power Spectral Density	RSS-247 Issue 2 Feb 2017 Section 5.2	$\leq 8\text{dBm}/3\text{kHz}$	PASS
Antenna Requirement	RSS-Gen Issue 4 Section 8.3	RSS-Gen Issue 4	PASS

**2.2. Test Frequency configuration:**

Modulation Mode	Channel	Frequency	Channel	Frequency	Channel	Frequency
802.11b	01	2412 MHz	06	2437 MHz	11	2462MHz
802.11g	01	2412 MHz	06	2437 MHz	11	2462MHz

### 2.3. Power setting parameter

Modulation Mode	Test Frequency	Ant
802.11b	2412	2F
	2437	2F
	2462	2F
802.11g	2412	22
	2417	2B
	2437	2F
	2457	2D
	2462	2D

## 2.4. Power vs Data Rate

MCS Index for 802.11n	Spatial Streams	Data Rate (Mbps)						
		802.11b	802.11g		20MHz Bandwidth		40MHz Bandwidth	
					800ns GI	400ns GI	800ns GI	400ns GI
0	1	1	6	---	6.5	7.2	13.5	15.0
1	1	2	9	---	13.0	14.4	27.0	30.0
2	1	5.5	12	---	19.5	21.7	40.5	45.0
3	1	11	18	---	26.0	28.9	54.0	60.0
4	1	---	24	---	39.0	43.3	81.0	90.0
5	1	---	36	---	52.0	57.8	108.0	120.0
6	1	---	48	---	58.5	65.0	121.5	135.0
7	1	---	54	---	65.0	72.2	135.0	150.0

Note 1 : The blue form is the maximum power data rate

## 2.5. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

## 2.6. Measurement Uncertainty

Test Items	Uncertainty
AC Power Line Conducted Emission	$\pm 2.02\text{dB}$
Radiated Emission	Below 1GHz $\pm 3.8\text{ dB}$
	Above 1GHz $\pm 3.9\text{ dB}$
RF Antenna Port Conducted Emission	$\pm 1.27\text{dB}$
Radiated Emission Band Edge	$\pm 3.9\text{dB}$
Occupied Bandwidth	$\pm 1\text{kHz}$
Power Spectral Density	$\pm 1.27\text{dB}$


### 3. AC Power Line Conducted Emission

#### 3.1. Test Equipment

AC Power Line Conducted Emission / TR-1					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100906	2017.03.05	2018.03.04
Two-Line V-Network	R&S	ENV 216	101189	2016.07.16	2017.07.15
Two-Line V-Network	R&S	ENV 216	101044	2016.09.16	2017.09.15
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	N/A	N/A
50ohm Termination	SHX	TF2	07081402	2016.09.16	2017.09.15
Temperature/Humidity Meter	Zhichen	ZC1-2	TR1-TH	2017.01.05	2018.01.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

#### 3.2. Test Setup





### 3.3. Limit

Frequency of Emission (MHz)	Conducted Limit	
	Quasi-peak (dB $\mu$ V)	Average (dB $\mu$ V)
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: The lower limit shall apply at the transition frequencies.  
 Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

### 3.4. Test Procedure

Test Method			
	References Rule	Chapter	Item
<input checked="" type="checkbox"/>	ANSI C63.10-2013	6.2	Standard test method for ac power-line conducted emissions from unlicensed wireless devices
<input checked="" type="checkbox"/>	ANSI C63.4-2014	7	AC power-line conducted emission measurements

### **3.5. Test Result**

**Note:** EUT is powered by battery, so this test item is not necessary performed.

## 4. Emissions in restricted frequency bands


### 4.1. Test Equipment

Emissions in restricted frequency bands (Below 1GHz) / AC-2					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100573	2017.03.29	2018.03.28
Loop Antenna	R&S	HFH2-Z2	833799/003	2016.11.16	2017.11.15
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2016.10.16	2017.10.15
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2017.03.02	2018.03.01
Temperature/Humidity Meter	Zhichen	ZC1-2	AC2-TH	2017.01.04	2018.01.03
Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					


Emissions in restricted frequency bands (Above 1GHz) / AC-5					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2017.01.04	2018.01.03
Preamplifier	Miteq	NSP1800-25	1364185	2017.05.06	2018.05.05
Preamplifier	QuieTek	AP-040G	CHM-0906001	2017.05.06	2018.05.05
DRG Horn	ETS-Lindgren	3117	00123988	2017.01.22	2018.01.21
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2016.11.25	2017.11.24
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2017.03.02	2018.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2017.03.02	2018.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2017.03.02	2018.03.01
EMI Receiver	Agilent	N9038A	MY51210196	2017.06.10	2018.06.09
Temperature/Humidity Meter	Zhichen	ZC1-2	AC5-TH	2017.01.04	2018.01.03
Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

## 4.2. Test Setup


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:



### 4.3. Limit

**For FCC:**

Restricted Bands of operation			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			

**For IC:**

Restricted Bands of operation			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090-0.110	13.36-13.41	1645.5-1646.5	9.0-9.2
2.1735-2.1905	16.42-16.423	1660-1710	9.3-9.5
3.020-3.026	16.69475-16.69525	1718.8-1722.2	10.6-12.7
4.125-4.128	16.80425-16.80475	2200-2300	13.25-13.4
4.17725-4.17775	25.5-25.67	2310-2390	14.47-14.5
4.20725-4.20775	37.5-38.25	2655-2900	15.35-16.2
5.677-5.683	73-74.6	3260-3267	17.7-21.4
6.215-6.218	74.8-75.2	3332-3339	22.01-23.12
6.26775-6.26825	108-138	3345.8-3358	23.6-24.0
6.31175-6.31225	156.52475-156.52525	3500-4400	31.2-31.8
8.291-8.294	156.7-156.9	4500-5150	36.43-36.5
8.362-8.366	240-285	5350-5460	Above 38.6
8.37625-8.38675	322-335.4	7250-7750	
8.41425-8.41475	399.9-410	8025-8500	
12.29-12.293	608-614		
12.51975-12.52025	960-1427		
12.57675-12.57725	1435-1626.5		

Emissions in restricted frequency bands			
Frequency (MHz)	Field strength ( $\mu$ V/m)	Field strength (dB $\mu$ V/m)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 <sub>(Note 1)</sub>
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 <sub>(Note 1)</sub>
1.705 - 30	30	29.5	30 <sub>(Note 1)</sub>
30 - 88	100	40	3 <sub>(Note 2)</sub>
88 - 216	150	43.5	3 <sub>(Note 2)</sub>
216 - 960	200	46	3 <sub>(Note 2)</sub>
Above 960	500	54	3 <sub>(Note 2)</sub>

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).







Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

#### 4.4. Test Procedure

Emissions in restricted frequency bands			
	References Rule	Chapter	Description
<input type="checkbox"/>	ANSI C63.10	11.11	Emissions in non-restricted frequency bands
	<input type="checkbox"/> ANSI C63.10	11.11.2	Reference level measurement
	<input type="checkbox"/> ANSI C63.10	11.11.3	Emission level measurement
<input checked="" type="checkbox"/>	ANSI C63.10	11.12	Emissions in restricted frequency bands
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.1	Radiated emission measurements
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.7	Radiated spurious emission test
	<input checked="" type="checkbox"/> ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
	<input checked="" type="checkbox"/> ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
	<input checked="" type="checkbox"/> ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz
	<input type="checkbox"/> ANSI C63.10	11.12.2.3	Quasi-peak measurement procedure
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.4	Peak power measurement procedure
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.5	Average power measurement procedures
	<input type="checkbox"/> ANSI C63.10	11.12.2.5.1	Trace averaging with continuous EUT transmission at full power
	<input type="checkbox"/> ANSI C63.10	11.12.2.5.2	Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.5.3	Reduced VBW averaging across ON and OFF times of the EUT transmissions with max hold




**4.5. EUT test Axis definition**

Item	Emissions in restricted frequency bands			
Device Category	<input type="checkbox"/>	Fixed point-to-point		
	<input type="checkbox"/>	Emit multiple directional beams, simultaneously or sequentially		
	<input checked="" type="checkbox"/>	Other cases		
Test mode	Mode 1~2			
Test method	<input checked="" type="checkbox"/>	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>	Worst Axis <input checked="" type="checkbox"/>
	<input type="checkbox"/>	Conducted		
	<input type="checkbox"/>	Chain 1		
				
	<input type="checkbox"/>	Chain 1	Chain 2	
				
	<input type="checkbox"/>	Chain 1	Chain 2	Chain 3
				


### 4.6. Test Result

Engineer: Simon	
Site: AC5	Time: 2017/06/23 - 09:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2412MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	4824.000	53.726	55.287	-0.274	54.000	-1.561	AV
2		4825.000	55.539	57.092	-18.461	74.000	-1.553	PK
3		7239.000	47.880	45.597	-26.120	74.000	2.283	PK
4		9644.500	51.145	46.970	-22.855	74.000	4.175	PK

Engineer: Simon	
Site: AC5	Time: 2017/06/23 - 09:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2412MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	4824.000	53.123	54.684	-0.877	54.000	-1.561	AV
2		4825.000	55.156	56.709	-18.844	74.000	-1.553	PK
3		7230.500	47.732	45.334	-26.268	74.000	2.398	PK
4		9644.500	51.650	47.475	-22.350	74.000	4.175	PK

Engineer: Simon	
Site: AC5	Time: 2017/06/23 - 09:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2437MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	4874.000	53.662	55.274	-0.338	54.000	-1.612	AV
2		4876.000	56.514	58.096	-17.486	74.000	-1.582	PK
3		7307.000	46.482	43.582	-27.518	74.000	2.900	PK
4		9746.500	48.836	44.533	-25.164	74.000	4.303	PK

Engineer: Simon	
Site: AC5	Time: 2017/06/23 - 09:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2437MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	4876.000	53.826	55.408	-20.174	74.000	-1.582	PK
2		7307.000	45.320	42.420	-28.680	74.000	2.900	PK
3		9746.500	47.823	43.520	-26.177	74.000	4.303	PK

Engineer: Simon	
Site: AC5	Time: 2017/06/23 - 09:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2462MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	4924.000	53.636	54.636	-0.364	54.000	-1.001	AV
2		4927.000	55.739	56.682	-18.261	74.000	-0.943	PK
3		7383.500	45.690	43.567	-28.310	74.000	2.123	PK
4		9848.000	44.359	39.289	-29.641	74.000	5.070	PK

Engineer: Simon	
Site: AC5	Time: 2017/06/23 - 09:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2462MHz by 802.11b	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	4924.000	52.984	53.984	-1.016	54.000	-1.001	AV
2		4927.000	55.438	56.381	-18.562	74.000	-0.943	PK
3		7383.500	44.454	42.331	-29.546	74.000	2.123	PK
4		9848.000	44.003	38.933	-29.997	74.000	5.070	PK


Engineer: Simon	
Site: AC5	Time: 2017/06/23 - 09:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2412MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4824.000	41.005	42.566	-32.995	74.000	-1.561	PK
2	*	7236.000	42.606	40.282	-31.394	74.000	2.323	PK
3		9548.000	42.303	37.850	-31.697	74.000	4.452	PK




Engineer: Simon	
Site: AC5	Time: 2017/06/23 - 09:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2412MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4824.000	40.658	42.219	-33.342	74.000	-1.561	PK
2	*	7236.000	42.315	39.991	-31.685	74.000	2.323	PK
3		9648.000	42.011	37.983	-31.989	74.000	4.028	PK

Engineer: Simon	
Site: AC5	Time: 2017/06/23 - 09:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2437MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	4874.000	50.556	52.168	-3.444	54.000	-1.612	AV
2		4876.000	57.341	58.923	-16.659	74.000	-1.582	PK
3		7307.000	47.954	45.054	-26.046	74.000	2.900	PK
4		9738.000	49.924	45.112	-24.076	74.000	4.812	PK

Engineer: Simon	
Site: AC5	Time: 2017/06/23 - 09:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2437MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	4874.000	50.836	52.448	-3.164	54.000	-1.612	AV
2		4876.000	55.398	56.980	-18.602	74.000	-1.582	PK
3		7311.000	46.572	43.697	-27.428	74.000	2.875	PK
4		9729.500	48.025	43.133	-25.975	74.000	4.892	PK

Engineer: Simon	
Site: AC5	Time: 2017/06/23 - 09:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2462MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	4924.000	51.871	52.871	-2.129	54.000	-1.001	AV
2		4927.000	55.614	56.557	-18.386	74.000	-0.943	PK
3		7375.000	47.539	45.355	-26.461	74.000	2.184	PK
4		9848.500	48.623	43.551	-25.377	74.000	5.072	PK


Engineer: Simon	
Site: AC5	Time: 2017/06/23 - 09:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2462MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	4924.000	53.249	54.249	-0.751	54.000	-1.001	AV
2		4927.000	56.126	57.069	-17.874	74.000	-0.943	PK
3		7383.500	46.896	44.773	-27.104	74.000	2.123	PK
4		9848.500	48.482	43.410	-25.518	74.000	5.072	PK

### The worst case of Radiated Emission below 1GHz:

Engineer: Leon	
Site: AC3	Time: 2017/07/12
Limit: FCC_Part15.109_RE(3m)_ClassB	Margin: 0
Probe: AC3_3m (30-1000MHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2412MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Probe (dB/m)	Cable (dB)	Amp (dB)	Ant Pos (cm)	Table Pos (deg)	Type
1	*	30.885	29.693	2.243	-10.307	40.000	20.990	6.460	0.000	200	110	QP
2		101.746	21.105	4.417	-22.395	43.500	9.822	6.866	0.000	200	152	QP
3		138.896	22.616	4.937	-20.884	43.500	10.650	7.029	0.000	102	360	QP
4		421.597	30.544	3.335	-15.456	46.000	19.249	7.961	0.000	100	289	QP
5		554.521	32.507	5.328	-13.493	46.000	18.868	8.312	0.000	170	360	QP
6		642.135	33.094	4.384	-12.906	46.000	20.178	8.532	0.000	127	360	QP

**Note:**

- " \* ", means this data is the worst emission level.
- Measurement Level = Reading Level + Factor(Probe+Cable-Amp).

Engineer: Leon	
Site: AC3	Time: 2017/07/12
Limit: FCC_Part15.109_RE(3m)_ClassB	Margin: 0
Probe: AC3_3m (30-1000MHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2412MHz by 802.11b	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Probe (dB/m)	Cable (dB)	Amp (dB)	Ant Pos (cm)	Table Pos (deg)	Type
1		102.934	26.759	4.688	-16.741	43.500	15.204	6.868	0.000	100	110	QP
2		211.556	27.599	4.368	-15.901	43.500	15.908	7.323	0.000	100	28	QP
3		310.002	29.895	4.476	-16.105	46.000	17.771	7.648	0.000	100	8	QP
4		618.597	32.732	5.364	-13.268	46.000	18.889	8.480	0.000	100	100	QP
5		774.356	36.080	3.754	-9.920	46.000	23.496	8.830	0.000	100	350	QP
6	*	946.126	37.034	2.426	-8.966	46.000	25.409	9.199	0.000	200	145	QP

**Note:**

1. " \* ", means this data is the worst emission level.
2. Measurement Level = Reading Level + Factor(Probe+Cable-Amp).

## 5. Emissions in non-restricted frequency bands


### 5.1. Test Equipment

Emissions in non-restricted frequency bands / TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.02.04	2018.02.03
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2017.04.09	2018.04.08
MXA Signal Analyzer	Keysight	N9020A	MY56060147	2017.04.09	2018.04.08
Temperature/Humidity Meter	zhichen	ZC1-2	TR8-TH	2017.04.10	2018.04.09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.



## 5.2. Test Setup









### 5.3. Limit

Un-Restricted Band Emissions Limit	
RF Output power (Detection methods)	Limit(dB)
RF Output power(Average detector)	30c(Note1)
RF Output power(PK detector)	20c(Note2)
<p>Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).</p> <p>Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).</p>	

### 5.4. Test Procedure

Emissions in non-restricted frequency bands			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	11.11	Emissions in non-restricted frequency bands
	<input checked="" type="checkbox"/> ANSI C63.10	11.11.2	Reference level measurement
	<input checked="" type="checkbox"/> ANSI C63.10	11.11.3	Emission level measurement
<input type="checkbox"/>	ANSI C63.10	11.12	Emissions in restricted frequency bands
	<input type="checkbox"/> ANSI C63.10	11.12.1	Radiated emission measurements
	<input type="checkbox"/> ANSI C63.10	11.12.2.7	Radiated spurious emission test
<input type="checkbox"/>	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
<input type="checkbox"/>	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
<input checked="" type="checkbox"/>	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2	Antenna-port conducted measurements
	<input type="checkbox"/> ANSI C63.10	11.12.2.3	Quasi-peak measurement procedure
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.4	Peak power measurement procedure
	<input type="checkbox"/> ANSI C63.10	11.12.2.5	Average power measurement procedures
	<input type="checkbox"/> ANSI C63.10	11.12.2.5.1	Trace averaging with continuous EUT transmission at full power
	<input type="checkbox"/> ANSI C63.10	11.12.2.5.2	Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction
	<input type="checkbox"/> ANSI C63.10	11.12.2.5.3	Reduced VBW averaging across ON and OFF times of the EUT transmissions with max hold

**5.5. EUT test Axis definition**

Item	Emissions in non-restricted frequency bands			
Device Category	<input type="checkbox"/>	Fixed point-to-point		
	<input type="checkbox"/>	Emit multiple directional beams, simultaneously or sequentially		
	<input checked="" type="checkbox"/>	Other cases		
Test mode	Mode 1 ~ 2			
Test method	<input type="checkbox"/>	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>
	<input checked="" type="checkbox"/>	Conducted		
	<input checked="" type="checkbox"/>	Chain 0		
				
	<input type="checkbox"/>	Chain 0	Chain 1	
				
	<input type="checkbox"/>	Chain 0	Chain 1	Chain 2
				

### 5.6. Test Result

Product Name	: Parrot Camera FPV	Power	: DC 3.3V
Test Mode	: Mode1~2	Test Site	: TR8
Test Date	: 2017.07.10		

Mode	Channel	Test Frequency (MHz)	In-Band PSD[a] (dBm/100kHz)	Frequency (MHz)	Out-Band PSD[b] (dBm/100kHz)	[a]-[b] (dB)	Limit (dB)	Result
1	01	2412	3.861	2400	-18.109	21.97	≥20	Pass
1	11	2462	2.298	2500	-64.136	66.434	≥20	Pass
2	01	2412	0.661	2400	-26.108	26.769	≥20	Pass
2	11	2462	2.020	2500	-52.023	54.043	≥20	Pass

Note: The worst case of emissions in non-restricted frequency bands as below:

Mode 1 CH01(2412MHz)




## 6. Radiated Emission Band Edge

### 6.1. Test Equipment

Radiated Emission Band Edge / AC-5					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Receiver	Agilent	N9038A	MY51210196	2016.07.16	2017.07.15
Pre-Amplifier	Miteq	NSP1800-25	1364185	2017.05.03	2018.05.02
DRG Horn Antenna	ETS-Lindgren	3117	00167055	2017.07.12	2018.07.11
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2016.09.18	2017.09.17
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2017.02.28	2018.02.27
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2017.02.28	2018.02.27
Temperature/Humidity Meter	Zhichen	ZC1-2	AC5-TH	2017.01.05	2018.01.04
Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

### 6.2. Test Setup



### 6.3. Limit

Radiated Emission Band edge

Frequency bands (MHz)	Detector	Limit (dB $\mu$ V/m)	RBW (MHz)	Distance (m)
2310-2390	PK	74	1	3
2483.5-2500	AV	54	1	3







Note: The field strength of emissions appearing within these frequency bands shall not exceed the limits.

### 6.4. Test Procedure

Radiated Emission Band Edge			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	6.10	Band-edge testing
	<input checked="" type="checkbox"/> ANSI C63.10	6.10.5	Restricted-band band-edge measurements
	<input type="checkbox"/> ANSI C63.10	6.10.6	Marker-delta method
<input checked="" type="checkbox"/>	ANSI C63.10	11.12	Emissions in restricted frequency bands
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.1	Radiated emission measurements
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.7	Radiated spurious emission test
<input type="checkbox"/>	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
<input type="checkbox"/>	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
<input checked="" type="checkbox"/>	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz
	<input type="checkbox"/> ANSI C63.10	11.12.2.3	Quasi-peak measurement procedure
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.4	Peak power measurement procedure
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.5	Average power measurement procedures
	<input type="checkbox"/> ANSI C63.10	11.12.2.5.1	Trace averaging with continuous EUT transmission at full power
	<input type="checkbox"/> ANSI C63.10	11.12.2.5.2	Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.5.3	Reduced VBW averaging across ON and OFF times of the EUT transmissions with max hold




**6.5. EUT test definition**

Item	Radiated Emission Band Edge			
Device Category	<input type="checkbox"/>	Fixed point-to-point		
	<input type="checkbox"/>	Emit multiple directional beams, simultaneously or sequentially		
	<input checked="" type="checkbox"/>	Other cases		
Test mode	Mode 1~2			
Test method	<input checked="" type="checkbox"/>	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>	Worst Axis <input checked="" type="checkbox"/>
	<input type="checkbox"/>	Conducted		
	<input type="checkbox"/>	Chain 0		
				
	<input type="checkbox"/>	Chain 0	Chain 1	
				
	<input type="checkbox"/>	Chain 0	Chain 1	Chain 2
				


### 6.6. Duty Cycle

Test Mode	Tx On (ms)	Tx Off (ms)	VBW	Tx On + Tx Off (ms)	Duty Cycle
802.11b	N/A	N/A	10Hz	N/A	100%
802.11g	N/A	N/A	10Hz	N/A	100%




### 6.7. Test Result

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 10:39
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2412MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2389.352	52.806	17.126	-1.194	54.000	35.680	AV
2		2390.000	51.005	15.323	-2.995	54.000	35.682	AV
3	*	2409.232	99.559	63.827	N/A	N/A	35.732	AV

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 11:00
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2412MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	58.779	23.097	-15.221	74.000	35.682	PK
2	*	2410.184	103.120	67.385	N/A	N/A	35.735	PK

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 11:02
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2412MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2389.296	51.538	15.858	-2.462	54.000	35.680	AV
2		2390.000	50.307	14.625	-3.693	54.000	35.682	AV
3	*	2409.400	99.689	63.956	N/A	N/A	35.733	AV

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 11:04
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2412MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	58.367	22.685	-15.633	74.000	35.682	PK
2	*	2410.296	103.407	67.672	N/A	N/A	35.735	PK

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 11:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2437MHz by 802.11b	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	44.491	8.809	-9.509	54.000	35.682	AV
2	*	2434.260	99.991	64.184	N/A	N/A	35.806	AV
3		2483.500	40.510	4.618	-13.490	54.000	35.891	AV


Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 11:16
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2437MHz by 802.11b	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	53.487	17.805	-20.513	74.000	35.682	PK
2	*	2438.535	103.491	67.685	N/A	N/A	35.805	PK
3		2483.500	51.696	15.804	-22.304	74.000	35.891	PK




Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 11:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2437MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	41.597	5.915	-12.403	54.000	35.682	AV
2	*	2434.545	99.759	63.952	N/A	N/A	35.807	AV
3		2483.500	39.681	3.789	-14.319	54.000	35.891	AV

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 11:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2437MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	52.601	16.919	-21.399	74.000	35.682	PK
2	*	2435.115	103.111	67.304	N/A	N/A	35.806	PK
3		2483.500	51.430	15.538	-22.570	74.000	35.891	PK

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 11:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2462MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2459.152	100.293	64.427	N/A	N/A	35.866	AV
2		2483.500	45.334	9.442	-8.666	54.000	35.891	AV
3		2486.776	52.778	16.863	-1.222	54.000	35.915	AV

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 11:34
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2462MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2460.472	103.768	67.896	N/A	N/A	35.871	PK
2		2483.500	55.301	19.409	-18.699	74.000	35.891	PK
3		2487.568	59.389	23.468	-14.611	74.000	35.921	PK

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 11:37
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2462MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2459.344	100.265	64.398	N/A	N/A	35.867	AV
2		2483.500	49.560	13.668	-4.440	54.000	35.891	AV
3		2486.872	53.444	17.528	-0.556	54.000	35.916	AV

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 11:40
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 1:Transmit at 2462MHz by 802.11b	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2463.112	103.713	67.836	N/A	N/A	35.877	PK
2		2483.500	55.985	20.093	-18.015	74.000	35.891	PK
3		2487.808	59.600	23.677	-14.400	74.000	35.922	PK

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 12:01
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2412MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	53.370	17.688	-0.630	54.000	35.682	AV
2	*	2404.696	94.428	58.708	N/A	N/A	35.720	AV


Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 12:21
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2412MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	71.958	36.276	-2.042	74.000	35.682	PK
2	*	2404.752	103.004	67.284	N/A	N/A	35.721	PK




Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 12:29
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2412MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	53.312	17.630	-0.688	54.000	35.682	AV
2	*	2404.976	94.554	58.833	N/A	N/A	35.721	AV

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 12:31
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2412MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	72.118	36.436	-1.882	74.000	35.682	PK
2	*	2404.752	103.112	67.392	N/A	N/A	35.721	PK

Engineer: Simon	
Site: AC5	Time: 2017/08/28 - 16:06
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2417MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2389.150	53.218	17.538	-0.782	54.000	35.680	AV
2		2390.000	53.089	17.407	-0.911	54.000	35.682	AV
3	*	2409.918	97.227	61.493	N/A	N/A	35.735	AV

Engineer: Simon	
Site: AC5	Time: 2017/08/28 - 16:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2417MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	66.565	30.883	-7.435	74.000	35.682	PK
2	*	2410.327	107.808	72.073	N/A	N/A	35.735	PK

Engineer: Simon	
Site: AC5	Time: 2017/08/28 - 16:09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2417MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	49.143	13.461	-4.857	54.000	35.682	AV
2	*	2409.918	97.913	62.179	N/A	N/A	35.735	AV

Engineer: Simon	
Site: AC5	Time: 2017/08/28 - 16:12
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2417MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	63.402	27.720	-10.598	74.000	35.682	PK
2	*	2410.269	106.847	71.112	N/A	N/A	35.735	PK

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 12:34
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2437MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	44.361	8.679	-9.639	54.000	35.682	AV
2	*	2430.080	97.831	62.023	N/A	N/A	35.808	AV
3		2483.500	41.388	5.496	-12.612	54.000	35.891	AV


Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 12:39
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2437MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	57.290	21.608	-16.710	74.000	35.682	PK
2	*	2429.605	106.589	70.781	N/A	N/A	35.808	PK
3		2483.500	54.795	18.903	-19.205	74.000	35.891	PK
4		2484.515	60.306	24.407	-13.694	74.000	35.898	PK




Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 12:41
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2437MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	43.559	7.877	-10.441	54.000	35.682	AV
2	*	2430.080	97.090	61.282	N/A	N/A	35.808	AV
3		2483.500	40.850	4.958	-13.150	54.000	35.891	AV

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 12:43
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2437MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	57.526	21.844	-16.474	74.000	35.682	PK
2	*	2430.460	106.183	70.375	N/A	N/A	35.808	PK
3		2483.500	54.581	18.689	-19.419	74.000	35.891	PK
4		2484.800	58.873	22.972	-15.127	74.000	35.901	PK

Engineer: Simon	
Site: AC5	Time: 2017/08/28 - 16:16
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2457MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2449.968	98.759	62.933	N/A	N/A	35.826	AV
2		2483.500	52.892	17.000	-1.108	54.000	35.891	AV

Engineer: Simon	
Site: AC5	Time: 2017/08/28 - 16:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2457MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2449.994	107.133	71.307	N/A	N/A	35.826	PK
2		2483.500	64.954	29.062	-9.046	74.000	35.891	PK
3		2484.842	67.075	31.174	-6.925	74.000	35.901	PK

Engineer: Simon	
Site: AC5	Time: 2017/08/28 - 16:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2457MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2464.304	98.937	63.061	N/A	N/A	35.876	AV
2		2483.500	51.499	15.607	-2.501	54.000	35.891	AV

Engineer: Simon	
Site: AC5	Time: 2017/08/28 - 16:24
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2457MHz by 802.11g	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2464.543	108.224	72.349	N/A	N/A	35.875	PK
2		2483.500	64.447	28.555	-9.553	74.000	35.891	PK
3		2484.948	65.882	29.980	-8.118	74.000	35.902	PK

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 13:04
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2462MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2455.096	95.721	59.873	N/A	N/A	35.848	AV
2		2483.500	53.081	17.190	-0.919	54.000	35.891	AV


Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 13:04
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2462MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2454.736	104.347	68.500	N/A	N/A	35.846	PK
2		2483.500	71.855	35.963	-2.145	74.000	35.891	PK




Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 13:06
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2462MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2455.024	94.757	58.909	N/A	N/A	35.848	AV
2		2483.500	53.402	17.510	-0.598	54.000	35.891	AV

Engineer: Simon	
Site: AC5	Time: 2017/07/12 - 13:09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Parrot Camera FPV	Power: DC 3.3V
Note: Mode 2:Transmit at 2462MHz by 802.11g	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2454.640	104.013	68.167	N/A	N/A	35.846	PK
2		2483.500	72.359	36.467	-1.641	74.000	35.891	PK


## 7. Occupied Bandwidth

### 7.1. Test Equipment

Occupied Bandwidth / TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.02.04	2018.02.03
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2017.04.09	2018.04.08
MXA Signal Analyzer	Keysight	N9020A	MY56060147	2017.04.09	2018.04.08
Temperature/Humidity Meter	zhichen	ZC1-2	TR8-TH	2017.04.10	2018.04.09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

### 7.2. Test Setup









### 7.3. Limit

Occupied Bandwidth
Systems using digital modulation techniques operate in the 2400-2483.5 MHz. The minimum 6 dB bandwidth shall be at least 500 kHz

### 7.4. Test Procedure

Test Method			
	Reference Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	11.8	DTS bandwidth
	<input type="checkbox"/> ANSI C63.10	11.8.1	Option 1
	<input checked="" type="checkbox"/> ANSI C63.10	11.8.2	Option 2

**7.5. EUT test definition**

Item	Occupied Bandwidth			
Device Category	<input type="checkbox"/>	Fixed point-to-point		
	<input type="checkbox"/>	Emit multiple directional beams, simultaneously or sequentially		
	<input checked="" type="checkbox"/>	Other cases		
Test mode	Mode 1~2			
Test method	<input type="checkbox"/>	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>
	<input checked="" type="checkbox"/>	Conducted		
	<input checked="" type="checkbox"/>	Chain 0		
				
	<input type="checkbox"/>	Chain 0	Chain 1	
				
	<input type="checkbox"/>	Chain 0	Chain 1	Chain 2
				


### 7.6. Test Result

Product Name	: Parrot Camera FPV	Power	: DC 3.3V
Test Mode	: Mode1~2	Test Site	: TR8
Test Date	: 2017.07.10		

Mode	CH.	Test Freq. (MHz)	99% Occupied Bandwidth (MHz)	6dB Occupied Bandwidth (MHz)	Limit (kHz)	Result
1	01	2412	13.591	10.12	>500	Pass
1	06	2437	13.335	10.12	>500	Pass
1	11	2462	15.086	10.14	>500	Pass
2	01	2412	17.008	16.54	>500	Pass
2	06	2437	24.746	16.48	>500	Pass
2	11	2462	24.429	16.58	>500	Pass

Note : The worst case of Occupied Bandwidth as below in next page:

Mode 1 CH06 (2437MHz)




## 8. Fundamental emission output power

### 8.1. Test Equipment

Fundamental emission output power/ TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2017.01.04	2018.01.03
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.02.04	2018.02.03
Wideband Peak Power Meter	Anritsu	ML2495A	0905006	2016.10.14	2017.10.13
Power Sensor	Anritsu	MA2411B	0846014	2016.10.14	2017.10.13
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2017.04.10	2018.04.09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

### 8.2. Test Setup



### 8.3. Limit







Fundamental emission output power			
<input checked="" type="checkbox"/>	$G_{TX} < 6\text{dBi}$	$P_{out} \leq 30\text{dBm}$	
<input type="checkbox"/>	$G_{TX} > 6\text{dBi}$		
	<input type="checkbox"/>	Fix point-to-point	$P_{out} \leq 30 - [(G_{TX} - 6)]/3$
	<input type="checkbox"/>	multiple directional beams	
	<input type="checkbox"/>	sequentially	$P_{out} \leq 30 - [(G_{TX} - 6)]/3$
	<input type="checkbox"/>	simultaneously	$P_{out} \leq 30 - [(G_{TX} - 6)]/3 + 8\text{dB}$
	<input type="checkbox"/>	All other cases	$P_{out} \leq 30 - (G_{TX} - 6)$
Note 1 : $G_{TX}$ directional gain of transmitting antennas.			
Note 2 : $P_{out}$ is maximum peak conducted output power .			



### 8.4. Test Procedure

Fundamental emission output power				
	References Rule		Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10		11.9	Fundamental emission output power
	<input checked="" type="checkbox"/>	ANSI C63.10	11.9.1	Maximum peak conducted output power
	<input type="checkbox"/>	ANSI C63.10	11.9.1.1	RBW $\geq$ DTS bandwidth
	<input type="checkbox"/>	ANSI C63.10	11.9.1.2	Integrated band power method
	<input checked="" type="checkbox"/>	ANSI C63.10	11.9.1.3	PKPM1 Peak power meter method
	<input type="checkbox"/>	ANSI C63.10	11.9.2	Maximum conducted (average) output power
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2	Measurement using a spectrum analyzer (SA)
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.2	Method AVGSA-1(Duty cycle $\geq$ 98%)
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.3	Method AVGSA-1A(Duty cycle $\geq$ 98%)
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.4	Method AVGSA-2(Duty cycle $\leq$ 98%)
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.5	Method AVGSA-2A(Duty cycle $\leq$ 98%)
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.4	Method AVGSA-3
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.5	Method AVGSA-3A
	<input type="checkbox"/>	ANSI C63.10	11.9.2.3	Measurement using a power meter (PM)
	<input type="checkbox"/>	ANSI C63.10	11.9.2.3.1	Method AVGPM
	<input type="checkbox"/>	ANSI C63.10	11.9.2.3.2	Method AVGPM-G

**8.5. EUT test definition**

Item	Fundamental emission output power			
Device Category	<input type="checkbox"/>	Fixed point-to-point		
	<input type="checkbox"/>	Emit multiple directional beams, simultaneously or sequentially		
	<input checked="" type="checkbox"/>	Other cases		
Test mode	Mode 1~2			
Test method	<input type="checkbox"/>	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>
	<input checked="" type="checkbox"/>	Conducted		
	<input checked="" type="checkbox"/>	Chain 0		
				
	<input type="checkbox"/>	Chain 0	Chain 1	
				
	<input type="checkbox"/>	Chain 0	Chain 1	Chain 2
				

## 8.6. Test Result

Product Name	: Parrot Camera FPV	Power	: DC 3.3V
Test Mode	: Mode1~2	Test Site	: TR8
Test Date	: 2017.07.11		

Mode	Channel	Test Frequency (MHz)	Peak Power Output (dBm)	Antenna Gain (dBi)	Limit (dBm)	Result
1	01	2412	21.53	-0.2	30	Pass
1	06	2437	21.41	-0.2	30	Pass
1	11	2462	21.19	-0.2	30	Pass
2	01	2412	21.48	-0.2	30	Pass
2	02	2417	22.07	-0.2	30	Pass
2	06	2437	22.41	-0.2	30	Pass
2	10	2457	22.34	-0.2	30	Pass
2	11	2462	22.32	-0.2	30	Pass


## 9. Power Spectral Density

### 9.1. Test Equipment

Power Spectral Density / TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.02.04	2018.02.03
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2017.04.09	2018.04.08
MXA Signal Analyzer	Keysight	N9020A	MY56060147	2017.04.09	2018.04.08
Temperature/Humidity Meter	zhichen	ZC1-2	TR8-TH	2017.04.10	2018.04.09

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

### 9.2. Test Setup









### 9.3. Limit

Power Spectral Density Limit
Power Spectral Density $\leq$ 8dBm/3kHz

### 9.4. Test Procedure

Power Spectral Density Test Method			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	11.10	Maximum power spectral density level in the fundamental emission
<input checked="" type="checkbox"/>	ANSI C63.10	11.10.2	Method PKPSD (peak PSD)
<input type="checkbox"/>	ANSI C63.10	11.10.3	Method AVGPSD-1(Duty cycle $\geq 98\%$ )
<input type="checkbox"/>	ANSI C63.10	11.10.4	Method AVGPSD-1A(Duty cycle $\geq 98\%$ )
<input type="checkbox"/>	ANSI C63.10	11.10.5	Method AVGPSD-2(Duty cycle $< 98\%$ )
<input type="checkbox"/>	ANSI C63.10	11.10.6	Method AVGPSD-2A(Duty cycle $< 98\%$ )
<input type="checkbox"/>	ANSI C63.10	11.10.7	Method AVGPSD-3
<input type="checkbox"/>	ANSI C63.10	11.10.8	Method AVGPSD-3A

**9.5. EUT test definition**


Item	Power Spectral Density			
Device Category	<input type="checkbox"/>	Fixed point-to-point		
	<input type="checkbox"/>	Emit multiple directional beams, simultaneously or sequentially		
	<input checked="" type="checkbox"/>	Other cases		
Test mode	Mode 1~2			
Test method	<input type="checkbox"/>	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>
	<input checked="" type="checkbox"/>	Conducted		
	<input checked="" type="checkbox"/>	Chain 0		
				
	<input type="checkbox"/>	Chain 0	Chain 1	
				
	<input type="checkbox"/>	Chain 0	Chain 1	Chain 2
				

### 9.6. Test Result

Product Name	: Parrot Camera FPV	Power	: DC 3.3V
Test Mode	: Mode1~2	Test Site	: TR8
Test Date	: 2017.07.10		

Mode	Channel	Test Frequency (MHz)	Measurement PSD (dBm/3kHz)	Antenna Gain (dBi)	Limit (dBm/3kHz)	Result
1	01	2412	-6.965	-0.2	8.0	Pass
1	06	2437	-7.651	-0.2	8.0	Pass
1	11	2462	-8.360	-0.2	8.0	Pass
2	01	2412	-9.975	-0.2	8.0	Pass
2	06	2437	-5.587	-0.2	8.0	Pass
2	11	2462	-8.305	-0.2	8.0	Pass

Mode 1 CH01(2412MHz)



## 10. Antenna Requirement

### 10.1. Limit

Antenna Requirement Limit
<p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.</p>

### 10.2. Antenna Connector Construction

Antenna Connector Construction	
<input checked="" type="checkbox"/>	The use of a permanently attached antenna
<input type="checkbox"/>	The antenna use of a unique coupling to the intentional radiator
<input type="checkbox"/>	The use of a nonstandard antenna jack or electrical connector
Please refer to the attached document "Internal Photograph" to show the antenna connector.	

\_\_\_\_\_ The End \_\_\_\_\_