



TESTING LABORATORY  
CERTIFICATE#4323.01





# FCC PART 15.247 TEST REPORT

For

## Hangzhou Meiri Technology Co., Ltd.

Room 604-605, Building 1, No.768 Jianghong Road, Changhe street, Binjiang District, Hangzhou, Zhejiang,  
China

**FCC ID: 2AG7C-BABY1M**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Baby Monitor
<b>Project Engineer:</b>	<u>Tyrone Wang</u> 
<b>Report Number:</b>	<u>RSA210309003-00B</u>
<b>Report Date:</b>	<u>2021-04-09</u>
<b>Reviewed By:</b>	<u>Oscar Ye</u> EMC Manager 
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**TABLE OF CONTENTS**

**GENERAL INFORMATION.....4**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4

    OBJECTIVE .....4

    RELATED SUBMITTAL(S)/GRANT(S).....4

    TEST METHODOLOGY .....5

    MEASUREMENT UNCERTAINTY .....5

    TEST FACILITY .....5

**SYSTEM TEST CONFIGURATION.....6**

    JUSTIFICATION .....6

    EUT EXERCISE SOFTWARE .....6

    SUPPORT EQUIPMENT LIST AND DETAILS .....7

    EXTERNAL I/O CABLE.....7

    BLOCK DIAGRAM OF TEST SETUP .....8

**SUMMARY OF TEST RESULTS .....10**

**TEST EQUIPMENT LIST .....11**

**FCC §1.1310& §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE).....12**

    CALCULATED FORMULARY:.....12

**FCC§15.203 - ANTENNA REQUIREMENT.....13**

    APPLICABLE STANDARD .....13

    ANTENNA CONNECTOR CONSTRUCTION .....13

**FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS .....14**

    APPLICABLE STANDARD .....14

    EUT SETUP .....14

    EMI TEST RECEIVER SETUP.....14

    TEST PROCEDURE .....14

    FACTOR & OVER LIMIT CALCULATION.....15

    TEST RESULTS SUMMARY .....15

    TEST DATA .....15

**FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS.....20**

    APPLICABLE STANDARD .....20

    EUT SETUP .....20

    EMI TEST RECEIVER SETUP.....21

    TEST PROCEDURE .....21

    TEST RESULTS SUMMARY .....21

    TEST DATA .....22

**FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH .....30**

    APPLICABLE STANDARD .....30

    TEST PROCEDURE .....30

    TEST DATA .....30

**FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER .....33**

    APPLICABLE STANDARD .....33

    TEST PROCEDURE .....33

    TEST DATA .....33

**FCC §15.247(D) – BAND EDGE.....34**

    APPLICABLE STANDARD .....34

---

TEST PROCEDURE .....	34
TEST DATA .....	34
<b>FCC §15.247(E) - POWER SPECTRAL DENSITY.....</b>	<b>36</b>
APPLICABLE STANDARD .....	36
TEST PROCEDURE .....	36
TEST DATA .....	36

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Applicant:	Hangzhou Meari Technology Co., Ltd.
Tested Model:	Baby 1M
Product Type:	Baby Monitor
Power Supply:	DC 5V from adapter, DC 3.7V from battery
Maximum Output Power:	29.62 dBm
RF Function:	SRD
Operating Band/Frequency:	905-925 MHz
Channel Number:	11
Channel Separation:	2 MHz
Modulation Type:	OFDM
Antenna Type:	PCB Antenna
*Maximum Antenna Gain	-1.05 dBi

#### Adapter-1 Information:

Model: GTA92-0501000US

Input: AC100-240V~50/60Hz 0.3A

Output: USB-A 5.0V,1.0A,5.0W

#### Adapter-2 Information:

Model: TPA-46B050100UU

Input: AC100-240V~50/60Hz,0.2A

Output: 5.0V, 1000mA

Note: The maximum antenna gain was provided by the applicant.

\*All measurement and test data in this report was gathered from production sample serial number: RSHA210309003-1.(Assigned by the BACL. The EUT supplied by the applicant was received on 2021-03-09.)

### Objective

This type approval report is prepared on behalf of *Hangzhou Meari Technology Co., Ltd.* in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine Compliant with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

Part of system submittal with FCC ID: 2AG7C-BABY1S.

## Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliant Testing of Unlicensed Wireless Devices and FCC 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliant Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

## Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

## Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

**SYSTEM TEST CONFIGURATION**

**Justification**

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	905	7	917
2	907	8	919
3	909	9	921
4	911	10	923
5	913	11	925
6	915	---	---

EUT was tested with Channel 1, 6 and 11.

**EUT Exercise Software**


RF test tool: XCOM

Mode	Channel	*Power Level Setting
SRD	Low	Default
	Middle	Default
	High	Default

Note: The power level setting was declared by the applicant.

**Duty Cycle:**

**Middle Channel: 915.00 MHz**



Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
SRD	51.02	0.832	1.20	2.92

**Support Equipment List and Details**


Manufacturer	Description	Model	Serial Number
SanDisk	SD Card	32GB	72812VCP912S

**External I/O Cable**


Cable Description	Length(m)	From Port	To
USB Cable	2.0	EUT	Adapter
Power Cable	1.0	Socket	LISN/AC Source

### Block Diagram of Test Setup

For Conducted Emissions:




For Radiated Emissions(Below 1GHz):





For Radiated Emissions(Above 1GHz):



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.247 (I), §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test (Chamber 1#)</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2020-11-27	2021-11-26
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2020-08-05	2023-08-04
Sonoma Instrument	Pre-amplifier	310N	171205	2020-08-14	2021-08-13
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICROTRONICS	Band Reject Filter	BRC50722	G013	2020-08-05	2021-08-04
MICRO-COAX	Coaxial Cable	Cable-8	008	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2020-08-15	2021-08-14
<b>Radiated Emission Test (Chamber 2#)</b>					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2020-07-15	2023-07-14
A.H.Systems, inc	Amplifier	PAM-0118P	512	2021-02-20	2022-02-19
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2020-08-15	2021-08-14
<b>RF Conducted Test</b>					
Rohde & Schwarz	Signal Analyzer	ESIB 26	836131/009	2020-12-14	2021-12-13
Agilent	Power Meter	N1912A	MY5000492	2020-11-18	2021-11-17
Agilent	Power Sensor	N1921A	MY54210024	2020-11-18	2021-11-17
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Hangzhou Meari	RF Cable	Hangzhou Meari C01	C01	Each Time	N/A
<b>Conducted Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2020-08-05	2021-08-04
Rohde & Schwarz	LISN	ENV216	3560655016	2020-11-27	2021-11-26
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3-Z2	0357.8810.54	2020-08-10	2021-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2020-08-15	2021-08-14

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**FCC §1.1310& §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

**Applicable Standard**

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

**Calculated Formulary:**

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

**Calculated Data:**

<b>Mode</b>	<b>Frequency Range (MHz)</b>	<b>Antenna Gain</b>		<b>Tune-up Conducted Power</b>		<b>Evaluation Distance (cm)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>MPE Limit (mW/cm<sup>2</sup>)</b>
		<b>(dBi)</b>	<b>(numeric)</b>	<b>(dBm)</b>	<b>(mW)</b>			
SRD	905-925	-1.05	0.79	30	1000	20	0.16	0.60

**Note:** The tune-up output power was declared by the manufacturer.

Conclusion: The device meets FCC MPE at 20 cm distance.

---

## **FCC§15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

### **Antenna Connector Construction**

The EUT has a PCB antenna and antenna gain is -1.05 dBi, the antenna was permanently attached to the EUT, fulfill the requirement of this section, please refer to the EUT photos.


**Result:** Compliant.

**FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS**

**Applicable Standard**

FCC§15.207

**EUT Setup**



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 30 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

**EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

**Test Procedure**

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

### Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

### Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	24.0 °C
<b>Relative Humidity:</b>	54 %
<b>ATM Pressure:</b>	101.1 kPa


*The testing was performed by Tyrone Wang on 2021-03-19.*

**Test Result:** Compliant.

*EUT operation mode: charging & transmitting*

For adapter-1:

AC 120V/60 Hz, Line




Trace: 1

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.164	15.50	19.83	35.33	55.25	-19.92	Average
2	0.164	35.67	19.83	55.50	65.25	-9.75	QP
3	0.197	11.80	19.82	31.62	53.72	-22.10	Average
4	0.197	30.90	19.82	50.72	63.72	-13.00	QP
5	0.295	8.20	19.83	28.03	50.37	-22.34	Average
6	0.295	24.36	19.83	44.19	60.37	-16.18	QP
7	0.491	13.50	19.76	33.26	46.15	-12.89	Average
8	0.491	19.70	19.76	39.46	56.15	-16.69	QP
9	2.338	1.80	19.58	21.38	46.00	-24.62	Average
10	2.338	13.93	19.58	33.51	56.00	-22.49	QP
11	5.062	3.50	19.49	22.99	50.00	-27.01	Average
12	5.062	14.69	19.49	34.18	60.00	-25.82	QP



AC 120V/60 Hz, Neutral



	Read Freq	Read Level	Factor	Limit Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.162	13.60	19.83	33.43	55.34	-21.91	Average
2	0.162	32.76	19.83	52.59	65.34	-12.75	QP
3	0.192	9.20	19.82	29.02	53.93	-24.91	Average
4	0.192	28.17	19.82	47.99	63.93	-15.94	QP
5	0.228	6.30	19.82	26.12	52.52	-26.40	Average
6	0.228	25.26	19.82	45.08	62.52	-17.44	QP
7	0.317	2.60	19.82	22.42	49.79	-27.37	Average
8	0.317	21.73	19.82	41.55	59.79	-18.24	QP
9	0.491	4.10	19.76	23.86	46.15	-22.29	Average
10	0.491	18.07	19.76	37.83	56.15	-18.32	QP
11	5.037	2.70	19.49	22.19	50.00	-27.81	Average
12	5.037	13.88	19.49	33.37	60.00	-26.63	QP


Note:

1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

2) Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)


For adapter-2:

AC 120V/60 Hz, Line



	Read Freq	Read Level	Factor	Limit Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.150	11.30	19.82	31.12	56.00	-24.88	Average
2	0.150	29.48	19.82	49.30	66.00	-16.70	QP
3	0.187	6.31	19.82	26.13	54.18	-28.05	Average
4	0.187	24.49	19.82	44.31	64.18	-19.87	QP
5	0.445	11.80	19.75	31.55	46.98	-15.43	Average
6	0.445	19.95	19.75	39.70	56.98	-17.28	QP
7	1.205	2.40	19.81	22.21	46.00	-23.79	Average
8	1.205	14.58	19.81	34.39	56.00	-21.61	QP
9	2.315	3.31	19.59	22.90	46.00	-23.10	Average
10	2.315	15.46	19.59	35.05	56.00	-20.95	QP
11	4.889	5.40	19.49	24.89	46.00	-21.11	Average
12	4.889	14.33	19.49	33.82	56.00	-22.18	QP

**AC 120V/60 Hz, Neutral**



	Freq	Read Level	Factor	Limit Level	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.151	13.50	19.82	33.32	55.96	-22.64 Average
2	0.151	32.68	19.82	52.50	65.96	-13.46 QP
3	0.186	8.31	19.82	28.13	54.22	-26.09 Average
4	0.186	28.22	19.82	48.04	64.22	-16.18 QP
5	0.263	4.40	19.82	24.22	51.32	-27.10 Average
6	0.263	21.39	19.82	41.21	61.32	-20.11 QP
7	0.486	2.10	19.76	21.86	46.23	-24.37 Average
8	0.486	17.01	19.76	36.77	56.23	-19.46 QP
9	2.350	2.30	19.57	21.87	46.00	-24.13 Average
10	2.350	12.46	19.57	32.03	56.00	-23.97 QP
11	4.938	3.30	19.49	22.79	46.00	-23.21 Average
12	4.938	14.25	19.49	33.74	56.00	-22.26 QP

**Note:**

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dBUV) + Factor (dB) - Limit (dBUV)


## FCC §15.209, §15.205 & §15.247(d) - Spurious Emissions

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

### EUT Setup

**Below 1 GHz:**



**Above 1GHz:**



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

## EMI Test Receiver Setup

The system was investigated from 30 MHz to 10 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Avg.

## Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30MHz - 1GHz, peak and Average detection mode for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB $\mu$ V/m) = Meter Reading (dB $\mu$ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB $\mu$ V/m) – Corrected Amplitude (dB $\mu$ V/m)

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	22.5-24.0 °C
<b>Relative Humidity:</b>	50-54 %
<b>ATM Pressure:</b>	101.1-101.3 kPa

The testing was performed by Tyrone Wang from 2021-03-19 to 2021-03-22.


Test Mode: charging&transmitting

For Adapter-1:

**Spurious Emission Test:**

**30 MHz - 1 GHz**

(Pre-scan in the X,Y and Z axes of orientation, the worst case **high channel in Z-axis of orientation** was recorded.)



Frequency (MHz)	Corrected Amplitude QuasiPeak (dBμV/m)	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
		Height (cm)	Polar (H/V)				
109.535600	30.03	100.0	V	125.0	-12.8	43.50	13.47
248.625300	41.34	100.0	H	9.0	-11.9	46.00	4.66
390.719950	45.37	100.0	H	0.0	-8.3	46.00	0.63
850.452300	44.93	100.0	H	350.0	-0.5	46.00	1.07
882.516750	38.93	100.0	H	22.0	-0.2	46.00	7.07
978.541450	42.27	100.0	H	232.0	2.3	54.00	11.73

**Note:**

Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)


Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

For Adapter-2:

**Spurious Emission Test:**

**30 MHz - 1 GHz**

(Pre-scan in the X,Y and Z axes of orientation, the worst case **high channel in Z-axis of orientation** was recorded.)



Frequency (MHz)	Corrected Amplitude QuasiPeak (dBµV/m)	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
		Height (cm)	Polar (H/V)				
38.288500	28.01	100.0	V	312.0	-9.3	40.00	11.99
107.460900	27.52	100.0	V	103.0	-13.2	43.50	15.98
249.944650	40.57	100.0	H	25.0	-11.9	46.00	5.43
390.200200	44.09	100.0	H	193.0	-8.3	46.00	1.91
850.527900	45.50	100.0	H	358.0	-0.5	46.00	0.50
979.500350	37.10	100.0	H	345.0	2.3	54.00	16.90

**Note:**

Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)

Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

For adapter-1(Worst Case):

**1GHz-10GHz**

(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.)

Note:


1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) - Amplifier Factor (dB)

Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)

Margin (dB) = Limit (dBμV/m) - Corrected Amplitude (dBμV/m)

**Low Channel: 905.00 MHz**

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1810.000000	---	50.02	200.0	V	186.0	-8.3	54.00	3.98
1810.000000	56.06	---	200.0	V	186.0	-8.3	74.00	17.94
2715.000000	---	40.42	150.0	H	51.0	-4.7	54.00	13.58
2715.000000	53.56	---	150.0	H	51.0	-4.7	74.00	20.44
3620.800000	---	52.35	150.0	H	0.0	-1.3	54.00	1.65
3620.800000	63.95	---	150.0	H	0.0	-1.3	74.00	10.05
4525.300000	---	50.14	150.0	H	190.0	0.9	54.00	3.86
4525.300000	65.01	---	150.0	H	190.0	0.9	74.00	8.99
5429.800000	---	46.13	150.0	H	12.0	1.9	54.00	7.87
5429.800000	57.01	---	150.0	H	12.0	1.9	74.00	16.99
6334.300000	---	48.24	150.0	H	298.0	6.2	54.00	5.76
6334.300000	60.91	---	200.0	H	266.0	6.2	74.00	13.09



**Middle Channel: 915.00 MHz**


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1830.000000	---	44.02	150.0	H	351.0	-8.3	54.00	9.98
1830.000000	50.36	---	150.0	H	351.0	-8.3	74.00	23.64
2745.000000	---	40.72	150.0	H	200.0	-4.5	54.00	13.28
2745.000000	57.95	---	150.0	H	200.0	-4.5	74.00	16.05
3658.600000	---	53.01	200.0	V	175.0	-1.1	54.00	0.99
3658.600000	62.21	---	200.0	V	175.0	-1.1	74.00	11.79
4574.800000	---	46.22	150.0	H	80.0	0.9	54.00	7.78
4574.800000	62.66	---	150.0	H	80.0	0.9	74.00	11.34
5488.300000	---	43.96	150.0	V	237.0	2.0	54.00	10.04
5488.300000	59.01	---	150.0	V	237.0	2.0	74.00	14.99
6404.500000	---	44.30	200.0	H	275.0	6.4	54.00	9.70
6404.500000	56.17	---	200.0	H	275.0	6.4	74.00	17.83

**High Channel: 925.00 MHz**

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1850.000000	53.29	---	200.0	V	79.0	-8.2	74.00	20.71
1850.000000	---	46.93	200.0	V	79.0	-8.2	54.00	7.07
2775.000000	51.94	---	150.0	H	190.0	-4.4	74.00	22.06
2775.000000	---	38.37	150.0	H	190.0	-4.4	54.00	15.63
3700.000000	---	52.61	200.0	V	214.0	-0.9	54.00	1.39
3700.000000	63.03	---	200.0	V	214.0	-0.9	74.00	10.97
4624.300000	57.72	---	150.0	H	0.0	1.0	74.00	16.28
4624.300000	---	45.37	150.0	H	0.0	1.0	54.00	8.63
5548.600000	55.33	---	150.0	V	0.0	2.3	74.00	18.67
5548.600000	---	41.69	150.0	V	0.0	2.3	54.00	12.31
6476.500000	54.03	---	150.0	H	297.0	6.6	74.00	19.97
6476.500000	---	41.50	150.0	H	297.0	6.6	54.00	12.50

**Fundamental Test & Restricted Bands Emissions Test:**

*(Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.)*


Note:

- 1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
- Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
- Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)


Frequency (MHz)	Corrected Amplitude (dBµV/m)	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
		Height (cm)	Polar (H/V)				
<b>Low Channel: 905.00MHz</b>							
902.00	39.98	100	H	253	1.10	46.00	6.02
902.00	38.76	150	V	112	1.10	46.00	7.24
<b>High Channel: 925.00MHz</b>							
928.00	34.59	100	H	337	1.50	46.00	11.41
928.00	33.47	150	V	249	1.50	46.00	12.53

Conducted Spurious Emissions at Antenna Port


Low Channel



Middle Channel



### High Channel



## **FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH**


### **Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### **Test Procedure**

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	24.3°C
<b>Relative Humidity:</b>	55 %
<b>ATM Pressure:</b>	101.3 kPa


*The testing was performed by Tyrone Wang on 2021-03-22.*

**Test Result:** Compliant.


*EUT operation mode: Transmitting*

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
Low	905.00	1.83	$\geq 0.5$
Middle	915.00	1.79	$\geq 0.5$
High	925.00	1.80	$\geq 0.5$


### Low Channel



### Middle Channel



### High Channel





## **FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER**

### **Applicable Standard**


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliant with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### **Test Procedure**

According to ANSI C63.10-2013 sub-clause 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	24.1°C
<b>Relative Humidity:</b>	55 %
<b>ATM Pressure:</b>	101.3 kPa

*The testing was performed by Tyrone Wang on 2021-03-22.*

*EUT operation mode: Transmitting*

<b>Channel</b>	<b>Frequency (MHz)</b>	<b>Max Conducted Peak Output Power (dBm)</b>	<b>Limit (dBm)</b>	<b>Result</b>
Low	905.00	29.48	30	Pass
Middle	915.00	29.48	30	Pass
High	925.00	29.62	30	Pass

## **FCC §15.247(d) – BAND EDGE**

### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliant with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **Test Procedure**

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### **Test Data**

#### **Environmental Conditions**


<b>Temperature:</b>	24.1°C
<b>Relative Humidity:</b>	55 %
<b>ATM Pressure:</b>	101.3 kPa

*The testing was performed by Tyrone Wang on 2021-03-22.*


*EUT operation mode: Transmitting*

**Test Result:** Compliant.

**Left Side**



**Right Side**



## **FCC §15.247(e) - POWER SPECTRAL DENSITY**

### **Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### **Test Procedure**

According to ANSI C63.10-2013 sub-clause 11.10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate Compliant.
2. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
3. Set the VBW  $\geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	24.1°C
<b>Relative Humidity:</b>	55 %
<b>ATM Pressure:</b>	101.3 kPa


*The testing was performed by Tyrone Wang on 2021-03-22.*

*EUT operation mode: Transmitting*


**Test Result:** Compliant.

<b>Channel</b>	<b>Frequency (MHz)</b>	<b>PSD (dBm/3kHz)</b>	<b>Limit (dBm/3kHz)</b>
Low	905.00	4.79	≤8
Middle	915.00	4.12	≤8
High	925.00	4.20	≤8


**Low Channel**



**Middle Channel**



### High Channel



## Declarations

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '\*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor  $K$  with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

\*\*\*\*\* END OF REPORT \*\*\*\*\*