



Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

RF Exposure evaluation

Report Reference No.....: GTS20210708001-1-12

FCC ID.: 2AG7C-BELL7T

Compiled by

(position+printed name+signature) .: File administrators Peter Xiao

Supervised by

(position+printed name+signature) .: Test Engineer Oliver Ou

Approved by

(position+printed name+signature) .: Manager Simon Hu

Date of issue: Jul.31, 2021

Representative Laboratory Name.: Shenzhen Global Test Service Co.,Ltd.

Address: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name.....: Hangzhou Meari Technology Co., Ltd.

Address: Room 604-605, Building 1, No.768 Jianghong Road, Changhe street, Binjiang District, Hangzhou, zhejiang, China

Test specification

Standard.....: **47CFR §1.1310**
47CFR §2.1091
KDB447498 D01 General RF Exposure Guidance v06

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description **Wireless DoorBell**

Trade Mark: N/A

Manufacturer: Hangzhou Meari Technology Co., Ltd.

Model/Type reference: Bell 7S

Listed Models: Bell 7SN, Bell 7T, Bell 7X, Bell 7Q, LV-PDB6

Modulation Type.....: 802.11b: DSSS; 802.11g/n: OFDM
OOK

Operation Frequency.....: From 2412MHz to 2462MHz, 915MHz

Hardware Version: PCB-BELL7S-T1MB_GC1 REV1_0(Version A)
PCB-BELL7NS-T1MB_GC1 REV1_0(Version B)

Software Version: N/A

Rating: DC 3.6V by battery

Rating: Recharged by DC 5.0V/1.0A
or AC/DC 12V-24V

Result: **PASS**

TEST REPORT

Test Report No. : GTS20210708001-1-12	Jul.31, 2021
	Date of issue

Equipment under Test : Wireless DoorBell

Model /Type : Bell 7S

Listed model : Bell 7SN, Bell 7T, Bell 7X, Bell 7Q, LV-PDB6

Applicant : **Hangzhou Meari Technology Co., Ltd.**

Address : Room 604-605, Building 1, No.768 Jianghong Road, Changhe street, Binjiang District, Hangzhou, zhejiang, China

Manufacturer : **Hangzhou Meari Technology Co., Ltd.**

Address : No. 91 Chutian Road, Xixing Street, Binjiang District, Hangzhou, Zhejiang, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

- 1. SUMMARY 4**
 - 1.1 EUT CONFIGURATION..... 4
 - 1.2 PRODUCT DESCRIPTION 4
 - 1.3 DIFFERENCE DESCRIPTION..... 5
- 2. TEST ENVIRONMENT 6**
 - 2.1 ADDRESS OF THE TEST LABORATORY 6
 - 2.2 TEST FACILITY 6
 - 2.3 ENVIRONMENTAL CONDITIONS 6
 - 2.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY 6
- 3. METHOD OF MEASUREMENT 7**
 - 3.1 APPLICABLE STANDARD..... 7
 - 3.2 REQUIREMENT 7
 - 3.3 LIMIT 7
 - 3.4 MPE CALCULATION METHOD..... 8
 - 3.5 ANTENNA INFORMATION 8
- 4. CONDUCTED POWER RESULTS 9**
- 5. MANUFACTURING TOLERANCE 10**
- 6. MEASUREMENT RESULTS 11**
 - 6.1 STANDALONE MPE EVALUATION..... 11
 - 6.2 SIMULTANEOUS TRANSMISSION MPE 12
- 7. CONCLUSION 13**

1. SUMMARY

1.1 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

● /	Length (m) :	/
	Shield :	/
	Detachable :	/

1.2 Product Description

Product Name	Wireless DoorBell
Trade Mark	N/A
Model/Type reference	Bell 7S
List Models	Bell 7SN, Bell 7T, Bell 7X, Bell 7Q, LV-PDB6
Model Declaration	PCB board, structure and internal of these model(s) are the same, Only the model name different , So no additional models were tested.
Power supply:	DC 3.6V by battery Recharged by DC 5.0V/1.0A or AC/DC 12V-24V
Sample ID	GTS20210708001-1-1# & GTS20210708001-1-2#& GTS20210708001-1-3#
WIFI(2.4G Band)	
Frequency Range	2412MHz ~ 2462MHz
Channel Spacing	5MHz
Channel Number	11 Channel for 20MHz bandwidth(2412~2462MHz)
Modulation Type	802.11b: DSSS; 802.11g/n: OFDM
Antenna Description	FPC Antenna, 3.00dBi(Max.)
SRD	
Frequency Range	915MHz
Channel Number	1Channel
Modulation Type	OOK
Antenna Description	FPC Antenna, 1.00dBi(Max.)

1.3 Difference description

The difference between Bell 7S is show in the below table:

Bell 7S	Version A	Version B
Main board	The main control of IC is different, the schematic is slightly different	The main control of IC is different, the schematic is slightly different
Frequency bands	The same, support Wi-Fi 2.4G Support SRD 433/915;	The same
Wi-Fi module	Hi3861LV100 802.11b/g/n20 1T1R	The same
Wi-Fi antenna	FPC antenna	The same
SRD module	433 for CE 915 for FCC	The same
SRD antenna	Integral antenna(CE) FPC antenna(FCC)	FPC antenna(CE) FPC antenna(FCC)
Appearance	Slightly different	Slightly different
Dimension	The same	The same
GPU	support	support
Rear camera	Not support	Not support
Front camera	The same	The same
Adapter	GPO GTA92-0501000US I/P: 100-240V ~ 50/60Hz, 0.3A O/P 5V= 1.0A, 5.0W SZTY TPA-46B050100UU I/P: 100-240V ~ 50/60Hz, 0.2A O/P 5V= 1000mA	The same
Battery	Rechargeable Li-ion Battery Model: CM-18650-2P 3.6V,3350mAh 2* Battery TUV SUD CB Certificate NO.:SG-PSB-BT-01712 Report NO.:211-282200068-000	Rechargeable Li-ion Battery Model: CM-18650-2P 3.6V,6700mAh 1* Battery CMC TESTING CB Report NO.:CMC210224001
Accessories	2 USB cables Black White	The same

Note:

Pre-test at both voltage AC/DC 12V-24V and DC 5V to Adapter, but we only recorded the worst case in this report.(DC 5V to Adapter)

2. TEST ENVIRONMENT

2.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1234.

FCC Registered Test Site Number is165725.

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. METHOD OF MEASUREMENT

3.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2 Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498 D01 General RF Exposure Guidance v06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3.3 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.4 MPE Calculation Method

Predication of MPE limit at a given distance
 Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum soure-baed Duty Cycle of 100%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, r =20cm, as well as the gain of the used antenna is 3.00dBi for WLAN, and the power drift from Turn-up Procedure provide by manufacturer as following states, the RF power density can be obtained.

3.5 Antenna Information

Bell 7S can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 1	WLAN ANT	FPC antenna	2400 – 2500MHz	3.00dBi(Max.)
Antenna 2	SRD ANT	FPC antenna	900 – 1000MHz	1.00dBi(Max.)

4. Conducted Power Results

Version A:

2.4GWLAN

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	01	2412	17.46
	06	2437	17.17
	11	2462	17.16
802.11g	01	2412	17.54
	06	2437	18.08
	11	2462	17.86
802.11n(HT20)	01	2412	18.07
	06	2437	18.78
	11	2462	18.67

SRD

Mode	Channel	Frequency (MHz)	EIRP (dBm)
OOK	01	915	-4.62

Version B:

2.4GWLAN

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	01	2412	17.25
	06	2437	17.34
	11	2462	17.29
802.11g	01	2412	17.41
	06	2437	17.89
	11	2462	17.96
802.11n(HT20)	01	2412	18.12
	06	2437	18.34
	11	2462	18.45

SRD

Mode	Channel	Frequency (MHz)	EIRP (dBm)
OOK	01	915	-4.62

5. Manufacturing Tolerance

Version A:

2.4GWLAN

IEEE 802.11b (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	17.0	17.0	17.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	17.0	18.0	17.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	18.0	18.0	18.0
Tolerance ±(dB)	1.0	1.0	1.0

SRD

915M (EIRP)	
Channel	Channel 01
Target (dBm)	-4.0
Tolerance ±(dB)	1.0

Version B:

2.4GWLAN

IEEE 802.11b (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	17.0	17.0	17.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	17.0	17.0	17.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	18.0	18.0	18.0
Tolerance ±(dB)	1.0	1.0	1.0

SRD

915M (EIRP)	
Channel	Channel 01
Target (dBm)	-4.0
Tolerance ±(dB)	1.0

6. Measurement Results

6.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Version A:

2.4G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11b	18.00	63.0957	3.00	1.9953	0.0250	1.0000
802.11g	19.00	79.4328	3.00	1.9953	0.0315	1.0000
802.11n(HT20)	19.00	79.4328	3.00	1.9953	0.0315	1.0000

SRD

Modulation Type	EIRP		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
SRD	-3.00	0.5012	1.00	1.2589	0.0001	0.6100

Version B:

2.4G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11b	18.00	63.0957	3.00	1.9953	0.0250	1.0000
802.11g	18.00	63.0957	3.00	1.9953	0.0250	1.0000
802.11n(HT20)	19.00	79.4328	3.00	1.9953	0.0315	1.0000

SRD

Modulation Type	EIRP		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
SRD	-3.00	0.5012	1.00	1.2589	0.0001	0.6100

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

6.2 Simultaneous Transmission MPE

The sample support one WLAN and one SRD modular and one WLAN antenna, and one SRD antenna, Need consider simultaneous transmission ;

According to KDB447498 D01 General RF Exposure Guidance v06 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

Σ of MPE ratios \leq 1.0

6.2.2 Summary simultaneous transmission results

Maximum Simultaneous transmission MPE Ratios for 2.4GWLAN, SRD .

Version A:

Maximum MPE ratio (2.4GWLAN)	Maximum MPE ratio SRD	Σ MPE ratios	Limit	Results
0.0315	0.0002	0.0317	1.0	PASS

Version B:

Maximum MPE ratio (2.4GWLAN)	Maximum MPE ratio SRD	Σ MPE ratios	Limit	Results
0.0315	0.0002	0.0317	1.0	PASS

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06, No SAR is required.

.....End of Report.....