

# FCC RF EXPOSURE REPORT

## FCC ID: 2AG7C-MINI7

**Project No.** : 2009H026  
**Equipment** : IP CAMERA  
**Brand Name** : N/A  
**Test Model** : Mini 7S  
**Series Model** : Mini 7X,Mini 11S;Mini 11X;Mini 14S;Mini 14X  
**Applicant** : Hangzhou Meari Technology Co., Ltd.  
**Address** : Room 604-605,Building 1,No.768 Jianghong Road,  
Changhe street,Binjiang District,Hangzhou,zhejiang,China  
**Manufacturer** : Hangzhou Meari Technology Co., Ltd.  
**Address** : Room 604-605,Building 1,No.768 Jianghong Road,  
Changhe street,Binjiang District,Hangzhou,zhejiang, China  
**Factory** : Hangzhou Meari Technology Co., Ltd.  
**Address** : No. 91 Chutian Road, Xixing Street, Binjiang District,  
Hangzhou, Zhejiang,China  
**Date of Receipt** : Sep.11, 2020  
**Date of Test** : Sep.11, 2020~Oct.14, 2020  
**Issued Date** : Oct.23, 2020  
**Report Version** : R01  
**Test Sample** : Engineering Sample No.: SH2020091129,SH2020091130,  
SH2020091129-1  
**Standard(s)** : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091  
FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

*Allen Wei*

Prepared by : Allen Wei

*Ryan Wang*

Approved by : Ryan Wang



Certificate # 5123. 03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210,China  
TEL: +86-021-61765666  
Web: www.newbtl.com

## REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Oct.20, 2020
R01	Revised the power value.	Oct.23, 2020

### 1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

For 2.4G:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	paster	N/A	3

### 2. TEST RESULTS

For 2.4GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
3.00	1.9953	9.64	9.204496	0.003654	1	Complies

Note: The calculated distance is 20 cm.  
Output power including tune up tolerance.

**End of Test Report**