

# **FCC RF EXPOSURE REPORT**

## FCC ID: 2AG7C-SPEED3S

Project No. : 2001H004
Equipment : CAMERA
Brand Name : N/A

Test Model : speed 3S
Series Model : Speed 3C

**Applicant**: Hangzhou Meari Technology Co., Ltd.

Address : No.91, Chutian Road, Xixing Block, Binjiang, Hangzhou, China 310051

Manufacturer : Hangzhou Meari Technology Co., Ltd.

Address : No.91, Chutian Road, Xixing Block, Binjiang, Hangzhou, China 310051

**Factory**: Hangzhou Meari Technology Co., Ltd.

Address : No.91, Chutian Road, Xixing Block, Binjiang, Hangzhou, China 310051

Date of Receipt : Jan. 07, 2020

**Date of Test** : Jan. 07, 2020~Apr. 20, 2020

**Issued Date** : Apr. 30, 2020

Report Version : R00

Test Sample : Engineering Sample No.: SH202001072,SH202001071-1,

SH2020031348-1

Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091

FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Prepared by : Krain Wu

Approved by: Rvan Wang

INC. MRA ACCREDITED

Certificate # 5123.03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China

TEL: +86-021-61765666 Web: www.newbtl.com



### **REPORT ISSUED HISTORY**

Report Version	Description	Issued Date	
R00	Original Issue	Apr. 30, 2020	





#### 1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRF}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna

Table for Filed Antenna

For 2.4G:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)	Note	
1	N/A			N/A	3	N/A	



### 2. TEST RESULTS

#### For 2.4GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. tune up Power (dBm)	Max. tune up Power (mW)	Power Density (S) (mW/cm²)	Limit of Power Density (S) (mW/cm²)	Test Result
3	1.9953	24.50	281.8383	0.11190	1	Complies

Note: The calculated distance is 20 cm.

Output power including tune up tolerance.

**End of Test Report**