Company: Wallys Communications Technologies Co.,Ltd

Add: Room 2723, Le Jia building, Jia Rui Xiang No.8, Suzhou Industrial Park,

Suzhou, P.R 215000 China Tel: +86-18912606205 Fax: +86-512-62815802

E-mail: jason@wallystech.com

Applicant		Wallys Communications Technologies Co.,Ltd							
FCC ID:		2AG7VDR882							
Section 15.212 Modular Transmitters									
Request	for Modular	Approval		Request	for Limited Modular Appro	val			
		Requiremen	its		EUT Conditions	Cor	nply(Y/N)		
Single Modular Approval Requirements									
1	transmitter r The physical	elements of nust have thei crystal and tu ited external ints.	r own	shielding. capacitors	Refer to external photos. This module does not have shield cover.	N			
2	buffered mo inputs are p module wi requirement		input ensure with condit	that the part 15	All inputs to the modules are buffered through logic or microprocessor inputs. Refer to Schematics.	Y			
3		ar transmitt ver supply re			The Module uses the chip QCA9882-BR4A with built-in power management components, the module rated power is 3.3V power, Refer to schematics.	Y			
4	with the anti- requirement 15.204(c). T permanently "unique" connections antenna, in "professiona §15.203 is n can apply t	er transmitter enna and trans s of §§15.203 he antenna reattached antenna coubetween the including the linstallation of applicable to limited moraph (b) of this	smission, 15.2 must or e upler modul cab r pro to mo dular	on system 04(b) and either be imploy a (at all le and the ole). The object of odules but approvals	The EUT has been tested with three external antennas for Wi-Fi. The antenna gain is 4dBi for Omni antenna, 19dBi for Directional antenna. Refer to external photo.	Y			

5 The modular transmitter must be Ν The modular transmitter tested in a stand-alone configuration, is test in the host Device. i.e., the module must not be inside Please refer to setup another device during testing for photo. compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in §15.207. AC or DC power lines and data input/output lines connected to module must not contain the ferrites, unless they will be marketed with the module (see §15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, support equipment connected to the module during testing shall be unmodified and commercially available (see §15.31(i)). 6 The device Uses a The modular transmitter must be permanently affixed label, equipped with either a permanently refer Label .when the affixed label or must be capable of module is installed inside electronically displaying its FCC another device, then the identification number outside of the device into which the module is installed, this exterior label must use wording such as the following: "Contains Transmitter Module FCC ID: 2AG7VDR882 " or "Contains FCC ID: 2AG7VDR882 ".

7	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the	Refer to manual	Y
	application for equipment authorization.		
8	The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	The EUT comply with RF exposure requirements § 2.1091.If the device built into a host as a portable usage, the RF exposure evaluation may be required as specified by§ 2.1093.	Υ

Sincerely,

Signature:

Typed or Printed Name: Jason Sun

Title: CEO