

**FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

**Applicable Standard**

According to §2.1091 and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guideline.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

**Calculated Formulary:**

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

**Calculated Data:****For worst case:**

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412~2462	2	1.58	25.00	316.23	20	0.0994	1.0
802.11g		2	1.58	23.50	223.87	20	0.0704	1.0
802.11n-HT20		2	1.58	28.00	630.96	20	0.1983	1.0
802.11n-HT40	2422~2452	2	1.58	24.50	281.84	20	0.0886	1.0
802.11a	5150~5250	2	1.58	17.50	56.23	20	0.0177	1.0
	5725~5850	2	1.58	20.50	112.20	20	0.0354	1.0
802.11ac20	5150~5250	2	1.58	21.00	125.89	20	0.0396	1.0
	5725~5850	2	1.58	24.00	251.19	20	0.0789	1.0
802.11n-HT20	5150~5250	2	1.58	21.00	125.89	20	0.0396	1.0
	5725~5850	2	1.58	24.00	251.19	20	0.0789	1.0
802.11ac40	5150~5250	2	1.58	17.00	50.12	20	0.0158	1.0
	5725~5850	2	1.58	23.00	199.53	20	0.0627	1.0
802.11n-HT40	5150~5250	2	1.58	17.00	50.12	20	0.0158	1.0
	5725~5850	2	1.58	23.00	199.53	20	0.0627	1.0
802.11ac80	5150~5250	2	1.58	15.00	31.62	20	0.0099	1.0
	5725~5850	2	1.58	23.00	199.53	20	0.0627	1.0
20MHz	4950-4980	2	1.58	22.50	117.83	20	0.0559	1.0

**Note:**

- (1) The tune-up output power was declared by the manufacturer.
- (2) 2.4G Wi-Fi ,4.9G,5G Wi-Fi can not transmit simultaneously.

**Conclusion:** The EUT meets exemption requirement - RF exposure evaluation greater than 20cm distance specified in § 2.1091. If the device built into a host as a portable usage, the additional RF exposure evaluation may be required as specified by§ 2.1093.