

Maximum Permissible Exposure

Applicable Standard According to §1.1307(b)(5), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

For 2.4G WIFI

- 1) The maximum output power for antenna 0 is 24.50 dBm (281.84mW) at 2412MHz, (with 3 dBi antenna gain (2 numeric antenna gain))
- 2) The maximum output power for antenna 1 is 21.74 dBm (149.28mW) at 2462MHz, (with 3 dBi antenna gain (2 numeric antenna gain))
- 3) The maximum output power for antenna 2 is 21.73 dBm (148.94mW) at 2412MHz, (with 3 dBi antenna gain (2 numeric antenna gain))
- 4) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

Calculation

Given $E = \sqrt{\frac{30 \times P \times G}{d}}$ & $S = \frac{E^2}{3770}$

Where E - Field Strength in Volts / meter
 P = Power in Watts
 G = Numeric antenna gain
 d = Distance in meters
 S = Power Density in milliwatts / square centimeter

Maximum Permissible Exposure

Antenna 0 output power=281.84mW

Antenna 1 output power=149.28mW

Antenna 2 output power=148.94mW

Numeric Antenna gain=2 Substituting the MPE safe distance using d=20cm into above equation.

Yields:

$$S = 0.000199 * P * G$$

Where P = Power in mW G = Numeric antenna gain
 S = Power density in mW/cm²

$$\text{Total Power density} = 0.112 + 0.059 + 0.059 = 0.23 \text{ mW/cm}^2$$

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.)

For 5G WIFI

- 1) The maximum output power for antenna 0 is 22.20 dBm (165.96mW) at 5220MHz, (with 3 dBi antenna gain (2 numeric antenna gain))
- 2) The maximum output power for antenna 1 is 22.01 dBm (158.85mW) at 5220MHz, (with 3 dBi antenna gain (2 numeric antenna gain))
- 3) The maximum output power for antenna 2 is 22.19 dBm (165.58mW) at 5220MHz, (with 3 dBi antenna gain (2 numeric antenna gain))

Maximum Permissible Exposure

Antenna 1 output power=165.96mW

Antenna 2 output power=158.85mW

Antenna 3 output power=165.58mW

Numeric Antenna gain=2 Substituting the MPE safe distance using d=20cm into above equation.

Yields:

$$S = 0.000199 * P * G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW/cm²

Total Power density= $0.066+0.063+0.066=0.195$ mW/cm²

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.)