



FCC RF Exposure Evaluation

1. Product Information

FCC ID	2AG87RM1700-2M
Product name	Mesh Rider Radio
Model number	RM-1700-22M3
Additional Model No.	RM-1700-22M RM-1700-22M3-IN RM-1700-22M4 RM-1700-22M4-IN
Power supply	Input: DC 5V, 3A
915MHz	
Frequency Range	902MHz~928MHz
Channel Spacing	1MHz
Channel Number	17 Channels for 10MHz bandwidth (907~923MHz) 21 Channels for 5MHz bandwidth (905~925MHz)
Modulation Type	g mode: OFDM (64QAM, 16QAM, QPSK, BPSK) n mode: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Type	Antenna 0: External Antenna Antenna 1: External Antenna
Antenna Gain	Antenna 0: 2.0dBi (Max.) Antenna 1: 2.0dBi (Max.)
2.4G Band	
Frequency Range	2412MHz ~ 2467MHz
Channel Spacing	5MHz
Channel Number	11 Channels for 20MHz bandwidth (2412~2462MHz) 12 Channels for 10MHz bandwidth (2412~2467MHz)
Modulation Type	IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Type	Antenna 0: External Antenna Antenna 1: External Antenna
Antenna Gain	Antenna 0: 2.2dBi (Max.) Antenna 1: 2.2dBi (Max.)
Hardware version	/
Software version	/
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Devices

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to





determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna





5. Antenna Information

External Antenna can only use antennas as below antenna information provided by manufacturer.

Internal Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Note
Antenna 0	External Antenna	2400MHz-2500MHz	2.2dBi	2.4G Antenna
Antenna 1	External Antenna	2400MHz-2500MHz	2.2dBi	2.4G Antenna
Antenna 2	External Antenna	902MHz-928MHz	2.0dBi	915MHz Antenna
Antenna 3	External Antenna	902MHz-928MHz	2.0dBi	915MHz Antenna

6. Conducted Power

<2.4G Max Conducted Power Ant0>

Mode	Channel	Frequency (MHz)	Max Conducted Power (dBm)
IEEE 802.11g-10M	1	2412	17.3
	6	2437	26.23
	12	2467	17.94
IEEE 802.11n-10M	1	2412	17.45
	6	2437	26.32
	12	2467	17.61
IEEE 802.11g-20M	1	2412	17.85
	6	2437	26.46
	11	2462	18.02
IEEE 802.11n-20M	1	2412	17.77
	6	2437	26.36
	11	2462	16.94

<2.4G Max Conducted Power Ant1>

Mode	Channel	Frequency (MHz)	Max Conducted Power (dBm)
IEEE 802.11g-10M	1	2412	17.53
	6	2437	26.43
	12	2467	16.9
IEEE 802.11n-10M	1	2412	17.65
	6	2437	26.34
	12	2467	16.75
IEEE 802.11g-20M	1	2412	17.85
	6	2437	26.38
	11	2462	16.77
IEEE 802.11n-20M	1	2412	17.26
	6	2437	26.32
	11	2462	17.64

<915M Max Conducted Power Ant0>

Mode	Channel	Frequency (MHz)	Max Conducted Power (dBm)
g-5M	1(Low)	905	26.1
	11(Mid)	915	26.02
	21(High)	925	26.49
n-5M	1(Low)	905	26.17
	11(Mid)	915	26.28
	21(High)	925	26.18
g-10M	1(Low)	907	26.27
	9(Mid)	915	26.18
	17(High)	923	26.69
n-10M	1(Low)	907	26.22
	9(Mid)	915	26.3
	17(High)	923	26.23



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



<915M Max Conducted Power Ant1>

Mode	Channel	Frequency (MHz)	Max Conducted Power (dBm)
g-5M	1(Low)	905	26.48
	11(Mid)	915	26.38
	21(High)	925	26.49
n-5M	1(Low)	905	26.51
	11(Mid)	915	26.51
	21(High)	925	26.38
g-10M	1(Low)	907	26.12
	9(Mid)	915	26.76
	17(High)	923	26.17
n-10M	1(Low)	907	26.09
	9(Mid)	915	26.06
	17(High)	923	26.14

7. Manufacturing Tolerance

<2.4G Ant0>

IEEE 802.11g-10M (Peak)			
Channel	Channel 1	Channel 6	Channel 12
Target (dBm)	17.0	26.0	17.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n-10M (Peak)			
Channel	Channel 1	Channel 6	Channel 12
Target (dBm)	17.0	26.0	17.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11g-20M (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	17.0	26.0	18.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n-20M (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	17.0	26.0	16.0
Tolerance ±(dB)	1.0	1.0	1.0

<2.4G Ant1>

IEEE 802.11g-10M (Peak)			
Channel	Channel 1	Channel 6	Channel 12
Target (dBm)	17.0	26.0	16.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n-10M (Peak)			
Channel	Channel 1	Channel 6	Channel 12
Target (dBm)	17.0	26.0	16.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11g-20M (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	17.0	26.0	16.0
Tolerance ±(dB)	1.0	1.0	1.0
IEEE 802.11n-20M (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	17.0	26.0	17.0
Tolerance ±(dB)	1.0	1.0	1.0





<915M Ant0>

11g-5M (Peak)			
Channel	Channel 1	Channel 11	Channel 21
Target (dBm)	26.0	26.0	26.0
Tolerance ±(dB)	1.0	1.0	1.0
11n-5M (Peak)			
Channel	Channel 1	Channel 11	Channel 21
Target (dBm)	26.0	26.0	26.0
Tolerance ±(dB)	1.0	1.0	1.0
11g-10M (Peak)			
Channel	Channel 1	Channel 9	Channel 17
Target (dBm)	26.0	26.0	26.0
Tolerance ±(dB)	1.0	1.0	1.0
11n-10M (Peak)			
Channel	Channel 1	Channel 9	Channel 17
Target (dBm)	26.0	26.0	26.0
Tolerance ±(dB)	1.0	1.0	1.0

<915M Ant1>

11g-5M (Peak)			
Channel	Channel 1	Channel 11	Channel 21
Target (dBm)	26.0	26.0	26.0
Tolerance ±(dB)	1.0	1.0	1.0
11n-5M (Peak)			
Channel	Channel 1	Channel 11	Channel 21
Target (dBm)	26.0	26.0	26.0
Tolerance ±(dB)	1.0	1.0	1.0
11g-10M (Peak)			
Channel	Channel 1	Channel 9	Channel 17
Target (dBm)	26.0	26.0	26.0
Tolerance ±(dB)	1.0	1.0	1.0
11n-10M (Peak)			
Channel	Channel 1	Channel 9	Channel 17
Target (dBm)	26.0	26.0	26.0
Tolerance ±(dB)	1.0	1.0	1.0

8. Measurement Results
8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[Antenna 0]

<2.4G Ant0>

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW			
IEEE 802.11g-10M	27.0	501.1872	2.2	0.165558	1.0000
IEEE 802.11n-10M	27.0	501.1872	2.2	0.165558	1.0000
IEEE 802.11g-20M	27.0	501.1872	2.2	0.165558	1.0000
IEEE 802.11n-20M	27.0	501.1872	2.2	0.165558	1.0000





[Antenna 1]

<2.4G Ant1>

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW			
IEEE 802.11g-10M	27.0	501.1872	2.2	0.165558	1.0000
IEEE 802.11n-10M	27.0	501.1872	2.2	0.165558	1.0000
IEEE 802.11g-20M	27.0	501.1872	2.2	0.165558	1.0000
IEEE 802.11n-20M	27.0	501.1872	2.2	0.165558	1.0000

[Antenna 2]

<915M Ant0>

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW			
g-5M	27.0	501.1872	2.0	0.158107	0.61
n-5M	27.0	501.1872	2.0	0.158107	0.61
g-10M	27.0	501.1872	2.0	0.158107	0.61
n-10M	27.0	501.1872	2.0	0.158107	0.61

[Antenna 3]

<915M Ant1>

Band/Mode	RF output power		Antenna Gain (dBi)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW			
g-5M	27.0	501.1872	2.0	0.158107	0.61
n-5M	27.0	501.1872	2.0	0.158107	0.61
g-10M	27.0	501.1872	2.0	0.158107	0.61
n-10M	27.0	501.1872	2.0	0.158107	0.61

8.2 Simultaneous Transmission MPE

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

ΣΣof MPE ratios ≤ 1.0

This modular can support 2.4G and 915MHz in hardware, while only can use 2.4GHz or 915MHz antenna for transmitter, cannot use 2.4GHz and 915MHz at same time, no need consider simultaneously transmission for 2.4GHz and 915MHz.

This modular can support 2.4GHz and 915MHz 2T2R MIMO in hardware.

Antenna 0 2.4GHz MPE ratios	Antenna 1 2.4GHz MPE ratios	Σ MPE ratios	Limit	Results
0.165558	0.165558	0.331116	1.0	Pass

Antenna 2 915MHz MPE ratios	Antenna 3 915MHz MPE ratios	Σ MPE ratios	Limit	Results
0.259192	0.259192	0.518384	1.0	Pass

Remark:

1. Output power including turn-up tolerance;
2. Output power is burst average power;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer;
4. MPE values = PG/4πR²

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

.....THE END OF REPORT.....

