



Fanguang Inspection & Testing Co., Ltd.
 Phone: +86-510-68790033
 Web: www.fgtest.cn



RF Exposure Evaluation Declaration

Report No.: S20210812863801E11
 Report Version: V01
 Issue Date: 10-08-2021

Applicant: Xi'an NovaStar Tech Co., Ltd.
Address: 101 Block D-F, 01 Square, Xi'an Software Park, No.72,
 2nd Keji Road, Xi'an, Shaanxi, China

FCC ID: 2AG8JT60
Application Type: Certification
Product: Taurus-MediaPlayer
Model No.: T60
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part 15 Subpart C (15.247)
Test Procedure(s): ANSI C63.10-2013, KDB 558074 D01v05r02
Test Date: Sept 02 ~ Sept 26, 2021

Compiled By Amos Xia
 (Amos Xia)
 Senior Test Engineer

Approved By Kerry Zhou
 (Kerry Zhou)
 Engineer Manager



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of Fanguang Inspection & Testing Co., Ltd. Wuxi Branch

The test report must not be used by the client to claim product certifications, approval, or endorsement by NVLAP, NIST or any agency of U.S. Government.

Revision History

Report No.	Version	Description	Issue Date
S20210812863801E11	Rev. 01	/	10-08-2021

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name:	Taurus-MediaPlayer
Model Name:	T60
Additional Model:	T30,T50,T60-X,T30-X,T50-X (X=blank, 0-9 or A-Z for different sale area,no impact on EMC & Safety)
Input Voltage Range:	DC 5V
Wi-Fi Specification:	802.11b/g/n-HT20
Antenna Type:	External Rod Antenna
Antenna Gain:	5.03dBi

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	Taurus-MediaPlayer
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Maximum PK Output Power (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
802.11b/g/n	2412 ~ 2462	14.86	0.0194	1
Note: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2) = (10^{(14.89+5.03)/10}) / (4 \cdot 3.1416 \cdot 20^2) = 0.0194 \text{ mW/cm}^2$				

CONCLUSION:

The Max Power Density at R (20 cm) = 0.0194mW/cm² < 1mW/cm².

So the EUT complies with the requirement.

_____ The End _____