

# FCC REPORT (WIFI)

**Applicant:** SHENZHENSHI XINZHONGXIN TECHNOLOGY CO., LTD.

**Address of Applicant:** Block 1, Dong Huan Industrial Park, NanPu Road, ShangLiao Community, XinQiao Street, Bao'an District, Shenzhen City, Guangdong Province, China

## Equipment Under Test (EUT)

Product Name: 2.4G Wifi & Bluetooth Module

Model No.: C-CB2L

Trade mark: C-Chip

**FCC ID:** 2AG94C-CB2L

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.247

**Date of sample receipt:** 24 Dec., 2021

**Date of Test:** 25 Dec., 2021 to 24 Jan., 2022

**Date of report issued:** 22 Feb., 2022

**Test Result:** PASS\*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the JYT product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	25 Jan., 2022	Original
01	22 Feb., 2022	Updated page 5/6/11/12

**Tested by:**

Mike.ou  
Test Engineer

**Date:**

22 Feb., 2022

**Reviewed by:**

Winner Zhang  
Project Engineer

**Date:**

22 Feb., 2022

### 3 Contents

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 VERSION.....</b>	<b>2</b>
<b>3 CONTENTS.....</b>	<b>3</b>
<b>4 TEST SUMMARY.....</b>	<b>4</b>
<b>5 GENERAL INFORMATION.....</b>	<b>5</b>
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST ENVIRONMENT AND MODE.....	6
5.4 DESCRIPTION OF SUPPORT UNITS.....	6
5.5 MEASUREMENT UNCERTAINTY.....	6
5.6 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD.....	6
5.7 LABORATORY FACILITY.....	7
5.8 LABORATORY LOCATION.....	7
5.9 TEST INSTRUMENTS LIST.....	8
<b>6 TEST RESULTS AND MEASUREMENT DATA.....</b>	<b>9</b>
6.1 ANTENNA REQUIREMENT.....	9
6.2 CONDUCTED EMISSION.....	10
6.3 CONDUCTED OUTPUT POWER.....	13
6.4 OCCUPY BANDWIDTH.....	14
6.5 POWER SPECTRAL DENSITY.....	15
6.6 BAND EDGE.....	16
6.6.1 Conducted Emission Method.....	16
6.6.2 Radiated Emission Method.....	17
6.7 SPURIOUS EMISSION.....	30
6.7.1 Conducted Emission Method.....	30
6.7.2 Radiated Emission Method.....	31
<b>7 TEST SETUP PHOTO.....</b>	<b>38</b>
<b>8 EUT CONSTRUCTIONAL DETAILS.....</b>	<b>39</b>

## 4 Test Summary

Test Items	Section in CFR 47	Test Data	Result
Antenna requirement	15.203 & 15.247 (b)	See Section 6.1	Pass
AC Power Line Conducted Emission	15.207	See Section 6.2	Pass
Duty Cycle	ANSI C63.10-2013	Appendix A – 2.4G Wi-Fi	Pass
Conducted Peak Output Power	15.247 (b)(3)	Appendix A – 2.4G Wi-Fi	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Appendix A – 2.4G Wi-Fi	Pass
Power Spectral Density	15.247 (e)	Appendix A – 2.4G Wi-Fi	Pass
Conducted Band Edge	15.247 (d)	Appendix A – 2.4G Wi-Fi	Pass
Radiated Band Edge		See Section 6.6.2	Pass
Conducted Spurious Emission	15.205 & 15.209	Appendix A – 2.4G Wi-Fi	Pass
Radiated Spurious Emission		See Section 6.7.2	Pass
<b>Remark:</b> <ol style="list-style-type: none"> <li>Pass: The EUT complies with the essential requirements in the standard.</li> <li>N/A: Not Applicable.</li> <li>The cable insertion loss used by “RF Output Power” and other conduction measurement items is 0.5dB (provided by the customer).</li> </ol>			
<b>Test Method:</b>	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02		

## 5 General Information

### 5.1 Client Information

Applicant:	SHENZHENSHI XINZHONGXIN TECHNOLOGY CO., LTD.
Address:	Block 1, Dong Huan Industrial Park, NanPu Road, ShangLiao Community, XinQiao Street, Bao'an District, Shenzhen City, Guangdong Province, China
Manufacturer:	SHENZHENSHI XINZHONGXIN TECHNOLOGY CO., LTD.
Address:	Block 1, Dong Huan Industrial Park, NanPu Road, ShangLiao Community, XinQiao Street, Bao'an District, Shenzhen City, Guangdong Province, China

### 5.2 General Description of E.U.T.

Product Name:	2.4G Wifi & Bluetooth Module
Model No.:	C-CB2L
Operation Frequency:	2412MHz~2462MHz: 802.11b/802.11g/802.11n(HT20)
Channel numbers:	11: 802.11b/802.11g/802.11(HT20)
Channel separation:	5MHz
Modulation technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum (DSSS)
Modulation technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Data speed (IEEE 802.11n):	Up to 150Mbps
Antenna Type:	PCB Antenna
Antenna gain:	0dBi
Power supply:	DC 3.3V
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

Operation Frequency each of channel for 802.11b/g/n(HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

- For 802.11n-HT40 mode, the channel number is from 3 to 9;
- Channel 1, 6 & 11 selected for 802.11b/g/n-HT20 as Lowest, Middle and Highest channel.

### 5.3 Test environment and mode

<b>Operating Environment:</b>	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
<b>Test mode:</b>	
Transmitting mode	Keep the EUT in continuous transmitting with modulation
Radiated Emission: The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
<b>Per-scan all kind of data rate, the follow list were the worst case.</b>	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	6.5Mbps

### 5.4 Description of Support Units

The EUT has been tested as an independent unit.

### 5.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%)
Conducted Emission (9kHz ~ 150KHz) for V-AMN	3.11 dB
Conducted Emission (150kHz ~ 30MHz) for V-AMN	2.62 dB
Conducted Emission (150kHz ~ 30MHz) for AAN	3.54 dB
Radiated Emission (9kHz ~ 30MHz electric field) for 3m SAC	3.13 dB
Radiated Emission (9kHz ~ 30MHz magnetic field) for 3m SAC	3.13 dB
Radiated Emission (30MHz ~ 1GHz) for 3m SAC	4.45 dB
Radiated Emission (1GHz ~ 18GHz) for 3m SAC	5.34 dB
Radiated Emission (18GHz ~ 40GHz) for 3m SAC	5.34 dB

### 5.6 Additions to, deviations, or exclusions from the method

No

## 5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

## 5.8 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

## 5.9 Test Instruments list

<b>Radiated Emission:</b>					
<b>Test Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Cal.Date (mm-dd-yy)</b>	<b>Cal.Due date (mm-dd-yy)</b>
3m SAC	ETS	RFD-100	Q1984	04-14-2021	04-13-2024
BiConiLog Antenna	SCHWARZBECK	VULB9163	9163-1246	03-07-2021	03-06-2022
Biconical Antenna	SCHWARZBECK	VUBA 9117	9117#359	06-17-2021	06-17-2022
Horn Antenna	SCHWARZBECK	BBHA9120D	912D-916	03-07-2021	03-06-2022
Broad-Band Horn Antenna	SCHWARZBECK	BBHA9170	1067	04-02-2021	04-01-2022
Broad-Band Horn Antenna	SCHWARZBECK	BBHA9170	1068	04-02-2021	04-01-2022
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-03-2021	03-02-2022
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-03-2021	03-02-2022
Spectrum analyzer	Keysight	N9010B	MY60240202	10-27-2021	10-26-2022
Low Pre-amplifier	SCHWARZBECK	BBV9743B	00305	03-07-2021	03-06-2022
High Pre-amplifier	SKET	LNPA_0118G-50	MF280208233	03-07-2021	03-06-2022
Cable	Qualwave	JYT3M-1G-NN-8M	JYT3M-1	03-07-2021	03-06-2022
Cable	Qualwave	JYT3M-18G-NN-8M	JYT3M-2	03-07-2021	03-06-2022
Cable	Qualwave	JYT3M-1G-BB-5M	JYT3M-3	03-07-2021	03-06-2022
Cable	Bost	JYT3M-40G-SS-8M	JYT3M-4	04-02-2021	04-01-2022
EMI Test Software	Tonscend	TS+	Version:3.0.0.1		

<b>Conducted Emission:</b>					
<b>Test Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Cal. Date (mm-dd-yy)</b>	<b>Cal. Due date (mm-dd-yy)</b>
EMI Test Receiver	Rohde & Schwarz	ESCI 3	101189	03-03-2021	03-02-2022
LISN	Schwarzbeck	NSLK 8127	QCJ001-13	03-18-2021	03-17-2022
LISN	Rohde & Schwarz	ESH3-Z5	843862/010	06-18-2020	06-17-2022
RF Switch	TOP PRECISION	RSU0301	N/A	03-03-2021	03-02-2022
Cable	Bost	JYTCE-1G-NN-2M	JYTCE-1	03-03-2021	03-02-2022
Cable	Bost	JYTCE-1G-BN-3M	JYTCE-2	03-03-2021	03-02-2022
EMI Test Software	AUDIX	E3	Version: 6.110919b		

<b>Conducted method:</b>					
<b>Test Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Cal. Date (mm-dd-yy)</b>	<b>Cal. Due date (mm-dd-yy)</b>
Spectrum Analyzer	Keysight	N9010B	MY60240202	10-27-2021	10-26-2022
Vector Signal Generator	Keysight	N5182B	MY59101009	10-27-2021	10-26-2022
Analog Signal Generator	Keysight	N5173B	MY59100765	10-27-2021	10-26-2022
Power Detector Box	MWRF-test	MW100-PSB	MW201020JYT	11-19-2021	11-18-2022
Simulated Station	Rohde & Schwarz	CMW270	102335	10-27-2021	10-26-2022
RF Control Box	MWRF-test	MW100-RFCB	MW200927JYT	N/A	N/A
PDU	MWRF-test	XY-G10	N/A	N/A	N/A
DC Power Supply	Keysight	E3642A	MY60296194	11-27-2020	11-26-2023
Temperature Humidity Chamber	Deli	8840	N/A	03-08-2021	03-07-2022
Test Software	MWRF-tes	MTS 8310	Version: 2.0.0.0		




## 6 Test results and Measurement Data

### 6.1 Antenna requirement


<b>Standard requirement:</b>	FCC Part 15 C Section 15.203 /247(b)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
<b>E.U.T Antenna:</b>	
<p>The Wi-Fi antenna is an PCB antenna which cannot replace by end-user, the best case gain of the antenna is 0 dBi.</p>	

## 6.2 Conducted Emission

Test Requirement:	FCC Part 15 C Section 15.207		
Test Frequency Range:	150 kHz to 30 MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9 kHz, VBW=30 kHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test procedure	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10(latest version) on conducted measurement.</li> </ol>		
Test setup:	 <p><i>Remark:</i>                  E.U.T: Equipment Under Test                  LISN: Line Impedance Stabilization Network                  Test table height=0.8m</p>		
Test Instruments:	Refer to section 5.9 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Passed		

Measurement Data:

Product name:	2.4G Wifi & Bluetooth Module	Product model:	C-CB2L
Test by:	Mike	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120V 60Hz	Environment:	Temp: 22.7°C Humi: 51%




Trace: 1

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.174	52.21	0.04	0.01	52.26	64.77	-12.51	QP
2	0.186	38.17	0.04	0.02	38.23	54.20	-15.97	Average
3	0.186	51.82	0.04	0.02	51.88	64.20	-12.32	QP
4	0.214	36.02	0.04	0.03	36.09	53.05	-16.96	Average
5	0.253	47.24	0.04	0.01	47.29	61.64	-14.35	QP
6	0.270	28.52	0.04	0.02	28.58	51.12	-22.54	Average
7	2.077	25.17	0.07	0.20	25.44	46.00	-20.56	Average
8	2.077	32.76	0.07	0.20	33.03	56.00	-22.97	QP
9	4.114	26.55	0.11	0.08	26.74	46.00	-19.26	Average
10	4.202	36.73	0.11	0.08	36.92	56.00	-19.08	QP
11	20.486	38.68	0.32	0.18	39.18	60.00	-20.82	QP
12	20.594	30.03	0.33	0.18	30.54	50.00	-19.46	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test by:</b>	Mike	<b>Test mode:</b>	Wi-Fi Tx mode
<b>Test frequency:</b>	150 kHz ~ 30 MHz	<b>Phase:</b>	Neutral
<b>Test voltage:</b>	AC 120V 60Hz	<b>Environment:</b>	Temp: 22.7°C Humi: 51%




	Freq	Read	LISN	Cable	Level	Limit	Over	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.150	53.52	0.05	0.01	53.58	66.00	-12.42	QP
2	0.194	49.39	0.04	0.03	49.46	63.84	-14.38	QP
3	0.206	38.55	0.04	0.04	38.63	53.36	-14.73	Average
4	0.211	49.25	0.04	0.03	49.32	63.18	-13.86	QP
5	0.253	46.02	0.04	0.01	46.07	61.64	-15.57	QP
6	0.274	32.39	0.04	0.02	32.45	50.98	-18.53	Average
7	3.074	26.36	0.08	0.07	26.51	46.00	-19.49	Average
8	4.049	41.46	0.09	0.08	41.63	56.00	-14.37	QP
9	4.092	27.35	0.09	0.08	27.52	46.00	-18.48	Average
10	14.440	26.28	0.24	0.13	26.65	50.00	-23.35	Average
11	21.600	29.02	0.32	0.16	29.50	50.00	-20.50	Average
12	21.600	37.72	0.32	0.16	38.20	60.00	-21.80	QP


**Notes:**

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.


### 6.3 Conducted Output Power

Test Requirement:	FCC Part 15 C Section 15.247 (b)(3)
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	<b>Refer to Appendix A - 2.4G WIFI</b>

### 6.4 Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.247 (a)(2)
Limit:	>500kHz
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	<b>Refer to Appendix A - 2.4G WIFI</b>


### 6.5 Power Spectral Density

Test Requirement:	FCC Part 15 C Section 15.247 (e)
Limit:	8dBm/3kHz
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	<b>Refer to Appendix A - 2.4G WIFI</b>




## 6.6 Band Edge

### 6.6.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	Refer to Appendix A - 2.4G WIFI




### 6.6.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205				
Test Frequency Range:	2310 MHz to 2390 MHz and 2483.5 MHz to 2500 MHz				
Test Distance:	3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
RMS		1MHz	3MHz	Average Value	
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	Above 1GHz	54.00		Average Value	
		74.00		Peak Value	
Test Procedure:	<ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>				
Test setup:					
Test Instruments:	Refer to section 5.9 for details				
Test mode:	Refer to section 5.3 for details				
Test results:	Passed				

802.11b mode:

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	802.11b Tx mode
<b>Test Channel:</b>	Lowest channel	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp:22.2°C Huni: 55%




NO.	Freq. [MHz]	Reading [dBuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	2349.42	15.71	51.26	35.55	54.00	2.74	AV	Vertical
2	2349.64	22.92	58.47	35.55	74.00	15.53	PK	Vertical
3	2376.52	14.98	50.72	35.74	54.00	3.28	AV	Vertical
4	2376.52	22.29	58.03	35.74	74.00	15.97	PK	Vertical
5	2390.19	16.08	51.92	35.84	54.00	2.08	AV	Vertical
6	2390.19	23.37	59.21	35.84	74.00	14.79	PK	Vertical

Remark:

- Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	802.11b Tx mode
<b>Test Channel:</b>	Lowest channel	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp:22.2°C Huni: 55%




NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	2358.38	23.90	59.51	35.61	74.00	14.49	PK	Horizontal
2	2359.05	15.88	51.50	35.62	54.00	2.50	AV	Horizontal
3	2377.42	24.68	60.43	35.75	74.00	13.57	PK	Horizontal
4	2377.64	15.92	51.67	35.75	54.00	2.33	AV	Horizontal
5	2390.19	23.15	58.99	35.84	74.00	15.01	PK	Horizontal
6	2390.19	15.37	51.21	35.84	54.00	2.79	AV	Horizontal

**Remark:**

- Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	802.11b Tx mode
<b>Test Channel:</b>	Highest channel	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp:22.2°C Huni: 55%




NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	2483.53	23.34	59.06	35.72	74.00	14.94	PK	Vertical
2	2483.53	13.61	49.33	35.72	54.00	4.67	AV	Vertical
3	2489.58	13.97	49.67	35.70	54.00	4.33	AV	Vertical
4	2491.26	24.27	59.97	35.70	74.00	14.03	PK	Vertical
5	2495.58	24.16	59.85	35.69	74.00	14.15	PK	Vertical
6	2496.64	13.99	49.68	35.69	54.00	4.32	AV	Vertical

**Remark:**

- Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	802.11b Tx mode
<b>Test Channel:</b>	Highest channel	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp:22.2°C Huni: 55%




NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	2483.53	23.95	59.67	35.72	74.00	14.33	PK	Horizontal
2	2483.53	13.82	49.54	35.72	54.00	4.46	AV	Horizontal
3	2490.40	13.85	49.55	35.70	54.00	4.45	AV	Horizontal
4	2491.50	24.32	60.02	35.70	74.00	13.98	PK	Horizontal
5	2496.25	14.09	49.78	35.69	54.00	4.22	AV	Horizontal
6	2498.36	24.44	60.12	35.68	74.00	13.88	PK	Horizontal

**Remark:**

1. Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11g mode:

Product name:	2.4G Wifi & Bluetooth Module	Product model:	C-CB2L
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 3.3V	Environment:	Temp:22.2°C Humi: 55%




NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	2342.70	16.62	52.12	35.50	54.00	1.88	AV	Vertical
2	2343.82	24.70	60.21	35.51	74.00	13.79	PK	Vertical
3	2378.54	15.76	51.52	35.76	54.00	2.48	AV	Vertical
4	2379.66	24.51	60.28	35.77	74.00	13.72	PK	Vertical
5	2390.19	15.28	51.12	35.84	54.00	2.88	AV	Vertical
6	2390.19	23.57	59.41	35.84	74.00	14.59	PK	Vertical

Remark:

1. Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	802.11g Tx mode
<b>Test Channel:</b>	Lowest channel	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp:22.2°C Huni: 55%




NO.	Freq. [MHz]	Reading [dBuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	2347.40	24.25	59.79	35.54	74.00	14.21	PK	Horizontal
2	2347.63	15.33	50.87	35.54	54.00	3.13	AV	Horizontal
3	2368.68	24.68	60.37	35.69	74.00	13.63	PK	Horizontal
4	2368.91	15.13	50.82	35.69	54.00	3.18	AV	Horizontal
5	2390.19	15.40	51.24	35.84	54.00	2.76	AV	Horizontal
6	2390.19	22.22	58.06	35.84	74.00	15.94	PK	Horizontal

**Remark:**

- Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	802.11g Tx mode
<b>Test Channel:</b>	Highest channel	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp:22.2℃ Huni: 55%




NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	2483.53	23.01	58.73	35.72	74.00	15.27	PK	Vertical
2	2483.53	13.62	49.34	35.72	54.00	4.66	AV	Vertical
3	2487.76	13.93	49.64	35.71	54.00	4.36	AV	Vertical
4	2488.62	22.85	58.56	35.71	74.00	15.44	PK	Vertical
5	2494.72	13.83	49.52	35.69	54.00	4.48	AV	Vertical
6	2494.81	24.43	60.12	35.69	74.00	13.88	PK	Vertical

**Remark:**

- Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.



<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	802.11g Tx mode
<b>Test Channel:</b>	Highest channel	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp:22.2°C Humi: 55%




NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	2483.53	23.62	59.34	35.72	74.00	14.66	PK	Horizontal
2	2483.53	13.50	49.22	35.72	54.00	4.78	AV	Horizontal
3	2489.53	24.31	60.01	35.70	74.00	13.99	PK	Horizontal
4	2489.92	14.05	49.75	35.70	54.00	4.25	AV	Horizontal
5	2499.37	13.72	49.40	35.68	54.00	4.60	AV	Horizontal
6	2499.56	24.16	59.84	35.68	74.00	14.16	PK	Horizontal

**Remark:**

- Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11n(HT20):

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	802.11n(HT20) Tx mode
<b>Test Channel:</b>	Lowest channel	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp:22.2°C Huni: 55%




NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	2342.70	15.97	51.47	35.50	54.00	2.53	AV	Vertical
2	2343.15	23.84	59.35	35.51	74.00	14.65	PK	Vertical
3	2367.56	15.68	51.36	35.68	54.00	2.64	AV	Vertical
4	2368.01	24.29	59.97	35.68	74.00	14.03	PK	Vertical
5	2390.19	15.40	51.24	35.84	54.00	2.76	AV	Vertical
6	2390.19	23.10	58.94	35.84	74.00	15.06	PK	Vertical

Remark:

1. Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	802.11n(HT20) Tx mode
<b>Test Channel:</b>	Lowest channel	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp:22.2°C Huni: 55%




NO.	Freq. [MHz]	Reading [dBuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	2337.77	16.43	51.90	35.47	54.00	2.10	AV	Horizontal
2	2339.56	24.16	59.64	35.48	74.00	14.36	PK	Horizontal
3	2380.56	16.49	52.26	35.77	54.00	1.74	AV	Horizontal
4	2380.56	23.98	59.75	35.77	74.00	14.25	PK	Horizontal
5	2390.19	22.82	58.66	35.84	74.00	15.34	PK	Horizontal
6	2390.19	15.13	50.97	35.84	54.00	3.03	AV	Horizontal

**Remark:**

- Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	802.11n(HT20) Tx mode
<b>Test Channel:</b>	Highest channel	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp:22.2°C Huni: 55%




NO.	Freq. [MHz]	Reading [dBuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	2483.53	22.75	58.47	35.72	74.00	15.53	PK	Vertical
2	2483.53	13.45	49.17	35.72	54.00	4.83	AV	Vertical
3	2486.36	13.85	49.56	35.71	54.00	4.44	AV	Vertical
4	2486.84	24.18	59.89	35.71	74.00	14.11	PK	Vertical
5	2492.17	13.73	49.43	35.70	54.00	4.57	AV	Vertical
6	2492.51	24.34	60.04	35.70	74.00	13.96	PK	Vertical

**Remark:**

- Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	802.11n(HT20) Tx mode
<b>Test Channel:</b>	Highest channel	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp:22.2°C Huni: 55%




NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	2483.53	23.16	58.88	35.72	74.00	15.12	PK	Horizontal
2	2483.53	13.52	49.24	35.72	54.00	4.76	AV	Horizontal
3	2485.26	13.82	49.53	35.71	54.00	4.47	AV	Horizontal
4	2485.36	24.32	60.03	35.71	74.00	13.97	PK	Horizontal
5	2492.84	13.89	49.59	35.70	54.00	4.41	AV	Horizontal
6	2493.18	24.03	59.73	35.70	74.00	14.27	PK	Horizontal

**Remark:**


1. Final Level = Receiver Read level + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.


## 6.7 Spurious Emission

### 6.7.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	<b>Refer to Appendix A - 2.4G WIFI</b>

### 6.7.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205				
Test Frequency Range:	9kHz to 25GHz				
Test Distance:	3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
RMS		1MHz	3MHz	Average Value	
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
	Above 1GHz	54.0		Average Value	
		74.0		Peak Value	
Test Procedure:	<ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table 0.8m(below 1GHz)/1.5m(above 1GHz) above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>				
Test setup:	<p>Below 1GHz</p>  <p>Above 1GHz</p>				


	
<p>Test Instruments:</p>	<p>Refer to section 5.9 for details</p>
<p>Test mode:</p>	<p>Refer to section 5.3 for details</p>
<p>Test results:</p>	<p>Passed</p>
<p>Remark:</p>	<ol style="list-style-type: none"> <li>1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case.</li> <li>2. 9 kHz to 30MHz is lower than the limit 20dB, so only shows the data of above 30MHz in this report.</li> </ol>



**Measurement Data (worst case):**

**Below 1GHz:**

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	Wi-Fi Tx mode
<b>Test Frequency:</b>	30 MHz ~ 1 GHz	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp: 20.5°C Humi: 46%




NO.	Freq. [MHz]	Reading [dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	40.4770	29.15	14.64	-14.51	40.00	25.36	PK	Vertical
2	67.3487	30.65	14.40	-16.25	40.00	25.60	PK	Vertical
3	250.018	30.32	16.53	-13.79	46.00	29.47	PK	Vertical
4	319.962	31.08	18.80	-12.28	46.00	27.20	PK	Vertical
5	480.028	31.95	24.34	-7.61	46.00	21.66	PK	Vertical
6	639.997	36.54	31.26	-5.28	46.00	14.74	PK	Vertical

**Remark:**

1. Final Level = Receiver Read level + Factor (Antenna Factor + Cable Loss – Pre-amplifier Factor).
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

<b>Product name:</b>	2.4G Wifi & Bluetooth Module	<b>Product model:</b>	C-CB2L
<b>Test By:</b>	Mike	<b>Test mode:</b>	Wi-Fi Tx mode
<b>Test Frequency:</b>	30 MHz ~ 1 GHz	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	DC 3.3V	<b>Environment:</b>	Temp:20.5°C Huni: 46%



NO.	Freq. [MHz]	Reading[dBµV/m]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	50.1780	28.67	13.96	-14.71	40.00	26.04	PK	Horizontal
2	239.929	30.74	16.52	-14.22	46.00	29.48	PK	Horizontal
3	319.962	35.07	22.79	-12.28	46.00	23.21	PK	Horizontal
4	480.125	32.34	24.73	-7.61	46.00	21.27	PK	Horizontal
5	640.094	43.01	37.73	-5.28	46.00	8.27	PK	Horizontal
6	800.160	34.58	31.89	-2.69	46.00	14.11	PK	Horizontal

**Remark:**

1. Final Level = Receiver Read level + Factor (Antenna Factor + Cable Loss – Preamplifier Factor).
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

**Above 1GHz**


802.11b						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	55.10	-9.46	45.64	74.00	28.36	Vertical
4824.00	55.15	-9.46	45.69	74.00	28.31	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	48.11	-9.46	38.65	54.00	15.35	Vertical
4824.00	47.56	-9.46	38.10	54.00	15.90	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	55.17	-9.11	46.06	74.00	27.94	Vertical
4874.00	55.10	-9.11	45.99	74.00	28.01	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	48.36	-9.11	39.25	54.00	14.75	Vertical
4874.00	47.31	-9.11	38.20	54.00	15.80	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	54.90	-8.74	46.16	74.00	27.84	Vertical
4924.00	55.37	-8.74	46.63	74.00	27.37	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	48.28	-8.74	39.54	54.00	14.46	Vertical
4924.00	47.57	-8.74	38.83	54.00	15.17	Horizontal
<i>Remark:</i> 1. <i>Final Level = Receiver Read level + Factor.</i> 2. <i>The emission levels of other frequencies are lower than the limit 20dB and not show in test report.</i>						

802.11g						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	54.73	-9.46	45.27	74.00	28.73	Vertical
4824.00	55.55	-9.46	46.09	74.00	27.91	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	48.24	-9.46	38.78	54.00	15.22	Vertical
4824.00	47.42	-9.46	37.96	54.00	16.04	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	55.40	-9.11	46.29	74.00	27.71	Vertical
4874.00	55.22	-9.11	46.11	74.00	27.89	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	48.17	-9.11	39.06	54.00	14.94	Vertical
4874.00	47.49	-9.11	38.38	54.00	15.62	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	54.98	-8.74	46.24	74.00	27.76	Vertical
4924.00	55.02	-8.74	46.28	74.00	27.72	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	48.20	-8.74	39.46	54.00	14.54	Vertical
4924.00	47.75	-8.74	39.01	54.00	14.99	Horizontal
<i>Remark:</i> 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						


802.11n(HT20)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	55.05	-9.46	45.59	74.00	28.41	Vertical
4824.00	55.32	-9.46	45.86	74.00	28.14	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	48.60	-9.46	39.14	54.00	14.86	Vertical
4824.00	47.50	-9.46	38.04	54.00	15.96	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	54.85	-9.11	45.74	74.00	28.26	Vertical
4874.00	55.14	-9.11	46.03	74.00	27.97	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	47.73	-9.11	38.62	54.00	15.38	Vertical
4874.00	47.54	-9.11	38.43	54.00	15.57	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	55.48	-8.74	46.74	74.00	27.26	Vertical
4924.00	54.84	-8.74	46.10	74.00	27.90	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	48.08	-8.74	39.34	54.00	14.66	Vertical
4924.00	47.11	-8.74	38.37	54.00	15.63	Horizontal
<i>Remark:</i> 1. <i>Final Level = Receiver Read level + Factor.</i> 2. <i>The emission levels of other frequencies are lower than the limit 20dB and not show in test report.</i>						

### 7 Test Setup Photo

Radiated Spurious Emission  
Below 1GHz



Above 1GHz





**Conducted Emission**

## 8 EUT Constructional Details

Reference to the test report No.: JYTSZ-R12-2200172.

-----End of report-----