



Total Quality. Assured.

Intertek
731 Enterprise Drive
Lexington, KY 40510

Tel 859 226 1000
Fax 859 226 1040

www.intertek.com

Stress Engineering Services, Inc. TEST REPORT

SCOPE OF WORK

EMC TESTING – IGROWTH GENERATION 2 KITCHEN DEVICE

REPORT NUMBER

104797984LEX-001

ISSUE DATE

12/3/2021

PAGES

22

DOCUMENT CONTROL NUMBER

Non-Specific EMC Report Shell Rev. December 2017
© 2017 INTERTEK



EMC TEST REPORT

(FULL COMPLIANCE)

Report Number: 104797984LEX-001

Project Number: G104797984

Report Issue Date: 12/3/2021

Model(s) Tested: iGrowth Generation 2 Kitchen Device

Standards: FCC Part 15B
FCC Part 15.225
RSS-210 Issue 10
ICES-003 Issue 7

Tested by:
Intertek Testing Services NA, Inc.
731 Enterprise Dr.
Lexington, KY 40510
USA

Client:
Stress Engineering Services, Inc.
7030 Stress Engineering Way
Mason, OH 45040-7386
USA

Report prepared by



Brian Lackey, Staff Engineer

Report reviewed by



Bryan Taylor, Team Leader

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



Table of Contents

1	<i>Introduction and Conclusion.....</i>	4
2	<i>Test Summary</i>	4
3	<i>Client Information</i>	5
4	<i>Description of Equipment under Test and Variant Models.....</i>	6
5	<i>System Setup and Method</i>	7
6	<i>Radiated Emissions</i>	8
7	<i>Radiated Emissions (RFID).....</i>	12
8	<i>Frequency Stability.....</i>	17
9	<i>Occupied Bandwidth</i>	19
10	<i>Antenna Requirement</i>	21
11	<i>Revision History.....</i>	22



1 Introduction and Conclusion

The tests indicated in section 2.0 were performed on the product constructed as described in section 4.0. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test Method, a list of the actual Test Equipment Used, documentation Photos, Results and raw Data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested **complies** with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested. Intertek does not make any claims of compliance for samples or variants which were not tested.

2 Test Summary

Section	Test full name	Result
6	Radiated Emissions (Transmitters Idle) (ANSI C63.4:2014)	Pass
7	Radiated Spurious Emissions (Transmitters Active) (ANSI C63.10:2013, RSS-210 Issue 10)	Pass
8	Frequency Stability (ANSI C63.10:2013, RSS-210-Issue 10)	Pass
9	Occupied Bandwidth (ANSI C63.10:2013, RSS-Gen Issue 5)	Pass
10	Antenna Requirement (FCC Part 15.203, RSS-Gen Issue 5)	Pass



3 Client Information

This product was tested at the request of the following:

Client Information	
Client Name:	Stress Engineering Services, Inc.
Address:	7030 Stress Engineering Way Mason, OH 45040-7386 USA
Contact:	Joe Bullard
Email:	Joseph.bullard@stress.com
Manufacturer Information	
Manufacturer Name:	Stress Engineering Services, Inc.
Manufacturer Address:	7030 Stress Engineering Way Mason, OH 45040-7386 USA



4 Description of Equipment under Test and Variant Models

Equipment Under Test	
Product Name	iGrowth Generation 2 Kitchen Device
Model Number	3283
Serial Number	PT2.0-P00021
Test Start Date	10/22/2021
Test End Date	12/1/2021
Device Received Condition	Good
Test Sample Type	Production
Input Rating	7.5VDC
Description of Equipment Under Test (provided by client)	
2nd Generation kitchen towel consumption monitoring device for consumer research studies.	

4.1 Variant Models:

There were no variant models covered by this evaluation.



5 System Setup and Method


5.1 Method:

Configuration as required by ANSI C63.4:2014 and ANSI C63.10:2013.

No.	Descriptions of EUT Exercising
1	During the testing the iGrowth Generation 2 Kitchen Device was transmitting a 13.5MHz RFID signal.
2	Idle mode with the RFID radio not transmitting.

Cables					
Qty	Description	Length (m)	Shielding	Ferrites	Termination
1	USB	1	None	None	Test Laptop

5.2 EUT Block Diagram:





6 Radiated Emissions

6.1 Method

Tests are performed in accordance with ANSI C63.4:2014.

TEST SITE: 10m ALSE

Site Designation: 10m Chamber

Measurement Uncertainty

Measurement	Frequency Range	Expanded Uncertainty (k=2)	Ucisp
Radiated Emissions, 10m	30-1000 MHz	3.9dB	6.3 dB
Radiated Emissions, 3m	30-1000 MHz	4.0dB	6.3 dB
Radiated Emissions, 3m	1-6 GHz	4.7dB	5.2 dB
Radiated Emissions, 3m	6-15 GHz	4.7dB	5.5 dB
Radiated Emissions, 3m	15-18 GHz	4.7dB	5.5 dB
Radiated Emissions, 3m	18-40 GHz	4.7dB	5.5 dB

As shown in the table above our radiated emissions U_{lab} is less than the corresponding U_{CISPR} reference value in CISPR 16-4-2 Table 1, hence the compliance of the product is only based on the measured value, and no measurement uncertainty correction is required.



6.2 Sample Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows.

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 52.0 dB μ V
AF = 7.4 dB/m
CF = 1.6 dB
AG = 29.0 dB
FS = 32 dB μ V/m

To convert from dB μ V to μ V or mV the following was used:

$$UF = 10^{(NF / 20)} \text{ where } UF = \text{Net Reading in } \mu\text{V}$$

NF = Net Reading in dB μ V

Example:

$$FS = RA + AF + CF - AG = 52.0 + 7.4 + 1.6 - 29.0 = 32.0$$
$$UF = 10^{(32 \text{ dB}\mu\text{V} / 20)} = 39.8 \mu\text{V/m}$$

**6.3 Test Equipment Used:**


Description	Asset	Manufacturer	Model	Cal Date	Cal Due
EMI Test Receiver	8131	Rhode & Schwarz	ESW44	1/15/2020	1/15/2022
Bilog Antenna (30MHz-1GHz)	7085	SunAR	JB6	10/5/2021	10/5/2022
System Controller	4096	ETS Lindgren	2090	Verify at Time of Use	Verify at Time of Use
Coaxial Cable	2589			12/21/2020	12/21/2021
Coaxial Cable	2590			12/21/2020	12/21/2021
Coaxial Cable	3172			12/21/2020	12/21/2021
Coaxial Cable	3339			12/21/2020	12/21/2021
Preamplifier (30MHz-1GHz)	3919	Rohde & Schwarz	TS-PR3	12/21/2020	12/21/2021

6.4 Software Utilized:

Name	Manufacturer	Version
EMC32	Rohde & Schwarz	Version 9.15.02

6.5 Results:

The sample tested was found to Comply.

**6.6 Plots/Data: Radiated Emissions, 30MHz – 1GHz (Transmitter Idle)**

Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
30.040000	14.13	39.09	24.95	120.000	100.0	H	90.0	-5
85.902778	13.86	39.09	25.23	120.000	366.0	V	258.0	-15
174.358333	17.93	43.52	25.60	120.000	400.0	H	290.0	-11
175.452222	14.76	43.52	28.76	120.000	400.0	H	6.0	-11
176.424444	14.26	43.52	29.27	120.000	374.0	H	60.0	-11
177.412222	14.42	43.52	29.10	120.000	275.0	H	194.0	-11
484.734444	16.99	46.44	29.45	120.000	114.0	H	342.0	-1
544.110000	23.14	46.44	23.31	120.000	141.0	H	318.0	0
801.810556	23.74	46.44	22.70	120.000	146.0	H	310.0	5
954.645000	23.44	46.44	23.01	120.000	400.0	H	176.0	8

Test Personnel: Brian Lackey
 Supervising/Reviewing Engineer: N/A
 (Where Applicable) FCC Part 15B
 Product Standard: ICES-003 Issue 7
 Input Voltage: 7.5VDC
 Pretest Verification w / Ambient Signals or BB Source: Yes

Test Date: 10/22/2021
 Limit Applied: Class A
 Ambient Temperature: 21.1C
 Relative Humidity: 51.8%
 Atmospheric Pressure: 982.9mbar

Deviations, Additions, or Exclusions: None

Note: The limits used above are for FCC Part 15B and are more restrictive than the ICES-003 Issue 7 limits.



7 Radiated Emissions (RFID)

7.1 Method

Tests are performed in accordance with ANSI C63.10:2013.

TEST SITE: 10m ALSE

Site Designation: 10m Chamber

Measurement Uncertainty

Measurement	Frequency Range	Expanded Uncertainty (k=2)	U _{CISPR}
Radiated Emissions, 3m	0.09-30 MHz	3.2dB	6.3 dB
Radiated Emissions, 3m	30-1000 MHz	4.0dB	6.3 dB

As shown in the table above our radiated emissions U_{lab} is less than the corresponding U_{CISPR} reference value in CISPR 16-4-2 Table 1, hence the compliance of the product is only based on the measured value, and no measurement uncertainty correction is required.



7.2 Sample Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor to the Receiver Amplitude (including preamplifier) and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows.

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 52.0 dB μ V
AF = 7.4 dB/m
CF = 1.6 dB
AG = 29.0 dB
FS = 32 dB μ V/m

To convert from dB μ V to μ V or mV the following was used:

$$UF = 10^{(NF / 20)} \text{ where } UF = \text{Net Reading in } \mu\text{V}$$

NF = Net Reading in dB μ V

Example:

$$FS = RA + AF + CF - AG = 52.0 + 7.4 + 1.6 - 29.0 = 32.0$$
$$UF = 10^{(32 \text{ dB}\mu\text{V} / 20)} = 39.8 \mu\text{V/m}$$

**7.3 Test Equipment Used:**


Description	Asset	Manufacturer	Model	Cal Date	Cal Due
EMI Test Receiver	8131	Rhode & Schwarz	ESW44	1/15/2020	1/15/2022
Magnetic Loop Antenna	2366	ETS	6502	7/30/2021	7/30/2022
Bilog Antenna (30MHz-1GHz)	7085	SunAR	JB6	10/5/2021	10/5/2022
System Controller	4096	ETS Lindgren	2090	Verify at Time of Use	Verify at Time of Use
Coaxial Cable	2592			12/21/2020	12/21/2021
Coaxial Cable	2593			12/21/2020	12/21/2021
Coaxial Cable	3172			12/21/2020	12/21/2021
Coaxial Cable	3339			12/21/2020	12/21/2021
Preamplifier (30MHz-1GHz)	3919	Rohde & Schwarz	TS-PR3	12/21/2020	12/21/2021

7.4 Software Utilized:

Name	Manufacturer	Version
EMC32	Rohde & Schwarz	Version 9.15.02

7.5 Results:

The sample tested was found to Comply.


**7.6 Radiated Spurious Emissions (Below 30MHz)**

Frequency (MHz)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Bandwidth (kHz)	Azimuth (deg)	Corr. (dB/m)
0.646037	33.29	71.41	38.12	9.000	167.0	12
3.534463	16.75	69.50	52.75	9.000	310.0	12
13.499096	60.56	90.50	29.94	9.000	262.0	11
26.518963	4.60	69.50	64.90	9.000	197.0	10

Test Personnel: Brian Lackey
Supervising/Reviewing Engineer: _____
(Where Applicable) NA
Product Standard: FCC Part 15C
Input Voltage: RSS-210 Issue 10
Pretest Verification w / Ambient 7.5VDC
Signals or BB Source: Yes

Test Date: 11/4/2021
Limit Applied: FCC Part 15.225
Ambient Temperature: 17.6C
Relative Humidity: 35.4%
Atmospheric Pressure: 991.3mbar

Deviations, Additions, or Exclusions: None

**7.7 Radiated Spurious Emissions (30MHz – 1GHz)**

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
67.452778	10.93	40.00	29.07	120.000	100.0	V	235.0	14
94.451111	28.88	43.50	14.62	120.000	169.0	H	99.0	16
121.449444	24.70	43.50	18.80	120.000	100.0	V	38.0	16
145.753333	15.12	43.50	28.38	120.000	400.0	H	0.0	17
182.290000	31.19	43.50	12.31	120.000	104.0	H	0.0	19
195.546667	28.05	43.50	15.45	120.000	200.0	H	102.0	20
199.588333	21.18	43.50	22.32	120.000	95.0	H	88.0	20
486.007778	23.25	46.00	22.75	120.000	335.0	V	333.0	29
925.687222	31.00	46.00	15.00	120.000	326.0	V	302.0	36

Test Personnel: Brian Lackey
 Supervising/Reviewing Engineer: NA
 (Where Applicable) FCC Part 15C
 Product Standard: RSS-210 Issue 10
 Input Voltage: 7.5VDC
 Pretest Verification w / Ambient Signals or BB Source: Yes

Test Date: 11/4/2021
 Limit Applied: FCC Part 15.225
 Ambient Temperature: 17.6C
 Relative Humidity: 35.4%
 Atmospheric Pressure: 991.3mbar

Deviations, Additions, or Exclusions: None



8 Frequency Stability

8.1 Test Limits

FCC Part 15.225:

(e) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

RSS-210 Issue 9 § B.6:

Carrier frequency stability shall be maintained to $\pm 0.01\%$ (± 100 ppm).

8.2 Test Method

Tests are performed in accordance with ANSI C63.10:2013.

8.3 Test Equipment Used

Description	Asset	Manufacturer	Model	Cal Date	Cal Due
Spectrum Analyzer	3099	Rohde & Schwarz	FSP7	9/22/2021	9/22/2022
Environmental Chamber	2150	Thermotron	SE-600-3-3	2/24/2021	2/24/2022

8.4 Test Results

The sample tested was found to be **compliant**.



8.5 Test Data

Voltage %	Voltage (VDC)	Temp (°C)	Measured Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	Limit (%)
100%	6	-20	13,499,924	-106	0.0008%	0.01%
100%	6	-10	13,499,980	-50	0.0004%	0.01%
100%	6	0	13,500,014	-16	0.0001%	0.01%
100%	6	10	13,500,034	4	0.0000%	0.01%
100%	6	20	13,500,030	0	0.0000%	0.01%
100%	6	30	13,500,014	-16	0.0001%	0.01%
100%	6	40	13,499,974	-56	0.0004%	0.01%
100%	6	50	13,499,958	-72	0.0005%	0.01%
115%	6.9	20	13,500,030	0	0.0000%	0.01%
85%	5.1	20	13,500,030	0	0.0000%	0.01%

Test Personnel: Brian Lackey
Supervising/Reviewing Engineer:
(Where Applicable) NA
FCC Part 15.225
Product Standard: RSS-210 Issue 9
Input Voltage: 7.5VDC
Pretest Verification w / Ambient
Signals or BB Source: Yes

Test Date: 12/1/2021
Limit Applied: See Above
Ambient Temperature: 22.5C
Relative Humidity: 41.1%
Atmospheric Pressure: 984.6mbar

Deviations, Additions, or Exclusions: None



9 Occupied Bandwidth

9.1 Test Limits

15.215(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. In the case of intentional radiators operating under the provisions of subpart E, the emission bandwidth may span across multiple contiguous frequency bands identified in that subpart. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

9.2 Test Method

Tests are performed in accordance with ANSI C63.10:2013.

9.3 Test Equipment Used

Description	Asset	Manufacturer	Model	Cal Date	Cal Due
Spectrum Analyzer	3900	Rohde & Schwarz	ESU40	10/11/2021	10/11/2022



9.4 Test Results

The sample tested was found to be **compliant**. The 99% power bandwidth was measured as was the 20dB down bandwidth. The 20dB bandwidth was entirely within the transmit band 13.11MHz – 14.01MHz as required by FCC Part 15.215.



9.5 Test Data

RBW	VBW	99% OBW	20dB BW
20 kHz	50 kHz	490.4 kHz	435.9 kHz



99% Occupied Power Bandwidth (left) and 20dB Bandwidth (right)

Test Personnel: Brian Lackey
Supervising/Reviewing Engineer: NA
(Where Applicable)
Product Standard: RSS-210 Issue 9
Input Voltage: 7.5VDC
Pretest Verification w / Ambient
Signals or BB Source: Yes

Test Date: 12/1/2021
Limit Applied: See Above
Ambient Temperature: 22.5C
Relative Humidity: 41.1%
Atmospheric Pressure: 984.6mbar

Deviations, Additions, or Exclusions: None



10 Antenna Requirement

10.1 Test Limits

FCC Part 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-Gen Issue 5 § 6.8:

The applicant for equipment certification, as per RSP-100, must provide a list of all antenna types that may be used with the license-exempt transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna.

License-exempt transmitters that have received equipment certification may operate with different types of antennas. However, it is not permissible to exceed the maximum equivalent isotropically radiated power (e.i.r.p.) limits specified in the applicable standard (RSS) for the license-exempt apparatus.

Testing shall be performed using the highest gain antenna of each combination of license-exempt transmitter and antenna type, with the transmitter output power set at the maximum level. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

User manuals for transmitters equipped with detachable antennas shall also contain the following notice in a conspicuous location:

This radio transmitter (identify the device by certification number) has been approved by Industry Canada to operate with the antenna types listed below with the maximum permissible gain indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types approved for use with the transmitter, indicating the maximum permissible antenna gain (in dBi).

10.2 Test Results

The device was found to be **compliant**. The device uses a permanently attached antenna.

**11 Revision History**

Revision Level	Date	Report Number	Prepared By	Reviewed By	Notes
0	12/3/2021	104797984LEX-001	BZ	BCT	Original Issue