

TEST REPORT

Reference No..... : WTX20X10072537W-2
FCC ID : 2AGA6-OZA3PROS
Applicant : Shenzhen AngSi Technology Co., Ltd.
Address..... : 6/F, Block B, Ding Xin Science Park, Hong Lang North No.2 Road, Bao An District, ShenZhen PRC
Product Name : Portable Bluetooth Speaker
Test Model. : OontZ Angle 3 PRO
Standards : FCC Part 15.247
Date of Receipt sample : Oct.09, 2020
Date of Test..... : Oct.09, 2020 to Nov.05, 2020
Date of Issue : Nov.05, 2020
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308

Fax.: +86-755-33663309

Tested by:

Jack Huang

Jack Huang/ Project Engineer

Reviewed By:

Lion Cai

Lion Cai / RF Manager

Approved & Authorized By:

Silin Chen

Silin Chen / Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY.....	5
1.5 EUT SETUP AND TEST MODE.....	6
1.6 MEASUREMENT UNCERTAINTY.....	7
1.7 TEST EQUIPMENT LIST AND DETAILS.....	8
2. SUMMARY OF TEST RESULTS	10
3. ANTENNA REQUIREMENT	11
3.1 STANDARD APPLICABLE.....	11
3.2 EVALUATION INFORMATION.....	11
4. POWER SPECTRAL DENSITY	12
4.1 STANDARD APPLICABLE.....	12
4.2 TEST SETUP BLOCK DIAGRAM.....	12
4.3 TEST PROCEDURE.....	12
4.4 SUMMARY OF TEST RESULTS/PLOTS.....	12
5. DTS BANDWIDTH	13
5.1 STANDARD APPLICABLE.....	13
5.2 TEST SETUP BLOCK DIAGRAM.....	13
5.3 TEST PROCEDURE.....	13
5.4 SUMMARY OF TEST RESULTS/PLOTS.....	13
6. RF OUTPUT POWER	14
6.1 STANDARD APPLICABLE.....	14
6.2 TEST SETUP BLOCK DIAGRAM.....	14
6.3 TEST PROCEDURE.....	14
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	14
7. FIELD STRENGTH OF SPURIOUS EMISSIONS	15
7.1 STANDARD APPLICABLE.....	15
7.2 TEST PROCEDURE.....	15
7.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	17
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	17
8. OUT OF BAND EMISSIONS	32
8.1 STANDARD APPLICABLE.....	32
8.2 TEST PROCEDURE.....	32
8.3 SUMMARY OF TEST RESULTS/PLOTS.....	33
9. CONDUCTED EMISSIONS	38
9.1 TEST PROCEDURE.....	38
9.2 BASIC TEST SETUP BLOCK DIAGRAM.....	38
9.3 TEST RECEIVER SETUP.....	38
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	38
APPENDIX SUMMARY	41
APPENDIX A	42
APPENDIX B	45
APPENDIX C	48
APPENDIX D	51
APPENDIX PHOTOGRAPHS	55

Report version

Version No.	Date of issue	Description
Rev.00	Nov.05, 2020	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen AngSi Technology Co., Ltd.
 Address of applicant: 6/F, Block B, Ding Xin Science Park, Hong Lang North No.2 Road, Bao An District, ShenZhen PRC

Manufacturer: Shenzhen AngSi Technology Co., Ltd.
 Address of manufacturer: 6/F, Block B, Ding Xin Science Park, Hong Lang North No.2 Road, Bao An District, ShenZhen PRC

General Description of EUT	
Product Name:	Portable Bluetooth Speaker
Trade Name	OontZ
Model No.:	OontZ Angle 3 PRO
Adding Model(s):	/
Rated Voltage:	Battery DC 7.2V and DC 5V, 3A
Battery Capacity:	2500mAh
Power Adapter:	/
Software Version:	V1.0
Hardware Version:	BS2043-main-01A1
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Bluetooth Version:	V5.0 (BLE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	5.87dBm (Conducted)
Data Rate:	1/2Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	3.91dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the Fcc rules.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low	2402MHz
TM2	Middle	2440MHz
TM3	High	2480MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	45~55 %
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Type-c Cable	1.30	Unshielded	Without Ferrite
AUX IN Cable	0.80	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Adapter	/	KA1517-0502000CNU	/
Mobile phone	HUAWEI	VOG-AL00	/
Notebook	Lenovo	E445	EB12648265
U Disk	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-26GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2020-04-28	2021-04-27
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2020-04-28	2021-04-27
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2020-04-28	2021-04-27
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2020-04-28	2021-04-27
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2020-04-28	2021-04-27
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2020-04-28	2021-04-27
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2020-04-28	2021-04-27
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2020-04-28	2021-04-27
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2020-04-28	2021-04-27
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2020-04-28	2021-04-27
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2020-04-28	2021-04-27
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2020-04-28	2021-04-27
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2020-04-28	2021-04-27
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2020-04-28	2021-04-27
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2020-03-17	2021-03-16
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2020-03-17	2021-03-16
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2020-03-17	2021-03-16
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2020-03-17	2021-03-16
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information


This product has an Integral antenna, fulfill the requirement of this section.

4. Power Spectral Density

4.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.2 Test Setup Block Diagram



4.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.2, the test method of power spectral density as below:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.4 Summary of Test Results/Plots


Please refer to Appendix A

5. DTS Bandwidth

5.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.4 Summary of Test Results/Plots


Please refer to Appendix B

6. RF Output Power

6.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

6.2 Test Setup Block Diagram



6.3 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.1.1 and ANSI C63.10-2013 Subclause 11.9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW \geq DTS bandwidth.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

6.4 Summary of Test Results/Plots

Please refer to Appendix C

7. Field Strength of Spurious Emissions

7.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


7.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.


The test setup for emission measurement below 30MHz..



The test setup for emission measurement from 30 MHz to 1 GHz..



The test setup for emission measurement above 1 GHz..



Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

7.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

7.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


- Spurious Emissions Below 1GHz
- 1M

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	43.6584	34.73	-11.84	22.89	40.00	-17.11	-	-	peak
2	100.9339	33.41	-13.32	20.09	43.50	-23.41	-	-	peak
3	368.1116	34.21	-7.26	26.95	46.00	-19.05	-	-	peak
4	878.3214	30.67	0.67	31.34	46.00	-14.66	-	-	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	43.8119	34.85	-11.84	23.01	40.00	-16.99	-	-	peak
2	97.7983	33.66	-13.69	19.97	43.50	-23.53	-	-	peak
3	372.0045	30.28	-7.22	23.06	46.00	-22.94	-	-	peak
4	912.8620	30.04	1.71	31.75	46.00	-14.25	-	-	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	45.3755	36.41	-11.78	24.63	40.00	-15.37	-	-	peak
2	107.5101	32.72	-13.32	19.40	43.50	-24.10	-	-	peak
3	334.8589	35.51	-8.36	27.15	46.00	-18.85	-	-	peak
4	909.6667	29.91	1.67	31.58	46.00	-14.42	-	-	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	45.0583	34.26	-11.80	22.46	40.00	-17.54	-	-	peak
2	100.5806	33.47	-13.33	20.14	43.50	-23.36	-	-	peak
3	338.4001	30.75	-8.14	22.61	46.00	-23.39	-	-	peak
4	869.1302	30.32	0.49	30.81	46.00	-15.19	-	-	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	50.4089	35.01	-11.65	23.36	40.00	-16.64	-	-	peak
2	105.2718	33.36	-13.32	20.04	43.50	-23.46	-	-	peak
3	357.9287	34.34	-7.36	26.98	46.00	-19.02	-	-	peak
4	884.5029	30.43	0.92	31.35	46.00	-14.65	-	-	peak


Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	43.2017	35.01	-11.86	23.15	40.00	-16.85	-	-	peak
2	103.8054	33.69	-13.32	20.37	43.50	-23.13	-	-	peak
3	361.7139	30.96	-7.32	23.64	46.00	-22.36	-	-	peak
4	578.6698	29.28	-2.47	26.81	46.00	-19.19	-	-	peak


➤ 2M

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	45.3755	34.82	-11.78	23.04	40.00	-16.96	-	-	peak
2	99.8777	32.87	-13.34	19.53	43.50	-23.97	-	-	peak
3	351.7079	34.58	-7.41	27.17	46.00	-18.83	-	-	peak
4	884.5029	29.46	0.92	30.38	46.00	-15.62	-	-	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	50.5860	35.23	-11.69	23.54	40.00	-16.46	-	-	peak
2	84.1100	36.85	-16.17	20.68	40.00	-19.32	-	-	peak
3	365.5391	30.92	-7.29	23.63	46.00	-22.37	-	-	peak
4	968.9338	29.86	1.45	31.31	54.00	-22.69	-	-	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	45.8553	34.62	-11.75	22.87	40.00	-17.13	-	-	peak
2	102.7192	33.15	-13.32	19.83	43.50	-23.67	-	-	peak
3	357.9287	34.24	-7.36	26.88	46.00	-19.12	-	-	peak
4	739.6605	30.49	-1.17	29.32	46.00	-16.68	-	-	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	44.2752	34.43	-11.83	22.60	40.00	-17.40	-	-	peak
2	104.1701	32.94	-13.31	19.63	43.50	-23.87	-	-	peak
3	406.0880	30.74	-6.31	24.43	46.00	-21.57	-	-	peak
4	887.6099	29.98	1.05	31.03	46.00	-14.97	-	-	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	51.8430	34.67	-12.04	22.63	40.00	-17.37	-	-	peak
2	99.1797	33.30	-13.45	19.85	43.50	-23.65	-	-	peak
3	360.4476	34.14	-7.34	26.80	46.00	-19.20	-	-	peak
4	903.3094	29.90	1.60	31.50	46.00	-14.50	-	-	peak

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	46.3402	35.58	-11.73	23.85	40.00	-16.15	-	-	peak
2	100.5806	32.73	-13.33	19.40	43.50	-24.10	-	-	peak
3	364.2595	31.50	-7.29	24.21	46.00	-21.79	-	-	peak
4	866.0879	30.19	0.45	30.64	46.00	-15.36	-	-	peak

Remark: '- 'Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

➤ Spurious Emissions Above 1GHz

➤ 1M

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2402MHz							
4804.000	53.15	-4.52	48.63	74.00	-25.37	H	PK
7260.000	49.01	-2.18	46.83	74.00	-27.17	H	PK
9608.000	49.69	1.73	51.42	74.00	-22.58	H	PK
4804.000	50.67	-4.52	46.15	74.00	-27.85	V	PK
7206.000	49.98	-2.20	47.78	74.00	-26.22	V	PK
9608.000	49.35	1.73	51.08	74.00	-22.92	V	PK
Middle Channel-2440MHz							
4883.019	39.03	-4.47	34.56	54.00	-19.44	H	AV
4883.519	60.07	-4.47	55.60	74.00	-18.40	H	PK
7230.000	49.97	-2.20	47.77	74.00	-26.23	H	PK
9760.000	49.61	1.95	51.56	74.00	-22.44	H	PK
4880.000	52.92	-4.47	48.45	74.00	-25.55	V	PK
7320.000	48.49	-2.17	46.32	74.00	-27.68	V	PK
9760.000	49.52	1.95	51.47	74.00	-22.53	V	PK
High Channel-2480MHz							
4958.678	62.89	-4.41	58.48	74.00	-15.52	H	PK
4959.178	55.58	-4.41	51.17	54.00	-2.83	H	AV
7440.000	50.76	-2.14	48.62	74.00	-25.38	H	PK
9919.908	46.54	2.19	48.73	54.00	-5.27	H	AV
9920.000	52.35	2.19	54.54	74.00	-19.46	H	PK
4958.678	54.47	-4.41	50.06	74.00	-23.94	V	PK
7440.000	48.87	-2.14	46.73	74.00	-27.27	V	PK
9917.140	47.48	2.18	49.66	54.00	-4.34	V	PK
9920.000	52.53	2.19	54.72	74.00	-19.28	V	PK

➤ 2M

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz							
4804.000	52.82	-4.52	48.30	74.00	-25.70	H	PK
7206.000	51.21	-2.20	49.01	74.00	-24.99	H	PK
9608.000	49.16	1.73	50.89	74.00	-23.11	H	PK
4804.000	50.76	-4.52	46.24	74.00	-27.76	V	PK
7206.000	50.42	-2.20	48.22	74.00	-25.78	V	PK
9608.000	48.93	1.73	50.66	74.00	-23.34	V	PK
Middle Channel-2440MHz							
4883.019	39.27	-4.47	34.80	54.00	-19.20	H	AV
4883.519	59.87	-4.47	55.40	74.00	-18.60	H	PK
7320.000	48.93	-2.17	46.76	74.00	-27.24	H	PK
9760.000	49.99	1.95	51.94	74.00	-22.06	H	PK
4880.000	52.42	-4.47	47.95	74.00	-26.05	V	PK
7320.000	48.66	-2.17	46.49	74.00	-27.51	V	PK
9760.000	49.30	1.95	51.25	74.00	-22.75	V	PK
High Channel-2480MHz							
4958.678	62.64	-4.41	58.23	74.00	-15.77	H	PK
4959.178	55.11	-4.41	50.70	54.00	-3.30	H	AV
7440.000	50.53	-2.14	48.39	74.00	-25.61	H	PK
9920.000	51.04	2.19	53.23	74.00	-20.77	H	PK
4958.678	54.01	-4.41	49.60	74.00	-24.40	V	PK
7440.000	49.82	-2.14	47.68	74.00	-26.32	V	PK
9935.053	51.41	2.21	53.62	74.00	-20.38	V	PK

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. Out of Band Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement

KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

RBW as a function of frequency

Frequency	RBW
9kHz to 150kHz	200Hz to 300Hz
0.15MHz to 30MHz	9kHz to 10kHz
30MHz to 1000MHz	100kHz to 120kHz
>1000MHz	1MHz


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

8.3 Summary of Test Results/Plots


- Radiated test
- 1M

Test Channel	Low	Polarity:	Horizontal (worst case)
--------------	-----	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.16	-9.66	31.50	54.00	-22.50	Average Detector
	2310.000	54.53	-9.66	44.87	74.00	-29.13	Peak Detector
2	2390.000	42.20	-9.50	32.70	54.00	-21.30	Average Detector
	2390.000	55.20	-9.50	45.70	74.00	-28.30	Peak Detector
3	2402.000	100.62	-9.47	91.15	/	/	Average Detector
	2402.300	104.52	-9.47	95.05	/	/	Peak Detector


Test Channel	High	Polarity:	Horizontal (worst case)
--------------	------	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.975	104.30	-9.32	94.98	/	/	Average Detector
	2480.200	108.15	-9.32	98.83	/	/	Peak Detector
2	2483.500	61.44	-9.31	52.13	54.00	-1.87	Average Detector
	2483.500	70.35	-9.31	61.04	74.00	-12.96	Peak Detector
3	2500.000	42.23	-9.28	32.95	54.00	-21.05	Average Detector
	2500.000	55.69	-9.28	46.41	74.00	-27.59	Peak Detector


➤ 2M

Test Channel	Low	Polarity:	Horizontal (worst case)
--------------	-----	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	40.89	-9.66	31.23	54.00	-22.77	Average Detector
	2310.000	51.66	-9.66	42.00	74.00	-32.00	Peak Detector
2	2390.000	41.95	-9.50	32.45	54.00	-21.55	Average Detector
	2390.000	54.07	-9.50	44.57	74.00	-29.43	Peak Detector
3	2402.000	96.29	-9.47	86.82	/	/	Average Detector
	2402.500	103.27	-9.47	93.80	/	/	Peak Detector

Test Channel	High	Polarity:	Horizontal (worst case)
--------------	------	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.975	98.90	-9.32	89.58	/	/	Average Detector
	2480.450	106.32	-9.32	97.00	/	/	Peak Detector
2	2483.500	61.19	-9.31	51.88	54.00	-2.12	Average Detector
	2483.500	71.02	-9.31	61.71	74.00	-12.29	Peak Detector
3	2500.000	42.28	-9.28	33.00	54.00	-21.00	Average Detector
	2500.000	55.43	-9.28	46.15	74.00	-27.85	Peak Detector

➤ Conducted test

Please refer to Appendix D

9. Conducted Emissions


9.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

9.2 Basic Test Setup Block Diagram




9.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150 kHz
Stop Frequency	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal


9.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.8020	37.80	10.18	47.98	56.00	-8.02	QP
2	0.9300	19.36	10.22	29.58	46.00	-16.42	AVG
3	1.5339	36.82	10.23	47.05	56.00	-8.95	QP
4	1.5540	18.00	10.24	28.24	46.00	-17.76	AVG
5	13.5900	22.72	10.50	33.22	50.00	-16.78	AVG
6	15.0380	41.37	10.58	51.95	60.00	-8.05	QP

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.9540	35.82	10.21	46.03	56.00	-9.97	QP
2	0.9540	17.27	10.21	27.48	46.00	-18.52	AVG
3	1.5500	15.34	10.24	25.58	46.00	-20.42	AVG
4	1.5980	31.92	10.24	42.16	56.00	-13.84	QP
5	14.0180	20.23	10.52	30.75	50.00	-19.25	AVG
6*	16.1259	39.51	10.58	50.09	60.00	-9.91	QP




APPENDIX SUMMARY




Project No.	WTX20X10072537W	Test Engineer	Moon
Start date	2020/10/12	Finish date	2020/10/12
Temperature	24.7°C	Humidity	48%

APPENDIX	Description of Test Item	Result
A	Power Spectral Density	Compliant
B	DTS Bandwidth	Compliant
C	RF Output Power	Compliant
D	Conducted Out of Band Emissions	Compliant

APPENDIX A


Power Spectral Density			
Test Mode	Test Channel	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
1MGFSK(BLE)	Low	-10.28	8
	Middle	-10.17	8
	High	-10.18	8
2MGFSK(BLE)	Low	-13.74	8
	Middle	-13.71	8
	High	-13.53	8




<p>1MLow</p>	 <p>Date: 12.OCT.2020 15:38:54</p>
<p>1MMiddle</p>	 <p>Date: 12.OCT.2020 15:39:38</p>
<p>1MHigh</p>	 <p>Date: 12.OCT.2020 15:40:56</p>

<p>2MLow</p>	 <p>Ref 20 dBm +Att 30 dB RBW 3 kHz Marker 1 [T1] -13.74 dBm V BW 10 kHz SWT 340 ms 2.401907000 GHz</p> <p>20 Offset 1 dB</p> <p>Center 2.402 GHz 300 kHz/ Span 3 MHz</p> <p>Date: 12.OCT.2020 15:51:53</p>
<p>2MMiddle</p>	 <p>Ref 20 dBm +Att 30 dB RBW 3 kHz Marker 1 [T1] -13.71 dBm V BW 10 kHz SWT 340 ms 2.439913000 GHz</p> <p>20 Offset 1 dB</p> <p>Center 2.44 GHz 300 kHz/ Span 3 MHz</p> <p>Date: 12.OCT.2020 15:52:16</p>
<p>2MHigh</p>	 <p>Ref 20 dBm +Att 30 dB RBW 3 kHz Marker 1 [T1] -13.53 dBm V BW 10 kHz SWT 340 ms 2.479907000 GHz</p> <p>20 Offset 1 dB</p> <p>Center 2.48 GHz 300 kHz/ Span 3 MHz</p> <p>Date: 12.OCT.2020 15:52:47</p>

APPENDIX B




Test Mode	Test Channel	6 dB Bandwidth kHz	Limit kHz
1MGFSK(BLE)	Low	711	≥ 500
	Middle	711	≥ 500
	High	708	≥ 500
2MGFSK(BLE)	Low	1254	≥ 500
	Middle	1254	≥ 500
	High	1254	≥ 500






<p>2MLow</p>	 <p>MARKER 1 2.40149 GHz 3.72 dBm Ref: 20 dBm ATT: 30 dB SWT: 5 ms 2.40149000 GHz</p> <p>ndB [T1] 6.00 dB BW 1.25400000 MHz Temp 1 [T1] ndB</p> <p>2.40133400 GHz -2.25 dBm 2.40255800 GHz -2.33 dBm</p> <p>Center 2.402 GHz 600 kHz/ Span 6 MHz</p> <p>Date: 12.OCT.2020 15:59:11</p>
<p>2MMiddle</p>	 <p>MARKER 1 2.43949 GHz 3.95 dBm Ref: 20 dBm ATT: 30 dB SWT: 5 ms 2.43949000 GHz</p> <p>ndB [T1] 6.00 dB BW 1.25400000 MHz Temp 1 [T1] ndB</p> <p>2.43933400 GHz -2.10 dBm 2.44058800 GHz -1.94 dBm</p> <p>Center 2.44 GHz 600 kHz/ Span 6 MHz</p> <p>Date: 12.OCT.2020 16:00:25</p>
<p>2MHigh</p>	 <p>MARKER 1 2.47949 GHz 4.18 dBm Ref: 20 dBm ATT: 30 dB SWT: 5 ms 2.47949000 GHz</p> <p>ndB [T1] 6.00 dB BW 1.25400000 MHz Temp 1 [T1] ndB</p> <p>2.47932800 GHz -1.89 dBm 2.48058200 GHz -1.70 dBm</p> <p>Center 2.48 GHz 600 kHz/ Span 6 MHz</p> <p>Date: 12.OCT.2020 16:01:07</p>

APPENDIX C




RF Output Power			
Test Mode	Test Channel	Reading dBm	Limit dBm
1MGFSK(BLE)	Low	4.85	30.00
	Middle	4.90	30.00
	High	5.16	30.00
2MGFSK(BLE)	Low	5.56	30.00
	Middle	5.72	30.00
	High	5.87	30.00


<p>1MLow</p>	 <p>Date: 12.OCT.2020 15:29:14</p>
<p>1MMiddle</p>	 <p>Date: 12.OCT.2020 15:29:58</p>
<p>1MHigh</p>	 <p>Date: 12.OCT.2020 15:30:26</p>

<p>2MLow</p>	 <p>Ref 20 dBm Att 30 dB RBW 3 MHz Marker 1 [F1] 5.56 dBm VBW 10 MHz SWT 2.5 ms 2.401900000 GHz</p> <p>20 Offset 1 dB</p> <p>Center 2.402 GHz 1 MHz/ Span 10 MHz</p> <p>Date: 3.NOV.2020 19:06:40</p>
<p>2MMiddle</p>	 <p>Ref 20 dBm Att 30 dB RBW 3 MHz Marker 1 [F1] 5.72 dBm VBW 10 MHz SWT 2.5 ms 2.440080000 GHz</p> <p>20 Offset 1 dB</p> <p>Center 2.44 GHz 1 MHz/ Span 10 MHz</p> <p>Date: 3.NOV.2020 19:07:09</p>
<p>2MHigh</p>	 <p>Ref 20 dBm Att 30 dB RBW 3 MHz Marker 1 [F1] 5.87 dBm VBW 10 MHz SWT 2.5 ms 2.479880000 GHz</p> <p>20 Offset 1 dB</p> <p>Center 2.48 GHz 1 MHz/ Span 10 MHz</p> <p>Date: 3.NOV.2020 19:07:26</p>


APPENDIX D

Conducted Out of Band Emissions


<p>1MLow</p>	 <p>Date: 12.OCT.2020 16:21:22</p>
	 <p>Date: 12.OCT.2020 16:22:04</p>
<p>1MMiddle</p>	 <p>Date: 12.OCT.2020 16:24:41</p>



2MLow




Date: 12.OCT.2020 16:28:43




Date: 12.OCT.2020 16:29:04

2MMiddle



Date: 12.OCT.2020 16:30:55



2MHigh

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

******* END OF REPORT *******