

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594 Report No.: SZEM150900609003

Email: ee.shenzhen@sgs.com Page: 1 of 52

FCC REPORT

Application No: SZEM1509006090CR

Applicant: New Audio LLC

Manufacturer/ Factory: Acoustic innovation(HuiZhou) Co,Ltd

Product Name: MW60 Bluetooth Headphone

Model No.(EUT): MW60

Trade Mark: Master & Dynamic PCC ID: 2AGA7MW60

Standards: 47 CFR Part 15, Subpart C (2014)

Date of Receipt: 2015-09-30

Date of Test: 2015-10-12 to 2015-10-27

Date of Issue: 2015-11-04

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM150900609003

Page: 2 of 52

2 Version

Revision Record						
Version Chapter Date Modifier Remark						
00		2015-11-03		Original		

Authorized for issue by:		
Tested By	Brir Chen	2015-10-27
	(Bill Chen) /Project Engineer	Date
Prepared By	Jarole Chen	2015-11-03
	(Jade Chen) /Clerk	Date
Checked By	Eric Fu	2015-11-03
	(Eric Fu) /Reviewer	Date



Report No.: SZEM150900609003

Page: 3 of 52

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2009	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2009	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2009	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2009	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2009	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2009	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2009	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS



Report No.: SZEM150900609003

Page: 4 of 52

4 Contents

		Paç	ge
1	COVER	R PAGE	1
2	VERSI	ON	2
3	_	SUMMARY	
_			_
4		ENTS	
5	GENER	RAL INFORMATION	5
		IENT INFORMATION	
	-	NERAL DESCRIPTION OF EUT	_
		ST ENVIRONMENT	
		SCRIPTION OF SUPPORT UNITS	
		ST LOCATIONST FACILITY	
		VIATION FROM STANDARDS	_
		NORMALITIES FROM STANDARD CONDITIONS	
		HER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10 Eq	UIPMENT LIST	9
6	TEST F	RESULTS AND MEASUREMENT DATA	12
	6.1 An	TENNA REQUIREMENT	12
		NDUCTED EMISSIONS	
		NDUCTED PEAK OUTPUT POWER	
		B OCCUPY BANDWIDTHwere Spectral Density	
		ND-EDGE FOR RF CONDUCTED EMISSIONS	
		URIOUS RF CONDUCTED EMISSIONS	
		DIATED SPURIOUS EMISSION	38
	6.8.1	Spurious Emissions	
	6.9 RE	STRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	45
7	PHOTO	OGRAPHS - EUT TEST SETUP	51
	7.1 Co	NDUCTED EMISSION	51
		DIATED EMISSION	
	7.3 RAI	DIATED SPURIOUS EMISSION	52
8	PHOTO	OGRAPHS - EUT CONSTRUCTIONAL DETAILS	52



Report No.: SZEM150900609003

Page: 5 of 52

5 General Information

5.1 Client Information

Applicant:	New Audio LLC		
Address of Applicant:	132 W. 31st 7th Floor New York, NY 10001		
Manufacturer:	Acoustic innovation(HuiZhou) Co,Ltd		
Address of Manufacturer:	Xiangshuihe Industrial Area, Dayawan Development District, HuiZhou City, Guangdong Province, China.		
Factory:	Acoustic innovation(HuiZhou) Co,Ltd		
Address of Factory:	Xiangshuihe Industrial Area, Dayawan Development District, HuiZhou City, Guangdong Province, China.		

5.2 General Description of EUT

Product Name:	MW60 Bluetooth Headphone
Model No.:	MW60
Trade Mark:	Master & Dynamic
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	BT 4.0 dual mode
	This report is for BLE mode
Modulation Type:	GFSK
Number of Channel:	40
Sample Type:	Portable production
Antenna Type:	Integral
Antenna Gain:	2.0dBi
Power Supply:	DC3.7V (1 x 3.7V Rechargeable battery) 300mAh Battery: Charge by DC 5V



Report No.: SZEM150900609003

Page: 6 of 52

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH0)	2402MHz
The middle channel (CH19)	2440MHz
The highest channel (CH39)	2480MHz



Report No.: SZEM150900609003

Page: 7 of 52

5.3 Test Environment

Operating Environment:			
Temperature:	25.0 °C		
Humidity:	53 % RH		
Atmospheric Pressure:	1010mbar		

5.4 Description of Support Units

The EUT has been tested independent unit.

5.5 Test Location

518057.

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab, No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM150900609003

Page: 8 of 52

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC - Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

The 3m Semi-anechoic chambers and the 10m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2, 4620C-3.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



Report No.: SZEM150900609003

Page: 9 of 52

5.10 Equipment List

	Conducted Emission								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date			
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2015-05-13	2016-05-13			
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2015-10-09	2016-10-09			
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2015-05-13	2016-05-13			
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLIS N-T8-02	SEL0162	2015-08-30	2016-08-30			
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLIS N-T4-02	SEL0163	2015-08-30	2016-08-30			
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLIS N-T2-02	SEL0164	2015-08-30	2016-08-30			
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2015-05-13	2016-05-13			
8	Coaxial Cable	SGS	N/A	SEL0025	2015-05-13	2016-05-13			
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-09	2016-10-09			
10	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2015-10-24	2016-10-24			
11	Barometer	Chang Chun	DYM3	SEL0088	2015-05-13	2016-05-13			



Report No.: SZEM150900609003

Page: 10 of 52

	RE in Chamber							
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date		
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-05-13	2016-05-13		
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16	2016-09-16		
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A		
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2014-11-15	2017-11-15		
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-17	2016-10-17		
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2014-11-24	2017-11-24		
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-13	2016-05-13		
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-17	2016-10-17		
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-13	2016-05-13		
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-13	2016-05-13		
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-13	2016-05-13		
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13		
13	Band filter	Amindeon	82346	SEL0094	2015-05-13	2016-05-13		
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-13	2016-05-13		
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-09	2016-10-09		
16	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2015-10-24	2016-10-24		
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-13	2016-05-13		
18	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-05-13	2016-05-13		



Report No.: SZEM150900609003

Page: 11 of 52

	RF connected test							
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)		
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-09	2016-10-09		
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24	2016-10-24		
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-17	2016-10-17		
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13		
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-13	2016-05-13		
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-13	2016-05-13		
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-04-25	2016-04-25		
8	POWER METER	R & S	NRVS	SEL0144	2015-10-09	2016-10-09		
9	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-04-25	2016-04-25		





Report No.: SZEM150900609003

Page: 12 of 52

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement:

47 CFR Part 15C Section 15.203 /247(c)


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.0dBi.



Report No.: SZEM150900609003

Page: 13 of 52

6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207			
Test Method:	ANSI C63.10: 2009			
Test Frequency Range:	150kHz to 30MHz			
Limit:		Limit (dBuV)		
	Frequency range (MHz)	Quasi-peak	Average	
	0.15-0.5	66 to 56*	56 to 46*	
	0.5-5	56	46	
	5-30	60	50	
	* Decreases with the logarithm	n of the frequency.		
Test Procedure:	 * Decreases with the logarithm of the frequency. 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane. 4) The test was performed with a vertical ground reference plane. The rear or the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to 		through a LISN 1 (Line is a 50Ω/50μH + 5Ω linear units of the EUT were d to the ground reference unit being measured. A multiple power cables to a not exceeded. Ilic table 0.8m above the trangement, the EUT was erence plane. The rear of and reference plane. The to the horizontal ground from the boundary of the erence plane for LISNs his distance was between All other units of the EUT m the LISN 2.	
Test Setup:	Shielding Room EUT AC Mains LISN1	AE LISN2 AC Mai Ground Reference Plane	Test Receiver	



Report No.: SZEM150900609003

Page: 14 of 52

Test Mode:	Transmitting with GFSK modulation. Charge +Transmitting mode.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass



Report No.: SZEM150900609003


Page: 15 of 52

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:



Site : Shielding Room

Condition: 47 CFR PART 15 C AV CE Line

Job No. : 6090CR

Test Mode: Charge + TX mode


		Cable	LISN	Read		Limit	0ver	
	Freq	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB		dBuV			dB	
	PHIZ	ub	ub	ubuv	ubuv	abav	ub	
1	0.16	0.07	9.82	32.02	41.91	55.30	-13.39	Peak
2	1.05	0.03	9.89	30.19	40.11	46.00	-5.89	Peak
3	3.99	0.10	10.08	27.22	37.40	46.00	-8.60	Peak
4	10.73	0.59	10.15	27.91	38.65	50.00	-11.35	Peak
5	15.47	0.98	10.17	29.01	40.16	50.00	-9.84	Peak
6	20.16	1.53	10.28	29.01	40.82	50.00	-9.18	Peak



Report No.: SZEM150900609003

Page: 16 of 52

Neutral line:



Site : Shielding Room

Condition: 47 CFR PART 15 C AV CE Neutral

Job No. : 6090CR

Test Mode: Charge + TX mode

		Cable	LISN	Read		Limit	0ver	
	Freq	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.17	0.07	9.82	34.08	43.97	54.72	-10.75	Peak
2	0.56	0.05	9.90	30.87	40.82	46.00	-5.18	Peak
3	1.89	0.04	10.11	29.02	39.17	46.00	-6.83	Peak
4	2.47	0.06	10.12	28.84	39.02	46.00	-6.98	Peak
5	7.45	0.28	10.13	26.50	36.91	50.00	-13.09	Peak
6	24.66	1.86	10.03	32.04	43.93	50.00	-6.07	Peak

Notes:


- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM150900609003

Page: 17 of 52

6.3 Conducted Peak Output Power



Measurement Data

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-3.75	30.00	Pass
Middle	-3.82	30.00	Pass
Highest	-3.95	30.00	Pass




Report No.: SZEM150900609003


Page: 18 of 52

Test plot as follows:

Test mode: GFSK Test channel: Lowest










Report No.: SZEM150900609003

Page: 19 of 52








Report No.: SZEM150900609003

Page: 20 of 52

6.4 6dB Occupy Bandwidth



Measurement Data

	GFSK mode		
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	0.690	≥500	Pass
Middle	0.693	≥500	Pass
Highest	0.699	≥500	Pass




Report No.: SZEM150900609003

Page: 21 of 52

Test plot as follows:

Test mode: GFSK Test channel: Lowest










Report No.: SZEM150900609003

Page: 22 of 52








Report No.: SZEM150900609003

Page: 23 of 52

6.5 Power Spectral Density




	GFSK mode		
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-19.92	≤8.00	Pass
Middle	-19.91	≤8.00	Pass
Highest	-20.11	≤8.00	Pass




Report No.: SZEM150900609003

Page: 24 of 52

Test plot as follows:










Report No.: SZEM150900609003

Page: 25 of 52

Test mode: GFSK Test channel: Highest






Report No.: SZEM150900609003

Page: 26 of 52

6.6 Band-edge for RF Conducted Emissions






Report No.: SZEM150900609003


Page: 27 of 52

Test plot as follows:

Test mode: GFSK Test channel: Lowest









Report No.: SZEM150900609003

Page: 28 of 52

6.7 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)		
Test Method:	ANSI C63.10 2009		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table		
	Ground Reference Plane		
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.		
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.		
Test Mode:	Transmitting with GFSK modulation.		
Instruments Used:	Refer to section 5.10 for details.		
Test Results:	Pass		





Report No.: SZEM150900609003

Page: 29 of 52

Test plot as follows:


Test mode: GFSK Test channel: Lowest









Report No.: SZEM150900609003








Report No.: SZEM150900609003











Report No.: SZEM150900609003

Page: 32 of 52


Test mode: GFSK Test channel: Middle









Report No.: SZEM150900609003








Report No.: SZEM150900609003










Report No.: SZEM150900609003

Page: 35 of 52












Report No.: SZEM150900609003








Report No.: SZEM150900609003





Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.



Report No.: SZEM150900609003

Page: 38 of 52

6.8 Radiated Spurious Emission


6.8.1 Spurious Emiss	rione								
•									
Test Requirement:		47 CFR Part 15C Section 15.209 and 15.205							
Test Method:	ANSI C63.10 2009								
Test Site:	Measurement Distance	: 3m	n (Semi-Anech	noic Cham	ber)				
Receiver Setup:	Frequency		Detector	RBW	VB	W	Remark		
	0.009MHz-0.090MH	Z	Peak	10kHz	30k	Ήz	Peak		
	0.009MHz-0.090MH	Z	Average	10kHz	30k	Ήz	Average		
	0.090MHz-0.110MH	Z	Quasi-peak	10kHz	2 30k	Ήz	Quasi-peak		
	0.110MHz-0.490MH	Z	Peak	10kHz	2 30k	Ήz	Peak		
	0.110MHz-0.490MH	Z	Average	10kHz	z 30k	Hz	Average		
	0.490MHz -30MHz		Quasi-peak	10kHz	z 30k	Hz	Quasi-peak		
	30MHz-1GHz		Quasi-peak	100 kH	lz 300	kHz	Quasi-peak		
	Ab 4011-		Peak	1MHz	: 3M	Hz	Peak		
	Above 1GHz		Peak	1MHz	: 10	Hz	Average		
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)	Rem	ark	Measureme distance (n		
	0.009MHz-0.490MHz	2	400/F(kHz)	-			300		
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-		30		
	1.705MHz-30MHz		30	-	-		30		
	30MHz-88MHz		100	40.0	Quasi-	peak	3		
	88MHz-216MHz		150	43.5	Quasi-	peak	3		
	216MHz-960MHz		200	46.0	Quasi-	peak	3		
	960MHz-1GHz		500	54.0	Quasi-	peak	3		
	Above 1GHz		500	54.0	Avera	age	3		
	frequency emissions is limit applicable to the e	Above 1GHz 500 54.0 Average 3 Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.							



Report No.: SZEM150900609003

Page: 39 of 52

Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz)
- h. The radiation measurements are performed in X, Y, Z axis positioning



Report No.: SZEM150900609003

Page: 40 of 52


	for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with GFSK modulation. Charge + Transmitting mode.
Final Test Mode:	Transmitting with GFSK modulation. Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case. For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass



Report No.: SZEM150900609003

Page: 41 of 52

Radiated Emission below 1GHz							
30MHz~1GHz (QP)							
Test mode:	Test mode: Charge + Transmitting mode Vertical						



Condition: FCC PART 15 C 3m 3142C VERTICAL

Job No. : 6090CR

Test Mode: Charge+TX mode

]	Cable Freq Loss	eAntenna s Factor					Over Limit
	MHz di	3 dB/m	dB	dBuV	$\overline{dBuV/m}$	$\overline{\text{dBuV/m}}$	dB
2 70 3 99 4 110 5 250	0.18 1.49 2.95 2.52	7.61 8.91 8.57	25. 25 25. 31 25. 54 24. 93	35. 27 35. 57 31. 48	21.31 20.28 20.09 21.43	40.00 43.50 43.50 46.00	-23. 22 -23. 41






Report No.: SZEM150900609003

42 of 52 Page:

Horizontal Test mode: Charge + Transmitting mode



Condition: FCC PART 15 C 3m 3142C HORIZONTAL

Job No. : 6090CR Test Mode: Charge+TX mode

Freq	Cable Loss		Preamp Factor				Over Limit
MHz	dB	_dB/m	dB	dBuV	$\overline{\text{dBuV/m}}$	$\overline{\text{dBuV/m}}$	——dB
1 32.86 2 105.64 3 280.02 4 387.99 5 793.40 6 938.83	1.46 2.66 3.22 4.84	8.81 13.03 16.17 22.08	26. 18 24. 68 25. 47	26.00 29.52 31.95 23.91	10. 09 20. 53 25. 87 24. 92	46.00 46.00	-33. 41 -25. 47 -20. 13



Report No.: SZEM150900609003

Page: 43 of 52

Transmitter	Transmitter Emission above 1GHz								
Test mo	de:	GFSK	Т	est channel:	Lowes	t	Remark:	Peak	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Pream Factor (dB)		Level (dBuV/m)	Limit Line (dBuV/m	Limit	Polarization	
3657.721	6.88	33.04	38.81	44.96	46.07	74	-27.93	Vertical	
4804.000	6.42	34.70	39.24	47.43	49.31	74	-24.69	Vertical	
6060.637	8.07	36.23	39.18	46.05	51.17	74	-22.83	Vertical	
7206.000	8.92	35.63	39.07	46.97	52.45	74	-21.55	Vertical	
9608.000	9.99	37.33	37.93	40.73	50.12	74	-23.88	Vertical	
12297.040	11.06	39.07	38.95	42.78	53.96	74	-20.04	Vertical	
3657.721	6.88	33.04	38.81	45.48	46.59	74	-27.41	Horizontal	
4804.000	6.42	34.70	39.24	51.69	53.57	74	-20.43	Horizontal	
5921.940	7.96	36.15	39.19	45.54	50.46	74	-23.54	Horizontal	
7206.000	8.92	35.63	39.07	47.00	52.48	74	-21.52	Horizontal	
9608.000	9.99	37.33	37.93	41.89	51.28	74	-22.72	Horizontal	
12297.040	11.06	39.07	38.95	42.52	53.70	74	-20.30	Horizontal	

Test mo	de:	GFSK	-	Tes	t channel:	Middle		Re	mark:	Peak
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Prean facto (dB)	r	Reading Level (dBµV)	Emission Level (dBµV/m)		mit ιV/m)	Over limit (dB)	Polarization
3647.151	6.88	33.04	38.8	1	45.65	46.76	7	' 4	-27.24	Vertical
4880.000	6.58	34.78	39.26	6	49.93	52.03	7	' 4	-21.97	Vertical
6131.199	8.05	36.15	39.17	7	45.33	50.36	7	' 4	-23.64	Vertical
7320.000	9.07	35.51	39.06	6	44.53	50.05	7	' 4	-23.95	Vertical
9760.000	9.90	37.80	37.84	4	41.60	51.46	7	' 4	-22.54	Vertical
12314.840	11.09	39.09	38.97	7	41.94	53.15	7	' 4	-20.85	Vertical
3584.372	6.92	32.98	38.78	8	45.15	46.27	7	' 4	-27.73	Horizontal
4880.000	6.58	34.78	39.26	6	51.21	53.31	7	' 4	-20.69	Horizontal
6184.658	8.04	36.10	39.16	6	46.09	51.07	7	' 4	-22.93	Horizontal
7320.000	9.07	35.51	39.06	6	45.36	50.88	7	' 4	-23.12	Horizontal
9760.000	9.90	37.80	37.84	4	41.55	51.41	7	' 4	-22.59	Horizontal
12297.040	11.06	39.07	38.9	5	42.10	53.28	7	' 4	-20.72	Horizontal



Report No.: SZEM150900609003

Page: 44 of 52

Test mo	de:	GFSK	Tes	t channel:	Highes	Highest I		mark:	Peak
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)		mit ιV/m)	Over limit (dB)	Polarization
3737.975	6.83	33.10	38.84	44.66	45.75	7	'4	-28.25	Vertical
4960.000	6.76	34.86	39.29	50.71	53.04	7	'4	-20.96	Vertical
6016.949	8.08	36.28	39.18	45.54	50.72	7	'4	-23.28	Vertical
7440.000	9.23	35.43	39.05	45.10	50.71	7	'4	-23.29	Vertical
9920.000	9.81	38.27	37.75	41.67	52.00	7	'4	-22.00	Vertical
12261.500	11.01	39.03	38.92	42.70	53.82	7	'4	-20.18	Vertical
3700.306	6.85	33.08	38.83	45.62	46.72	7	'4	-27.28	Horizontal
4960.000	6.76	34.86	39.29	51.04	53.37	7	'4	-20.63	Horizontal
5956.314	8.01	36.22	39.19	46.25	51.29	7	'4	-22.71	Horizontal
7440.000	9.23	35.43	39.05	46.72	52.33	7	'4	-21.67	Horizontal
9920.000	9.81	38.27	37.75	41.36	51.69	7	'4	-22.31	Horizontal
12226.070	10.95	38.98	38.89	42.19	53.23	7	'4	-20.77	Horizontal

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.




Report No.: SZEM150900609003

Page: 45 of 52

6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205							
Test Method:	ANSI C63.10 2009	ANSI C63.10 2009						
Test Site:	Measurement Distance: 3m	(Semi-Anechoic Chambe	r)					
Limit:	Frequency	Limit (dBuV/m @3m)	Remark					
	30MHz-88MHz	40.0	Quasi-peak Value					
	88MHz-216MHz	43.5	Quasi-peak Value					
	216MHz-960MHz	46.0	Quasi-peak Value					
	960MHz-1GHz	54.0	Quasi-peak Value					
	Above 1GHz	54.0	Average Value					
	Above IGHZ	74.0	Peak Value					
Test Setup:								






Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz

Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel



Report No.: SZEM150900609003

Page: 46 of 52


	 g. Test the EUT in the lowest channel, the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. 					
Exploratory Test Mode:	Transmitting with GFSK modulation.					
	Transmitting mode, Charge + Transmitting mode.					
Final Test Mode:	Transmitting with GFSK modulation.					
	Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case.					
	Only the worst case is recorded in the report.					
Instruments Used:	Refer to section 5.10 for details.					
Test Results:	Pass					



Report No.: SZEM150900609003

Page: 47 of 52

Worse case mode:	GFSK	Test channel:	Lowest	Remark:	Peak	Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 6090CR

Mode: : 2402 Band edge

: BLE


Cable Limit Ant Preamp Read Over Loss Factor Factor Level Level Line Limit MHz dB dB/m dB dBuV dBuV/m dBuV/m dB 2390.00 4.90 32.35 38.46 45.14 43.93 74.00 -30.07 4.92 32.41 38.46 91.96 2 pp 2402.38 90.83 74.00 16.83



Report No.: SZEM150900609003

Page: 48 of 52

Worse case mode: GFSK Test channel: Lowest Remark: Peak Vertical



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 6090CR

Mode: : 2402 Band edge

: BLE


Cable Ant Preamp Limit Read 0ver Loss Factor Factor Limit Freq Level Level Line MHz dB dBuV dBuV/m dBuV/m dB/m dB 1 pk 2390.00 4.90 32.35 38.46 45.97 44.76 74.00 -29.24 2 pp 2402.48 4.92 32.41 38.46 98.84 97.71 74.00 23.71



Report No.: SZEM150900609003

Page: 49 of 52

Worse case mode:	GFSK	Test channel:	Highest	Remark:	Peak	Horizontal



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 6090CR

Mode: : 2480 Band edge

: BLE


Cable Ant Preamp Read Limit 0ver Freq Loss Factor Factor Level Level Line Limit MHz dB dB/m dB dBuV dBuV/m dBuV/m 1 pp 2479.73 5.02 32.44 38.47 93.83 92.82 74.00 18.82 5.03 32.44 38.47 51.59 50.59 74.00 -23.41 2 pk 2483.50



Report No.: SZEM150900609003

Page: 50 of 52

Worse case mode:	GFSK	Test channel:	Highest	Remark:	Peak	Vertical
			0			



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical

Job No: : 6090CR

Mode: : 2480 Band edge

: BLE

	Freq			Preamp Factor				
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
	2479.76 2483.50							

Note:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

2) The peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.



Report No.: SZEM150900609003

Page: 51 of 52


7 Photographs - EUT Test Setup

Test model No.: MW60

7.1 Conducted Emission



7.2 Radiated Emission







Report No.: SZEM150900609003

Page: 52 of 52

7.3 Radiated Spurious Emission



8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1509006090CR.