

FCC Part 15B TEST REPORT

Report No: STS1706154E01

Issued for

XTR S.A.C.

Av. Camino Real 1225 Of 201-A San Isidro Lima, Peru

Product Name:	3G Smartphone
Brand Name:	EKS
Test Model Name:	X4U+
Series Model:	N/A
FCC ID:	2AGAK-X4UP
Test Standard:	FCC Part 15B

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from BZT, All Test Data Presented in this report is only applicable to presented Test sample.

BZT Testing Technology Co., Ltd
Add. : Buliding 17, Xinghua Road Xingwei industrial Park Fuyong,
Baoan District, Shenzhen, Guangdong, China
TEL: +86-755 3307 1680 FAX: +86-755 27341758 E-mail:bruce@bzt.cn

TEST RESULT CERTIFICATION**Applicant's name**: XTR S.A.C.

Address.....: Av. Camino Real 1225 Of 201-A San Isidro Lima, Peru

Manufacture's Name: Encorp LimitedAddress.....: FLAT/RM 5 , BLK B , 14/F WAH HEN COMMERCIAL CENTRE
383 HENNESSY ROAD, WANCHAI , HK**Product description**

Product name.....: 3G Smartphone

Model and/or type reference ..: X4U+

Standards: FCC Part 15B

Test procedure ANSI C63.4-2014

This device described above has been tested by BZT, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BZT, this document may be altered or revised by BZT, personal only, and shall be noted in the revision of the document


Date of Test.....

Date of performance of tests 19 June. 2017 ~ 23 June. 2017

Date of Issue..... 24 June. 2017

Test Result **Pass**

Testing Engineer :



(Barry li)

Technical Manager :



(Chopin Xiao)

Authorized Signatory :



(Vita Li)

TABLE OF CONTENTS

1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACtory	5
1.2 MEASUREMENT UNCERTAINTY	5
2. GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	7
2.4 DESCRIPTION OF SUPPORT UNITS	8
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3. EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.2 RADIATED EMISSION MEASUREMENT	14
APPENDIX 1-PHOTOS OF TEST SETUP	20

Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	24 June. 2017	STS1706154E01	ALL	Initial Issue

Note: **Format version** of the report -V01

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

EMISSION			
Standard	Item	Result	Remarks
FCC 47 CFR Part 15 Subpart B (10-1-05 Edition)	Conducted Emission	PASS	Meet Class B limit
	Radiated Emission	PASS	Meet Class B limit

NOTE:

(1) " N/A" denotes test is not applicable in this Test Report

1.1 TEST FACTORY

Company Name:	BZT Testing Technology Co., Ltd.
Address:	Buliding 17, Xinghua Road Xingwei industrial Park Fuyong, Baoan District, Shenzhen, Guangdong, China
Registration No.:	FCC Registration No.: 701733

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	± 2.88 dB
2	Conducted Emission (150KHz-30MHz)	± 2.67 dB
5	All emissions,radiated(<1G) 30MHz-200MHz	± 3.80 dB
6	All emissions,radiated(<1G) 200MHz-1000MHz	± 3.97 dB
7	All emissions,radiated(>1G)	± 3.03 dB

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	3G Smartphone
Trade Name	EKS
Model Name	X4U+
Series Model	N/A
Model Difference	N/A
Adapter	Input: AC100-240V, 500mA,50/60 Hz Output: DC5V,500 mA
Battery	Rated Voltage: 3.8V Capacity: 1500mAh
Hardware version number	FS280-MB-V0.1
Software version number	N/A

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	USB port communication with PC


For Conducted Test	
Final Test Mode	Description
Mode 1	USB port communication with PC

For Radiated Test	
Final Test Mode	Description
Mode 1	USB port communication with PC

NOTE:

1. Due to the different configuration and test, in this list only some worse mode. The worst test data of the worse mode is reported by this report.
2. We have be tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz) for which the device is capable of operation.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Note
E-1	3G Smartphone	EKS	X4U+	EUT
E-2	PC	HP	500-320cx	N/A
E-3	Mouse	HP	MODGUO	N/A
E-4	Keyboard	Acer	SK-9624	N/A
E-5	Printer	LENOVO	LJ2400L	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable (FTP)	NO	85cm	N/A
C-2	Shielded	NO	95cm	N/A
C-3	Shielded	NO	110cm	N/A
C-4	Shielded	NO	120cm	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.
- (4) PC is the FCC DOC is approved.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	101427	2016.10.25	2017.10.24
Loop Antenna	Daze	ZN30900N	SEL0097	2016.10.27	2017.10.26
Bilog Antenna	TESEQ	CBL6111D	34678	2016.11.25	2017.11.24
Horn Antenna	Schwarzbeck	BBHA 9120D(1201)	9120D-1343	2017.03.06	2018.03.05
PreAmplifier	Agilent	8449B	60538	2016.10.25	2017.10.24
Temperature & Humidity	Mieo	HH660	N/A	2016.10.28	2017.10.27
Unversal radio communication tester	R&S	CMU200	111764	2016.10.25	2017.10.24
Spectrum Analyzer	Agilent	E4407B	MY50140340	2016.10.25	2017.10.24
Low frequency cable	EM	R01	N/A	N/A	N/A
High frequency cable	SCHWARZBECK	AK9515H	SN-96286/96287	N/A	N/A
Semi-anechoic chamber	Changling	966	N/A	2016.10.25	2017.10.24

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESPI	102086	2016.10.23	2017.10.22
LISN	R&S	ENV216	101242	2016.10.23	2017.10.22
LISN	EMCO	3810/2NM	000-23625	2016.10.23	2017.10.22
Conduction Cable	EM	C01	N/A	N/A	N/A
Shielding Room	Changling	854	N/A	2016.10.25	2017.10.24

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
 - I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
 - LISN at least 80 cm from nearest part of EUT chassis.
 - For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



- Note: 1. Support units were connected to second LISN.**
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.6 TEST RESULTS

Temperature:	25.4°C	Relative Humidity:	61%
Pressure:	1010hPa	Phase:	L
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1580	45.16	9.23	54.39	65.57	-11.18	QP
2	0.1580	26.85	9.23	36.08	55.57	-19.49	AVG
3	0.2180	39.02	9.21	48.23	62.89	-14.66	QP
4	0.2180	22.38	9.21	31.59	52.89	-21.30	AVG
5	0.5180	25.10	9.15	34.25	56.00	-21.75	QP
6	0.5180	13.71	9.15	22.86	46.00	-23.14	AVG
7	1.9020	33.52	9.24	42.76	56.00	-13.24	QP
8	1.9020	12.53	9.24	21.77	46.00	-24.23	AVG
9	3.5180	25.36	9.26	34.62	56.00	-21.38	QP
10	3.5180	10.20	9.26	19.46	46.00	-26.54	AVG
11	7.2940	29.81	9.30	39.11	60.00	-20.89	QP
12	7.2940	14.52	9.30	23.82	50.00	-26.18	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) – Limit




Temperature:	25.4 °C	Relative Humidity:	61%
Pressure:	1010hPa	Phase:	N
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1540	45.74	9.23	54.97	65.78	-10.81	QP
2	0.1540	22.19	9.23	31.42	55.78	-24.36	AVG
3	0.3100	27.21	9.16	36.37	59.97	-23.60	QP
4	0.3100	12.59	9.16	21.75	49.97	-28.22	AVG
5	0.5260	25.41	9.15	34.56	56.00	-21.44	QP
6	0.5260	10.81	9.15	19.96	46.00	-26.04	AVG
7	1.6980	32.99	9.22	42.21	56.00	-13.79	QP
8	1.6980	14.91	9.22	24.13	46.00	-21.87	AVG
9	3.6620	24.31	9.26	33.57	56.00	-22.43	QP
10	3.6620	8.63	9.26	17.89	46.00	-28.11	AVG
11	9.8620	28.65	9.49	38.14	60.00	-21.86	QP
12	9.8620	17.00	9.49	26.49	50.00	-23.51	AVG

Remark:

- All readings are Quasi-Peak and Average values.
- Margin = Result (Result = Reading + Factor) - Limit

100.0 dBuV



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 Radiated Emission Limits

In case the emission fall within the restricted band specified on 15.105(a)&109(a) limit in the table below has to be followed.

Frequencies (MHz)	Class A (at 10m) dBuV/m	Class B (at 3m) dBuV/m
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Note:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	5th harmonic (Peak/AV)
RB / VB (emission in restricted band)	30MHz to 1000MHz: 100 KHz / 300 KHz Above 1000MHz: 1 MHz / 3 MHz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	30MHz to 1000MHz: 100 KHz / 300 KHz Above 1000MHz: 1 MHz / 3 MHz

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz.

The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.

- c. the height of the antenna shall vary between 1m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.

- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency 30MHz~1GHz



(B) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS


Between 30-1000MHz

Temperature:	26 °C	Relative Humidity:	60%
Pressure:	1010hPa	Phase:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	79.5210	45.83	-22.76	23.07	40.00	-16.93	QP
2	167.8243	54.53	-19.15	35.38	43.50	-8.12	QP
3	206.3976	54.29	-19.89	34.40	43.50	-9.10	QP
4	399.0302	46.16	-11.28	34.88	46.00	-11.12	QP
5	599.3212	44.86	-7.14	37.72	46.00	-8.28	QP
6	721.7260	41.62	-4.54	37.08	46.00	-8.29	QP

Remark:

1. All readings are Quasi-Peak .
2. Margin = Result (Result =Reading + Factor)–Limit




Temperature:	26 °C	Relative Humidity:	60%
Pressure:	1010hPa	Phase:	Vertical
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	76.7808	42.63	-23.15	19.48	40.00	-20.52	QP
2	119.8556	40.80	-17.70	23.10	43.50	-20.40	QP
3	167.8243	51.24	-19.15	32.09	43.50	-11.41	QP
4	400.4319	48.99	-11.22	37.77	46.00	-8.23	QP
5	599.3213	49.60	-7.14	42.46	46.00	-3.54	QP
6	721.7259	45.73	-4.54	41.19	46.00	-4.81	QP

Remark:

1. All readings are Quasi-Peak .
2. Margin = Result (Result =Reading + Factor)–Limit



(1 GHz to 25GHz.)

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	Vertical/Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

PK

Freq.	Ant. Pol	Peak	Amplifier	Loss	Antenna Factor	Orrected Factor	Actual Fs	Peak	Peak
(MHz)	H/V	Reading (dBuV)	(dB)	(dB)	(dB/m)	(dB)	Peak (dBuV/m)	Limit (dBuV/m)	margin (dB)
2062.8	H	56.64	43.8	5.4	25.9	-12.5	45.14	74.00	-28.86
2506.1	H	54.32	44.4	6.0	27.6	-10.8	41.52	74.00	-32.48
3052.2	H	62.85	44.7	6.7	28.2	-9.8	54.05	74.00	-19.95
3533.3	H	50.89	44.4	7.1	28.5	-8.8	44.09	74.00	-29.91
N/A									
2062.8	V	55.76	43.8	5.4	25.9	-12.5	40.26	74.00	-33.74
2506.1	V	43.64	44.4	6.0	27.6	-10.8	38.84	74.00	-35.16
3052.2	V	64.64	44.7	6.7	28.2	-9.8	53.84	74.00	-20.16
3533.3	V	46.69	44.4	7.1	28.5	-8.8	40.89	74.00	-33.11
N/A									

AV

Freq.	Ant. Pol	AV	Amplifier	Loss	Antenna Factor	Orrected Factor	AV	AV	AV
(MHz)	H/V	Reading (dBuV)	(dB)	(dB)	(dB/m)	(dB)	AV (dBuV/m)	Limit (dBuV/m)	margin (dB)
2062.8	H	43.32	43.8	5.4	25.9	-12.5	28.82	54.00	-25.18
2506.1	H	35.65	44.4	6.0	27.6	-10.8	27.85	54.00	-26.15
3052.2	H	49.53	44.7	6.7	28.2	-9.8	32.73	54.00	-21.27
3533.3	H	36.32	44.4	7.1	28.5	-8.8	29.52	54.00	-24.48
N/A									
2062.8	V	34.73	43.8	5.4	25.9	-12.5	25.23	54.00	-28.77
2506.1	V	32.35	44.4	6.0	27.6	-10.8	22.55	54.00	-31.45
3052.2	V	54.74	44.7	6.7	28.2	-9.8	45.94	54.00	-8.06
3533.3	V	39.53	44.4	7.1	28.5	-8.8	25.73	54.00	-28.27
N/A									



Notes:

1. Measuring frequencies from 1 GHz to 25GHz.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode of the emission shown in Actual FS column.
3. The frequency that above 5.5GHz is mainly from the environment noise.

APPENDIX 1-PHOTOS OF TEST SETUP

Radiated Measurement Photos

30MHz- 1GHz



Conducted Measurement Photos



Conducted Measurement Photos



*****END OF THE REPORT*****