

Application for FCC Certification  
On behalf of

Philips Lighting (China) Investment Co., Ltd.

Product Name: LED MODULE

Model No.: 2AGBW324131254491X

FCC ID: 2AGBW324131254491X

(MPE Calculation)

Prepared For : Philips Lighting (China) Investment Co., Ltd.  
Building 9#, Lane 888, Tianlin Road, Minhang District,  
Shanghai 200233, China

Prepared By : Audix Technology (Shanghai) Co., Ltd.  
3F and 4F, 34Bldg 680 Guiping Rd.,  
Caohejing Hi-Tech Park,  
Shanghai 200233, China

Tel: +86-21-64955500  
Fax: +86-21-64955491

Report No. : ACI-F16262  
Date of Test : Aug. 11, 2016  
Date of Report : Nov.01, 2016

## TABLE OF CONTENTS

	Page
<b>1 GENERAL INFORMATION.....</b>	<b>4</b>
1.1 Description of Equipment Under Test.....	4
1.2 Description of Test Facility .....	5
1.3 Measurement Uncertainty .....	5
<b>2 SUMMARY OF STANDARDS AND RESULTS.....</b>	<b>6</b>
2.1 Applicable Standard .....	6
2.2 Specification Limits .....	6
2.3 MPE Calculation Method.....	6
2.4 Calculated Result.....	7

# TEST REPORT FOR FCC CERTIFICATE

Applicant : Philips Lighting (China) Investment Co., Ltd.  
 EUT Description : LED MODULE;  
 (A) Model No. : 2AGBW324131254491X  
 (B) Power Supply : DC 5V  
 Test Procedure Used:

*FCC Part 1 Subpart I and Part 2 Subpart J  
 KDB 447498 D01 General RF Exposure Guidance v06*

The device described above is tested by Audix Technology (Shanghai) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part2.

The test results are contained in this test report and Audix Technology (Shanghai) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. This report also shows that the EUT (M/N: Refer to Sec2.1), which was tested on Aug. 11, 2016 is technically compliance with the FCC limits.


This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shanghai) Co., Ltd.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Aug. 11, 2016 Date of Report : Nov. 01, 2016

Producer : *Alan He*  
 ALAN HE / Assistant

Review : *Byron Wu*  
 BYRON WU / Deputy Assistant Manager

 For and on behalf of  
 Audix Technology (Shanghai) Co., Ltd.

Signatory : *EMC Byron Kwo*  
 Authorized Signature EMC BYRON KWO / Assistant General Manager

# 1 GENERAL INFORMATION

## 1.1 Description of Equipment Under Test

Description : LED MODULE;

Type of EUT  Production  Pre-product  Pro-type

Model Number : 2AGBW324131254491X

Radio Tech : Zigbee

Channel Freq. : 2405MHz, 2425MHz, 2450MHz, 2475MHz, 2480MHz

Tested Freq. : 2405MHz, 2450MHz, 2480MHz

Modulation : O-QPSK

Antenna Gain : -5 dBi

Applicant : Philips Lighting (China) Investment Co., Ltd.  
Building 9#, Lane 888, Tianlin Road, Minhang District,  
Shanghai 200233, China

## 1.2 Description of Test Facility

Site Description (Semi-Anechoic Chamber) : Sept. 17, 1998 file on  
Jan. 15, 2015 Renewed  
Federal Communications Commission  
FCC Engineering Laboratory  
7435 Oakland Mills Road  
Columbia, MD 21046, USA

Name of Firm : Audix Technology (Shanghai) Co., Ltd.

Site Location : 3F 34 Bldg 680 Guiping Rd.,  
Caohejing Hi-Tech Park,  
Shanghai 200233, China

FCC registration Number : 91789

Accredited by NVLAP, Lab Code : 200371-0

## 1.3 Measurement Uncertainty

Output Power Expanded Uncertainty :  $U = \pm 1.56$  dB

## 2 SUMMARY OF STANDARDS AND RESULTS

### 2.1 Applicable Standard

FCC Part1 §1.1310

### 2.2 Specification Limits

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

\*Plane-wave equivalent power density

NOTE: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The limit value 1.0mW/cm<sup>2</sup> is available for this EUT.

### 2.3 MPE Calculation Method

$$S = PG / (4 \pi R^2)$$

$$R = [PG / (4 \pi S)]^{0.5}$$

where: S = power density (in appropriate units, e.g. mW/ cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

(the measured power value see Report: F16053 Section 5.6)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

## 2.4 Calculated Result

### 2.4.1 Radio Frequency Radiation Exposure Evaluation

Frequency	Peak Power	Output Power to Antenna	Antenna Gain		Power Density	Limit
(MHz)	(dBm)	(mW)	(dBi)	(Numeric)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
2405	3.750	2.37	0	1	<b>0.000471</b>	1.0
2450	4.188	2.62	0	1	<b>0.000521</b>	1.0
2480	-16.278	0.02	0	1	<b>0.000004</b>	1.0

Separation distance R= 20cm.

Frequency	Peak Power	Output Power to Antenna	Antenna Gain		Limit	Distance
(MHz)	(dBm)	(mW)	(dBi)	(Numeric)	(mW/cm <sup>2</sup> )	(cm)
2405	3.750	2.37	0	1	1.0	0.43
2450	4.188	2.62	0	1	1.0	0.46
2480	-16.278	0.02	0	1	1.0	0.04

The antenna used for this transmitter must be installed to provide a separation distance of at least 0.46 cm from all persons.