



Test Report

FCC Part15 Subpart C & ISED RSS-247 Issue 2 (Class II Permissive Change)

Product Name : LED Lamp
Model No. : 9290011369B
FCC ID : 2AGBW9290011369BX
IC : 20812-1369BX

Applicant : Philips Lighting(China) Investment Co.,Ltd.
Address : Building 9,Lane 888,Tian Lin Road,Minhang
district,Shanghai,China

Date of Receipt : Apr. 19th, 2017
Test Date : Apr. 19th, 2017~ May. 05th, 2017
Issued Date : Jun. 06th, 2017
Report No. : 1742090R-RF-US-P06V01
Report Version : V1.1

Note: This report is based on Audix report No. ACWE-F1702001, it is only modify driver and added two PCB suppliers, so we re-evaluate items are AC Line Conducted Emission, output power, radiated emission and band edge.

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing & Certification (Suzhou) Co., Ltd.



Test Report Certification

Issued Date : Jun. ()
Report No. : 1742090R-RF-US-P06V01



Product Name : LED Lamp
 Applicant : Philips Lighting(China) Investment Co.,Ltd.
 Address : Building 9,Lane 888,Tian Lin Road,Minhang district,Shanghai,China
 Manufacturer : Philips Lighting(China) Investment Co.,Ltd.
 Address : Building 9,Lane 888,Tian Lin Road,Minhang district,Shanghai,China
 Model No. : 9290011369B
 FCC ID : 2AGBW9290011369BX
 IC : 20812-1369BX
 EUT Voltage : AC 110-130V/50/60Hz
 Test Voltage : AC 120V/60Hz
 Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2015
 ANSI C63.4:2014; ANSI C63.10:2013;
 KDB 558074 D01v04
 RSS GEN: Issue4; RSS 247: Issue2
 Test Result : Complied
 Performed Location : DEKRA Testing and Certification (Suzhou) ()
 No.99 Hongye Rd., Suzhou Industrial Park,
 215006, Jiangsu, China
 TEL: +86-512-6251-5088 / FAX: +86-512-6251-5089
 FCC Registration Number: 800392; IC Lab: 1742090R-RF-US-P06V01

Documented By : Kathy Feng
 (Adm. Specialist: Kathy Feng)

Reviewed By : Frank He
 (Senior Engineer: Frank He)

Approved By : Harry Zhu
 (Engineering Manager: Harry Zhu)

TABLE OF CONTENTS

Description	Page
1. General Information	5
1.1. EUT Description	5
1.2. Working Frequency of Each Channel:	6
1.3. Antenna information	6
1.4. Mode of Operation.....	7
1.5. Tested System Details	7
1.6. Configuration of Tested System.....	8
1.7. EUT Exercise Software.....	10
2. Technical Test.....	11
2.1. Summary of Test Result.....	11
2.2. Test Environment.....	12
2.3. Measurement Uncertainty	12
3. Emissions in restricted frequency bands.....	13
3.1. Test Equipment.....	17
3.2. Test Setup.....	18
3.3. Limit.....	19
3.4. Test Procedure	22
3.5. EUT test Axis definition.....	23
3.6. Test Result.....	24
4. Radiated Emission Band Edge.....	27
4.1. Test Equipment.....	27
4.2. Test Setup.....	28
4.3. Limit.....	28
4.4. Test Procedure	29
4.5. EUT test definition	30
4.6. Duty Cycle	31
4.7. Test Result	32
5. Fundamental emission output power	40
5.1. Test Equipment.....	40
5.2. Test Setup.....	40
5.3. Limit.....	41
5.4. Test Procedure	42
5.5. EUT test definition	43
5.6. Test Result.....	44
6. Antenna Requirement	45
6.1. Limit.....	45
6.2. Antenna Connector Construction.....	45

History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
1742090R-RF-US-P06V01	V1.0	Initial Issued Report	May. 05th, 2017
1742090R-RF-US-P06V01	V1.1	Add AC Line Conducted Emission test.	Jun. 06th, 2017

1. General Information

1.1. EUT Description

Product Name	LED Lamp
Model No.	9290011369B
EUT Voltage	AC 110-130V/50/60Hz
Test Voltage	AC 120V/60Hz
Zigbee	
Frequency Range	2405 ~ 2480MHz
Channel Number	16
Type of Modulation	DSSS-OQPSK
Data Rate	250kbps
Antenna Type	Reference to Antenna List

1.2. Working Frequency of Each Channel:

Zigbee Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
11	2405 MHz	12	2410 MHz	13	2415 MHz	14	2420 MHz
15	2425 MHz	16	2430 MHz	17	2435 MHz	18	2440 MHz
19	2445 MHz	20	2450 MHz	21	2455 MHz	22	2460 MHz
23	2465 MHz	24	2470 MHz	25	2475 MHz	26	2480 MHz

1.3. Antenna information

Antenna manufacturer	N/A					
Antenna Delivery	<input checked="" type="checkbox"/>	1*TX+1*RX	<input type="checkbox"/>	2*TX+2*RX	<input type="checkbox"/>	3*TX+3*RX
Antenna technology	<input checked="" type="checkbox"/>	SISO				
	<input type="checkbox"/>	MIMO	<input type="checkbox"/>	Basic		
			<input type="checkbox"/>	CDD		
			<input type="checkbox"/>	Beam-forming		
Antenna Type	<input type="checkbox"/>	External	<input type="checkbox"/>	Dipole		
	<input checked="" type="checkbox"/>	Internal	<input type="checkbox"/>	PIFA		
			<input checked="" type="checkbox"/>	PCB		
			<input type="checkbox"/>	Ceramic Chip Antenna		
			<input type="checkbox"/>	Microstrip Patch Antenna		
Antenna Gain	5dBi					

1.4. Mode of Operation


Test Mode
Mode 1: Transmit


1.5. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

No.	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	N/A	N/A	N/A	N/A	N/A

1.6. Configuration of Tested System





1.7. EUT Exercise Software

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of equipment.
3	Select the transmission test channel, start test.



2. Technical Test
2.1. Summary of Test Result

Performed Test Item	Normative References	Worst case mode	
AC Power Line Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.207	Mode 1	FCI
Emissions in restricted frequency bands	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.209	Mode 1	FCI
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2015 15.247(d)	Mode 1	FCI
Fundamental emission output power	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(b)(3)	Mode 1	

Performed Test Item	Normative References	Worst case
AC Power Line Conducted Emission	RSS-Gen Issue 4 Section 8.8	N/A
Emissions in restricted frequency bands	RSS-Gen Issue 4 Section 8.9	Mode
Radiated Emission Band Edge	RSS-247 Issue 2 Section A5.5	Mode
Fundamental emission output power	RSS-247 Issue 2 Section A5.4(4)	Mode

2.2. Test Environment

Items	Required (IEC)
Temperature (°C)	15-35
Humidity (%RH)	25-75
Barometric pressure (mbar)	860-106

2.3. Measurement Uncertainty

Test Items	Unc
AC Power Line Conducted Emission	
Radiated Emission	
RF Antenna Port Conducted Emission	
Radiated Emission Band Edge	
Occupied Bandwidth	
Power Spectral Density	


3. AC Power Line Conducted Emission

3.1. Test Equipment

AC Power Line Conducted Emission / TR-1					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100906	2017.03.05	2018.03.04
Two-Line V-Network	R&S	ENV 216	101189	2016.07.16	2017.07.15
Two-Line V-Network	R&S	ENV 216	101044	2016.09.16	2017.09.15
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	N/A	N/A
50ohm Termination	SHX	TF2	07081402	2016.09.16	2017.09.15
Temperature/Humidity Meter	Zhichen	ZC1-2	TR1-TH	2017.01.04	2018.01.03

Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

3.2. Test Setup



3.3. Limit


Frequency of Emission (MHz)	Conduc	
	Quasi-peak (dB)	
0.15-0.5	66 to 56	
0.5-5	56	
5-30	60	
Note 1: The lower limit shall apply at the transition		
Note 2: The limit decreases linearly with the logarithm of frequency from 66 dB at 0.15 MHz to 56 dB at 0.5 MHz.		

3.4. Test Procedure

Test Method			
	References Rule	Chapter	Item
<input checked="" type="checkbox"/>	ANSI C63.10-2013	6.2	Standards for emissions
<input checked="" type="checkbox"/>	ANSI C63.4-2014	7	AC power


3.5. Test Result

Site: TR1	Time: 2017/05/05
Limit: FCC_Part15.207_CE_AC Power	Margin: 0
Probe: ENV216-L1	Polarity: Line
EUT: LED Lamp	Power: AC 120V/60Hz
Note: Transmit at 2405MHz	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Probe (dB)	Cable (dB)	Amp (dB)	Type
1	*	0.154	58.405	48.672	-7.376	65.781	9.673	0.060	0.000	QP
2		0.154	42.427	32.694	-13.354	55.781	9.673	0.060	0.000	AV
3		0.174	54.869	45.149	-9.898	64.767	9.660	0.060	0.000	QP
4		0.174	39.164	29.444	-15.603	54.767	9.660	0.060	0.000	AV
5		0.206	50.614	40.904	-12.751	63.365	9.650	0.060	0.000	QP
6		0.206	36.348	26.638	-17.017	53.365	9.650	0.060	0.000	AV
7		0.230	47.253	37.543	-15.197	62.450	9.650	0.060	0.000	QP
8		0.230	33.931	24.221	-18.519	52.450	9.650	0.060	0.000	AV
9		0.286	39.236	29.536	-21.404	60.640	9.640	0.060	0.000	QP
10		0.286	27.176	17.476	-23.464	50.640	9.640	0.060	0.000	AV
11		0.434	33.058	23.358	-24.118	57.176	9.630	0.070	0.000	QP
12		0.434	26.924	17.224	-20.252	47.176	9.630	0.070	0.000	AV

Site: TR1	Time: 2017/05/05
Limit: FCC_Part15.207_CE_AC Power	Margin: 0
Probe: ENV216-N	Polarity: Neutral
EUT: LED Lamp	Power: AC 120V/60Hz
Note: Transmit at 2405MHz	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Probe (dB)	Cable (dB)	Amp (dB)	Type
1	*	0.150	58.522	48.786	-7.478	66.000	9.676	0.060	0.000	QP
2		0.150	42.514	32.778	-13.486	56.000	9.676	0.060	0.000	AV
3		0.202	50.406	40.686	-13.122	63.528	9.660	0.060	0.000	QP
4		0.202	35.961	26.241	-17.567	53.528	9.660	0.060	0.000	AV
5		0.254	44.344	34.626	-17.281	61.625	9.658	0.060	0.000	QP
6		0.254	31.771	22.053	-19.854	51.625	9.658	0.060	0.000	AV
7		0.310	36.923	27.213	-23.047	59.970	9.650	0.060	0.000	QP
8		0.310	25.209	15.499	-24.761	49.970	9.650	0.060	0.000	AV
9		0.438	36.359	26.652	-20.741	57.100	9.637	0.070	0.000	QP
10		0.438	28.962	19.255	-18.138	47.100	9.637	0.070	0.000	AV
11		0.698	18.261	8.551	-37.739	56.000	9.640	0.070	0.000	QP
12		0.698	10.310	0.600	-35.690	46.000	9.640	0.070	0.000	AV

4. Emissions in restricted frequency bands


4.1. Test Equipment

Radiated Emission(Below 1GHz) / AC-2					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100573	2017.03.29	2018.03.28
Loop Antenna	R&S	HFH2-Z2	833799/003	2016.11.16	2017.11.15
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2016.10.16	2017.10.15
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2017.03.02	2018.03.01
Temperature/Humidity Meter	Zhichen	ZC1-2	AC2-TH	2017.01.04	2018.01.03
Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					


Radiated Emission(Above 1GHz) / AC-5					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2017.01.04	2018.01.03
Preamplifier	Miteq	NSP1800-25	1364185	2016.05.06	2017.05.05
Preamplifier	QuieTek	AP-040G	CHM-0906001	2016.05.06	2017.05.05
DRG Horn	ETS-Lindgren	3117	00123988	2017.01.22	2018.01.21
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2016.11.25	2017.11.24
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2017.03.02	2018.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2017.03.02	2018.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2017.03.02	2018.03.01
EMI Receiver	Agilent	N9038A	MY51210196	2016.06.10	2017.06.09
Temperature/Humidity Meter	Zhichen	ZC1-2	AC5-TH	2017.01.04	2018.01.03
Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

4.2. Test Setup


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:



4.3. Limit

For FCC:

Restricted Bands of operation			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			

For IC:

Restricted Bands of operation			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090-0.110	13.36-13.41	1645.5-1646.5	9.0-9.2
2.1735-2.1905	16.42-16.423	1660-1710	9.3-9.5
3.020-3.026	16.69475-16.69525	1718.8-1722.2	10.6-12.7
4.125-4.128	16.80425-16.80475	2200-2300	13.25-13.4
4.17725-4.17775	25.5-25.67	2310-2390	14.47-14.5
4.20725-4.20775	37.5-38.25	2655-2900	15.35-16.2
5.677-5.683	73-74.6	3260-3267	17.7-21.4
6.215-6.218	74.8-75.2	3332-3339	22.01-23.12
6.26775-6.26825	108-138	3345.8-3358	23.6-24.0
6.31175-6.31225	156.52475-156.52525	3500-4400	31.2-31.8
8.291-8.294	156.7-156.9	4500-5150	36.43-36.5
8.362-8.366	240-285	5350-5460	Above 38.6
8.37625-8.38675	322-335.4	7250-7750	
8.41425-8.41475	399.9-410	8025-8500	
12.29-12.293	608-614		
12.51975-12.52025	960-1427		
12.57675-12.57725	1435-1626.5		

Restricted Band Emissions Limit	
Frequency (MHz)	Field stren (
0.009 - 0.49	
0.49 - 1.705	
1.705 - 30	
30 - 88	
88 - 216	
216 - 960	
Above 960	







Note 1: At frequencies bel than that specified in the r measurements in the nea procedure for measureme closer distance than spec either making measureme the proper extrapolation f extrapolation factor (40 dE

Note 2: At frequencies at other than what is specific where it can be shown th of the device; and it can b distance employed can be be performed at a distanc measurements at a distar measurements at a distar specified distance using a field strength measureme measurements).

4.4. Test Procedure

Test Method			
	References Rule	Chapter	Description
<input type="checkbox"/>	ANSI C63.10	11.11	Emissions in non-restricted frequency bands
	<input type="checkbox"/> ANSI C63.10	11.11.2	Reference level measurement
	<input type="checkbox"/> ANSI C63.10	11.11.3	Emission level measurement
<input checked="" type="checkbox"/>	ANSI C63.10	11.12	Emissions in restricted frequency bands
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.1	Radiated emission measurements
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.7	Radiated spurious emission test
	<input checked="" type="checkbox"/> ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
	<input checked="" type="checkbox"/> ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
	<input checked="" type="checkbox"/> ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz
	<input type="checkbox"/> ANSI C63.10	11.12.2.3	Quasi-peak measurement procedure
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.4	Peak power measurement procedure
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.5	Average power measurement procedures
	<input type="checkbox"/> ANSI C63.10	11.12.2.5.1	Trace averaging with continuous EUT transmission at full power
	<input type="checkbox"/> ANSI C63.10	11.12.2.5.2	Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.5.3	Reduced VBW averaging across ON and OFF times of the EUT transmissions with max hold

4.5. EUT test Axis definition

Item	Emissions in restricted frequency bands			
Device Category	<input type="checkbox"/>	Fixed point-to-point		
	<input type="checkbox"/>	Emit multiple directional beams, simultaneously or sequentially		
	<input checked="" type="checkbox"/>	Other cases		
Test mode	Mode 1			
Test method	<input checked="" type="checkbox"/>	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis <input checked="" type="checkbox"/>	Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>
	<input type="checkbox"/>	Conducted		
	<input type="checkbox"/>	Chain 0		
				
	<input type="checkbox"/>	Chain 0	Chain 1	
				
		Worst Chain <input type="checkbox"/>	Worst Chain <input type="checkbox"/>	
	<input type="checkbox"/>	Chain 0	Chain 1	Chain 2
				
	Worst Chain <input type="checkbox"/>	Worst Chain <input type="checkbox"/>	Worst Chain <input type="checkbox"/>	

4.6. Test Result

Product Name	: LED Lamp	Power	: AC 120V/60Hz
Test Mode	: Mode 1	Test Site	: AC-5
Test Date	: 2017.04.28		

Chain	CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector
Ant 0	11	H	4808.000	40.128	4.665	44.793	54(Note3)	-9.207	PK
		V	4810.000	38.631	4.678	43.310	54(Note3)	-10.690	PK
		H	7213.500	41.911	7.686	49.597	54(Note3)	-4.403	PK
		V	7213.500	41.673	7.686	49.359	54(Note3)	-4.641	PK
		H	9620.000	34.965	9.284	44.249	54(Note3)	-9.751	PK
		V	9620.000	35.827	9.284	45.111	54(Note3)	--8.889	PK
	18	H	4876.000	41.251	5.013	46.264	54(Note3)	-7.736	PK
		V	4876.000	39.810	5.013	44.823	54(Note3)	-9.177	PK
		H	7324.000	44.523	7.806	52.329	54(Note3)	-1.671	PK
		V	7324.000	41.892	7.806	49.698	54(Note3)	-4.302	PK
		H	9760.000	37.271	9.805	47.075	54(Note3)	-6.925	PK
		V	9760.000	37.051	9.805	46.855	54(Note3)	-7.145	PK
	26	H	4960.000	37.664	5.059	42.724	54(Note3)	-1.276	PK
		V	4960.000	37.726	5.059	42.786	54(Note3)	-1.214	PK
		H	7440.000	37.342	7.943	45.285	54(Note3)	-8.715	PK
		V	7440.000	37.535	7.943	45.478	54(Note3)	-8.522	PK
		H	9920.000	35.511	10.101	45.613	54(Note3)	-8.387	PK
		V	9920.000	34.808	10.101	44.910	54(Note3)	-9.090	PK

Note: 1. Measure Level = Reading Level + Factor.


Note: 2. The test frequency range, 9kHz~30MHz, 18GHz~25GHz, both of the worst case are at least 20dB below the limits, therefore no data appear in the report.

Note: 3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Note: 4. The RBW set up, see Clause 6.6.

The worst case of Radiated Emission below 1GHz:

Site: AC3	Time: 2017/04/27
Limit: FCC_Part15.109_RE(3m)_ClassB	Margin: 0
Probe: AC3_3m (30-1000MHz)	Polarity: Horizontal
EUT: LED Lamp	Power: AC 120V/60Hz
Note: Transmit at 2405MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Probe (dB/m)	Cable (dB)	Amp (dB)	Ant Pos (cm)	Table Pos (deg)	Type
1		30.849	25.600	29.782	-14.400	40.000	18.307	0.609	23.098	200	41	QP
2		169.559	33.200	45.245	-10.300	43.500	9.614	1.410	23.069	200	154	QP
3		235.276	35.500	46.203	-10.500	46.000	10.933	1.650	23.286	200	314	QP
4	*	287.899	39.600	47.764	-6.400	46.000	13.058	1.820	23.041	200	314	QP
5		662.073	32.500	33.000	-13.500	46.000	18.976	2.840	22.316	100	67	QP
6		960.109	34.500	32.389	-19.500	54.000	20.981	3.420	22.290	200	314	QP

Note:

1. " * ", means this data is the worst emission level.
2. Measurement Level = Reading Level + Factor (Probe+Cable-Amp).

Site: AC3	Time: 2017/04/27
Limit: FCC_Part15.109_RE(3m)_ClassB	Margin: 0
Probe: AC3_3m (30-1000MHz)	Polarity: Vertical
EUT: LED Lamp	Power: AC 120V/60Hz
Note: Transmit at 2405MHz	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Probe (dB/m)	Cable (dB)	Amp (dB)	Ant Pos (cm)	Table Pos (deg)	Type
1		167.255	23.600	35.578	-19.900	43.500	9.682	1.400	23.060	100	96	QP
2		240.732	32.600	42.649	-13.400	46.000	11.581	1.670	23.300	200	154	QP
3		287.899	32.500	40.664	-13.500	46.000	13.058	1.820	23.041	100	49	QP
4		384.111	29.600	34.863	-16.400	46.000	15.587	2.160	23.010	300	321	QP
5	*	662.198	35.400	35.902	-10.600	46.000	18.975	2.840	22.318	100	69	QP
6		951.015	34.200	32.197	-11.800	46.000	20.908	3.400	22.305	200	341	QP

Note:


- " * ", means this data is the worst emission level.
- Measurement Level = Reading Level + Factor (Probe+Cable-Amp).

5. Radiated Emission Band Edge

5.1. Test Equipment

Radiated Emission Band Edge / AC-5					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Receiver	Agilent	N9038A	MY51210196	2016.07.16	2017.07.15
Pre-Amplifier	Miteq	NSP1800-25	1364185	2017.05.03	2018.05.02
DRG Horn Antenna	ETS-Lindgren	3117	00167055	2016.07.12	2017.07.11
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2016.09.18	2017.09.17
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2017.02.28	2018.02.27
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2017.02.28	2018.02.27
Temperature/Humidity Meter	Zhichen	ZC1-2	AC5-TH	2017.01.05	2018.01.04

5.2. Test Setup



5.3. Limit







Band edge Limit		
Frequency bands (MHz)	Detector	Limit (dB)
2310-2390	PK	
2483.5-2500	AV	

Note: The field strength of emissions appea

5.4. Test Procedure


Test Method			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	6.10	Band-edge testing
	<input checked="" type="checkbox"/> ANSI C63.10	6.10.5	Restricted-band band-edge measurements
	<input type="checkbox"/> ANSI C63.10	6.10.6	Marker-delta method
<input checked="" type="checkbox"/>	ANSI C63.10	11.12	Emissions in restricted frequency bands
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.1	Radiated emission measurements
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.7	Radiated spurious emission test
<input type="checkbox"/>	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
<input type="checkbox"/>	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
<input checked="" type="checkbox"/>	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz
	<input type="checkbox"/> ANSI C63.10	11.12.2.3	Quasi-peak measurement procedure
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.4	Peak power measurement procedure
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.5	Average power measurement procedures
	<input type="checkbox"/> ANSI C63.10	11.12.2.5.1	Trace averaging with continuous EUT transmission at full power
	<input type="checkbox"/> ANSI C63.10	11.12.2.5.2	Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.5.3	Reduced VBW averaging across ON and OFF times of the EUT transmissions with max hold

5.5. EUT test definition

Item	Radiated Emission Band Edge			
Device Category	<input type="checkbox"/>	Fixed point-to-point		
	<input type="checkbox"/>	Emit multiple directional beams, simultaneously or sequentially		
	<input checked="" type="checkbox"/>	Other cases		
Test mode	Mode 1			
Test method	<input checked="" type="checkbox"/>	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis <input checked="" type="checkbox"/>	Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>
	<input type="checkbox"/>	Conducted		
	<input type="checkbox"/>	Chain 0		
				
	<input type="checkbox"/>	Chain 0	Chain 1	
				
	<input type="checkbox"/>	Chain 0	Chain 1	Chain 2
				


5.6. Duty Cycle

Test Mode	Tx On (ms)	Tx Off (ms)	Reduced VBW (Hz)	Tx On + Tx Off (ms)	Duty Cycle
Zigbee	N/A	N/A	10	N/A	100%




4.7. Test Result

Engineer: Damon	
Site: AC5	Time: 2017/04/28 - 01:04
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: LED Lamp	Power: AC 120V/60Hz
Note: Mode 1:Transmit at channel 2405MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	48.868	13.186	-25.132	74.000	35.682	PK
2	*	2404.915	94.560	58.839	20.560	74.000	35.721	PK

Engineer: Damon	
Site: AC5	Time: 2017/04/28 - 01:18
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: LED Lamp	Power: AC 120V/60Hz
Note: Mode 1:Transmit at channel 2405MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	37.151	1.469	-16.849	54.000	35.682	AV
2	*	2405.108	94.504	58.783	40.504	54.000	35.721	AV

Engineer: Damon	
Site: AC5	Time: 2017/04/28 - 01:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: LED Lamp	Power: AC 120V/60Hz
Note: Mode 1:Transmit at channel 2405MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	49.311	13.629	-24.689	74.000	35.682	PK
2	*	2405.108	93.241	57.520	19.241	74.000	35.721	PK

Engineer: Damon	
Site: AC5	Time: 2017/04/28 - 01:21
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: LED Lamp	Power: AC 120V/60Hz
Note: Mode 1:Transmit at channel 2405MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	36.997	1.315	-17.003	54.000	35.682	AV
2	*	2404.963	92.868	57.147	38.868	54.000	35.721	AV

Engineer: Damon	
Site: AC5	Time: 2017/04/28 - 01:36
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: LED Lamp	Power: AC 120V/60Hz
Note: Mode 1:Transmit at channel 2480MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.013	81.691	45.825	7.691	74.000	35.866	PK
2		2483.500	50.546	14.654	-23.454	74.000	35.891	PK

Engineer: Damon	
Site: AC5	Time: 2017/04/28 - 01:49
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: LED Lamp	Power: AC 120V/60Hz
Note: Mode 1:Transmit at channel 2475MHz	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.980	84.020	48.154	30.020	54.000	35.866	AV
2		2483.500	38.833	2.941	-15.167	54.000	35.891	AV

Engineer: Damon	
Site: AC5	Time: 2017/04/28 - 01:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: LED Lamp	Power: AC 120V/60Hz
Note: Mode 1:Transmit at channel 2480MHz	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.002	80.096	44.230	6.096	74.000	35.866	PK
2		2483.500	50.085	14.193	-23.915	74.000	35.891	PK

Engineer: Damon	
Site: AC5	Time: 2017/04/28 - 01:52
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: LED Lamp	Power: AC 120V/60Hz
Note: Mode 1:Transmit at channel 2475MHz	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.013	83.910	48.044	29.910	54.000	35.866	AV
2		2483.500	38.918	3.026	-15.082	54.000	35.891	AV


6. Fundamental emission output power

6.1. Test Equipment

Fundamental emission output power/ TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2017.01.04	2018.01.03
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.02.04	2018.01.15
Wideband Peak Power Meter	Anritsu	ML2495A	0905006	2016.10.14	2017.10.13
Power Sensor	Anritsu	MA2411B	0846014	2016.10.14	2017.10.13
Temperature/Humidity Meter	zhicheng	ZC1-2	TR8-TH	2017.04.10	2018.04.09

Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

6.2. Test Setup



6.3. Limit







Fundamental emiss	
<input checked="" type="checkbox"/>	GTX
<input type="checkbox"/>	GTX
	<input type="checkbox"/>
	<input type="checkbox"/>
	<input type="checkbox"/>
	<input type="checkbox"/>
	<input type="checkbox"/>
	<input type="checkbox"/>
	<input type="checkbox"/>
Note 1 :	
Note 2 :	



6.4. Test Procedure

Fundamental emission output power Test Method				
	References Rule		Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10		11.9	Fundamental emission output power
	<input checked="" type="checkbox"/>	ANSI C63.10	11.9.1	Maximum peak conducted output po
	<input type="checkbox"/>	ANSI C63.10	11.9.1.1	RBW ≥ DTS bandwidth
	<input type="checkbox"/>	ANSI C63.10	11.9.1.2	Integrated band power method
	<input checked="" type="checkbox"/>	ANSI C63.10	11.9.1.3	PKPM1 Peak power meter method
	<input type="checkbox"/>	ANSI C63.10	11.9.2	Maximum conducted (average) outpu
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2	Measurement using a spectrum anal
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.2	Method AVGSA-1(Duty cycle
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.3	Method AVGSA-1A(Duty c
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.4	Method AVGSA-2(Duty cy
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.5	Method AVGSA-2A(Duty c
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.4	Method AVGSA-3
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.5	Method AVGSA-3A
	<input type="checkbox"/>	ANSI C63.10	11.9.2.3	Measurement using a pow
	<input type="checkbox"/>	ANSI C63.10	11.9.2.3.1	Method AVGPM
<input type="checkbox"/>	ANSI C63.10	11.9.2.3.2	Method AVGPM-G	

6.5. EUT test definition

Item	Fundamental emission output power			
Device Category	<input type="checkbox"/>	Fixed point-to-point		
	<input type="checkbox"/>	Emit multiple directional beams, simultaneously or sequentially		
	<input checked="" type="checkbox"/>	Other cases		
Test mode	Mode 1			
Test method	<input type="checkbox"/>	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>
	<input checked="" type="checkbox"/>	Conducted		
	<input checked="" type="checkbox"/>	Chain 0		
				
	<input type="checkbox"/>	Chain 0	Chain 1	
				
	<input type="checkbox"/>	Chain 0	Chain 1	Chain 2
				

6.6. Test Result

Product Name	: LED Lamp	Power	: AC 120V/60Hz
Test Mode	: Mode 1	Test Site	: TR-8
Test Date	: 2017.04.28		

Mode	Channel	Test Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
1	11	2405	1.367	30	Pass
1	18	2440	0.925	30	Pass
1	26	2480	-7.574	30	Pass

7. Antenna Requirement

7.1. Limit

Antenna Requirement Limit

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

7.2. Antenna Connector Construction

The EUT use permanently attached antennas and comply with FCC 15.203.
Please refer to the attached "Internal Photograph".

————— The End —————