

APPLICATION FOR CERTIFICATION

On Behalf of

Philips Lighting(China) Investment Co., Ltd.

LED Lamps

Model No. : 9290013012

Brand : Philips

FCC ID : 2AGBW9290013012X

Prepared for

Philips Lighting(China) Investment Co., Ltd.

Building 9, Lane 888, Tian Lin Road, Minhang district, Shanghai, China

Prepared by

Audix Technology (Wujiang) Co., Ltd. EMC Dept.

No. 1289 Jiangxing East Road, the Part of Wujiang Economic Development Zone
Jiangsu China 215200

Tel : +86-512-63403993

Fax :+86-512-63403339

Report Number : ACWE-F1611006

Date of Test : Nov.14~15, 2016

Date of Report : Nov.28, 2016

TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
TEST REPORT CERTIFICATION	4
1. GENERAL INFORMATION.....	4
1.1. Description of Device (EUT).....	4
1.2. Description of Test Facility	5
1.3. Measurement Uncertainty	5
2. RADIO FRREQUENCY EXPOSURE COMPLIANCE RESULT	6

TEST REPORT CERTIFICATION

Applicant : Philips Lighting(China) Investment Co., Ltd.
 Manufacturer : Philips Lighting(China) Investment Co., Ltd.
 EUT Description : LED Lamp
 FCC ID : 2AGBW9290013012X
 (A) Model No. : 9290013012
 (B) Brand : Philips
 (C) Power Supply : AC 110-130V, 60Hz
 (D) Test Voltage : AC 120V, 60Hz

Applicable Standards:

KDB 447498 D01

The device described above was tested by Audix Technology (Wujiang) Co., Ltd. EMC Dept. to determine the maximum emission levels emanating from the device.

The measurement results are contained in this test report and Audix Technology (Wujiang) Co., Ltd. EMC Dept. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this test report shows that the EUT to be technically compliant with the FCC limits.

This test report applies to above tested sample only. This test report shall not be reproduced in part without written approval of Audix Technology (Wujiang) Co., Ltd. EMC Dept.

Date of Test: Nov.14~15, 2016

Date of Report: Nov.28, 2016

Prepared by

:



(Emma Hu/Assistant Administrator)

Reviewer

:



(Danny Sun/ Deputy Manager)

Approved & Authorized Signer

:



(Ken Lu/Assistant General Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Description	:	LED Lamp
Model No.	:	9290013012
FCC ID	:	2AGBW9290013012X
Brand	:	Philips
Applicant	:	Philips Lighting(China) Investment Co., Ltd. Building 9, Lane 888, Tian Lin Road, Minhang district, Shanghai, China
Manufacturer	:	Philips Lighting(China) Investment Co., Ltd. Building 9, Lane 888, Tian Lin Road, Minhang district, Shanghai, China
Radio Technology	:	IEEE 802.15.4 (ZigBee®)
Antenna Gain	:	3.24dBi
Fundamental Range	:	2405 MHz -2480MHz
Tested Frequency	:	2405MHz (CH11) 2450MHz (CH20) 2475MHz (CH25) 2480MHz (CH26)
Channel Setting Method	:	Channel is changed according to EUT's power on or power off.
Highest Working Frequency	:	2.4GHz
Modulation type	:	O-QPSK
Date of Receipt of Sample	:	Oct.28, 2016
Date of Test	:	Nov.14~15, 2016

1.2. Description of Test Facility

Name of Firm : **Audix Technology (Wujiang) Co., Ltd. EMC Dept.**

Site Location : No. 1289 Jiangxing East Road, the Eastern Part of Wujiang Economic Development Zone
Jiangsu China 215200

Test Facilities : **RF Fully Chamber**

NVLAP Lab Code : 200786-0
Valid until on Sep.30, 2017
(NVLAP is a signatory member of ILAC MRA)
Remark: This report shall not be imply endorsement, certification or approval by NVLAP, NIST, or any agency of the U.S. Federal Government.

1.3. Measurement Uncertainty

Test Item	Uncertainty
Maximum Peak Output Power	± 0.12dB

Remark: Uncertainty = $ku_c(y)$

2. RADIO FRREQUENCY EXPOSURE COMPLIANCE RESULT

Test Standard : FCC KDB Publication 447498 D01 Clause 4.3.1

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step b below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

According to the actual measurement,

max. power of channel, including tune-up tolerance =2.67mW

min. test separation distance= 5mm

$\sqrt{f_{(\text{GHz})}}=1.57$

The test result is $0.84 \leq 3.0$ for 1-g SAR ≤ 7.5 for 10-g SAR, hence the EUT is excluded from SAR evaluation according to FCC KDB Publication 447498 D01: General RF Exposure Guidance V06.