

APPLICATION FOR CERTIFICATION

On Behalf of

Philips Lighting(China) Investment Co., Ltd.

LED Lamp

Model No. : 9290013015

Brand : Philips

FCC ID : 2AGBW9290013015X

Prepared for

Philips Lighting(China) Investment Co., Ltd.

Building 9, Lane 888, Tian Lin Road, Minhang district, Shanghai, China

Prepared by

Audix Technology (Wujiang) Co., Ltd. EMC Dept.

No. 1289 Jiangxing East Road, the Part of Wujiang Economic Development Zone
Jiangsu China 215200

Tel : +86-512-63403993

Fax :+86-512-63403339

Report Number : ACWE-F1612006

Date of Test : Nov.16~26, 2016

Date of Report : Dec.13, 2016

TABLE OF CONTENTS

Description	Page
TEST REPORT CERTIFICATION	4
1. SUMMARY OF MEASUREMENTS AND RESULTS	5
2. GENERAL INFORMATION.....	6
2.1. Description of Device (EUT).....	6
2.2. Description of Test Facility	7
2.3. Measurement Uncertainty.....	7
3. CONDUCTED EMISSION MEASUREMENT	8
3.1. Test Equipment.....	8
3.2. Block Diagram of Test Setup.....	8
3.3. Power line Conducted Emission Limit	8
3.4. Test Procedure	9
3.5. Conducted Emission Measurement Results.....	9
4. RADIATED EMISSION MEASUREMENT	16
4.1. Test Equipment.....	16
4.2. Block Diagram of Test Setup.....	16
4.3. Radiated Emission Limits.....	17
4.4. Test Procedure	17
4.5. Measurement Results.....	19
4.6. Restricted Bands Measurement Results (For Below 1GHz).....	20
4.7. Restricted Bands Measurement Results (For Above 1GHz)	26
4.8. Spurious Emission Measurement Results in Band Edge Emission (FCC Part 15, 15.205).....	32
5. 6 DB BANDWIDTH MEASUREMENT	44
5.1. Test Equipment.....	44
5.2. Block Diagram of Test Setup.....	44
5.3. Specification Limits (§15.247(a)(2))	44
5.4. Test Procedure	44
5.5. Test Results.....	44
6. OUTPUT POWER MEASUREMENT.....	47
6.1. Test Equipment.....	47
6.2. Block Diagram of Test Setup.....	47
6.3. Specification Limits (§15.247(b)(3)).....	47
6.4. Test Procedure	48
6.5. Test Results.....	48
7. BAND EDGES MEASUREMENT	49
7.1. Test Equipment.....	49
7.2. Block Diagram of Test Setup.....	49
7.3. Specification Limits (§15.247(d)).....	49
7.4. Test Procedure	49
7.5. Test Results.....	49
8. POWER SPECTRAL DENSITY MEASUREMENT	52
8.1. Test Equipment.....	52
8.2. Block Diagram of Test Setup.....	52
8.3. Specification Limits (§15.247(e)).....	52
8.4. Test Results.....	52

9. EMISSION LIMITATIONS MEASUREMENT.....55
9.1. Test Equipment..... 55
9.2. Block Diagram of Test Setup..... 55
9.3. Specification Limits (§15.247(d))..... 55
9.4. Test Procedure 55
9.5. Test Results..... 56

10. DUTY CYCLE78
10.1. Test Equipment..... 78
10.2. Test Results 78

11. DEVIATION TO TEST SPECIFICATIONS79

TEST REPORT CERTIFICATION

Applicant : Philips Lighting(China) Investment Co., Ltd.
 Manufacturer : Philips Lighting(China) Investment Co., Ltd.
 EUT Description : LED Lamp
 FCC ID : 2AGBW9290013015X
 (A) Model No. : 9290013015
 (B) Brand : Philips
 (C) Power Supply : AC 110-130V, 50/60Hz
 (D) Test Voltage : AC 120V, 60Hz

Applicable Standards:

FCC RULES AND REGULATIONS PART 15 SUBPART C, Oct. 2015
ANSI C63.10: 2013

The device described above was tested by Audix Technology (Wujiang) Co., Ltd. EMC Dept. to determine the maximum emission levels emanating from the device. The maximum emission levels were compared to the FCC Part 15 subpart C section 15.207, 15.209&15.247 limits.

The measurement results are contained in this test report and Audix Technology (Wujiang) Co., Ltd. EMC Dept. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this test report shows that the EUT to be technically compliant with the FCC limits.

This test report applies to above tested sample only. This test report shall not be reproduced in part without written approval of Audix Technology (Wujiang) Co., Ltd. EMC Dept.

Date of Test: Nov.16~26, 2016

Date of Report: Dec.13, 2016

Prepared by

:



(Emma Hu/Assistant Administrator)

Reviewer


:



(Danny Sun/ Deputy Manager)

Approved & Authorized Signer

:



(Ken Lu/Assistant General Manager)

1. SUMMARY OF MEASUREMENTS AND RESULTS

The EUT has been tested according to the applicable standards and test results are referred as below.

Description of Test Item	Standard	Results	Remark
CONDUCTED EMISSION	FCC 47 CFR Part 15 Subpart C/ Section 15.207 And ANSI C63.10:2013	PASS	Minimum passing margin is 4.82 dB at 0.47 MHz
RADIATED EMISSION	FCC 47 CFR Part 15 Subpart C/ Section 15.209& Section 15.205 And ANSI C63.10:2013	PASS	Minimum passing margin is 13.12 dB at 42.61 MHz
6 dB BANDWIDTH	FCC 47 CFR Part 15 Subpart C/ Section 15.247(a)(2) And ANSI C63.10:2013	PASS	> 500kHz
OUTPUT POWER	FCC 47 CFR Part 15 Subpart C/ Section 15.247(b)(3) And ANSI C63.10:2013	PASS	Minimum passing margin is 25.60 dB at CH 11
BAND EDGES	FCC 47 CFR Part 15 Subpart C/ Section 15.247(d) And ANSI C63.10:2013	PASS	---
POWER SPECTRAL DENSITY	FCC 47 CFR Part 15 Subpart C/ Section 15.247(e) And ANSI C63.10:2013	PASS	Minimum passing margin is 9.736 dB at CH 11
EMISSION LIMITATIONS	FCC 47 CFR Part 15 Subpart C/ Section 15.247(d) And ANSI C63.10:2013	PASS	---

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Description	:	LED Lamp
Model No.	:	9290013015
FCC ID	:	2AGBW9290013015X
Brand	:	Philips
Applicant	:	Philips Lighting(China) Investment Co., Ltd. Building 9, Lane 888, Tian Lin Road, Minhang district, Shanghai, China
Manufacturer	:	Philips Lighting(China) Investment Co., Ltd. Building 9, Lane 888, Tian Lin Road, Minhang district, Shanghai, China
Radio Technology	:	IEEE 802.15.4 (ZigBee®)
Antenna Gain	:	5dBi
Fundamental Range	:	2405 MHz -2480MHz
Tested Frequency	:	2405MHz (CH11) 2450MHz (CH20) 2475MHz (CH25) 2480MHz (CH26)
Channel Setting Method	:	Channel is changed according to EUT's power on or power off.
Highest Working Frequency	:	2.4GHz
Modulation type	:	O-QPSK
Date of Receipt of Sample	:	Nov.03, 2016
Date of Test	:	Nov.16~26, 2016

2.2. Description of Test Facility

Name of Firm : **Audix Technology (Wujiang) Co., Ltd. EMC Dept.**

Site Location : No. 1289 Jiangxing East Road, the Eastern Part of Wujiang Economic Development Zone Jiangsu China 215200

Test Facilities : **No.1 Conducted Shielding Enclosure**
No.1 3m Semi-anechoic Chamber
 Date of Validity: Mar.30, 2018
 FCC Registration No.: 897661
 IC Registration No.:5183D-2

RF Fully Chamber

NVLAP Lab Code : 200786-0
 Valid until on Sep.30, 2017
 (NVLAP is a signatory member of ILAC MRA)
 Remark: This report shall not be imply endorsement, certification or approval by NVLAP, NIST, or any agency of the U.S. Federal Government.

2.3. Measurement Uncertainty

Test Item	Range Frequency	Uncertainty
No.1 Conducted Disturbance Measurement	0.15MHz ~ 30MHz	± 2.65dB
Radiated Disturbance Measurement (At 3m Chamber)	30MHz ~ 300MHz	± 3.18dB
	300MHz ~ 1GHz	± 3.12dB
Radiated Disturbance Measurement (At 3m Chamber)	1GHz ~ 6GHz	± 4.56dB
	6GHz ~ 18GHz	± 5.03dB

Remark: Uncertainty = $ku_c(y)$

Test Item	Uncertainty
6 dB Bandwidth	± 0.16 MHz
Maximum Peak Output Power	± 0.12dB
Band Edges	± 0.38dB
Power Spectral Density	± 0.38dB
Emission Limitations	± 0.38dB


Remark: Uncertainty = $ku_c(y)$

3. CONDUCTED EMISSION MEASUREMENT

3.1. Test Equipment

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Test Receiver	R & S	ESCI	100839	2016-01-05	2017-01-04
2.	A.M.N	R&S	ESH2-Z5	100153	2016-05-15	2017-05-14
3.	Pulse Limiter	R&S	ESH3-Z2	100605	2016-01-05	2017-01-04
4.	RF Cable	Harbour Industries	RG400	002	2016-01-05	2017-01-04
5.	Software	Audix/e3(6.7.0313)				

3.2. Block Diagram of Test Setup



3.3. Power line Conducted Emission Limit

(FCC Part 15, Section 15.207, Class B)

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level	Average Level
150kHz ~ 500kHz	66 ~ 56 dB μ V	56 ~ 46 dB μ V
500kHz ~ 5MHz	56 dB μ V	46 dB μ V
5MHz ~ 30MHz	60 dB μ V	50 dB μ V

Remark1: If the average limit is met when using a Quasi-Peak detector, the EUT shall be deemed to meet both limits and measurement with the average detector is unnecessary.

2: The lower limit applies at the band edges.

3.4. Test Procedure

The measuring process is according to ANSI C63.10-2013 and laboratory internal procedure TKC-301-004. (For FCC Part15 Subpart C)

In the conducted emission measurement, the EUT and all peripheral devices were set up on a non-metallic table which was 0.8 meter height above the ground plane, and 0.4 meter far away from the vertical plane. The mains cable of the EUT connected to one Artificial Main Network(AMN). All other unit of the EUT and AE connected to a second Line Impedance Stabilization Network(L.I.S.N.). The telecommunication cable connected to the AE through a Impedance Stabilization Network(ISN) which terminated a 50Ω resistor. For the measurement, the A.M.N measuring port was terminated by a 50Ω measuring equipment and the second L.I.S.N measuring port was terminated by a 50Ω terminator. All measurements were done between the phase lead and the reference ground, and between the neutral lead and the reference ground. All cables or wires placement were verified to find out the maximum emission.

The bandwidth of measuring receiver was set at 9 kHz.

The required frequency band (0.15 MHz ~ 30 MHz) was pre-scanned with peak detector; the final measurement was measured with quasi-peak detector and average detector. (If the average limit is met when using a quasi-peak detector, the average detector is unnecessary).

The emission level is calculated automatically by the test system which uses the following equation:

$$\text{Emission level (dB}\mu\text{V)} = \text{Reading (dB}\mu\text{V)} + \text{A.M.N factor (dB)} + \text{Cable loss (dB)}.$$

(Cable loss includes pulse limiter loss)

3.5. Conducted Emission Measurement Results

For FCC Part15 Subpart C

PASSED.

EUT was performed during this section testing and all the test results are attached in next pages.

Test Date : Nov.26, 2016

Temperature : 20.6

Humidity : 51%

Mode	Test Condition	Reference Test Data No.	
		Neutral	Line
1	TX CH11 2405MHz	# 5	# 6
2	TX CH20 2450MHz	# 7	# 8
3	TX CH25 2475MHz	# 9	# 10


NOTE 1- ‘ ’ means the worst test mode.

NOTE 2- The worst emission is detected at 0.47 MHz with emission level of 51.66 dB (μV) and with QP detector (Limit is 56.48 dB (μV)), when the Neutral of the EUT is connected to AMN.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,Eastern Part of WuJiang
 Economic Development Zone,JiangSu,China
 Tel:0512-63403993 Fax:0512-63403339

Data: 5 File: F:\2016Test Data\Report\11\G1611015.EM6 (10)



Site no. : No.1 Conducted shielding Enclosure Data no. : 5
 AMN/LISN : ESH2-Z5-1605 Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Env. / Ins. : 20.6*C&51%/ESCI Engineer : KM.Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating : 120Vac/60Hz
 Test mode : TX CH11 2405MHz
 Memo


	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	0.15	9.89	39.90	49.94	65.94	16.00	QP
2	0.15	0.15	9.89	25.60	35.64	55.94	20.30	Average
3	0.30	0.15	9.90	41.80	51.85	60.13	8.28	QP
4	0.30	0.15	9.90	25.60	35.65	50.13	14.48	Average
5	0.46	0.16	9.90	39.90	49.96	56.71	6.75	QP
6	0.46	0.16	9.90	23.30	33.36	46.71	13.35	Average
7	0.61	0.17	9.90	36.90	46.97	56.00	9.03	QP
8	0.61	0.17	9.90	20.20	30.27	46.00	15.73	Average
9	1.19	0.19	9.91	32.60	42.70	56.00	13.30	QP
10	1.19	0.19	9.91	16.60	26.70	46.00	19.30	Average
11	1.36	0.19	9.92	30.30	40.41	56.00	15.59	QP
12	1.36	0.19	9.92	11.60	21.71	46.00	24.29	Average

Remarks:
 1.Emission Level= AMN factor + Cable loss(Include Pulse Att) + Reading .



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,Eastern Part of WuJiang
 Economic Development Zone,JiangSu,China
 Tel:0512-63403993 Fax:0512-63403339

Data: 6 File: F:\2016Test Data\Report\11\G16111015.EM6 (10)



Site no. : No.1 Conducted shielding Enclosure Data no. : 6
 AMN/LISN : ESH2-Z5-1605 Phase : LINE
 Limit : FCC PART 15B QP
 Env. / Ins. : 20.6*C&51%/ESCI Engineer : KM.Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating : 120Vac/60Hz
 Test mode : TX CH11 2405MHz
 Memo


	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	0.16	9.89	39.90	49.95	65.94	15.99	QP
2	0.15	0.16	9.89	23.80	33.85	55.94	22.09	Average
3	0.30	0.16	9.90	40.60	50.66	60.30	9.64	QP
4	0.30	0.16	9.90	25.20	35.26	50.30	15.04	Average
5	0.46	0.17	9.90	36.90	46.97	56.73	9.76	QP
6	0.46	0.17	9.90	20.30	30.37	46.73	16.36	Average
7	0.58	0.17	9.90	32.21	42.28	56.00	13.72	QP
8	0.58	0.17	9.90	16.61	26.68	46.00	19.32	Average
9	1.06	0.19	9.91	16.80	26.90	46.00	19.10	Average
10	1.06	0.19	9.91	30.20	40.30	56.00	15.70	QP
11	1.21	0.20	9.91	13.60	23.71	46.00	22.29	Average
12	1.21	0.20	9.91	30.60	40.71	56.00	15.29	QP

Remarks:
 1.Emission Level= AMN factor + Cable loss(Include Pulse Att) + Reading .



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,Eastern Part of WuJiang
 Economic Development Zone,JiangSu,China
 Tel:0512-63403993 Fax:0512-63403339

Data: 7 File: F:\2016Test Data\Report\11\G1611015.EM6 (10)



Site no. : No.1 Conducted shielding Enclosure Data no. : 7
 AMN/LISN : ESH2-Z5-1605 Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Env. / Ins. : 20.6*C&51%/ESCI Engineer : KM.Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating : 120Vac/60Hz
 Test mode : TX CH20 2450MHz
 Memo


Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	9.89	38.60	48.64	65.94	17.30	QP
2	0.15	9.89	24.60	34.64	55.94	21.30	Average
3	0.31	9.90	42.30	52.35	59.92	7.57	QP
4	0.31	9.90	25.90	35.95	49.92	13.97	Average
5	0.47	9.90	41.60	51.66	56.48	4.82	QP
6	0.47	9.90	22.90	32.96	46.48	13.52	Average
7	0.63	9.90	32.60	42.67	56.00	13.33	QP
8	0.63	9.90	16.60	26.67	46.00	19.33	Average
9	1.09	9.91	18.50	28.59	46.00	17.41	Average
10	1.09	9.91	31.20	41.29	56.00	14.71	QP
11	1.27	9.91	16.60	26.70	46.00	19.30	Average
12	1.27	9.91	30.60	40.70	56.00	15.30	QP

Remarks:
 1.Emission Level= AMN factor + Cable loss(Include Pulse Att) + Reading .



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,Eastern Part of WuJiang
 Economic Development Zone,JiangSu,China
 Tel:0512-63403993 Fax:0512-63403339

Data: 8 File: F:\2016Test Data\Report\11\G16111015.EM6 (10)



Site no. : No.1 Conducted shielding Enclosure Data no. : 8
 AMN/LISN : ESH2-Z5-1605 Phase : LINE
 Limit : FCC PART 15B QP
 Env. / Ins. : 20.6*C&51%/ESCI Engineer : KM.Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating : 120Vac/60Hz
 Test mode : TX CH20 2450MHz
 Memo


	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.16	0.16	9.89	37.90	47.95	65.62	17.67	QP
2	0.16	0.16	9.89	23.90	33.95	55.62	21.67	Average
3	0.32	0.16	9.90	39.90	49.96	59.79	9.83	QP
4	0.32	0.16	9.90	22.60	32.66	49.79	17.13	Average
5	0.47	0.17	9.90	39.90	49.97	56.53	6.56	QP
6	0.47	0.17	9.90	23.30	33.37	46.53	13.16	Average
7	0.63	0.18	9.90	31.20	41.28	56.00	14.72	QP
8	0.63	0.18	9.90	14.60	24.68	46.00	21.32	Average
9	1.09	0.19	9.91	19.80	29.90	46.00	16.10	Average
10	1.09	0.19	9.91	30.60	40.70	56.00	15.30	QP
11	1.25	0.20	9.91	15.50	25.61	46.00	20.39	Average
12	1.25	0.20	9.91	30.60	40.71	56.00	15.29	QP

Remarks:
 1.Emission Level= AMN factor + Cable loss(Include Pulse Att) + Reading .



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,Eastern Part of WuJiang
 Economic Development Zone,JiangSu,China
 Tel:0512-63403993 Fax:0512-63403339

Data: 9 File: F:\2016Test Data\Report\11\G1611015.EM6 (10)



Site no. : No.1 Conducted shielding Enclosure Data no. : 9
 AMN/LISN : ESH2-Z5-1605 Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Env. / Ins. : 20.6*C&51%/ESCI Engineer : KM.Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating : 120Vac/60Hz
 Test mode : TX CH25 2475MHz
 Memo


	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	0.15	9.89	25.50	35.54	56.00	20.46	Average
2	0.15	0.15	9.89	39.90	49.94	66.00	16.06	QP
3	0.30	0.15	9.90	38.90	48.95	60.13	11.18	QP
4	0.30	0.15	9.90	22.60	32.65	50.13	17.48	Average
5	0.44	0.16	9.90	39.90	49.96	57.08	7.12	QP
6	0.44	0.16	9.90	23.80	33.86	47.08	13.22	Average
7	0.60	0.17	9.90	18.80	28.87	46.00	17.13	Average
8	0.60	0.17	9.90	36.60	46.67	56.00	9.33	QP
9	1.19	0.19	9.91	33.30	43.40	56.00	12.60	QP
10	1.19	0.19	9.91	13.60	23.70	46.00	22.30	Average
11	3.72	0.26	9.96	29.19	39.41	56.00	16.59	QP
12	3.72	0.26	9.96	13.59	23.81	46.00	22.19	Average

Remarks:
 1.Emission Level= AMN factor + Cable loss(Include Pulse Att) + Reading .



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,Eastern Part of WuJiang
 Economic Development Zone,JiangSu,China
 Tel:0512-63403993 Fax:0512-63403339

Data: 10 File: F:\2016Test Data\Report\11\G1611015.EM6 (10)



Site no. : No.1 Conducted shielding Enclosure Data no. : 10
 AMN/LISN : ESH2-Z5-1605 Phase : LINE
 Limit : FCC PART 15B QP
 Env. / Ins. : 20.6*C&51%/ESCI Engineer : KM.Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating : 120Vac/60Hz
 Test mode : TX CH25 2475MHz
 Memo

	Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	0.16	9.89	36.90	46.95	65.89	18.94	QP
2	0.15	0.16	9.89	22.60	32.65	55.89	23.24	Average
3	0.30	0.16	9.90	40.90	50.96	60.30	9.34	QP
4	0.30	0.16	9.90	25.50	35.56	50.30	14.74	Average
5	0.45	0.17	9.90	39.90	49.97	56.84	6.87	QP
6	0.45	0.17	9.90	21.60	31.67	46.84	15.17	Average
7	0.61	0.18	9.90	33.90	43.98	56.00	12.02	QP
8	0.61	0.18	9.90	16.90	26.98	46.00	19.02	Average
9	1.06	0.19	9.91	15.50	25.60	46.00	20.40	Average
10	1.06	0.19	9.91	30.30	40.40	56.00	15.60	QP
11	1.19	0.20	9.91	13.30	23.41	46.00	22.59	Average
12	1.19	0.20	9.91	30.60	40.71	56.00	15.29	QP

Remarks:
 1.Emission Level= AMN factor + Cable loss(Include Pulse Att) + Reading .

4. RADIATED EMISSION MEASUREMENT


4.1. Test Equipment

The following test equipment was used during the radiated emission measurement:
At 3m Semi-Anechoic Chamber


Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Preamplifier	Agilent	8449B	3008A02233	2016-01-05	2017-01-04
2.	Preamplifier	Agilent	8447D	2944A10921	2016-07-03	2017-07-02
3.	PXA Signal Analyzer	Agilent	N9030A	MY53120367	2016-05-15	2017-05-14
4.	Test Receiver	R&S	ESCI	100361	2016-01-05	2017-01-04
5.	Bi-log Antenna	Schaffner	CBL6112D	22252	2016-02-02	2017-02-01
6.	Horn Antenna	EMCO	3115	62959	2016-06-20	2017-06-19
7.	Horn Antenna	ETS	3116	62641	2016-09-30	2017-09-29
8.	RF Cable #1	Yuhang CSYH	cable-3m	001(0.5m)	2016-01-05	2017-01-04
9.	RF Cable #2	Yuhang CSYH	cable-3m	002(0.5m)	2016-01-05	2017-01-04
10.	RF Cable #3	Yuhang CSYH	cable-3m	003(3.0m)	2016-01-05	2017-01-04
11.	Software	Audix/e3(6.7.0313)				

4.2. Block Diagram of Test Setup


4.2.1. Block Diagram of Test Setup between EUT and simulators



4.2.2. No. 1 3m Semi-Anechoic Chamber Setup Diagram (Test distance:3m) for 30-1000MHz



4.2.3. No. 1 3m Semi-Anechoic Chamber Setup Diagram (Test distance: 3m) for above 1GHz



4.3. Radiated Emission Limits

Radiated Emission Limits (FCC Part15 C, section 15.209, CISPR22)

Frequency MHz	Distance Meters	Field Strengths Limits
		dB μ V/m
30 ~ 88	3	40
88 ~ 216	3	43.5
216 ~ 960	3	46
Above 960	3	54
Above 1000	3	74 (Peak) 54 (Average)

Remark : (1) Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
 (2)The tighter limit applies at the edge between two frequency bands.

4.4. Test Procedure

The measuring process is according to ANSI C63.10-2013 and laboratory internal procedure TKC-301-001. (For FCC Part15 Subpart C)

In the radiated disturbance measurement, the EUT and all simulators were set up on a non-metallic turn table which was 0.8 meter above the ground plane. Measurement distance between EUT and receiving antennas was set at 3 meters at 30MHz~1GHz and 3 meters at 1GHz~6GHz. The measurement distance is the shortest horizontal distance between an imaginary circular periphery which consists of EUT periphery and cables and the reference point of the antenna. During the radiated measurement, the EUT was rotated 360° and receiving antennas were moved from 1 ~ 4 meters for finding maximum emission. Two receiving antennas were used for both horizontal and vertical polarization detection for 30MHz~1GHz, One receiving antennas was used for both horizontal and vertical polarization detection for 1GHz~6GHz (the absorbing material was added when testing of 1GHz~6GHz was done). All cables or wires placement were verified to find out the maximum emission.

The bandwidth of measuring receiver (or spectrum analyzer) was set to:

RBW (120 kHz), VBW (300 kHz) for QP detector below 1GHz
 RBW (1 MHz), VBW (1MHz) for Peak detector above 1GHz
 RBW (1 MHz), VBW (10Hz) for AV detector above 1GHz

The frequency range from 30MHz to 10th harmonic(25GHz) are checked, and no any emissions were found from 18GHz to 25GHz.

The emission level is calculated automatically by the test system which uses the following equation :

- For 30MHz-1GHz measurement:
 Emission Level (dB μ V/m) = Reading (dB μ V)+Antenna Factor (dB/m)+Cable Loss (dB)
- For Above 1GHz measurement:
 Emission Level (dB μ V/m) = Reading (dB μ V)+Antenna Factor (dB/m)+Cable Loss(dB)
 -Pre-amplifier factor (dB)

The three orthogonal planes have been all tested, and the data of the worst mode XZ plan(in Horizontal) & XY plan(in Vertical) is shown in the report.

4.5. Measurement Results

PASSED

4.5.1. For Restricted Bands:

The EUT was tested in restricted bands and all the test results are listed in section 5.7 & 5.8.
(The restricted bands defined in part 15.205(a))

For Frequency range : below 1GHz

No.	Test Mode and Frequency		Reference Test Data No.	
			Horizontal	Vertical
1.	Transmitting	2405MHz (Channel 11)	# 5	# 6
2.		2450MHz (Channel 20)	# 7	# 8
3.		2475MHz (Channel 25)	# 9	# 10

For Frequency range : above 1GHz

No.	Test Mode and Frequency		Reference Test Data No.	
			Horizontal	Vertical
1.	Transmitting	2405MHz (Channel 11)	# 23	# 24
2.		2450MHz (Channel 20)	# 25	# 26
3.		2475MHz (Channel 25)	# 27	# 28

4.5.2. For Band Edge Emission

The EUT was tested in restricted bands and all the test results are listed in section 5.9. The restricted bands defined in part 15.205(a)


No.	Test Mode and Frequency		Reference Test Data No.	
			Horizontal	Vertical
1.	Transmitting	2405MHz (Channel 11)	# 11, # 13	# 12, # 14
2.		2475MHz (Channel 25)	# 15, # 17	# 16, # 18
3.		2480MHz (Channel 26)	# 19, # 21	# 20, # 22

4.6. Restricted Bands Measurement Results (For Below 1GHz)



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 5 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m chamber Data NO. :5
 Dis. / Ant. : 3m 6112D(22252)-1602 Ant. pol. : HORIZONTAL
 Limit : FCC PART15 B QP
 Env. / Ins. : 19.8*CS58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating : 120Vac/60Hz
 Test Mode : TX CH11 2405MHz
 Memo :


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	30.00	19.70	0.47	21.65	14.47	40.00	25.53	QP
2	149.31	11.35	1.06	31.73	17.14	43.50	26.36	QP
3	378.23	15.78	1.81	25.91	16.35	46.00	29.65	QP
4	614.91	19.28	2.40	23.79	17.50	46.00	28.50	QP
5	756.53	20.36	2.72	30.86	26.25	46.00	19.75	QP
6	960.23	22.22	3.22	28.58	27.00	54.00	27.00	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 6 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m chamber
 Dis. / Ant. : 3m 6112D(22252)-1602
 Limit : FCC PART15 B QP
 Env. / Ins. : 19.8*C&58%/ESCI
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating : 120Vac/60Hz
 Test Mode : TX CH11 2405MHz
 Memo :
 Data NO. :6
 Ant. pol. : VERTICAL
 Engineer : KM Tong


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	32.91	18.83	0.49	32.28	24.26	40.00	15.74	QP
2	42.61	13.43	0.56	39.81	26.48	40.00	13.52	QP
3	378.23	15.78	1.81	39.01	29.45	46.00	16.55	QP
4	756.53	20.36	2.72	33.16	28.55	46.00	17.45	QP
5	948.59	22.08	3.19	26.36	24.58	46.00	21.42	QP
6	960.23	22.22	3.22	28.55	26.97	54.00	27.03	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 7 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m chamber
 Dis. / Ant. : 3m 6112D(22252)-1602
 Limit : FCC PART15 B QP
 Env. / Ins. : 19.8*C&58%/ESCI
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating : 120Vac/60Hz
 Test Mode : TX CH20 2450MHz
 Memo :
 Data NO. : 7
 Ant. pol. : HORIZONTAL
 Engineer : KM Tong


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.00	19.70	0.47	21.90	14.72	40.00	25.28	QP
2	66.86	6.44	0.70	32.84	12.71	40.00	27.29	QP
3	149.31	11.35	1.06	29.13	14.54	43.50	28.96	QP
4	476.20	17.60	2.07	23.94	15.86	46.00	30.14	QP
5	591.63	19.03	2.35	24.82	18.21	46.00	27.79	QP
6	960.23	22.22	3.22	27.35	25.77	54.00	28.23	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel:(0512)63403993 Fax:(0512)63403993

Data: 8 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m chamber
 Dis. / Ant. : 3m 6112D(22252)-1602
 Limit : FCC PART15 B QP
 Env. / Ins. : 19.8*C&58%/ESCI
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating : 120Vac/60Hz
 Test Mode : TX CH20 2450MHz
 Memo :
 Data NO. :8
 Ant. pol. : VERTICAL
 Engineer : KM Tong


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.00	19.70	0.47	30.50	23.32	40.00	16.68	QP
2	42.61	13.43	0.56	40.21	26.88	40.00	13.12	QP
3	53.28	7.88	0.63	44.24	25.46	40.00	14.54	QP
4	378.23	15.78	1.81	38.53	28.97	46.00	17.03	QP
5	756.53	20.36	2.72	35.32	30.71	46.00	15.29	QP
6	960.23	22.22	3.22	28.64	27.06	54.00	26.94	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 9 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m chamber
 Dis. / Ant. : 3m 6112D(22252)-1602
 Limit : FCC PART15 B QP
 Env. / Ins. : 19.8*C&58%/ESCI
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating : 120Vac/60Hz
 Test Mode : TX CH25 2475MHz
 Memo :
 Data NO. : 9
 Ant. pol. : HORIZONTAL
 Engineer : KM Tong

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	30.00	19.70	0.47	22.58	15.40	40.00	24.60	QP
2	63.95	6.32	0.68	36.03	15.76	40.00	24.24	QP
3	146.40	11.57	1.05	31.89	17.50	43.50	26.00	QP
4	533.43	18.47	2.21	25.72	18.47	46.00	27.53	QP
5	756.53	20.36	2.72	30.42	25.81	46.00	20.19	QP
6	960.23	22.22	3.22	26.32	24.74	54.00	29.26	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel:(0512)63403993 Fax:(0512)63403993

Data: 10 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)

Date: 2016-11-16



Site NO. : 3m chamber
 Dis. / Ant. : 3m 6112D(22252)-1602
 Limit : FCC PART15 B QP
 Env. / Ins. : 19.8*C&58%/ESCI
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating : 120Vac/60Hz
 Test Mode : TX CH25 2475MHz
 Memo :
 Data NO. :10
 Ant. pol. : VERTICAL
 Engineer : KM Tong

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	42.61	13.43	0.56	39.57	26.24	40.00	13.76	QP
2	53.28	7.88	0.63	44.36	25.58	40.00	14.42	QP
3	140.58	11.90	1.02	34.62	20.50	43.50	23.00	QP
4	378.23	15.78	1.81	40.40	30.84	46.00	15.16	QP
5	756.53	20.36	2.72	33.65	29.04	46.00	16.96	QP
6	960.23	22.22	3.22	31.06	29.48	54.00	24.52	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

4.7. Restricted Bands Measurement Results (For Above 1GHz)



Audix Technology(Wujiang) Co., Ltd.
 No.1289, Jiang Xing East Road, The Eastern Part of Wu Jiang
 Economic Development Zone, JiangSu, China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 23 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28) Date: 2016-11-16



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 23
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 C PK
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M-N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH11 2405MHz
 Memo :


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2411.00	29.05	5.09	92.31	34.50	91.95	74.00	-17.95	Peak
2	7216.27	36.08	9.00	33.20	34.04	44.24	54.00	9.76	Average
3	7222.00	36.08	9.00	41.55	34.04	52.59	74.00	21.41	Peak
4	11251.00	39.65	11.38	35.73	33.68	53.08	74.00	20.92	Peak
5	11255.34	39.65	11.38	23.18	33.68	40.53	54.00	13.47	Average
6	12032.24	41.73	11.55	22.38	33.74	41.92	54.00	12.08	Average
7	12033.00	41.73	11.55	34.17	33.74	53.71	74.00	20.29	Peak
8	13733.00	41.75	12.70	32.77	31.84	55.38	74.00	18.62	Peak
9	13734.64	41.75	12.70	21.26	31.84	43.87	54.00	10.13	Average
10	14447.00	43.40	12.99	30.79	32.20	54.98	74.00	19.02	Peak
11	14449.89	43.40	12.99	21.75	32.20	45.94	54.00	8.06	Average
12	17813.00	45.60	13.81	28.47	32.90	54.98	74.00	19.02	Peak
13	17815.33	45.60	13.81	16.56	32.90	43.07	54.00	10.93	Average

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 24 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 24
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : VERTICAL
 Limit : FCC PART 15 C PK
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH11 2405MHz
 Memo :


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2411.00	29.05	5.09	87.15	34.50	86.79	74.00	-12.79	Peak
2	8495.29	39.30	9.78	28.29	34.26	43.11	54.00	10.89	Average
3	8497.00	39.30	9.78	38.15	34.26	52.97	74.00	21.03	Peak
4	11812.00	41.44	11.48	34.43	33.78	53.57	74.00	20.43	Peak
5	11815.42	41.44	11.48	24.65	33.78	43.79	54.00	10.21	Average
6	13682.00	41.61	12.67	32.53	31.88	54.93	74.00	19.07	Peak
7	13685.39	41.61	12.67	21.28	31.88	43.68	54.00	10.32	Average
8	15280.00	40.11	13.54	34.18	33.28	54.55	74.00	19.45	Peak
9	15281.64	40.11	13.54	23.95	33.28	44.32	54.00	9.68	Average
10	17184.00	42.65	13.89	31.63	32.84	55.33	74.00	18.67	Peak
11	17185.39	42.65	13.89	21.59	32.84	45.29	54.00	8.71	Average
12	17862.19	45.82	13.80	20.27	32.90	46.99	54.00	7.01	Average
13	17864.00	45.82	13.80	28.51	32.90	55.23	74.00	18.77	Peak

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 25 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 25
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 C PK
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH20 2450MHz
 Memo :


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2445.00	28.83	5.15	91.08	34.50	90.56	74.00	-16.56	Peak
2	4893.00	33.03	7.37	39.65	33.94	46.11	74.00	27.89	Peak
3	4894.25	33.03	7.37	33.61	33.94	40.07	54.00	13.93	Average
4	7358.00	36.44	9.10	41.55	34.05	53.04	74.00	20.96	Peak
5	7359.25	36.44	9.10	33.26	34.05	44.75	54.00	9.25	Average
6	11948.00	41.78	11.50	34.25	33.80	53.73	74.00	20.27	Peak
7	11950.19	41.78	11.50	22.95	33.80	42.43	54.00	11.57	Average
8	12849.00	40.06	12.19	34.81	32.66	54.40	74.00	19.60	Peak
9	12851.26	40.06	12.19	23.97	32.66	43.56	54.00	10.44	Average
10	14243.00	42.98	12.92	30.34	31.92	54.32	74.00	19.68	Peak
11	14245.78	42.98	12.92	20.20	31.92	44.18	54.00	9.82	Average
12	16690.15	40.77	14.09	21.86	33.18	43.54	54.00	10.46	Average
13	16691.00	40.77	14.09	32.42	33.18	54.10	74.00	19.90	Peak

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 26 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 26
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : VERTICAL
 Limit : FCC PART 15 C PK
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH20 2450MHz
 Memo :


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2445.00	28.83	5.15	89.85	34.50	89.33	74.00	-15.33	Peak
2	7358.00	36.44	9.10	39.55	34.05	51.04	74.00	22.96	Peak
3	7359.62	36.44	9.10	29.12	34.05	40.61	54.00	13.39	Average
4	13305.48	40.80	12.48	22.44	32.19	43.53	54.00	10.47	Average
5	13308.00	40.80	12.48	32.94	32.19	54.03	74.00	19.97	Peak
6	13935.62	42.31	12.81	18.94	31.66	42.40	54.00	11.60	Average
7	13937.00	42.31	12.81	32.22	31.66	55.68	74.00	18.32	Peak
8	14770.00	42.22	13.10	31.66	32.67	54.31	74.00	19.69	Peak
9	14775.28	42.22	13.10	18.94	32.67	41.59	54.00	12.41	Average
10	16655.28	40.67	14.10	23.58	33.21	45.14	54.00	8.86	Average
11	16657.00	40.67	14.10	33.80	33.21	55.36	74.00	18.64	Peak
12	17930.76	46.11	13.79	19.45	32.91	46.44	54.00	7.56	Average
13	17932.00	46.11	13.79	28.71	32.91	55.70	74.00	18.30	Peak

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel:(0512)63403993 Fax:(0512)63403993

Data: 27 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 27
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 C PK
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH25 2475MHz
 Memo :


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.00	28.61	5.18	91.66	34.49	90.96	74.00	-16.96	Peak
2	4944.00	33.12	7.39	40.22	33.93	46.80	74.00	27.20	Peak
3	4945.69	33.12	7.39	32.60	33.93	39.18	54.00	14.82	Average
4	7426.00	36.62	9.15	42.88	34.06	54.59	74.00	19.41	Peak
5	7427.58	36.62	9.15	32.61	34.06	44.32	54.00	9.68	Average
6	11895.35	41.65	11.49	24.75	33.79	44.10	54.00	9.90	Average
7	11897.00	41.65	11.49	34.26	33.79	53.61	74.00	20.39	Peak
8	13801.00	41.94	12.74	31.59	31.77	54.50	74.00	19.50	Peak
9	13805.29	41.94	12.74	20.26	31.77	43.17	54.00	10.83	Average
10	15059.00	40.91	13.24	32.89	33.05	53.99	74.00	20.01	Peak
11	15061.28	40.91	13.24	21.74	33.05	42.84	54.00	11.16	Average
12	16350.35	39.84	14.27	22.15	33.56	42.70	54.00	11.30	Average
13	16351.00	39.84	14.27	34.05	33.56	54.60	74.00	19.40	Peak

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 28 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 28
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : VERTICAL
 Limit : FCC PART 15 C PK
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH25 2475MHz
 Memo :

Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1 2479.00	28.61	5.18	90.68	34.49	89.98	74.00	-15.98	Peak
2 8547.26	39.23	9.81	25.75	34.28	40.51	54.00	13.49	Average
3 8548.00	39.23	9.81	38.06	34.28	52.82	74.00	21.18	Peak
4 11404.00	40.28	11.41	35.26	33.71	53.24	74.00	20.76	Peak
5 11406.29	40.28	11.41	26.19	33.71	44.17	54.00	9.83	Average
6 12747.00	39.90	12.11	35.46	32.80	54.67	74.00	19.33	Peak
7 12750.25	39.90	12.11	24.32	32.80	43.53	54.00	10.47	Average
8 14700.25	42.54	13.07	22.64	32.57	45.68	54.00	8.32	Average
9 14702.00	42.54	13.07	31.81	32.57	54.85	74.00	19.15	Peak
10 16912.00	41.44	13.96	33.09	32.91	55.58	74.00	18.42	Peak
11 16915.48	41.44	13.96	21.65	32.91	44.14	54.00	9.86	Average
12 17265.33	43.09	13.88	21.28	32.85	45.40	54.00	8.60	Average
13 17269.00	43.09	13.88	31.35	32.85	55.47	74.00	18.53	Peak


Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.

4.8. Spurious Emission Measurement Results in Band Edge Emission (FCC Part 15, 15.205)



Audix Technology(Wujiang) Co., Ltd.
 No.1289, Jiang Xing East Road, The Eastern Part of Wu Jiang
 Economic Development Zone, JiangSu, China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 11 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28) Date: 2016-11-16



Site NO. : 3m Semi-Anechoic Chamber	Data NO. : 11
Dis. / Ant. : 3m 3115-62959-160620	Ant. pol. : HORIZONTAL
Limit : FCC PART 15 C PK	Engineer : KM Tong
Env. / Ins. : 19.8*C&58%/ESCI	
EUT : LED Lamp	
M/N : 9290013015	
Power Rating: 120Vac/60Hz	
Test Mode : TX CH11 2405MHz	
Memo :	


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	29.16	5.09	44.88	34.50	44.63	74.00	29.37	Peak
2	2404.55	29.05	5.09	95.97	34.50	95.61	74.00	-21.61	Peak

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 12 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 12
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : VERTICAL
 Limit : FCC PART 15 C PK
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH11 2405MHz
 Memo :


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	29.16	5.09	44.63	34.50	44.38	74.00	29.62	Peak
2	2404.55	29.05	5.09	91.34	34.50	90.98	74.00	-16.98	Peak

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 13 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 13
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 C AV
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH11 2405MHz
 Memo :


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	29.16	5.09	33.95	34.50	33.70	54.00	20.30	Average
2	2405.09	29.05	5.09	92.16	34.50	91.80	54.00	-37.80	Average

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 14 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 14
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : VERTICAL
 Limit : FCC PART 15 C AV
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH11 2405MHz
 Memo :


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	29.16	5.09	32.96	34.50	32.71	54.00	21.29	Average
2	2405.09	29.05	5.09	88.37	34.50	88.01	54.00	-34.01	Average

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 15 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber	Data NO. : 15
Dis. / Ant. : 3m 3115-62959-160620	Ant. pol. : HORIZONTAL
Limit : FCC PART 15 C PK	Engineer : KM Tong
Env. / Ins. : 19.8*C&58%/ESCI	
EUT : LED Lamp	
M/N : 9290013015	
Power Rating: 120Vac/60Hz	
Test Mode : TX CH25 2475MHz	
Memo :	


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2474.57	28.61	5.18	93.78	34.49	93.08	74.00	-19.08	Peak
2	2483.50	28.61	5.18	50.25	34.49	49.55	74.00	24.45	Peak

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 16 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 16
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : VERTICAL
 Limit : FCC PART 15 C PK
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH25 2475MHz
 Memo :

	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2475.55	28.61	5.18	93.59	34.49	92.89	74.00	-18.89	Peak
2	2483.50	28.61	5.18	48.46	34.49	47.76	74.00	26.24	Peak

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.




Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 17

File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)

Date: 2016-11-16



Site NO. : 3m Semi-Anechoic Chamber
 Dis. / Ant. : 3m 3115-62959-160620
 Limit : FCC PART 15 C AV
 Env. / Ins. : 19.8*C&58%/ESCI
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH25 2475MHz
 Memo :
 Data NO. : 17
 Ant. pol. : HORIZONTAL
 Engineer : KM Tong

	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2475.06	28.61	5.18	90.80	34.49	90.10	54.00	-36.10	Average
2	2483.50	28.61	5.18	37.33	34.49	36.63	54.00	17.37	Average

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.




Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 18

File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)

Date: 2016-11-16



Site NO. : 3m Semi-Anechoic Chamber
 Dis. / Ant. : 3m 3115-62959-160620
 Limit : FCC PART 15 C AV
 Env. / Ins. : 19.8*C&58%/ESCI
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH25 2475MHz
 Memo :

Data NO. : 18
 Ant. pol. : VERTICAL
 Engineer : KM Tong


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2475.06	28.61	5.18	92.24	34.49	91.54	54.00	-37.54	Average
2	2483.50	28.61	5.18	39.41	34.49	38.71	54.00	15.29	Average

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 19 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 19
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 C PK
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH26 2480MHz
 Memo :


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.61	28.61	5.18	86.79	34.49	86.09	74.00	-12.09	Peak
2	2483.50	28.61	5.18	56.68	34.49	55.98	74.00	18.02	Peak

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 20 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 20
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : VERTICAL
 Limit : FCC PART 15 C PK
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH26 2480MHz
 Memo :


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.54	28.61	5.18	87.10	34.49	86.40	74.00	-12.40	Peak
2	2483.50	28.61	5.18	55.60	34.49	54.90	74.00	19.10	Peak

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 21 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 21
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 C AV
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH26 2480MHz
 Memo :


	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.03	28.61	5.18	85.25	34.49	84.55	54.00	-30.55	Average
2	2483.50	28.61	5.18	45.47	34.49	44.77	54.00	9.23	Average

Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Audix Technology(Wujiang)Co.,Ltd.
 No.1289,Jiang Xing East Road,The Eastern Part of Wu Jiang
 Economic Development Zone,JiangSu,China
 Tel: (0512) 63403993 Fax: (0512) 63403993

Data: 22 File: G:\Test Data\2016\Reports\11\G1611015.EM6 (28)



Site NO. : 3m Semi-Anechoic Chamber Data NO. : 22
 Dis. / Ant. : 3m 3115-62959-160620 Ant. pol. : VERTICAL
 Limit : FCC PART 15 C AV
 Env. / Ins. : 19.8*C&58%/ESCI Engineer : KM Tong
 EUT : LED Lamp
 M/N : 9290013015
 Power Rating: 120Vac/60Hz
 Test Mode : TX CH26 2480MHz
 Memo :

	Freq. (MHz)	Ant. Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Preamp Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.03	28.61	5.18	85.42	34.49	84.72	54.00	-30.72	Average
2	2483.50	28.61	5.18	45.59	34.49	44.89	54.00	9.11	Average


Remarks: 1. Emission Level= Ant.Factor + Cable Loss + Reading - Preamp.Factor.
 2. The emission levels that are 20dB below the official limit are not reported.

5. 6 dB BANDWIDTH MEASUREMENT

5.1. Test Equipment

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	PXA Signal Analyzer	Agilent	N9030A	MY53120367	2016-05-15	2017-05-14

5.2. Block Diagram of Test Setup



5.3. Specification Limits (§15.247(a)(2))

Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.

5.4. Test Procedure

The steps for the first option are as bellow:


- Set RBW = 100 kHz.
- Set the VBW [3 × RBW].
- Detector = peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.5. Test Results


PASSED. All the test results are attached in next pages.

Channel	Center Frequency(MHz)	6 dB Bandwidth(MHz)
11	2405	1.390
20	2450	1.550
25	2475	1.600


CH 11



CH 20



CH 25




6. OUTPUT POWER MEASUREMENT

6.1. Test Equipment

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	PXA Signal Analyzer	Agilent	N9030A	MY53120367	2016-05-15	2017-05-14

6.2. Block Diagram of Test Setup



6.3. Specification Limits (§15.247(b)(3))

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

6.4. Test Procedure

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW $\geq 3 \times$ RBW.
- d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle $< 98 \%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98 \%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

6.5. Test Results

PASSED. All the test results are attached in next pages.

Channel	Frequency	Power(dBm)	Limit(dBm)
11	2405	4.40	30
20	2450	4.08	30
25	2475	3.77	30
26	2480	-4.24	30

7. BAND EDGES MEASUREMENT

7.1. Test Equipment

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	PXA Signal Analyzer	Agilent	N9030A	MY53120367	2016-05-15	2017-05-14

7.2. Block Diagram of Test Setup

The same as section 5.2.

7.3. Specification Limits (§15.247(d))

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).


7.4. Test Procedure

The transmitter output was connected to the test receiver / spectrum analyzer. Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz with suitable frequency span including 100kHz bandwidth from band edge.


7.5. Test Results

PASSED. The testing data was attached in the next pages.


CH11



CH25



CH26



8. POWER SPECTRAL DENSITY MEASUREMENT

8.1. Test Equipment

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	PXA Signal Analyzer	Agilent	N9030A	MY53120367	2016-05-15	2017-05-14

8.2. Block Diagram of Test Setup

The same as section 5.2.

8.3. Specification Limits (§15.247(e))


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.4. Test Results


PASSED. All the test results are attached in next page.

Channel	Frequency(GHz)	Value(dBm/3kHz)
11	2.405	-1.736
20	2.450	-3.266
25	2.475	-2.935


CH 11



CH 20



CH 25



9. EMISSION LIMITATIONS MEASUREMENT

9.1. Test Equipment

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	PXA Signal Analyzer	Agilent	N9030A	MY53120367	2015-05-15	2017-05-14

9.2. Block Diagram of Test Setup

The same as section 5.2.

9.3. Specification Limits (§15.247(d))

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

9.4. Test Procedure

The transmitter output was connected to the spectrum analyzer. Set RBW = 100kHz, VBW \geq 300 kHz, scan up through 10th harmonic. All harmonics/spurs must be at least 30 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. The measurement guideline was according to KDB558074 v03r05.



9.5. Test Results



PASSED. All the test results are attached in next pages.



Channel	Frequency(MHz)	Amplitude(dBm)
11	88.93	-49.793
	2405.10	3.388
	1897.65	-43.422
	3208.70	-48.752
	5116.65	-55.549
	7153.10	-55.901
	10893.05	-56.557
	12552.60	-56.299
	14413.05	-55.961
	15584.05	-55.304
	18508.20	-54.053
	19437.40	-53.834
	22607.10	-52.164
	23913.35	-51.869
20	64.77	-51.044
	2450.10	2.104
	1895.35	-47.062
	3226.30	-48.840
	5049.05	-55.515
	7121.25	-56.277
	9167.90	-56.210
	11103.00	-56.567
	14001.55	-55.528
	15550.80	-55.970
	18386.40	-54.022
	19438.05	-54.095
	22744.70	-52.798
	23886.10	-51.060
25	50.47	-50.718
	2475.10	2.253
	3122.10	-48.875
	5818.30	-55.611



	8718.10	-55.525
	9688.45	-55.968
	12694.85	-56.564
	14264.50	-55.418
	15578.90	-55.518
	18445.60	-54.584
	19333.05	-53.225
	22743.70	-52.599
	23926.55	-51.886



CH 11



























CH 20





























CH 25















10.DUTY CYCLE


10.1. Test Equipment

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	PXA Signal Analyzer	Agilent	N9030A	MY53120367	2016-05-15	2017-05-14

10.2. Test Results

The measurement of duty cycle is 100%.

CH 25



11.DEVIATION TO TEST SPECIFICATIONS

【NONE】