



RF Exposure Evaluation Declaration

Product Name : LED lamp
Model No. : 9290022166
FCC ID : 2AGBW9290022166X
IC : 20812-2166X

Applicant : Signify (China) Investment Co., Ltd.
Address : Building no.9, Lane 888, Tianlin Road, Minhang
District, Shanghai 200233, China

Date of Receipt : May. 22, 2019
Issued Date : May. 24, 2019
Report No. : 1952138R-RF-US-P20V01
Report Version : V 1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by A2LA or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing & Certification (Suzhou) Co., Ltd.

Test Report Certification

Issued Date : May. 24, 2019

Report No. : 1952138R-RF-US-P20V01



Product Name : LED lamp
 Applicant : Signify (China) Investment Co., Ltd.
 Address : Building no.9, Lane 888, Tianlin Road, Minhang District,
 Shanghai 200233, China
 Manufacturer : Signify (China) Investment Co., Ltd.
 Address : Building no.9, Lane 888, Tianlin Road, Minhang District,
 Shanghai 200233, China
 Model No. : 9290022166
 FCC ID : 2AGBW9290022166X
 IC : 20812-2166X
 Brand Name : PHILIPS
 EUT Voltage : 110-130 Vac, 50-60 Hz, 9.5W
 Test Voltage : AC 120V/60Hz
 Applicable Standard : KDB 447498D01V06
 FCC Part1.1310
 RSS-102: Issue 5, 2015
 Test Result : Complied
 Performed Location : DEKRA Testing & Certification (Suzhou) Co., Ltd.
 No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006,
 Jiangsu, China
 TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
 FCC Registration Number: CN1199;ISED CAB identifier:
 CN0040

Documented By : Kathy Feng
 (Adm. Specialist: Kathy Feng)

Reviewed By : Frank he
 (Senior Project Manager: Frank He)

Approved By : Jack Zhang
 (Engineering Supervisor: Jack Zhang)

1. RF Exposure Evaluation

1.1.Limits

For FCC:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (Minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational/ Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100,000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/ Uncontrolled Exposures | | | | |
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100,000 | -- | -- | 1 | 30 |

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/ cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

For ISED:

According to RSS 102 Issue 5: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in RSS 102 Clause 4

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz) | Electric Field (V/m rms) | Magnetic Field (A/m rms) | Power Density (W/m²) | Reference Period (minutes) |
|---|----------------------------------|---|--|-----------------------------------|
| 0.003-10 ²¹ | 83 | 90 | - | Instantaneous* |
| 0.1-10 | - | 0.73/ <i>f</i> | - | 6** |
| 1.1-10 | 87/ <i>f</i> ^{0.5} | - | - | 6** |
| 10-20 | 27.46 | 0.0728 | 2 | 6 |
| 20-48 | 58.07/ <i>f</i> ^{0.25} | 0.1540/ <i>f</i> ^{0.25} | 8.944/ <i>f</i> ^{0.5} | 6 |
| 48-300 | 22.06 | 0.05852 | 1.291 | 6 |
| 300-6000 | 3.142 <i>f</i> ^{0.3417} | 0.008335 <i>f</i> ^{0.3417} | 0.02619 <i>f</i> ^{0.6834} | 6 |
| 6000-15000 | 61.4 | 0.163 | 10 | 6 |
| 15000-150000 | 61.4 | 0.163 | 10 | 616000/ <i>f</i> ^{1.2} |
| 150000-300000 | 0.158 <i>f</i> ^{0.5} | 4.21 x 10 ⁻⁴ <i>f</i> ^{0.5} | 6.67 x 10 ⁻⁵ <i>f</i> | 616000/ <i>f</i> ^{1.2} |
| <p>Note: <i>f</i> is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).</p> | | | | |

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 0.540 mW/cm² for 2.4GHz . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18 and 78% RH.

1.3. Test Result of RF Exposure Evaluation

| | | |
|-----------|---|------------------------|
| Product | : | LED Lamp |
| Test Item | : | RF Exposure Evaluation |
| Test Site | : | AC-6 |

● Antenna Information:

| | | | |
|----------------------|-------------------------------------|-----------|---|
| Antenna manufacturer | N/A | | |
| Antenna Delivery | <input checked="" type="checkbox"/> | 1*TX+1*RX | <input type="checkbox"/> 2*TX+2*RX <input type="checkbox"/> 3*TX+3*RX |
| Antenna technology | <input checked="" type="checkbox"/> | SISO | |
| | <input type="checkbox"/> | MIMO | <input type="checkbox"/> Basic |
| | | | <input type="checkbox"/> CDD |
| | | | <input type="checkbox"/> Beam-forming |
| Antenna Type | <input type="checkbox"/> | External | <input type="checkbox"/> Dipole |
| | <input checked="" type="checkbox"/> | Internal | <input type="checkbox"/> PIFA |
| | | | <input checked="" type="checkbox"/> PCB |
| | | | <input type="checkbox"/> Ceramic Chip Antenna |
| | | | <input type="checkbox"/> Metal plate type F antenna |
| Antenna Gain | -1.22dBi | | |

- **Power Density:**

The tune-up power is $\pm 0.5\text{dB}$, so the maximum conducted power we used to calculate RF exposure is **9.06dBm**.

| Test Mode | Frequency Band (MHz) | EIRP (dBm) | Limit of Power Density S(mW/cm ²) | | Power Density at R = 20 cm (mW/cm ²) |
|-----------|----------------------|------------|---|------|--|
| | | | FCC | IC | |
| Zigbee | 2400 ~ 2483.5 | 7.84 | 1 | 0.54 | 0.00121 |

Note:

1. The power density is 0.00121mW/cm² for LED Lamp without any other radio equipment.

————— The End —————