



TESTING LABORATORY  
CERTIFICATE#4323.01



FCC PART 15.247

## TEST REPORT

For

**Signify (China) Investment Co., Ltd.**

Building no.9, Lane 888, Tianlin Road, Minhang District, Shanghai, 200233, China

**FCC ID: 2AGBW9290022415AX**

<b>Report Type:</b> Original Report	<b>Product Type:</b> LED Lamp
<b>Test Engineer:</b>	Winnie Yang <i>Winnie Yang</i>
<b>Report Number:</b>	RXM200327061-00B
<b>Report Date:</b>	2020-04-20
<b>Reviewed By:</b>	Oscar Ye <i>Oscar Ye</i>
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## TABLE OF CONTENTS

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EQUIPMENT MODIFICATIONS .....	6
EUT EXERCISE SOFTWARE .....	6
SUPPORT EQUIPMENT LIST AND DETAILS .....	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP .....	9
<b>SUMMARY OF TEST RESULTS .....</b>	<b>11</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>12</b>
<b>FCC §1.1310 &amp; §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....</b>	<b>13</b>
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>14</b>
APPLICABLE STANDARD .....	14
ANTENNA CONNECTOR CONSTRUCTION .....	14
<b>FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS.....</b>	<b>15</b>
APPLICABLE STANDARD .....	15
EUT SETUP .....	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE .....	15
FACTOR & OVER LIMIT CALCULATION.....	16
TEST RESULTS SUMMARY .....	16
TEST DATA .....	16
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>21</b>
APPLICABLE STANDARD .....	21
EUT SETUP .....	21
EMI TEST RECEIVER SETUP.....	22
TEST PROCEDURE .....	22
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	22
TEST RESULTS SUMMARY .....	23
TEST DATA .....	23
<b>FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH .....</b>	<b>37</b>
APPLICABLE STANDARD .....	37
TEST PROCEDURE .....	37
TEST DATA .....	37
<b>FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....</b>	<b>42</b>
APPLICABLE STANDARD .....	42
TEST PROCEDURE .....	42
TEST DATA .....	42
<b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b>	<b>47</b>
APPLICABLE STANDARD .....	47

---

TEST PROCEDURE .....	47
TEST DATA .....	47
<b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>	<b>50</b>
APPLICABLE STANDARD .....	50
TEST PROCEDURE .....	50
TEST DATA .....	50

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Applicant:	Signify (China) Investment Co., Ltd.
Tested Model:	9290022415
Product Type:	LED Lamp
Power Supply:	AC 110~130V
RF Function:	BLE (1Mbps), BLE (2Mbps)
Operating Band/Frequency:	2402-2480MHz
Channel Number:	40
Channel Separation:	2MHz
Modulation Type	GFSK
Antenna Type:	PCB Antenna
Maximum Antenna Gain:	1.0 dBi

*\*All measurement and test data in this report was gathered from production sample serial number: 20200327061. (Assigned by the BACL. The EUT supplied by the applicant was received on 2020-03-27)*

### Objective

This report is prepared on behalf of *Signify (China) Investment Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions' rules.

The tests were performed in order to determine Compliant with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS submittal with FCC ID: 2AGBW9290022415AX.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliant Testing of Unlicensed Wireless Devices and FCC 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliant Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

### Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

### Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

**SYSTEM TEST CONFIGURATION**

**Description of Test Configuration**

Channel List for BLE mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
18	2438	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

**Equipment Modifications**

No modification was made to the EUT tested.

**EUT Exercise Software**


RF test tool: UartAssitant

Pre-scan with all the data rates, and the worst case was performed as below:


Mode	Data Rate	Frequency Range	Power Level Setting
BLE	1Mbps	2402-2480MHz	9
	2Mbps	2402-2480MHz	7

**Duty Cycle:**

**1Mbps:Middle Channel**



**2Mbps:Middle Channel**



Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
BLE(1Mbps)	67.36	0.421	2.38	1.72
BLE(2Mbps)	36.75	0.223	4.48	4.35

**Note:** “x” means the Duty Cycle.

**Support Equipment List and Details**

Manufacturer	Description	Model	Serial Number
/	/	/	/


**External I/O Cable**

Cable Description	Length(m)	From Port	To
Power Cable	1.0	EUT	AC Source




### Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§1.1310 & §2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test (Chamber 1#)</b>					
Rohde & Schwarz	EMI Test receiver	ESR	1316.3003K03-102454-Qd	2019-06-25	2020-06-24
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2017-12-26	2020-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Audix	Test Software	e3	V9	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
<b>Radiated Emission Test (Chamber 2#)</b>					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2019-05-30	2020-05-29
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2017-07-15	2020-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2020-01-17	2023-01-16
A.H.Systems, inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
SELECTOR	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2019-08-05	2020-08-04
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2019-05-30	2020-05-29
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2017-07-15	2020-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2020-01-17	2023-01-16
<b>RF Conducted Test</b>					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/0009	2019-12-14	2020-12-13
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Signify	RF Cable	Signify C01	/	Each Time	/
<b>Conducted Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2019-07-11	2020-07-10
Rohde & Schwarz	LISN	ENV216	3560655016	2019-12-14	2020-12-13
Audix	Test Software	e3	V9	---	---
Rohde & Schwarz	Pulse limiter	ESH3-Z2	0357.8810.54	2019-08-10	2020-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2019-08-15	2020-08-14

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

**Applicable Standard**

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

**Calculated Data:**

<b>Mode</b>	<b>Frequency Range (MHz)</b>	<b>Antenna Gain</b>		<b>Target Output Power</b>		<b>Evaluation Distance (cm)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>MPE Limit (mW/cm<sup>2</sup>)</b>
		<b>(dBi)</b>	<b>(numeric)</b>	<b>(dBm)</b>	<b>(mW)</b>			
Zigbee	2405~2480	1.0	1.26	9.00	7.94	20	0.0020	1.0
BLE	2402~2480	1.0	1.26	10.00	10.00	20	0.0025	1.0

- Note:** 1.The target output power was declared by the manufacturer.  
 2.The BLE & Zigbee can't support transmission simultaneously.

Conclusion: The device meets FCC MPE at 20 cm distance.

---

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliant with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
  - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **Antenna Connector Construction**

The EUT has a PCB antenna for BLE and the antenna gain is 1.0 dBi, which was permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.


**Result:** Compliant.

## FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC §15.207(a)

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

### Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the EUT was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Factor & Over Limit Calculation

The Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Attenuator. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Attenuator (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	22.3~25.2 °C
<b>Relative Humidity:</b>	49~50 %
<b>ATM Pressure:</b>	101.2~102.3 kPa


*The testing was performed by Winnie Yang from 2020-04-03 to 2020-04-14.*

*EUT operation mode: Transmitting in low channel (worst case)*



**BLE(1Mbps):**


**AC 120V/60 Hz, Line**



	Read	Limit	Over				
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.152	24.20	19.82	44.02	55.87	-11.85	Average
2	0.152	34.50	19.82	54.32	65.87	-11.55	QP
3	0.192	13.60	19.82	33.42	53.93	-20.51	Average
4	0.192	24.90	19.82	44.72	63.93	-19.21	QP
5	0.232	18.10	19.82	37.92	52.39	-14.47	Average
6	0.232	27.80	19.82	47.62	62.39	-14.77	QP
7	0.299	11.60	19.83	31.43	50.28	-18.85	Average
8	0.299	19.50	19.83	39.33	60.28	-20.95	QP
9	0.444	10.60	19.75	30.35	46.98	-16.63	Average
10	0.444	20.40	19.75	40.15	56.98	-16.83	QP
11	1.303	6.90	19.82	26.72	46.00	-19.28	Average
12	1.303	17.30	19.82	37.12	56.00	-18.88	QP

AC 120V/60 Hz, Neutral

Date: 2020-04-03




	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.153	24.30	19.82	44.12	55.82	-11.70	Average
2	0.153	34.40	19.82	54.22	65.82	-11.60	QP
3	0.230	20.10	19.82	39.92	52.44	-12.52	Average
4	0.230	29.20	19.82	49.02	62.44	-13.42	QP
5	0.299	9.40	19.83	29.23	50.28	-21.05	Average
6	0.299	18.30	19.83	38.13	60.28	-22.15	QP
7	0.510	10.30	19.76	30.06	46.00	-15.94	Average
8	0.510	20.70	19.76	40.46	56.00	-15.54	QP
9	1.269	7.10	19.82	26.92	46.00	-19.08	Average
10	1.269	17.50	19.82	37.32	56.00	-18.68	QP
11	2.409	3.40	19.53	22.93	46.00	-23.07	Average
12	2.409	15.20	19.53	34.73	56.00	-21.27	QP

**BLE(2Mbps):**

**AC 120V/60 Hz, Line**


Date: 2020-04-14



	Read Freq	Read Level	Read Factor	Limit Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.156	22.50	19.82	42.32	55.69	-13.37	Average
2	0.156	32.70	19.82	52.52	65.69	-13.17	QP
3	0.229	20.30	19.82	40.12	52.48	-12.36	Average
4	0.229	29.30	19.82	49.12	62.48	-13.36	QP
5	0.273	13.00	19.82	32.82	51.03	-18.21	Average
6	0.273	20.50	19.82	40.32	61.03	-20.71	QP
7	0.456	12.60	19.75	32.35	46.76	-14.41	Average
8	0.456	21.10	19.75	40.85	56.76	-15.91	QP
9	1.411	6.31	19.83	26.14	46.00	-19.86	Average
10	1.411	16.91	19.83	36.74	56.00	-19.26	QP
11	2.435	1.81	19.51	21.32	46.00	-24.68	Average
12	2.435	13.61	19.51	33.12	56.00	-22.88	QP

**AC 120V/60 Hz, Neutral**

Date: 2020-04-14



	Read	Limit	Over	Remark			
Freq	Level	Factor	Level	Line			
MHz	dBuV	dB	dBuV	dBuV			
1	0.153	24.20	19.82	44.02	55.82	-11.80	Average
2	0.153	34.30	19.82	54.12	65.82	-11.70	QP
3	0.230	19.30	19.82	39.12	52.44	-13.32	Average
4	0.230	29.00	19.82	48.82	62.44	-13.62	QP
5	0.283	13.00	19.82	32.82	50.72	-17.90	Average
6	0.283	20.20	19.82	40.02	60.72	-20.70	QP
7	0.447	11.40	19.75	31.15	46.93	-15.78	Average
8	0.447	20.20	19.75	39.95	56.93	-16.98	QP
9	1.367	6.50	19.83	26.33	46.00	-19.67	Average
10	1.367	17.10	19.83	36.93	56.00	-19.07	QP
11	2.409	1.70	19.53	21.23	46.00	-24.77	Average
12	2.409	13.50	19.53	33.03	56.00	-22.97	QP

**Note:**

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)


**FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**

**Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

**EUT Setup**

**Below 1 GHz:**



**Above 1GHz:**



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

## EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

## Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30MHz - 1GHz, peak and Average detection mode for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

**Test Results Summary**

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	24.2 -25.6 °C
<b>Relative Humidity:</b>	48-51 %
<b>ATM Pressure:</b>	100.6-101.2 kPa

The testing was performed by Winnie Yang from 2020-04-15 to 2020-04-16.


EUT operation mode: Transmitting

**BLE 1Mbps (worst case):**

**Spurious Emission Test**

**30MHz-1GHz:**

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **low channel of operation in X-axis of orientation** was recorded.)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
32.43	23.79	100	V	34.0	-5.6	40.00	16.21
92.993	21.80	100	V	238.0	-16.7	43.50	21.70
132.80	28.55	100	V	116.0	-11.7	43.50	14.95
166.53	35.47	100	V	0.0	-13.0	43.50	8.03
216.018	34.18	100	H	153.0	-12.3	46.00	11.82
299.73	35.96	100	H	159.0	-10.5	46.00	10.04

**For BLE 1Mbps:**

**1GHz-18GHz**


(Pre-scan in the X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)

Note:

1. This test was performed with the 2.4 - 2.5 GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) - Amplifier Factor (dB)  
 Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)  
 Margin (dB) = Limit (dBµV/m) - Corrected Amplitude (dBµV/m)

**Low Channel: 2402 MHz**

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1110.50	---	25.12	200	H	296.0	-18.5	54.00	28.88
1110.50	40.03	---	200	H	296.0	-18.5	74.00	33.97
1596.70	---	37.54	150	V	237.0	-16.0	54.00	16.46
1596.70	41.67	---	150	V	237.0	-16.0	74.00	32.33
2123.70	---	30.60	150	V	268.0	-14.0	54.00	23.40
2123.70	41.10	---	150	V	268.0	-14.0	74.00	32.90
4804.00	---	41.07	200	V	159.0	-5.6	54.00	12.93
4804.00	48.45	---	200	V	159.0	-5.6	74.00	25.55
7206.00	---	40.91	150	H	115.0	0.4	54.00	13.09
7206.00	47.11	---	150	H	115.0	0.4	74.00	26.89
17977.90	---	48.29	200	H	347.0	8.8	54.00	5.71
17977.90	55.09	---	200	H	347.0	8.8	74.00	18.91



**Middle Channel: 2440 MHz**


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1112.20	---	29.09	200	H	280.0	-18.5	54.00	24.91
1112.20	39.48	---	200	H	280.0	-18.4	74.00	34.52
1593.30	---	32.44	150	V	250.0	-16.0	54.00	21.56
1593.30	39.36	---	150	V	250.0	-16.0	74.00	34.64
2123.70	---	29.46	200	V	250.0	-14.0	54.00	24.54
2123.70	37.00	---	200	V	250.0	-14.0	74.00	37.00
4880.00	---	41.05	200	V	191.0	-5.4	54.00	12.95
4880.00	47.28	---	200	V	191.0	-5.4	74.00	26.72
8163.80	---	41.59	200	H	322.0	1.7	54.00	12.41
8163.80	48.87	---	200	H	322.0	1.7	74.00	25.13
17976.20	---	47.82	150	V	220.0	8.8	54.00	6.18
17976.20	55.16	---	150	V	220.0	8.8	74.00	18.84

**High Channel: 2480 MHz**

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1113.90	40.95	---	200	H	159.0	-18.5	74.00	33.05
1113.90	---	26.48	200	H	159.0	-18.4	54.00	27.52
1593.30	42.87	---	150	H	162.0	-16.0	74.00	31.13
1593.30	---	36.17	150	H	162.0	-16.0	54.00	17.83
2123.70	38.40	---	200	V	248.0	-14.0	74.00	35.60
2123.70	---	29.49	200	V	248.0	-14.0	54.00	24.51
4960.00	46.62	---	150	H	177.0	-5.3	74.00	27.38
4960.00	---	41.65	150	H	177.0	-5.3	54.00	12.35
7698.00	47.91	---	200	V	110.0	1.3	74.00	26.09
7698.00	---	38.61	200	V	110.0	1.3	54.00	15.39
17950.70	55.42	---	150	V	62.0	8.8	74.00	18.58
17950.70	---	47.77	150	H	62.0	8.8	54.00	6.23

**18 GHz – 25 GHz**


(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case low channel of operation in X-axis of orientation was recorded)

**Horizontal**



Date: 16.APR.2020 08:11:23

**Vertical**




Date: 16.APR.2020 08:21:13

**For BLE 2Mbps:**

**Spurious Emission Test:**

**30MHz-1GHz**

*(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case low channel of operation in X-axis of orientation was recorded)*



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
31.35	22.80	100	V	0.0	-4.9	40.00	17.20
91.05	21.01	100	V	242.0	-17.2	43.50	22.49
133.02	27.04	100	V	82.0	-11.7	43.50	16.46
166.51	35.90	100	V	358.0	-13.0	43.50	7.60
215.97	33.18	100	H	170.0	-12.3	43.50	10.32
287.99	36.42	100	H	165.0	-10.9	46.00	9.58

**1GHz-18GHz**


(Pre-scan in the X,Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)

Note:

1. This test was performed with the 2.4 - 2.5 GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) - Amplifier Factor (dB)  
 Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)  
 Margin (dB) = Limit (dBµV/m) - Corrected Amplitude (dBµV/m)

**Low Channel: 2402 MHz**


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1115.60	---	26.10	200	H	296.0	-18.4	54.00	27.90
1115.60	39.87	---	200	H	296.0	-18.5	74.00	34.13
1596.70	---	35.98	200	V	243.0	-16.0	54.00	18.02
1596.70	39.97	---	200	V	243.0	-16.0	74.00	34.03
2127.10	---	28.59	200	V	258.0	-13.9	54.00	25.41
2127.10	36.06	---	200	V	258.0	-13.9	74.00	37.94
4804.00	---	40.24	200	V	19.0	-5.6	54.00	13.76
4804.00	44.84	---	200	V	19.0	-5.6	74.00	29.16
8157.00	---	40.22	200	H	145.0	1.7	54.00	13.78
8157.00	48.76	---	200	H	145.0	1.7	74.00	25.24
17501.90	---	46.68	200	V	125.0	8.9	54.00	7.32
17501.90	54.75	---	200	V	125.0	8.9	74.00	19.25

**Middle Channel: 2440 MHz**


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1113.90	---	24.55	150	V	305.0	-18.5	54.00	29.45
1113.90	41.14	---	150	V	305.0	-18.5	74.00	32.86
1591.60	---	32.34	150	V	247.0	-16.0	54.00	21.66
1591.60	41.98	---	150	V	247.0	-16.0	74.00	32.02
2130.50	---	29.58	150	V	82.0	-13.9	54.00	24.42
2130.50	37.32	---	150	V	82.0	-13.9	74.00	36.68
4880.00	---	38.76	150	V	158.0	-5.4	54.00	15.24
4880.00	45.79	---	150	V	158.0	-5.4	74.00	28.21
9739.70	---	41.15	150	V	144.0	2.0	54.00	12.85
9739.70	48.71	---	150	V	144.0	2.0	74.00	25.29
17510.40	---	46.65	150	H	276.0	8.9	54.00	7.35
17510.40	54.44	---	150	H	276.0	8.9	74.00	19.56

**High Channel: 2480 MHz**

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1052.70	38.88	---	200	V	254.0	-18.8	74.00	35.12
1052.70	---	25.82	200	V	254.0	-18.8	54.00	28.18
1593.30	40.29	---	200	V	240.0	-16.0	74.00	33.71
1593.30	---	33.01	200	V	240.0	-16.0	54.00	20.99
2130.50	35.23	---	200	V	254.0	-13.9	74.00	38.77
2130.50	---	27.66	200	V	254.0	-13.9	54.00	26.34
4960.00	46.06	---	150	V	151.0	-5.3	74.00	27.94
4960.00	---	37.49	150	V	151.0	-5.3	54.00	16.51
8624.50	47.51	---	200	V	299.0	1.5	74.00	26.49
8624.50	---	39.99	200	V	299.0	1.5	54.00	14.01
17969.40	55.05	---	200	H	358.0	8.8	74.00	18.95
17969.40	---	47.09	200	H	358.0	8.8	54.00	6.91

**18 GHz – 25 GHz**


*(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case low channel of operation in X-axis of orientation was recorded)*

**Horizontal**



Date: 16.APR.2020 08:31:41

**Vertical**



Date: 16.APR.2020 08:43:01



**Restricted Bands Emissions Test:**

(Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) - Amplifier Factor (dB)

Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)

Margin (dB) = Limit (dBµV/m) - Corrected Amplitude (dBµV/m)

**BLE: 1Mbps**

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
<b>Low Channel: 2402 MHz</b>								
2390.00	47.77	---	150.0	V	6.0	-2.9	74.00	26.23
2390.00	---	39.97	150.0	V	6.0	-2.9	54.00	14.03
<b>High Channel: 2480 MHz</b>								
2483.50	60.09	---	150.0	V	254.0	-2.5	74.00	13.91
2483.50	---	50.95	150.0	V	254.0	-2.5	54.00	3.05


**BLE: 2Mbps**

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
<b>Low Channel: 2402 MHz</b>								
2390.00	47.12	---	200.0	V	16.0	-2.9	74.00	26.88
2390.00	---	39.61	200.0	V	16.0	-2.9	54.00	14.39
<b>High Channel: 2480 MHz</b>								
2483.50	---	45.31	150.0	V	251.0	-2.5	54.00	8.69
2483.50	52.22	---	150.0	V	251.0	-2.5	74.00	21.78


**Conducted Spurious Emissions at Antenna Port:**

BLE: 1Mps


**Low Channel**



**Middle Channel**




### High Channel




BLE: 2Mps


### Low Channel



### Middle Channel



### High Channel



**FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH**


**Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

**Test Procedure**

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 \* RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	24.2 °C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	101.2kPa

The testing was performed by Winnie Yang on 2020-04-15.


EUT operation mode: Transmitting

**Test Result:** Pass


**IMbps:**

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
Low	2402	0.752	≥ 0.5
Middle	2440	0.746	≥ 0.5
High	2480	0.739	≥ 0.5


### Low Channel



### Middle Channel




### High Channel



2Mbps:


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
Low	2402	1.232	≥ 0.5
Middle	2440	1.232	≥ 0.5
High	2480	1.222	≥ 0.5

Low Channel






### Middle Channel



### High Channel



## **FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER**

### **Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliant with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### **Test Procedure**

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW  $\geq$  DTS bandwidth.
2. Set VBW  $\geq 3 \times$  RBW.
3. Set span  $\geq 3 \times$  RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	24.2 °C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	101.2kPa


*The testing was performed by Winnie Yang on 2020-04-15.*

EUT operation mode: Transmitting


1Mbps:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	9.89	30	Pass
Middle	2440	9.49	30	Pass
High	2480	8.95	30	Pass


Low Channel



### Middle Channel




### High Channel




**2Mbps:**

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	7.22	30	Pass
Middle	2440	6.62	30	Pass
High	2480	6.10	30	Pass


**Low Channel**



### Middle Channel



### High Channel



## **FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**

### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliant with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **Test Procedure**

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	24.2 °C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	101.2kPa


*The testing was performed by Winnie Yang on 2020-04-15.*

*EUT operation mode: Transmitting*


**Test Result:** Compliant

1Mbps:

Left Side




Right Side






2Mbps:

Left Side



Right Side



## **FCC §15.247(e) - POWER SPECTRAL DENSITY**

### **Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### **Test Procedure**

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine Compliant, and it is optional if the maximum conducted (average) output power was used to determine Compliant:

1. Set the RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
2. Set the VBW  $\geq 3 \times \text{RBW}$ .
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	24.2 °C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	101.2kPa

*The testing was performed by Winnie Yang on 2020-04-15.*


*EUT operation mode: Transmitting*

**Test Result:** Pass


**IMbps:**

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-5.58	$\leq 8$
Middle	2440	-6.04	$\leq 8$
High	2480	-6.40	$\leq 8$


**Low Channel**



**Middle Channel**




### High Channel




**2Mbps:**

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-9.96	≤ 8
Middle	2440	-10.49	≤ 8
High	2480	-11.05	≤ 8


**Low Channel**



### Middle Channel



### High Channel



\*\*\*\*\* END OF REPORT \*\*\*\*\*