



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247

TEST REPORT

For

Signify (China) Investment Co., Ltd.

Building no.9, Lane 888, Tianlin Road, Minhang District, Shanghai, 200233, China

FCC ID: 2AGBW9290024405X

Report Type: Original Report	Product Type: LED Lamp
Test Engineer: Jack Jiao	<i>Jack Jiao</i>
Report Number: <u>RXM200605050-00C</u>	
Report Date: 2020-06-23	
Reviewed By: Oscar Ye EMC Manager	<i>Oscar Ye</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC §1.1310 & §2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)	12
CALCULATED FORMULARY:.....	12
FCC §15.203 - ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	15
CORRECTED FACTOR & OVER LIMIT CALCULATION.....	15
TEST RESULTS SUMMARY	15
TEST DATA	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	20
APPLICABLE STANDARD	20
EUT SETUP	20
EMI TEST RECEIVER SETUP.....	21
TEST PROCEDURE	21
FACTOR & OVER LIMIT CALCULATION - BELOW 1 GHz.....	21
CORRECTED AMPLITUDE & MARGIN CALCULATION - ABOVE 1 GHz.....	21
TEST RESULTS SUMMARY	22
TEST DATA	22
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST DATA	39
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	44
APPLICABLE STANDARD	44
TEST PROCEDURE	44
TEST DATA	45

FCC §15.247(d) – BAND EDGE.....	49
APPLICABLE STANDARD	49
TEST PROCEDURE	49
TEST DATA	49
FCC §15.247(e) - POWER SPECTRAL DENSITY	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST DATA	52

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Signify (China) Investment Co., Ltd.
Tested Model:	9290024405
Product Type:	LED Lamp
Power Supply:	AC 110~130V
RF Function:	BLE (1Mbps), BLE (2Mbps)
Operating Band/Frequency:	2402-2480MHz
Channel Number:	40
Channel Separation:	2 MHz
Modulation Type	GFSK
Antenna Type:	PCB Antenna
Maximum Antenna Gain:	3.44 dBi

*All measurement and test data in this report was gathered from production sample serial number: 20200605050. (Assigned by BACL, Kunshan). The EUT was received on 2020-06-05.

Objective

This report is prepared on behalf of *Signify (China) Investment Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communications Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS submittal with FCC ID: 2AGBW9290024405X.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item	Uncertainty	
AC Power Lines Conducted Emissions	3.19dB	
RF conducted test with spectrum	0.9dB	
RF Output Power with Power meter	0.5dB	
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth	0.5kHz	
Temperature	1.0°C	
Humidity	6%	

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel List for BLE mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
18	2438	38	2478
19	2440	39	2480

EUT was tested with channel 0, 20 and 39.

Equipment Modifications

No modification was made to the EUT tested.


EUT Exercise Software


RF test software: UartAssist.exe

Power Level Setting: BLE (1Mbps): Default; BLE (2Mbps): Default

Duty Cycle:

BLE (1Mbps): Middle Channel



BLE (2Mbps): Middle Channel

Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
BLE (1Mbps)	66.72	0.421	2.38	1.76
BLE (2Mbps)	35.18	0.222	4.5	4.54

Note: "x" means the Duty Cycle.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
Power Cable	1.0	EUT	AC Source

Block Diagram of Test Setup

For Conducted Emissions:



Non-Conductive Table 80cm
above Ground Plane

1.5 Meter


LISN

EUT

1.0 Meter

For Radiated Emissions (Below 1GHz):

Turntable
2m Diameter



Non-Conductive Table
80cm above Ground Plane


1.5 Meter

1.0 Meter

AC Source

EUT

For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2019-08-05	2020-08-04
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2017-12-26	2020-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Audix	Test Software	e3	V9	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2017-07-15	2020-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2020-01-17	2023-01-16
A.H.Systems, inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
SELECTOR	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2019-08-05	2020-08-04
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
RF Conducted Test					
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2019-12-14	2020-12-13
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Signify	RF Cable	Signify C01	/	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2019-08-05	2020-08-04
Rohde & Schwarz	LISN	ENV216	3560655016	2019-12-14	2020-12-13
Audix	Test Software	e3	V9	/	/
Rohde & Schwarz	Pulse limiter	ESH3-Z2	0357.8810.54	2019-08-10	2020-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2019-08-15	2020-08-14

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

S = PG/4πR² = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
Zigbee	2405~2480	3.44	2.21	10.50	11.22	20	0.0049	1.0
BLE(1Mbps)	2402~2480	3.44	2.21	7.00	5.01	20	0.0022	1.0
BLE(2Mbps)	2402~2480	3.44	2.21	7.00	5.01	20	0.0022	1.0

Note:

- (1) The tune-up output power was declared by the manufacturer.
- (2) Zigbee and BLE can't transmit simultaneously.

Conclusion: The device meets FCC MPE at 20 cm distance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a PCB antenna for BLE, which the antenna gain is 3.44 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the EUT was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Over Limit Calculation

The Corrected Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of 7 dB means the emission is 7 dB above the limit. The equation for over limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.


Test Data

Environmental Conditions


Temperature:	24.3 °C
Relative Humidity:	50 %
ATM Pressure:	102.3 kPa

The testing was performed by Jack Jiao on 2020-06-15.

EUT operation mode: Transmitting in low channel (worst case)

BLE (1Mbps)**AC 120V/60 Hz, Line**


Freq	Read		Limit		Over		
	Freq	Level	Factor	Level	Line	Limit	Remark
1	0.151	27.60	19.82	47.42	55.96	-8.54	Average
2	0.151	41.30	19.82	61.12	65.96	-4.84	QP
3	0.188	24.21	19.82	44.03	54.11	-10.08	Average
4	0.188	35.01	19.82	54.83	64.11	-9.28	QP
5	0.251	19.80	19.82	39.62	51.73	-12.11	Average
6	0.251	28.20	19.82	48.02	61.73	-13.71	QP
7	0.308	15.69	19.83	35.52	50.02	-14.50	Average
8	0.308	23.99	19.83	43.82	60.02	-16.20	QP
9	0.686	6.90	19.75	26.65	46.00	-19.35	Average
10	0.686	13.80	19.75	33.55	56.00	-22.45	QP
11	1.242	3.51	19.81	23.32	46.00	-22.68	Average
12	1.242	9.51	19.81	29.32	56.00	-26.68	QP

AC 120V/60 Hz, Neutral


	Freq	Read		Limit	Over	Remark
		Level	Factor			
1	0.150	27.80	19.82	47.62	56.00	-8.38 Average
2	0.150	41.40	19.82	61.22	66.00	-4.78 QP
3	0.189	24.40	19.82	44.22	54.06	-9.84 Average
4	0.189	35.10	19.82	54.92	64.06	-9.14 QP
5	0.253	19.50	19.82	39.32	51.64	-12.32 Average
6	0.253	28.20	19.82	48.02	61.64	-13.62 QP
7	0.315	16.40	19.82	36.22	49.84	-13.62 Average
8	0.315	24.00	19.82	43.82	59.84	-16.02 QP
9	0.440	11.60	19.75	31.35	47.07	-15.72 Average
10	0.440	18.90	19.75	38.65	57.07	-18.42 QP
11	0.853	4.41	19.71	24.12	46.00	-21.88 Average
12	0.853	11.61	19.71	31.32	56.00	-24.68 QP

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dB μ V) + Factor (dB) - Limit (dB μ V)

BLE (2Mbps)**AC 120V/60 Hz, Line**

Freq	Read		Limit	Over	Remark	
	Freq	Level	Factor	Level	Line	Limit
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.159	25.10	19.82	44.92	55.52	-10.60 Average
2	0.159	38.50	19.82	58.32	65.52	-7.20 QP
3	0.187	24.31	19.82	44.13	54.15	-10.02 Average
4	0.187	34.81	19.82	54.63	64.15	-9.52 QP
5	0.252	19.80	19.82	39.62	51.69	-12.07 Average
6	0.252	28.50	19.82	48.32	61.69	-13.37 QP
7	0.315	16.40	19.82	36.22	49.84	-13.62 Average
8	0.315	24.00	19.82	43.82	59.84	-16.02 QP
9	0.437	11.60	19.75	31.35	47.11	-15.76 Average
10	0.437	18.90	19.75	38.65	57.11	-18.46 QP
11	1.242	3.31	19.81	23.12	46.00	-22.88 Average
12	1.242	9.21	19.81	29.02	56.00	-26.98 QP

AC 120V/60 Hz, Neutral



Freq	Read		Limit	Over	Remark	
	MHz	Level	Factor	Level	Line	Limit
1	0.150	28.00	19.82	47.82	56.00	-8.18 Average
2	0.150	41.40	19.82	61.22	66.00	-4.78 QP
3	0.189	24.50	19.82	44.32	54.06	-9.74 Average
4	0.189	35.20	19.82	55.02	64.06	-9.04 QP
5	0.255	19.10	19.82	38.92	51.60	-12.68 Average
6	0.255	27.90	19.82	47.72	61.60	-13.88 QP
7	0.343	13.70	19.81	33.51	49.13	-15.62 Average
8	0.343	21.80	19.81	41.61	59.13	-17.52 QP
9	0.474	10.50	19.76	30.26	46.45	-16.19 Average
10	0.474	18.00	19.76	37.76	56.45	-18.69 QP
11	0.943	3.90	19.77	23.67	46.00	-22.33 Average
12	0.943	11.10	19.77	30.87	56.00	-25.13 QP

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dB μ V) + Factor (dB) - Limit (dB μ V)

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	Peak
	1MHz	3 MHz	1MHz	AVG

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz, Peak and average detection mode above 1 GHz.

Factor & Over Limit Calculation - Below 1 GHz

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Over Limit” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Corrected Amplitude & Margin Calculation - Above 1 GHz

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	23.6~24.3°C
Relative Humidity:	50~52%
ATM Pressure:	101.1~101.3 kPa


The testing was performed by Jack Jiao from 2020-06-09 to 2020-06-20.

Test Result: Compliant.


EUT operation mode: Transmitting

Spurious Emission Test:**BLE (1Mbps)****30MHz-1GHz**

(Pre-scan with Low channel, Middle channel, High channel of operation in the X,Y and Z axes of orientation, the worst case low channel of operation in X-axis of orientation was recorded)

Horizontal:

Freq	Read			Limit Line	Over Limit	APos	TPos	Remark
	Freq	Level	Factor					
1	30.11	22.60	-3.22	19.38	40.00	-20.62	100	85 QP
2	39.16	25.59	-10.74	14.85	40.00	-25.15	100	151 QP
3	75.45	30.90	-17.04	13.86	40.00	-26.14	200	266 QP
4	85.30	33.20	-17.21	15.99	40.00	-24.01	200	76 QP
5	202.10	27.39	-11.81	15.58	43.50	-27.92	200	95 QP
6	298.27	32.00	-10.31	21.69	46.00	-24.31	100	79 QP


Vertical:

	Freq	Read		Limit	Over	APos	TPos	Remark
		Level	Factor					
1	32.52	31.09	-5.22	25.87	40.00	-14.13	100	63 QP
2	39.44	39.49	-10.97	28.52	40.00	-11.48	100	229 QP
3	45.38	44.50	-14.40	30.10	40.00	-9.90	100	211 QP
4	50.06	44.30	-16.94	27.36	40.00	-12.64	100	3 QP
5	59.03	48.19	-17.49	30.70	40.00	-9.30	100	47 QP
6	94.10	43.39	-16.16	27.23	43.50	-16.27	100	20 QP

1GHz-18GHz:(Pre-scan in the X,Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)

Note:


1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2402MHz

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1596.700000	37.29	---	150.0	V	190.0	-16.0	74.00	36.71
1596.700000	---	32.82	150.0	V	190.0	-16.0	54.00	21.18
2125.400000	38.39	---	100.0	V	243.0	-14.0	74.00	35.61
2125.400000	---	28.92	100.0	V	243.0	-14.0	54.00	25.08
4804.000000	---	35.74	200.0	V	171.0	-5.6	54.00	18.26
4804.000000	41.42	---	200.0	V	171.0	-5.6	74.00	32.58
7206.000000	52.15	---	100.0	V	258.0	0.4	74.00	21.85
7206.000000	---	47.23	100.0	V	258.0	0.4	54.00	6.77
10431.600000	---	38.56	100.0	H	160.0	2.3	54.00	15.44
10431.600000	47.86	---	100.0	H	160.0	2.3	74.00	26.14
17904.800000	---	47.74	100.0	H	25.0	8.8	54.00	6.26
17904.800000	55.68	---	100.0	H	25.0	8.8	74.00	18.32

Middle Channel: 2442MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1571.200000	40.01	---	150.0	V	161.0	-16.1	74.00	33.99
1571.200000	---	27.18	150.0	V	161.0	-16.1	54.00	26.82
2127.100000	37.21	---	100.0	V	244.0	-13.9	74.00	36.79
2127.100000	---	26.34	100.0	V	244.0	-13.9	54.00	27.66
4884.000000	---	35.41	100.0	V	155.0	-5.4	54.00	18.59
4884.000000	42.44	---	100.0	V	155.0	-5.4	74.00	31.56
7326.000000	---	37.45	150.0	V	41.0	0.6	54.00	16.55
7326.000000	46.99	---	150.0	V	41.0	0.6	74.00	27.01
10967.100000	---	39.53	100.0	H	48.0	2.9	54.00	14.47
10967.100000	48.12	---	100.0	H	48.0	2.9	74.00	25.88
17790.900000	---	47.12	200.0	V	281.0	8.8	54.00	6.88
17790.900000	55.59	---	200.0	V	281.0	8.8	74.00	18.41

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1595.000000	39.59	---	200.0	V	63.0	-16.0	74.00	34.41
1595.000000	---	29.74	200.0	V	63.0	-16.0	54.00	24.26
3463.300000	---	31.22	150.0	H	273.0	-8.9	54.00	22.78
3463.300000	39.36	---	150.0	H	273.0	-8.9	74.00	34.64
4960.000000	44.54	---	200.0	V	155.0	-5.3	74.00	29.46
4960.000000	---	37.12	200.0	V	155.0	-5.3	54.00	16.88
7440.000000	---	36.73	200.0	V	16.0	0.9	54.00	17.27
7440.000000	45.80	---	200.0	V	16.0	0.9	74.00	28.20
10356.800000	---	38.74	200.0	H	100.0	2.2	54.00	15.26
10356.800000	47.99	---	200.0	H	100.0	2.2	74.00	26.01
17860.600000	---	47.01	100.0	V	0.0	8.8	54.00	6.99
17860.600000	57.07	---	100.0	V	0.0	8.8	74.00	16.93

18GHz-25GHz:

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case low channel of operation in X-axis of orientation was recorded)

Horizontal


Date: 20.JUN.2020 18:56:01

Vertical


Date: 20.JUN.2020 19:06:28

BLE (2Mbps)**30MHz-1GHz**

(Pre-scan with Low channel, Middle channel, High channel of operation in the X,Y and Z axes of orientation, the worst case low channel of operation in X-axis of orientation was recorded)

Horizontal:

Freq	Read			Limit Line	Over Limit	APos	TPos	Remark
	MHz	dB _{BuV}	dB/m					
1	31.29	21.70	-4.20	17.50	40.00	-22.50	100	348 QP
2	39.30	25.30	-10.86	14.44	40.00	-25.56	100	1 QP
3	75.45	30.80	-17.04	13.76	40.00	-26.24	200	257 QP
4	85.60	32.30	-17.21	15.09	40.00	-24.91	200	213 QP
5	202.81	27.81	-11.89	15.92	43.50	-27.58	200	81 QP
6	295.15	33.20	-10.34	22.86	46.00	-23.14	100	71 QP

Vertical:

	Freq	Read		Limit	Over	APos	TPos	Remark
		Level	Factor					
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg
1	33.33	31.29	-5.89	25.40	40.00	-14.60	100	119 QP
2	39.30	38.90	-10.86	28.04	40.00	-11.96	100	92 QP
3	45.22	45.40	-14.31	31.09	40.00	-8.91	100	256 QP
4	50.59	44.70	-16.98	27.72	40.00	-12.28	100	156 QP
5	59.44	47.49	-17.52	29.97	40.00	-10.03	200	136 QP
6	88.00	47.41	-17.24	30.17	40.00	-9.83	100	122 QP


1GHz-18GHz:(Pre-scan in the X, Y and Z axes of orientation, the worst case **X-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1494.700000	36.11	---	100.0	V	313.0	-16.4	74.00	37.89
1494.700000	---	29.34	100.0	V	313.0	-16.4	54.00	24.66
2123.700000	39.98	---	150.0	V	287.0	-14.0	74.00	34.02
2123.700000	---	33.28	150.0	V	287.0	-14.0	54.00	20.72
4804.000000	43.62	---	100.0	H	32.0	-5.6	74.00	30.38
4804.000000	---	35.88	100.0	H	32.0	-5.6	54.00	18.12
7206.000000	47.90	---	200.0	H	5.0	0.4	74.00	26.10
7206.000000	---	39.19	200.0	H	5.0	0.4	54.00	14.81
10443.500000	---	37.97	100.0	H	0.0	2.3	54.00	16.03
10443.500000	48.46	---	100.0	H	0.0	2.3	74.00	25.54
17840.200000	---	47.37	200.0	V	351.0	8.8	54.00	6.63
17840.200000	55.79	---	200.0	V	351.0	8.8	74.00	18.21

Middle Channel: 2442MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1493.000000	35.58	---	150.0	V	38.0	-16.4	74.00	38.42
1493.000000	---	29.68	150.0	V	38.0	-16.4	54.00	24.32
2125.400000	35.18	---	150.0	V	176.0	-14.0	74.00	38.82
2125.400000	---	30.27	150.0	V	176.0	-14.0	54.00	23.73
4884.000000	41.29	---	150.0	V	86.0	-5.4	74.00	32.71
4884.000000	---	34.93	150.0	V	86.0	-5.4	54.00	19.07
7326.000000	---	37.37	150.0	V	312.0	0.6	54.00	16.63
7326.000000	46.08	---	150.0	V	312.0	0.6	74.00	27.92
10453.700000	---	39.50	200.0	H	0.0	2.3	54.00	14.50
10453.700000	48.77	---	200.0	H	0.0	2.3	74.00	25.23
17898.000000	---	46.84	150.0	V	131.0	8.8	54.00	7.16
17898.000000	56.00	---	150.0	V	131.0	8.8	74.00	18.00

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1295.800000	37.53	---	100.0	V	266.0	-17.5	74.00	36.47
1295.800000	---	26.82	100.0	V	266.0	-17.5	54.00	27.18
2127.100000	---	30.23	100.0	V	297.0	-13.9	54.00	23.77
2127.100000	35.65	---	100.0	V	297.0	-13.9	74.00	38.35
4960.000000	---	35.46	100.0	H	20.0	-5.3	54.00	18.54
4960.000000	40.95	---	100.0	H	20.0	-5.3	74.00	33.05
7440.000000	---	39.48	100.0	H	344.0	0.9	54.00	14.52
7440.000000	44.56	---	100.0	H	344.0	0.9	74.00	29.44
11024.900000	---	38.80	150.0	V	272.0	2.9	54.00	15.20
11024.900000	48.23	---	150.0	V	272.0	2.9	74.00	25.77
17729.700000	---	46.35	150.0	H	141.0	8.8	54.00	7.65
17729.700000	55.84	---	150.0	H	141.0	8.8	74.00	18.16

18GHz-25GHz:

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case low channel of operation in X-axis of orientation was recorded)

Horizontal

Date: 20.JUN.2020 19:16:51

Vertical

Date: 20.JUN.2020 19:27:58

Restricted Bands Emissions Test:*(Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded.)*

Note:



1. The test is performed with a 10dB Attenuator.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)



BLE (1Mbps)



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.00	52.35	---	100.0	H	167.0	-2.9	74.00	21.65
2390.00	---	39.59	100.0	H	167.0	-2.9	54.00	14.41
High Channel: 2480MHz								
2483.50	54.40	---	150.0	H	0.0	-2.4	74.00	19.60
2483.50	---	42.17	150.0	H	0.0	-2.4	54.00	11.83

BLE (2Mbps)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.00	---	38.30	150.0	H	193.0	-2.9	54.00	15.70
2390.00	53.63	---	150.0	H	193.0	-2.9	74.00	20.37
High Channel: 2480MHz								
2483.50	50.44	---	200.0	H	167.0	-2.4	74.00	23.56
2483.50	---	43.01	200.0	H	167.0	-2.4	54.00	10.99

Conducted Spurious Emissions at Antenna Port:**BLE (1Mbps)****Low Channel****Middle Channel**

High Channel**BLE (2Mbps)****Low Channel**

Middle Channel**High Channel**

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	48 %
ATM Pressure:	101.2kPa


The testing was performed by Jack Jiao on 2020-06-15.



Test Result: Compliant.

EUT operation mode: Transmitting

BLE (1Mbps)


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
Low	2402	0.733	≥ 0.5
Middle	2442	0.727	≥ 0.5
High	2480	0.721	≥ 0.5



Low Channel

Middle Channel**High Channel**

BLE (2Mbps)

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
Low	2402	1.214	≥ 0.5
Middle	2442	1.214	≥ 0.5
High	2480	1.214	≥ 0.5

Low Channel

Middle Channel**High Channel**

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW \geq DTS bandwidth.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 3 \times$ RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data

Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Jack Jiao on 2020-06-15.


Test Result: Compliant.

EUT operation mode: Transmitting


BLE (1Mbps)

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	6.80	30	Pass
Middle	2442	6.63	30	Pass
High	2480	6.43	30	Pass


Low Channel



Middle Channel




High Channel




BLE (2Mbps)


Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
Low	2402	6.69	30	Pass
Middle	2442	6.58	30	Pass
High	2480	6.39	30	Pass

Low Channel

Middle Channel



High Channel



FCC §15.247(d) – BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data



Environmental Conditions



Temperature:	25.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Jack Jiao on 2020-06-15.

Test Result: Compliant.

EUT operation mode: Transmitting

BLE (1Mbps)**Left Side****Right Side**

BLE (2Mbps)**Left Side****Right Side**

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 \times \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Jack Jiao on 2020-06-15.


Test Result: Compliant.

EUT operation mode: Transmitting


BLE (1Mbps)


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-8.44	≤ 8
Middle	2442	-8.66	≤ 8
High	2480	-8.81	≤ 8

Low Channel






Middle Channel



High Channel**BLE (2Mbps)**

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-9.49	≤8
Middle	2442	-9.65	≤8
High	2480	-9.95	≤8

Low Channel**Middle Channel**

High Channel******* END OF REPORT *******