

MPE Calculation - FCC ID: 2AGBW9290030171AX

The FCC requires that the calculated MPE be equal to or less than a given limit dependent on frequency at a distance of 20 cm from a device to the body of a user.

The transmitter operation for the Wall Switch Module covers the 2.4GHz operating band.

Simultaneous transmission is not supported.

The following FCC Rule Parts are applicable:

Part 1.1310 – Radiofrequency radiation exposure limits

Part 2.1091(c) – Radiofrequency radiation exposure evaluation: mobile devices

CALCULATION

The following far field power density equation is applicable:

$$S = \text{EIRP} / 4 \pi R^2$$

Where

S = Power density (mW/cm²)

EIRP = Effective Isotropically Radiated Power (EIRP = P x G) (mW)

P = Conducted Transmitter Power (dBm)

G = Antenna Gain (relative to an isotropic radiator)

R = distance to the centre of radiation of the antenna (safe operating distance) (cm)

Calculation for 2.4GHz Zigbee:**Values:**

Transmitter frequency range = 2402 – 2480MHz

P = 6.37dBm

G = 0.55dBi

EIRP = 6.92dBm (4.9mW)

R = 20cm

Power Density Requirement

From table 1 (b) - Limits for General Population/ Uncontrolled Exposure of FCC Rule Part 1.1310 for 2.4GHz

$$S_{\text{req1}} = 1.0 \text{ mW/cm}^2$$

Calculation:

$$\begin{aligned} S &= \text{EIRP}/4 \pi R^2 \\ &= 6.92/(12.56 \times 20^2) \\ &= 6.92/(5024) \end{aligned}$$

$$S_1 = 0.001377 \text{ mW/cm}^2$$

Conclusion

The required 20cm RF exposure limits for General Population/ Uncontrolled Exposure FCC Rule Part 1.1310 limits will not be exceeded for the Wall Switch Module using antennas having a maximum gain of 0.55dBi.



Tim Su

Approbation Engineer

Signify (China) Investment Co., Ltd.