

Radio Exposure Evaluation Report

FCC ID : 2AGBW9290034996X
Equipment : HDMI Sync Box
Brand Name : PHILIPS
Model Name : 9290034996
Applicant : Signify (China) Investment Co., Ltd.
Building 9, Lane 888, Tianlin Road,
Minhang District, Shanghai 200233 China
Manufacturer : Signify (China) Investment Co., Ltd.
Building 9, Lane 888, Tianlin Road,
Minhang District, Shanghai 200233 China
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Sep. 23, 2022, and testing was started from Oct. 24, 2022 and completed on Nov. 10, 2022. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT3

1 GENERAL DESCRIPTION5

1.1 Information.....5

1.2 Applicable Standards6

1.3 Testing Location6

2 MAXIMUM PERMISSIBLE EXPOSURE7

2.1 Limit of Maximum Permissible Exposure7

2.2 RF Exposure Exempt Measurement7

2.3 Multiple RF Sources Exposure.....8

2.4 MPE Calculation Method.....9

2.5 Calculated Result and Limit.....9

Photographs of EUT V01



History of this test report

Report No.	Version	Description	Issued Date
FA271604	01	Initial issue of report	Jul. 26, 2024
FA271604	02	Describe the EUT does not supports WLAN + BT simultaneous transmission (This report is the latest version replacing for the report issued on Jul. 26, 2024)	Jul. 29, 2024



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None

Reviewed by: Ryan Hsiao

Report Producer: Ann Hou



1 General Description

1.1 Information

1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	ESPRESSIF	ESP32-S3-WROOM-2	PIFA antenna	N/A	2.4

Note 1: The EUT has one antenna.

For 2.4GHz function:

For IEEE 802.11 b/g/n mode (1TX/1RX)

Ant. 1 could transmit/receive.

For BT function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)

Ant. 1 could transmit/receive.

1.1.3 Table for Multiple Listing

Table for Explanation of 2nd Source.

Object/part or Description (location)	Location	Main source (SKU 1)	2nd source (SKU 2)
level shift	U37	Brand: UTC Model: ULSF0204G-P14-R	Brand: TI Model: LSF0204PWR
Power IC	U2	Brand: GMT Model: G5335QT1U	Brand: ANPEC Model: APW8713EQBI-TRG
IO IC	U27,U56	Brand: NOVOSENSE Model: NCA9555	Brand: NXP Model: PCA9555APW
Fuse	F1	Brand: Littelfuse Model: 2016L260/24	Brand: PTTC Model: 2016P260TF/24

From the above SKU, all of SKUs were verified and Main source (SKU 1) was selected as representative SKU for the test and its data was recorded in this report.

1.1.4 Accessories

Accessories				
AC Adapter	Brand Name	PHILIPS	Model Name	S024CSM1200200
	Power Rating	I/P: 100-240Vac, 0.6A, O/P: 12.0Vdc, 2.0A		
	Power Cord	1.25 meter, non-shielded cable, w/o ferrite core		
HDMI Cable	Signal Line	1.0 meter, shielded cable, w/o ferrite core		

Reminder: Regarding to more detail and other information, please refer to user manual.

1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 2 Subpart J, section 2.1091
 - ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01
- The following reference test guidance is not within the scope of accreditation of TAF.
- ♦ 47 CFR Part 1.1307
 - ♦ 47 CFR Part 1.1310

1.3 Testing Location

Test Lab. : Sporton International Inc. Hsinhua Laboratory		
☒	Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)
		TEL: 886-3-327-3456 FAX: 886-3-327-0973
Test site Designation No. TW3785 with FCC.		
☐	Wen 33rd.St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)
		TEL: 886-3-318-0787 FAX: 886-3-318-0287
Test site Designation No. TW0008 with FCC.		

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
A	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
B	§1.1307(b)(3)(i)(B)	$P_{th}(mW) = \begin{cases} ERP_{20cm} (d / 20cm)^x \rightarrow d \leq 20cm \\ ERP_{20cm} \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040 f (mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060 (mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2R^2 \end{cases}$ $f \text{ is in MHz; } R \text{ is in m; } R > \lambda / 2\pi$

2.3 Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)
§1.1307(b)(3)(ii)(B)	$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added. b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added. c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters. P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive). P_{th,i} = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i. ERP_j = the ERP of fixed, mobile, or portable RF source j. ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section. Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure. Evaluated Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.

2.4 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.
The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

2.5 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

2.4GHz WLAN

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	2.40	20.31	22.71	0.50	127.6762	20	0.04166	1.00000	B	3060	0.0417
2.4G;D1D	2.40	20.06	22.46	0.50	120.5341	20	0.03933	1.00000	B	3060	0.0394

Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;BT-LE	2.40	20.24	22.64	0.50	125.6348	20	0.04099	1.00000	B	3060	0.0411

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Note 4: The EUT does not supports WLAN + BT simultaneous transmission.

————THE END————