

RF Exposure Evaluation Report

FCC 47 CFR § 2.1091

for
Digital Device

Model Name.: 9290035625, 9290035626

Prepared for:

Signify (China) Investment Co., Ltd.
Building no.9, Lane 888, Tianlin Road, Minhang District, Shanghai,
200233, China

Prepared by

Compliance Certification Services Inc.
Wugu Laboratory
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City, Taiwan.
Issue Date: August 18, 2023

Note: This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, NIST or any government agencies. The test results in the report only apply to the tested sample.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

| Rev. | Issue Date | Revisions | Effect Page | Revised By |
|------|-----------------|----------------------------------|----------------------|------------|
| 00 | August 2, 2023 | Initial Issue | ALL | Doris Chu |
| 01 | August 14, 2023 | See the following Note Rev. (01) | P.9, P.14-16, P.6 | Doris Chu |
| 02 | August 18, 2023 | See the following Note Rev. (02) | P.6 | Doris Chu |

Rev. (01)

1. Modify test data in section 3.2, 5 and 6.
2. Modify Model Discrepancy in section 3.1.


Rev. (02)

1. Remove HW Version in section 3.1.

Table of Contents

| | | |
|----------|---|-----------|
| 1 | ATTESTATION OF TEST RESULTS | 4 |
| 2 | TEST SPECIFICATION, METHODS AND PROCEDURES | 5 |
| 3 | DEVICE UNDER TEST (DUT) INFORMATION | 6 |
| 3.1 | DUT DESCRIPTION | 6 |
| 3.2 | WIRELESS TECHNOLOGIES | 7 |
| 4 | MAXIMUM PERMISSIBLE EXPOSURE | 10 |
| 4.1 | LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE) | 10 |
| 4.2 | MPE CALCULATION METHOD | 11 |
| 4.3 | MPE EXEMPTION | 12 |
| 4.4 | MULTIPLE RF SOURCES | 13 |
| 5 | MPE EXEMPTION OPTION B | 14 |
| 6 | SIMULTANEOUS TRANSMISSION EXEMPT | 16 |
| 6.1 | SUM OF THE WIFI 2.4GHZ & WIFI 5GHZ+ BLUETOOTH+ ZIGBEE | 16 |
| 7 | FACILITIES | 17 |

1 Attestation of Test Results

| | |
|--|---|
| Applicant Name | Signify (China) Investment Co., Ltd. |
| Model Name | 9290035625, 9290035626 |
| Applicable Standards | FCC 47 CFR § 2.1091 FCC 47 CFR § 1.1307 FCC 47 CFR § 1.1310 Published RF exposure KDB procedures |
| Receive EUT Date: | June 2, 2023 |
| <p>Compliance Certification Services Inc. , tested the above equipment in accordance with the requirements set forth in the above standards. Determination of compliance is based on the results of the compliance measurement,not taking into account measurement instrumentation uncertainty.All indications of Pass/Fail in this report are opinions expressed by Compliance Certification Services Inc, based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.</p> | |
| <p>Approved & Released By:</p>  | |
| <p>Sky Zhou Asst. Section Manager Compliance Certification Services Inc.</p> | |

2 Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1091, the following FCC Published RF exposure [KDB](#) procedures:

- 447498 D04 Interim General RF Exposure Guidance v01
- 865664 D02 RF Exposure Reporting v01r02

Report No.: TMWK2305001708KS

3 Device Under Test (DUT) Information

3.1 DUT Description

| | | |
|-------------------|------------------------|--|
| Product | Digital Device | |
| Trade Name | Philips | |
| Model No. | 9290035625, 9290035626 | |
| Model Discrepancy | Model | Difference |
| | 9290035625 | 1.without Battery components 2. without level shift IC 3. Zigbee Antenna model: RFFPA203007IMAB402 WiFi Antenna model: RFFPA203006IMLB403 |
| | 9290035626 | 1. with Battery components 2.with level shift IC 3. Zigbee Antenna model: RFFPA203007IMAB401 WiFi Antenna model: RFFPA203006IMLB402 |
| Software Version | V1.0.02R25 | |
| Sample Stage | Identical prototype | |

3.2 Wireless Technologies

| | |
|--------------------------------|--|
| Frequency bands | <input checked="" type="checkbox"/> Bluetooth: 2402MHz-2480MHz <input checked="" type="checkbox"/> 802.11b/g/n HT20/ac VHT20: 2412MHz ~ 2462 MHz <input checked="" type="checkbox"/> 802.11n HT40/ac VHT40: 2422MHz ~ 2452MHz <input checked="" type="checkbox"/> 802.11a/n HT20: 5180MHz ~ 5240MHz / 5260MHz ~ 5320MHz / 5500MHz ~ 5700MHz / 5745MHz ~ 5825MHz <input checked="" type="checkbox"/> 802.11ac VHT20: 5180MHz ~ 5240MHz / 5260MHz ~ 5320MHz / 5500MHz ~ 5700MHz / 5745MHz ~ 5825MHz <input checked="" type="checkbox"/> 802.11n HT40: 5190MHz ~ 5230MHz / 5270MHz ~ 5310MHz / 5510MHz ~ 5670MHz / 5755MHz ~ 5795MHz <input checked="" type="checkbox"/> 802.11ac VHT 40: 5190MHz ~ 5230MHz / 5270MHz ~ 5310MHz / 5510MHz ~ 5670MHz / 5755MHz ~ 5795MHz <input checked="" type="checkbox"/> 802.11ac VHT80: 5210MHz / 5290MHz / 5530MHz ~ 5610MHz / 5775MHz <input checked="" type="checkbox"/> Zigbee: 2405~2480MHz <input type="checkbox"/> Others |
| Exposure classification | <input type="checkbox"/> Occupational/Controlled exposure <input checked="" type="checkbox"/> General Population/Uncontrolled exposure |

Report No.: TMWK2305001708KS

| | | | |
|----------------------------------|-------------------------------|----------|----------------------------|
| Antenna Specification | Type: Monopole Antenna | | |
| | BLE: | | |
| | 9290035625: Gain: 1.45 dBi | | |
| | 9290035626: Gain: 1.81 dBi | | |
| | WIFI 2.4GHz: | | |
| | 9290035625: Gain: 1.45 dBi | | |
| | 9290035626: Gain: 1.81 dBi | | |
| | WIFI 5GHz: | | |
| | 5150~5250 | | |
| | 9290035625: Gain: 1.24 dBi | | |
| 9290035626: Gain: 1.05 dBi | | | |
| 5250~5350: | | | |
| 9290035625: Gain: 2.27 dBi | | | |
| 9290035626: Gain: 2.66 dBi | | | |
| 5470~5725: | | | |
| 9290035625: Gain: 2.27 dBi | | | |
| 9290035626: Gain: 2.66 dBi | | | |
| 5725~5850 | | | |
| 9290035625: Gain: 1.38 dBi | | | |
| 9290035626: Gain: 0.91 dBi | | | |
| Zigbee: | | | |
| 9290035625: Gain: 1.3 dBi | | | |
| 9290035626: Gain: 1.1 dBi | | | |
| | | | |
| BT: | Antenna Gain : | 1.81 dBi | (Numeric gain: 1.52) Worst |
| 2.4GHz: | Antenna Gain: | 1.81 dBi | (Numeric gain: 1.52) Worst |
| 5GHz(U-NII-1): | Antenna Gain: | 1.24 dBi | (Numeric gain: 1.33) Worst |
| 5GHz(U-NII-2A) | Antenna Gain: | 2.66 dBi | (Numeric gain: 1.85) Worst |
| 5GHz(U-NII-2C) | Antenna Gain: | 2.66 dBi | (Numeric gain: 1.85) Worst |
| 5GHz(U-NII-3): | Antenna Gain: | 1.38 dBi | (Numeric gain: 1.37) Worst |
| Zigbee: | Antenna Gain: | 1.30 dBi | (Numeric gain: 1.35) Worst |

Report No.: TMWK2305001708KS

| | | | |
|--------------------------------------|------------------------|------------|-------------|
| Maximum Average power | BLE | 7.92 dBm | (6.194 mW) |
| | 2.4GHz | | |
| | IEEE 802.11b | 19.65 dBm | (92.257 mW) |
| | IEEE 802.11g | 18.36 dBm | (68.549 mW) |
| | IEEE 802.11n HT 20 | 18.33 dBm | (68.08 mW) |
| | IEEE 802.11n HT 40 | 13.47 dBm | (22.23 mW) |
| | IEEE 802.11ac VHT20 | 17.95 dBm | (62.37 mW) |
| | IEEE 802.11ac VHT40 | 13.45 dBm | (22.13 mW) |
| | 5GHz (U-NII-1) | | |
| | IEEE 802.11a | 18.18 dBm | (65.77 mW) |
| | IEEE 802.11n HT 20 | 17.97 dBm | (62.66 mW) |
| | IEEE 802.11n HT 40 | 16.66 dBm | (46.34 mW) |
| | IEEE 802.11ac VHT 20 | 17.92 dBm | (61.94 mW) |
| | IEEE 802.11ac VHT 40 | 16.60 dBm | (45.71 mW) |
| | IEEE 802.11ac VHT 80 | 12.60 dBm | (18.20 mW) |
| | 5GHz (U-NII-2A) | | |
| | IEEE 802.11a | 17.48 dBm | (55.98 mW) |
| | IEEE 802.11n HT 20 | 17.63 dBm | (57.94 mW) |
| | IEEE 802.11n HT 40 | 17.37 dBm | (54.58 mW) |
| | IEEE 802.11ac VHT 20 | 17.56 dBm | (57.02 mW) |
| | IEEE 802.11ac VHT 40 | 17.36 dBm | (54.45 mW) |
| | IEEE 802.11ac VHT 80 | 13.40 dBm | (21.88 mW) |
| | 5GHz (U-NII-2C) | | |
| | IEEE 802.11a | 17.19 dBm | (52.36 mW) |
| | IEEE 802.11n HT 20 | 17.05 dBm | (50.70 mW) |
| | IEEE 802.11n HT 40 | 16.03 dBm | (40.09 mW) |
| | IEEE 802.11ac VHT 20 | 16.95 dBm | (49.55 mW) |
| | IEEE 802.11ac VHT 40 | 15.99 dBm | (39.72 mW) |
| | IEEE 802.11ac VHT 80 | 16.40 dBm | (43.65 mW) |
| | 5GHz (U-NII-3) | | |
| IEEE 802.11a | 18.67 dBm | (73.62 mW) | |
| IEEE 802.11n HT 20 | 18.81 dBm | (76.03 mW) | |
| IEEE 802.11n HT 40 | 19.23 dBm | (83.75 mW) | |
| IEEE 802.11ac VHT 20 | 18.72 dBm | (74.47 mW) | |
| IEEE 802.11ac VHT 40 | 19.16 dBm | (82.41 mW) | |
| IEEE 802.11ac VHT 80 | 16.88 dBm | (48.75 mW) | |
| Zigbee | 10.50 dBm | (11.22 mW) | |

Notes:

1. For more details, please refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.
3. Disclaimer: The variant model numbers / trademarks are assessed as identical in hardware and software to each other, hence all variants are fully covered by the test results in this test report without further verification test.
4. The power referred the AVG power of the test report TMWK2305001703KR, TMWK2305001704KR, TMWK2305001705KR and TMWK2305001706KR for RF Exposure assessment purpose.

Report No.: TMWK2305001708KS

4 Maximum Permissible Exposure

4.1 Limits for Maximum Permissible Exposure (MPE)

Table 1 - Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposure | | | | |
| 0.3-3.0 | 614 | 1.63 | * 100 | 6 |
| 3.0-30 | 1842/f | 4.89/f | * 900/f ² | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1,500 | | | f/300 | 6 |
| 1,500-100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | * 100 | 30 |
| 1.34-30 | 824/f | 2.19/f | * 180/f ² | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1,500 | | | f/1500 | 30 |
| 1,500-100,000 | | | 1.0 | 30 |

4.2 MPE Calculation Method

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \text{ Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

If, Substituting the MPE safe distance using d = 20 cm into Equation 1:

$$S = 0.000199 \times P \times G$$

4.3 MPE EXEMPTION

- (A) The available maximum time-averaged power is no more than 1 mW
- (B) The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

- (C) Using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

| Single RF Sources Subject to Routine Environmental Evaluation | |
|---|-----------------------|
| RF Source frequency (MHz) | Threshold ERP (watts) |
| 0.3-1.34 | 1,920 R^2 . |
| 1.34-30 | 3,450 R^2/f^2 . |
| 30-300 | 3.83 R^2 . |
| 300-1,500 | 0.0128 R^2f . |
| 1,500-100,000 | 19.2 R^2 . |

Note: R is in meters, f is in MHz.

4.4 Multiple RF sources

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

5 MPE Exemption Option B

Bluetooth

| Mode | Frequency (MHz) | R(m) | Max. Avg power(dBm) | G(dBi) | Max. Avg EIRP(dBm) | Max. Avg ERP(dBm) | Max. Avg ERP(mW) | ERP Threshold (mW) | MPE Exemption |
|------|-----------------|------|---------------------|--------|--------------------|-------------------|------------------|--------------------|---------------|
| BLE | 2440.00 | 0.2 | 7.92 | 1.81 | 9.73 | 7.58 | 5.728 | 3060 | Complies |

WIFI 2.4GHz (DTS)

| Mode | Frequency (MHz) | R(m) | Max. Avg power(dBm) | G(dBi) | Max. Avg EIRP(dBm) | Max. Avg ERP(dBm) | Max. Avg ERP(mW) | ERP Threshold (mW) | MPE Exemption |
|----------------------|-----------------|------|---------------------|--------|--------------------|-------------------|------------------|--------------------|---------------|
| IEEE 802.11b | 2437.00 | 0.2 | 19.65 | 1.81 | 21.46 | 19.31 | 85.310 | 3060 | Complies |
| IEEE 802.11g | 2437.00 | 0.2 | 18.36 | 1.81 | 20.17 | 18.02 | 63.387 | 3060 | Complies |
| IEEE 802.11n HT 20 | 2437.00 | 0.2 | 18.33 | 1.81 | 20.14 | 17.99 | 62.951 | 3060 | Complies |
| IEEE 802.11n HT 40 | 2437.00 | 0.2 | 13.47 | 1.81 | 15.28 | 13.13 | 20.559 | 3060 | Complies |
| IEEE 802.11ac VHT 20 | 2437.00 | 0.2 | 17.95 | 1.81 | 19.76 | 17.61 | 57.677 | 3060 | Complies |
| IEEE 802.11ac VHT 40 | 2437.00 | 0.2 | 13.45 | 1.81 | 15.26 | 13.11 | 20.464 | 3060 | Complies |

WIFI 5.2GHz (U-NII-1)

| Mode | Frequency (MHz) | R(m) | Max. Avg power(dBm) | G(dBi) | Max. Avg EIRP(dBm) | Max. Avg ERP(dBm) | Max. Avg ERP(mW) | ERP Threshold (mW) | MPE Exemption |
|----------------------|-----------------|------|---------------------|--------|--------------------|-------------------|------------------|--------------------|---------------|
| IEEE 802.11a | 5220.00 | 0.2 | 18.18 | 1.24 | 19.42 | 17.27 | 53.333 | 3060 | Complies |
| IEEE 802.11n HT 20 | 5240.00 | 0.2 | 17.97 | 1.24 | 19.21 | 17.06 | 50.816 | 3060 | Complies |
| IEEE 802.11n HT 40 | 5230.00 | 0.2 | 16.66 | 1.24 | 17.90 | 15.75 | 37.584 | 3060 | Complies |
| IEEE 802.11ac VHT 20 | 5220.00 | 0.2 | 17.92 | 1.24 | 19.16 | 17.01 | 50.234 | 3060 | Complies |
| IEEE 802.11ac VHT 40 | 5230.00 | 0.2 | 16.60 | 1.24 | 17.84 | 15.69 | 37.068 | 3060 | Complies |
| IEEE 802.11ac VHT 80 | 5210.00 | 0.2 | 12.60 | 1.24 | 13.84 | 11.69 | 14.757 | 3060 | Complies |

WIFI 5.3GHz (U-NII-2A)

| Mode | Frequency (MHz) | R(m) | Max. Avg power(dBm) | G(dBi) | Max. Avg EIRP(dBm) | Max. Avg ERP(dBm) | Max. Avg ERP(mW) | ERP Threshold (mW) | MPE Exemption |
|----------------------|-----------------|------|---------------------|--------|--------------------|-------------------|------------------|--------------------|---------------|
| IEEE 802.11a | 5300.00 | 0.2 | 17.48 | 2.66 | 20.14 | 17.99 | 62.951 | 3060 | Complies |
| IEEE 802.11n HT 20 | 5300.00 | 0.2 | 17.63 | 2.66 | 20.29 | 18.14 | 65.163 | 3060 | Complies |
| IEEE 802.11n HT 40 | 5270.00 | 0.2 | 17.37 | 2.66 | 20.03 | 17.88 | 61.376 | 3060 | Complies |
| IEEE 802.11ac VHT 20 | 5300.00 | 0.2 | 17.56 | 2.66 | 20.22 | 18.07 | 64.121 | 3060 | Complies |
| IEEE 802.11ac VHT 40 | 5270.00 | 0.2 | 17.36 | 2.66 | 20.02 | 17.87 | 61.235 | 3060 | Complies |
| IEEE 802.11ac VHT 80 | 5290.00 | 0.2 | 13.40 | 2.66 | 16.06 | 13.91 | 24.604 | 3060 | Complies |

WIFI 5.5GHz (U-NII-2C)

| Mode | Frequency (MHz) | R(m) | Max. Avg power(dBm) | G(dBi) | Max. Avg EIRP(dBm) | Max. Avg ERP(dBm) | Max. Avg ERP(mW) | ERP Threshold (mW) | MPE Exemption |
|----------------------|-----------------|------|---------------------|--------|--------------------|-------------------|------------------|--------------------|---------------|
| IEEE 802.11a | 5580.00 | 0.2 | 17.19 | 2.66 | 19.85 | 17.70 | 58.884 | 3060 | Complies |
| IEEE 802.11n HT 20 | 5580.00 | 0.2 | 17.05 | 2.66 | 19.71 | 17.56 | 57.016 | 3060 | Complies |
| IEEE 802.11n HT 40 | 5550.00 | 0.2 | 16.03 | 2.66 | 18.69 | 16.54 | 45.082 | 3060 | Complies |
| IEEE 802.11ac VHT 20 | 5580.00 | 0.2 | 16.95 | 2.66 | 19.61 | 17.46 | 55.719 | 3060 | Complies |
| IEEE 802.11ac VHT 40 | 5550.00 | 0.2 | 15.99 | 2.66 | 18.65 | 16.50 | 44.668 | 3060 | Complies |
| IEEE 802.11ac VHT 80 | 5610.00 | 0.2 | 16.40 | 2.66 | 19.06 | 16.91 | 49.091 | 3060 | Complies |

WIFI 5.8GHz (U-NII-3)

| Mode | Frequency (MHz) | R(m) | Max. Avg power(dBm) | G(dBi) | Max. Avg EIRP(dBm) | Max. Avg ERP(dBm) | Max. Avg ERP(mW) | ERP Threshold (mW) | MPE Exemption |
|---------------------|-----------------|------|---------------------|--------|--------------------|-------------------|------------------|--------------------|---------------|
| IEEE 802.11a | 5745.00 | 0.2 | 18.67 | 1.38 | 20.05 | 17.90 | 61.660 | 3060 | Complies |
| IEEE 802.11n HT20 | 5825.00 | 0.2 | 18.81 | 1.38 | 20.19 | 18.04 | 63.680 | 3060 | Complies |
| IEEE 802.11n HT40 | 5755.00 | 0.2 | 19.23 | 1.38 | 20.61 | 18.46 | 70.146 | 3060 | Complies |
| IEEE 802.11ac VHT20 | 5825.00 | 0.2 | 18.72 | 1.38 | 20.10 | 17.95 | 62.373 | 3060 | Complies |
| IEEE 802.11ac VHT40 | 5755.00 | 0.2 | 19.16 | 1.38 | 20.54 | 18.39 | 69.024 | 3060 | Complies |
| IEEE 802.11ac VHT80 | 5775.00 | 0.2 | 16.88 | 1.38 | 18.26 | 16.11 | 40.832 | 3060 | Complies |

Zigbee

| Mode | Frequency (MHz) | R(m) | Max. Avg power(dBm) | G(dBi) | Max. Avg EIRP(dBm) | Max. Avg ERP(dBm) | Max Tune-up ERP(mW) | ERP Threshold (mW) | MPE Exemption |
|--------|-----------------|------|---------------------|--------|--------------------|-------------------|---------------------|--------------------|---------------|
| Zigbee | 2440.00 | 0.2 | 10.50 | 1.30 | 11.80 | 9.65 | 9.226 | 3060 | Complies |

6 Simultaneous Transmission Exempt

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation),

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

Simultaneous Transmission Condition

| RF Exposure Condition | Item | Capable Transmit Configurations | | | | |
|-----------------------|-------|---------------------------------|----|----|--------|--------|
| | 1 | DTS | + | BT | + | Zigbee |
| 2 | U-NII | + | BT | + | Zigbee | |

6.1 Sum of the WIFI 2.4GHz & WIFI 5GHz+ Bluetooth+ Zigbee

WiFi 2.4GHz + Bluetooth + Zigbee

| Mode | Frequency (MHz) | Max. Avg ERP(mW) | ERP Threshold (mW) | simultaneous Transmission | simultaneous Transmission Limit |
|-------------|-----------------|------------------|--------------------|---------------------------|---------------------------------|
| WiFi 2.4GHz | 2437.00 | 85.310 | 3060 | 0.033 | ≤1 |
| Bluetooth | 2440.00 | 5.728 | 3060 | | |
| Zigbee | 2440.00 | 9.226 | 3060 | | |

WiFi 5GHz + Bluetooth + Zigbee

| Mode | Frequency (MHz) | Max. Avg ERP(mW) | ERP Threshold (mW) | simultaneous Transmission | simultaneous Transmission Limit |
|-----------|-----------------|------------------|--------------------|---------------------------|---------------------------------|
| WiFi 5GHz | 5755.00 | 70.146 | 3060 | 0.028 | ≤1 |
| Bluetooth | 2440.00 | 5.728 | 3060 | | |
| Zigbee | 2440.00 | 9.226 | 3060 | | |



Report No.: TMWK2305001708KS

Page 17 / 17

Rev.: 02

7 Facilities

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

No. 12, Ln. 116, Wugong 3rd Rd., Wugu Dist., New Taipei City, Taiwan.

--End of Test Report--