

Report No.: SUZR/2022/1002202

Rev.: 02

Page: 85 of 102

Test Band = NSA DC_2A_n66_ TM1 Test Channel = High Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3521.25	72.79	-111.40	-38.61	-13.00	25.61	142	191	Horizontal				
2	5283.27	50.47	-106.69	-56.22	-13.00	43.22	264	64	Horizontal				
3	7044.36	48.66	-101.57	-52.91	-13.00	39.91	175	222	Horizontal				
4	8805.45	47.03	-95.98	-48.95	-13.00	35.95	298	240	Horizontal				
5	10566.54	42.97	-92.37	-49.40	-13.00	36.40	175	321	Horizontal				
6	12327.63	41.62	-91.42	-49.80	-13.00	36.80	264	222	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3521.25	61.03	-111.40	-50.37	-13.00	37.37	152	360	Vertical				
2	5283.27	51.40	-106.69	-55.29	-13.00	42.29	175	3	Vertical				
3	7044.36	47.47	-101.57	-54.10	-13.00	41.10	264	360	Vertical				
4	8805.45	47.18	-95.98	-48.80	-13.00	35.80	175	66	Vertical				
5	10566.54	43.34	-92.37	-49.03	-13.00	36.03	264	31	Vertical				
6	12327.63	41.41	-91.42	-50.01	-13.00	37.01	174	307	Vertical				





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 86 of 102

Test Band = NSA DC_5A_n66_ TM1 Test Channel = Low Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3422.18	50.32	-111.71	-61.39	-13.00	48.39	263	27	Horizontal				
2	5133.27	49.05	-106.90	-57.85	-13.00	44.85	214	225	Horizontal				
3	6844.36	48.24	-101.87	-53.63	-13.00	40.63	211	88	Horizontal				
4	8555.45	46.01	-96.83	-50.82	-13.00	37.82	155	160	Horizontal				
5	9830.25	56.40	-94.16	-37.76	-13.00	24.76	264	27	Horizontal				
6	11796.75	49.26	-91.76	-42.50	-13.00	29.50	177	40	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3422.18	49.72	-111.71	-61.99	-13.00	48.99	214	38	Vertical				
2	5133.27	48.64	-106.90	-58.26	-13.00	45.26	196	321	Vertical				
3	6844.36	47.95	-101.87	-53.92	-13.00	40.92	352	333	Vertical				
4	8555.45	47.01	-96.83	-49.82	-13.00	36.82	174	137	Vertical				
5	9830.25	57.96	-94.16	-36.20	-13.00	23.20	175	357	Vertical				
6	11796.75	54.28	-91.76	-37.48	-13.00	24.48	264	0	Vertical				





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 87 of 102

Test Band = NSA DC_5A_n66_ TM1 Test Channel = Mid Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3471	72.81	-111.61	-38.80	-13.00	25.80	241	273	Horizontal				
2	5206.5	54.88	-106.80	-51.92	-13.00	38.92	163	346	Horizontal				
3	6942	53.10	-101.67	-48.57	-13.00	35.57	384	238	Horizontal				
4	8680.45	46.98	-96.47	-49.49	-13.00	36.49	175	357	Horizontal				
5	9830.25	57.62	-94.16	-36.54	-13.00	23.54	264	0	Horizontal				
6	11796.75	48.00	-91.76	-43.76	-13.00	30.76	175	66	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3471	71.46	-111.61	-40.15	-13.00	27.15	214	285	Vertical				
2	5206.5	61.09	-106.80	-45.71	-13.00	32.71	264	0	Vertical				
3	6942	52.53	-101.67	-49.14	-13.00	36.14	174	285	Vertical				
4	8677.5	51.36	-96.49	-45.13	-13.00	32.13	265	31	Vertical				
5	9830.25	56.93	-94.16	-37.23	-13.00	24.23	178	189	Vertical				
6	11796.75	54.78	-91.76	-36.98	-13.00	23.98	264	177	Vertical				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is darwn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sold responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443.



Report No.: SUZR/2022/1002202

Rev.: 02

Page: 88 of 102

Test Band = NSA DC_5A_n66_ TM1 Test Channel = High Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3521.25	61.47	-111.40	-49.93	-13.00	36.93	231	129	Horizontal				
2	5283.27	50.78	-106.69	-55.91	-13.00	42.91	142	274	Horizontal				
3	7044.36	48.24	-101.57	-53.33	-13.00	40.33	265	30	Horizontal				
4	8805.45	45.33	-95.98	-50.65	-13.00	37.65	144	228	Horizontal				
5	9830.25	55.00	-94.16	-39.16	-13.00	26.16	175	192	Horizontal				
6	11796.75	48.55	-91.76	-43.21	-13.00	30.21	268	178	Horizontal				

Final	Final Data List												
NO	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3521.25	58.33	-111.40	-53.07	-13.00	40.07	362	259	Vertical				
2	5283.27	50.74	-106.69	-55.95	-13.00	42.95	241	346	Vertical				
3	7044.36	48.44	-101.57	-53.13	-13.00	40.13	185	346	Vertical				
4	8805.45	46.46	-95.98	-49.52	-13.00	36.52	264	334	Vertical				
5	9830.25	59.12	-94.16	-35.04	-13.00	22.04	175	96	Vertical				
6	11796.75	54.52	-91.76	-37.24	-13.00	24.24	266	321	Vertical				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sps.com/en/Terms-end-Conditions.aspx and, for electronic Documents at http://www.sps.com/en/Terms-end-Conditions-End-Conditions-

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国 (江苏) 自由贸易试验区苏州片区苏州工业园区测胜路1号的6号厂房南部 鄉鄉: 215000

t (86–512) 62992980 www.sgsgroup.com.cn t (86–512) 62992980 sgs.china@sgs.com



Report No.: SUZR/2022/1002202

Rev.: 02

Page: 89 of 102

Test Band = NSA DC_12A_n66_ TM1 Test Channel = Low Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3422.18	50.71	-111.71	-61.00	-13.00	48.00	214	99	Horizontal				
2	5133.27	49.18	-106.90	-57.72	-13.00	44.72	162	272	Horizontal				
3	6844.36	47.65	-101.87	-54.22	-13.00	41.22	241	16	Horizontal				
4	8555.45	45.44	-96.83	-51.39	-13.00	38.39	175	357	Horizontal				
5	9830.25	56.35	-94.16	-37.81	-13.00	24.81	264	0	Horizontal				
6	11796.75	49.85	-91.76	-41.91	-13.00	28.91	175	160	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3422.18	49.12	-111.71	-62.59	-13.00	49.59	217	310	Vertical				
2	5133.27	48.67	-106.90	-58.23	-13.00	45.23	288	248	Vertical				
3	6844.36	47.81	-101.87	-54.06	-13.00	41.06	174	346	Vertical				
4	8555.45	45.88	-96.83	-50.95	-13.00	37.95	266	223	Vertical				
5	9830.25	56.52	-94.16	-37.64	-13.00	24.64	241	162	Vertical				
6	11796.75	53.25	-91.76	-38.51	-13.00	25.51	162	357	Vertical				





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 90 of 102

Test Band = NSA DC_12A_n66_ TM1 Test Channel = Mid Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3471	72.81	-111.61	-38.80	-13.00	25.80	264	273	Horizontal				
2	5206.5	54.88	-106.80	-51.92	-13.00	38.92	175	346	Horizontal				
3	6942	53.10	-101.67	-48.57	-13.00	35.57	268	238	Horizontal				
4	8680.45	46.98	-96.47	-49.49	-13.00	36.49	175	357	Horizontal				
5	9830.25	57.62	-94.16	-36.54	-13.00	23.54	269	0	Horizontal				
6	11796.75	48.00	-91.76	-43.76	-13.00	30.76	241	66	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3471	71.46	-111.61	-40.15	-13.00	27.15	210	285	Vertical				
2	5206.5	61.09	-106.80	-45.71	-13.00	32.71	145	0	Vertical				
3	6942	52.53	-101.67	-49.14	-13.00	36.14	268	285	Vertical				
4	8677.5	51.36	-96.49	-45.13	-13.00	32.13	175	31	Vertical				
5	9830.25	56.93	-94.16	-37.23	-13.00	24.23	266	189	Vertical				
6	11796.75	54.78	-91.76	-36.98	-13.00	23.98	274	177	Vertical				





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 91 of 102

Test Band = NSA DC_12A_n66_ TM1 Test Channel = High Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3521.25	61.47	-111.40	-49.93	-13.00	36.93	214	129	Horizontal				
2	5283.27	50.78	-106.69	-55.91	-13.00	42.91	175	274	Horizontal				
3	7044.36	48.24	-101.57	-53.33	-13.00	40.33	264	30	Horizontal				
4	8805.45	45.33	-95.98	-50.65	-13.00	37.65	175	228	Horizontal				
5	9830.25	55.00	-94.16	-39.16	-13.00	26.16	211	192	Horizontal				
6	11796.75	48.55	-91.76	-43.21	-13.00	30.21	177	178	Horizontal				

Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority			
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	3521.25	58.33	-111.40	-53.07	-13.00	40.07	222	259	Vertical			
2	5283.27	50.74	-106.69	-55.95	-13.00	42.95	163	346	Vertical			
3	7044.36	48.44	-101.57	-53.13	-13.00	40.13	324	346	Vertical			
4	8805.45	46.46	-95.98	-49.52	-13.00	36.52	175	334	Vertical			
5	9830.25	59.12	-94.16	-35.04	-13.00	22.04	264	96	Vertical			
6	11796.75	54.52	-91.76	-37.24	-13.00	24.24	177	321	Vertical			





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 92 of 102

Test Band = NSA DC_13A_n66_ TM1 Test Channel = Low Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3424.18	49.51	-111.70	-62.19	-13.00	49.19	263	333	Horizontal				
2	5136.27	49.45	-106.90	-57.45	-13.00	44.45	341	258	Horizontal				
3	6848.36	49.28	-101.86	-52.58	-13.00	39.58	175	146	Horizontal				
4	8555.45	46.76	-96.83	-50.07	-13.00	37.07	321	36	Horizontal				
5	9830.25	54.91	-94.16	-39.25	-13.00	26.25	264	1	Horizontal				
6	11796.75	48.88	-91.76	-42.88	-13.00	29.88	175	345	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3424.18	51.49	-111.70	-60.21	-13.00	47.21	263	335	Vertical				
2	5136.27	50.05	-106.90	-56.85	-13.00	43.85	341	198	Vertical				
3	6848.36	47.86	-101.86	-54.00	-13.00	41.00	185	40	Vertical				
4	9830.25	56.76	-94.16	-37.40	-13.00	24.40	264	2	Vertical				
5	11796.75	53.70	-91.76	-38.06	-13.00	25.06	175	0	Vertical				
6	14745.75	46.49	-89.54	-43.05	-13.00	30.05	268	149	Vertical				





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 93 of 102

Test Band = NSA DC_13A_n66_ TM1 Test Channel = Mid Channel

Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority			
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	3454.18	49.97	-111.64	-61.67	-13.00	48.67	264	189	Horizontal			
2	5181.27	49.13	-106.84	-57.71	-13.00	44.71	174	19	Horizontal			
3	5898	60.20	-104.87	-44.67	-13.00	31.67	214	298	Horizontal			
4	6908.36	48.04	-101.69	-53.65	-13.00	40.65	294	56	Horizontal			
5	9830.25	56.25	-94.16	-37.91	-13.00	24.91	162	9	Horizontal			
6	11796.75	49.21	-91.76	-42.55	-13.00	29.55	275	29	Horizontal			

Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority			
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	3454.18	50.57	-111.64	-61.07	-13.00	48.07	210	250	Vertical			
2	5181.27	49.81	-106.84	-57.03	-13.00	44.03	196	201	Vertical			
3	5898.75	55.77	-104.86	-49.09	-13.00	36.09	354	238	Vertical			
4	9830.25	55.31	-94.16	-38.85	-13.00	25.85	244	0	Vertical			
5	11796.75	54.39	-91.76	-37.37	-13.00	24.37	174	357	Vertical			
6	14745.75	45.94	-89.54	-43.60	-13.00	30.60	268	42	Vertical			





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 94 of 102

Test Band = NSA DC_13A_n66_ TM1 Test Channel = High Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3520.5	64.97	-111.40	-46.43	-13.00	33.43	221	78	Horizontal				
2	5281.5	54.24	-106.70	-52.46	-13.00	39.46	177	176	Horizontal				
3	7044.36	48.42	-101.57	-53.15	-13.00	40.15	155	126	Horizontal				
4	8838	48.94	-95.93	-46.99	-13.00	33.99	265	188	Horizontal				
5	9830.25	55.26	-94.16	-38.90	-13.00	25.90	177	96	Horizontal				
6	11796.75	49.54	-91.76	-42.22	-13.00	29.22	144	321	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3521.25	62.55	-111.40	-48.85	-13.00	35.85	265	163	Vertical				
2	5281.5	59.58	-106.70	-47.12	-13.00	34.12	296	249	Vertical				
3	7042.5	59.86	-101.57	-41.71	-13.00	28.71	147	286	Vertical				
4	9830.25	56.98	-94.16	-37.18	-13.00	24.18	174	347	Vertical				
5	11796.75	55.98	-91.76	-35.78	-13.00	22.78	170	0	Vertical				
6	14745.75	46.29	-89.54	-43.25	-13.00	30.25	136	213	Vertical				





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 95 of 102

Test Band = NSA DC_30A_n66_ TM1 Test Channel = Low Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3422.18	49.88	-111.71	-61.83	-13.00	48.83	263	174	Horizontal				
2	5133.27	50.20	-106.90	-56.70	-13.00	43.70	321	103	Horizontal				
3	6844.36	48.11	-101.87	-53.76	-13.00	40.76	152	149	Horizontal				
4	8555.45	46.17	-96.83	-50.66	-13.00	37.66	264	149	Horizontal				
5	10266.54	43.94	-93.20	-49.26	-13.00	36.26	175	20	Horizontal				
6	11977.63	43.18	-91.95	-48.77	-13.00	35.77	211	9	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3422.18	49.58	-111.71	-62.13	-13.00	49.13	211	345	Vertical				
2	5133.27	48.58	-106.90	-58.32	-13.00	45.32	163	21	Vertical				
3	6916.5	55.77	-101.68	-45.91	-13.00	32.91	241	54	Vertical				
4	8555.45	45.97	-96.83	-50.86	-13.00	37.86	174	249	Vertical				
5	10266.54	43.18	-93.20	-50.02	-13.00	37.02	266	54	Vertical				
6	11977.63	42.07	-91.95	-49.88	-13.00	36.88	252	0	Vertical				





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 96 of 102

Test Band = NSA DC_30A_n66_ TM1 Test Channel = Mid Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3472.18	50.15	-111.61	-61.46	-13.00	48.46	241	3	Horizontal				
2	5208.27	50.85	-106.80	-55.95	-13.00	42.95	162	19	Horizontal				
3	6944.36	46.66	-101.67	-55.01	-13.00	42.01	214	314	Horizontal				
4	8680.45	46.47	-96.47	-50.00	-13.00	37.00	175	230	Horizontal				
5	10416.54	42.19	-92.76	-50.57	-13.00	37.57	365	35	Horizontal				
6	12152.63	41.14	-91.73	-50.59	-13.00	37.59	175	0	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3472.18	51.80	-111.61	-59.81	-13.00	46.81	241	248	Vertical				
2	5208.27	50.27	-106.80	-56.53	-13.00	43.53	152	0	Vertical				
3	6944.36	47.87	-101.67	-53.80	-13.00	40.80	264	248	Vertical				
4	8680.45	47.41	-96.47	-49.06	-13.00	36.06	175	164	Vertical				
5	10416.54	41.37	-92.76	-51.39	-13.00	38.39	261	18	Vertical				
6	12152.63	42.55	-91.73	-49.18	-13.00	36.18	142	115	Vertical				





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 97 of 102

Test Band = NSA DC_30A_n66_ TM1 Test Channel = High Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3522.18	49.76	-111.39	-61.63	-13.00	48.63	214	230	Horizontal				
2	5283.27	50.04	-106.69	-56.65	-13.00	43.65	263	328	Horizontal				
3	7044.36	47.63	-101.57	-53.94	-13.00	40.94	217	0	Horizontal				
4	8805.45	45.38	-95.98	-50.60	-13.00	37.60	265	213	Horizontal				
5	10566.54	41.96	-92.37	-50.41	-13.00	37.41	175	197	Horizontal				
6	12327.63	42.01	-91.42	-49.41	-13.00	36.41	260	35	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3522.18	49.88	-111.39	-61.51	-13.00	48.51	233	231	Vertical				
2	5283.27	53.47	-106.69	-53.22	-13.00	40.22	362	357	Vertical				
3	7044.36	47.02	-101.57	-54.55	-13.00	41.55	214	248	Vertical				
4	8805.45	45.67	-95.98	-50.31	-13.00	37.31	152	48	Vertical				
5	10566.54	42.29	-92.37	-50.08	-13.00	37.08	265	96	Vertical				
6	12327.63	41.75	-91.42	-49.67	-13.00	36.67	214	325	Vertical				





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 98 of 102

Test Band = NSA DC_48A_n66_ TM1 Test Channel = Low Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3422.18	39.19	-88.29	-49.10	-13.00	36.10	241	132	Horizontal				
2	5133.27	49.08	-105.65	-56.57	-13.00	43.57	175	360	Horizontal				
3	6844.36	48.24	-101.68	-53.44	-13.00	40.44	264	113	Horizontal				
4	8555.45	44.93	-96.80	-51.87	-13.00	38.87	222	224	Horizontal				
5	10266.54	43.77	-93.23	-49.46	-13.00	36.46	211	63	Horizontal				
6	11977.63	42.98	-91.90	-48.92	-13.00	35.92	196	29	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3422.18	39.14	-88.29	-49.15	-13.00	36.15	142	349	Vertical				
2	5133.27	49.15	-105.65	-56.50	-13.00	43.50	214	95	Vertical				
3	6844.36	49.09	-101.68	-52.59	-13.00	39.59	175	210	Vertical				
4	8555.45	46.14	-96.80	-50.66	-13.00	37.66	294	64	Vertical				
5	10266.54	43.88	-93.23	-49.35	-13.00	36.35	176	3	Vertical				
6	11977.63	42.98	-91.90	-48.92	-13.00	35.92	266	126	Vertical				





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 99 of 102

Test Band = NSA DC_48A_n66_ TM1 Test Channel = Mid Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3472.18	45.10	-88.08	-42.98	-13.00	29.98	163	133	Horizontal				
2	5208.27	50.22	-105.7	-55.56	-13.00	42.56	326	327	Horizontal				
3	6944.36	48.08	-101.4	-53.36	-13.00	40.36	286	360	Horizontal				
4	8680.45	46.83	-96.34	- 49.51	-13.00	36.51	247	32	Horizontal				
5	10416.54	41.48	-92.81	-51.33	-13.00	38.33	186	358	Horizontal				
6	12152.63	41.39	-91.64	-50.25	-13.00	37.25	241	279	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority.				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3472.18	39.13	-88.08	-48.95	-13.00	35.95	142	143	Vertical				
2	5208.27	49.69	-105.7	-56.09	-13.00	43.09	264	4	Vertical				
3	6944.36	47.38	-101.4	-54.06	-13.00	41.06	178	114	Vertical				
4	8680.45	46.49	-96.34	-49.85	-13.00	36.85	296	344	Vertical				
5	10416.54	42.59	-92.81	-50.22	-13.00	37.22	241	16	Vertical				
6	12152.63	41.42	-91.64	-50.22	-13.00	37.22	221	4	Vertical				





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 100 of 102

Test Band = NSA DC_48A_n66_ TM1 Test Channel = High Channel

Final	Data List								
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity
1	3522.18	45.96	-87.89	-41.93	-13.00	28.93	152	151	Horizontal
2	5283.27	50.18	-105.7	-55.53	-13.00	42.53	174	125	Horizontal
3	7044.36	49.17	-101.3	-52.20	-13.00	39.20	163	125	Horizontal
4	8805.45	45.09	-95.82	-50.73	-13.00	37.73	321	319	Horizontal
5	10566.54	44.70	-92.36	-47.66	-13.00	34.66	186	240	Horizontal
6	12327.63	41.28	-91.41	-50.13	-13.00	37.13	269	240	Horizontal

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3522.18	39.00	-87.89	-48.89	-13.00	35.89	174	120	Vertical				
2	5283.27	50.40	-105.7	-55.31	-13.00	42.31	186	178	Vertical				
3	7044.36	47.84	-101.3	-53.53	-13.00	40.53	264	212	Vertical				
4	8805.45	47.14	-95.82	-48.68	-13.00	35.68	179	3	Vertical				
5	10566.54	43.30	-92.36	-49.06	-13.00	36.06	284	229	Vertical				
6	12327.63	43.08	-91.41	-48.33	-13.00	35.33	177	161	Vertical				





Report No.: SUZR/2022/1002202

Rev.: 02

Page: 101 of 102

Frequency Stability for SA

Test Result

Frequency Error VS. Voltage

	Voltage												
Band	scs	Bandwid th	Modulation	Cha nnel	RB Config	Voltage	Temp eratur e	Deviation(Hz	Deviation (ppm)	Verdict			
N66	15	40	DFT-PI2BPSK	М	Outer_Full	VH	NT	4.600000	0.002636	PASS			
N66	15	40	DFT-PI2BPSK	М	Outer_Full	VN	NT	1.900000	0.001089	PASS			
N66	15	40	DFT-PI2BPSK	М	Outer_Full	VL	NT	1.200000	0.000688	PASS			
N66	15	40	CP-QPSK	М	Outer_Full	VH	NT	-2.400000	-0.001375	PASS			
N66	15	40	CP-QPSK	М	Outer_Full	VN	NT	-0.500000	-0.000287	PASS			
N66	15	40	CP-QPSK	М	Outer_Full	VL	NT	2.900000	0.001662	PASS			



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sps.com/en/ferms-and-Conditions.aspx and, for electronic Documents at http://www.sps.com/en/ferms-end-Conditions/ferms-e-Document aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction for or the company and the reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention:Corkek the autheriticity of testing furgection report & carrificate please carbactus at telephone; (66-755) \$307 1443.



Report No.: SUZR/2022/1002202

Rev.: 02

Page: 102 of 102

Frequency Error VS. Temperature

					Temperati	ıre				
Band	scs	Bandwid th	Modulation	Cha nnel	RB Config	Voltage	Temp eratur e	Deviation(Hz	Deviation (ppm)	Verdict
N66	15	40	DFT-PI2BPSK	М	Outer_Full	NV	-30	3.800000	0.002178	PASS
N66	15	40	DFT-PI2BPSK	М	Outer_Full	NV	-20	3.900000	0.002235	PASS
N66	15	40	DFT-PI2BPSK	М	Outer_Full	NV	-10	3.400000	0.001948	PASS
N66	15	40	DFT-PI2BPSK	М	Outer_Full	NV	0	1.100000	0.000630	PASS
N66	15	40	DFT-PI2BPSK	М	Outer_Full	NV	10	2.500000	0.001433	PASS
N66	15	40	DFT-PI2BPSK	М	Outer_Full	NV	20	4.700000	0.002693	PASS
N66	15	40	DFT-PI2BPSK	М	Outer_Full	NV	30	0.500000	0.000287	PASS
N66	15	40	DFT-PI2BPSK	М	Outer_Full	NV	40	3.200000	0.001834	PASS
N66	15	40	DFT-PI2BPSK	М	Outer_Full	NV	50	-0.900000	-0.000516	PASS
N66	15	40	CP-QPSK	М	Outer_Full	NV	-30	3.400000	0.001948	PASS
N66	15	40	CP-QPSK	М	Outer_Full	NV	-20	1.200000	0.000688	PASS
N66	15	40	CP-QPSK	М	Outer_Full	NV	-10	0.100000	0.000057	PASS
N66	15	40	CP-QPSK	М	Outer_Full	NV	0	-2.300000	-0.001318	PASS
N66	15	40	CP-QPSK	М	Outer_Full	NV	10	-1.600000	-0.000917	PASS
N66	15	40	CP-QPSK	М	Outer_Full	NV	20	-1.800000	-0.001032	PASS
N66	15	40	CP-QPSK	М	Outer_Full	NV	30	-0.700000	-0.000401	PASS
N66	15	40	CP-QPSK	М	Outer_Full	NV	40	0.200000	0.000115	PASS
N66	15	40	CP-QPSK	М	Outer_Full	NV	50	-1.900000	-0.001089	PASS

The End

