



REPORT No. : SZ19050394W02

TEST REPORT

APPLICANT : JACS Solutions LLC

PRODUCT NAME : 8 INCH TABLET

MODEL NAME : TG0802

BRAND NAME : JACS

FCC ID : 2AGCDJACSTG0802

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2019-06-25

TEST DATE : 2019-07-05 to 2019-07-31

ISSUE DATE : 2019-08-07

Edited by: Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by: Peng Huarui
Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

1. Technical Information	4
1.1. Applicant and Manufacturer Information	4
1.2. Equipment Under Test (EUT) Description	4
1.3. Test Standards and Results	6
1.4. Environmental Conditions	6
2. 47 CFR Part 15C Requirements	7
2.1. Antenna requirement	7
2.2. Duty Cycle Of Test Signal	7
2.3. Maximum Peak and Average Conducted Output Power	11
2.4. Bandwidth	14
2.5. Conducted Spurious Emissions and Band Edge	21
2.6. Power spectral density (PSD)	31
2.7. Conducted Emission	38
2.8. Restricted Frequency Bands	42
2.9. Radiated Emission	51
Annex A Test Uncertainty	67
Annex B Testing Laboratory Information	68



REPORT No. : SZ19050394W02

Change History		
Version	Date	Reason for change
1.0	2019-08-07	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	JACS Solutions LLC
Applicant Address:	8808 Centre Park Drive Suite 305 Columbia, Maryland 21045, USA
Manufacturer:	JACS Solutions LLC
Manufacturer Address:	8808 Centre Park Drive Suite 305 Columbia, Maryland 21045, USA

1.2. Equipment Under Test (EUT) Description

Product Name:	8 INCH TABLET	
Serial No:	(N/A, marked #1 by test site)	
Hardware Version:	V1.0	
Software Version:	V1.0	
Equipment type:	WLAN2.4G	
Modulation Type:	DSSS, OFDM	
Operating Frequency Range:	802.11b/g/ n(HT20): 2.412GHz - 2.462GHz	
Antenna Type:	FPC Antenna	
Antenna Gain:	0.21 dBi	
Accessory Information:	Battery	
	Brand Name:	VEKEN
	Model No.:	72104114
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	8000mAh
	Rated Voltage:	3.7V
	Charge Limit:	5.0 V
Accessory Information:	AC Adapter	
	Brand Name:	Jacs
	Model No.:	JML-0500200-LW
	Serial No.:	(N/A, marked #1 by test site)
	Rated Output:	5V=2A
	Rated Input:	100-240V ~ 50/60Hz 0.3A



Note 1: We use the dedicated software to control the EUT continuous transmission.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3.The channel number and frequency

Test Mode	Channel	Frequency (MHz)	Channel	Frequency (MHz)
802.11b/g/ n(HT20)	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432		
	6	2437		

Note1: The Lowest Channel (1), Middle Channel (6) and Highest Channel (11) was selected test for 802.11b/g/n(HT20) mode;



1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result
1	15.203	Antenna Requirement	N/A	N/A	PASS
2	N/A	Duty Cycle Of Test Signal	Jul 05, 2019	Ouyang Feng	PASS
3	15.247(b)	Maximum Peak and Average Conducted Output Power	Jul 11, 2019	Ouyang Feng	PASS
4	15.247(a)	Bandwidth	Jul 11, 2019	Ouyang Feng	PASS
5	15.247(d)	Conducted Spurious Emission and Band Edge	Jul 11, 2019	Ouyang Feng	PASS
6	15.247(e)	Power spectral density (PSD)	Jul 11, 2019	Ouyang Feng	PASS
7	15.207	Conducted Emission	Jul 31, 2019	Gao Jianrou	PASS
8	15.247(d)	Restricted Frequency Bands	Jul 22, 2019	Gao Jianrou	PASS
9	15.209, 15.247(d)	Radiated Emission	Jul 31, 2019	Gao Jianrou	PASS

Note1: The tests were performed according to the method of measurements prescribed in ANSIC63.10-2013, KDB558074 D01 v05r02 and KDB594280 D01 v02r01.

Note2: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 12dB contains two parts that cable loss 2dB and Attenuator 10dB.

1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106



2. 47 CFR Part 15C Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Duty Cycle Of Test Signal


2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this subclause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be nonconstant.

2.2.2. Test Description

A. Test Set:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.

2.2.3. Test Result

A. Test Verdict:


Test Mode	Duty Cycle (%) (D)	Duty Factor ($10 \cdot \lg[1/D]$)
802.11b	100.00	0.00
802.11g	96.53	0.15
802.11n(HT20)	97.04	0.13




B. Test Plots



(Channel 1, 2412MHz, 802.11b)



(Channel 1, 2412MHz, 802.11g)



(Channel 1, 2412MHz, 802.11 n(HT20))

2.3. Maximum Peak and Average Conducted Output Power


2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.3.2. Test Description

The measured output power was calculated by the reading of the USB Wideband Power Sensor and calibration.

A. Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

**2.3.3. Test Result****Maximum Peak Conducted Output Power****802.11b Test Mode**

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	12.14	0.016	30	1	PASS
6	2437	12.00	0.016			PASS
11	2462	12.51	0.018			PASS

802.11g Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	18.73	0.075	30	1	PASS
6	2437	18.48	0.070			PASS
11	2462	19.98	0.100			PASS

802.11n(HT20) Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	17.32	0.054	30	1	PASS
6	2437	17.22	0.053			PASS
11	2462	17.76	0.060			PASS

**Maximum Average Conducted Output Power****802.11b Test Mode**

Channel	Frequency (MHz)	Average Power			Limit		Verdict
		Measured	Duty factor Calculated				
		dBm	dBm	W	dBm	W	
1	2412	9.15	9.15	0.008	30	1	PASS
6	2437	8.73	8.73	0.007			PASS
11	2462	9.03	9.03	0.008			PASS

802.11g Test mode

Channel	Frequency (MHz)	Average Power			Limit		Verdict
		Measured	Duty factor Calculated				
		dBm	dBm	W	dBm	W	
1	2412	8.21	8.36	0.007	30	1	PASS
6	2437	7.97	8.12	0.006			PASS
11	2462	8.28	8.43	0.007			PASS

802.11n(HT20) Test mode

Channel	Frequency (MHz)	Average Power			Limit		Verdict
		Measured	Duty factor Calculated				
		dBm	dBm	W	dBm	W	
1	2412	6.71	6.84	0.005	30	1	PASS
6	2437	6.41	6.54	0.005			PASS
11	2462	6.88	7.01	0.005			PASS


2.4. Bandwidth

2.4.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.4.2. Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.4.3. Test procedure

KDB 558074 Section 8.2 was used in order to prove compliance.



2.4.4. Test Result

802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	8.54	≥500	PASS
6	2437	8.53	≥500	PASS
11	2462	8.06	≥500	PASS

B. Test Plots



(Channel 1, 802.11b)



(Channel 6, 802.11b)



(Channel 11, 802.11b)




802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	15.10	≥500	PASS
6	2437	15.10	≥500	PASS
11	2462	15.10	≥500	PASS

B. Test Plots:



(Channel 1, 802.11g)



(Channel 6, 802.11g)



(Channel 11, 802.11g)




802.11n(HT20) Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	15.11	≥500	PASS
6	2437	15.11	≥500	PASS
11	2462	15.10	≥500	PASS

B. Test Plots:



(Channel 1, 802.11n(HT20))



(Channel 6, 802.11n(HT20))



(Channel 11, 802.11n(HT20))


2.5. Conducted Spurious Emissions and Band Edge

2.5.1. Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.5.2. Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.5.3. Test procedure

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.




2.5.4. Test Result

802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-24.34	14.37	-5.63	PASS
6	2437	-24.84	13.47	-6.53	PASS
11	2462	-24.57	14.15	-5.85	PASS

B. Test Plots:



(Channel = 1, 30MHz to 25GHz)



(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)




802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-22.99	6.75	-13.25	PASS
6	2437	-23.99	8.20	-11.80	PASS
11	2462	-24.01	8.67	-11.33	PASS


B. Test Plots:



(Channel = 1, 30MHz to 25GHz)



(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)




802.11n(HT20) Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-23.10	8.79	-11.21	PASS
6	2437	-24.91	7.81	-12.19	PASS
11	2462	-24.73	8.89	-11.11	PASS


B. Test Plots:



(Channel = 1, 30MHz to 25GHz)



(Band Edge, Channel = 1)



(Channel = 6, 30MHz to 25GHz)



(Channel = 11, 30MHz to 25GHz)



(Band Edge, Channel = 11)


2.6. Power spectral density (PSD)

2.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.6.2. Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.6.3. Test procedure

KDB 558074 Section 8.4 was used in order to prove compliance.

2.6.4. Test Result

802.11b Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	1.12	8	PASS
6	2437	0.71	8	PASS
11	2462	1.63	8	PASS

B. Test Plots:



(Channel = 1, 802.11b)



(Channel = 6, 802.11b)



(Channel = 11, 802.11b)



A. Test Verd0.90t:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-3.85	8	PASS
6	2437	-2.74	8	PASS
11	2462	-3.12	8	PASS

Agilent Spectrum Analyzer - Swept SA

Marker 1 2.41233000000 GHz

PNO: Fast IF Gain: Low Trig: Free Run Atten: 18 dB

Avg Type: Log-Pwr Avg Hold: >10/10

04:06:55 PM Jul 05, 2019

Ref Offset 12 dB Ref 20.00 dBm

10 dB/div Log

Mkr1 2.412 33 GHz -3.848 dBm

The spectrum analyzer display shows a signal with a peak at 2.41233 GHz. The peak is labeled 'Mkr1' and has a power level of -3.848 dBm. The signal is noisy and has a bandwidth of 30.00 MHz. The center frequency is 2.41200 GHz. The resolution bandwidth is 3.0 kHz. The video bandwidth is 10 kHz. The sweep time is 3.163 s (1001 pts). The reference level is 20.00 dBm. The offset is 12 dB. The peak is marked with a green diamond and the number '1'.

Center 2.41200 GHz Span 30.00 MHz

#Res BW 3.0 kHz #VBW 10 kHz Sweep 3.163 s (1001 pts)

MSG STATUS

Peak Search

Next Peak

Next Pk Right

Next Pk Left

Marker Delta

Mkr→CF

Mkr→Ref Lvl

More 1 of 2

(Channel = 1, 802.11g)



(Channel = 6, 802.11g)



(Channel = 11, 802.11g)

**802.11n(HT20) Test mode****A. Test Verdict:**

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-3.86	8	PASS
6	2437	-3.92	8	PASS
11	2462	-3.87	8	PASS

B. Test Plots:

(Channel = 1, 802.11n(HT20))



(Channel = 6, 802.11n(HT20))



(Channel = 11, 802.11n(HT20))

2.7. Conducted Emission

2.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.7.2. Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10 2013.



2.7.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test setup:

Test Mode: EUT+ADAPTOR + WIFI TX

Test Voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plots:



(L Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1591	39.50	30.44	65.51	55.51	Line	PASS
2	0.5635	36.42	29.37	56.00	46.00		PASS
3	1.5900	30.23	24.20	56.00	46.00		PASS
4	3.4102	24.31	16.29	56.00	46.00		PASS
5	8.6879	34.72	22.35	60.00	50.00		PASS
6	9.3834	36.40	24.02	60.00	50.00		PASS



(N Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1589	43.52	33.98	65.52	55.52	Neutral	PASS
2	0.5008	38.93	30.06	56.00	46.00		PASS
3	0.5635	41.26	31.32	56.00	46.00		PASS
4	1.8736	33.55	25.03	56.00	46.00		PASS
5	9.4480	39.65	28.20	60.00	50.00		PASS
6	15.8343	30.55	22.34	60.00	50.00		PASS


2.8. Restricted Frequency Bands

2.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.8.2. Test Description

A. Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.



2.8.3. Test procedure

KDB 558074 Section 8.6 and 8.7 was used in order to prove compliance.

2.8.4. Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.


802.11b Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2381.54	PK	49.68	-29.67	32.56	52.57	74	PASS
1	2386.22	AV	47.25	-29.67	32.56	50.14	54	PASS
11	2483.50	PK	41.61	-29.67	32.56	44.50	74	PASS
11	2485.82	AV	43.05	-29.67	32.56	45.94	54	PASS



B. Test Plots:



(Channel = 1 PEAK, 802.11b)



(Channel = 1 AVG, 802.11b)



(Channel = 11 PEAK, 802.11b)



(Channel = 11 AVG, 802.11b)




802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBuV/m)	Limit (dBuV/m)	Verdict
		PK/ AV						
1	2390.00	PK	42.30	-29.67	32.56	45.19	74	PASS
1	2390.00	AV	43.17	-29.67	32.56	46.06	54	PASS
11	2483.50	PK	48.05	-29.67	32.56	50.94	74	PASS
11	2483.50	AV	47.49	-29.67	32.56	50.38	54	PASS

B. Test Plots:




(Channel = 1 PEAK, 802.11g)



(Channel = 1 AVG, 802.11g)



(Channel = 11 PEAK, 802.11g)



(Channel = 11 AVG, 802.11g)

802.11 n(HT20) Test mode

A. Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading U _R (dBμV)	A _T (dB)	A _{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2390.00	PK	42.72	-29.67	32.56	45.61	74	PASS
1	2390.00	AV	42.29	-29.67	32.56	45.18	54	PASS
11	2483.50	PK	47.02	-29.67	32.56	49.91	74	PASS
11	2483.50	AV	46.66	-29.67	32.56	49.55	54	PASS




B. Test Plots:




(Channel = 1 PEAK, 802.11n(HT20))



(Channel = 1 AVG, 802.11n(HT20))



(Channel = 11 PEAK, 802.11n(HT20))



(Channel = 11 AVG, 802.11n(HT20))



2.9. Radiated Emission

2.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.


For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


2.9.2. Test Description

A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The RF absorbing material used on the reference ground plane and on the turntable have a maximum height (thickness) of 30 cm (12 in) and have a minimum-rated attenuation of 20 dB at all frequencies from 1 GHz to 18 GHz. Test site have a minimum area of the ground plane covered with RF absorbing material as specified in Figure 6 of ANSI C63.4: 2014.

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10 (2013). For radiated emissions below or equal to 1GHz, The EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading



For the Test Antenna:

(a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Place the test antenna at 3m away from area of the EUT, while keeping the test antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The test antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final test antenna elevation shall be that which maximizes the emissions. The test antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The emission levels at both horizontal and vertical polarizations should be tested.

2.9.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 25GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

**802.11b Test mode**


Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
71.277	34.07	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
396.633	39.91	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1182.900	53.49	N/A	36.31	74.00	N/A	54.00	Horizontal	PASS
1989.400	63.04	N/A	41.74	74.00	N/A	54.00	Horizontal	PASS
2380.700	54.75	N/A	43.13	74.00	N/A	54.00	Horizontal	PASS
3168.503	62.99	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2782.033	53.86	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3168.503	53.99	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3618.000	58.43	N/A	47.62	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)


Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1499.700	53.51	N/A	36.90	74.00	N/A	54.00	Vertical	PASS
1800.000	52.42	N/A	34.10	74.00	N/A	54.00	Vertical	PASS
2100.300	53.95	N/A	36.97	74.00	N/A	54.00	Vertical	PASS
3000.300	57.49	N/A	23.95	74.00	N/A	54.00	Vertical	PASS
3300.100	58.63	N/A	24.49	74.00	N/A	54.00	Vertical	PASS
3617.800	53.59	N/A	24.10	74.00	N/A	54.00	Vertical	PASS
4824.000	55.39	N/A	32.46	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
395.419	38.49	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1188.235	54.53	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
1984.900	63.07	N/A	41.66	74.00	N/A	54.00	Horizontal	PASS
2520.000	58.89	N/A	46.67	74.00	N/A	54.00	Horizontal	PASS
3168.100	55.22	N/A	39.67	74.00	N/A	54.00	Horizontal	PASS
3655.700	57.19	N/A	49.16	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1500.200	54.22	N/A	37.41	74.00	N/A	54.00	Vertical	PASS
2100.200	56.55	N/A	41.08	74.00	N/A	54.00	Vertical	PASS
3000.100	58.32	N/A	40.25	74.00	N/A	54.00	Vertical	PASS
3300.000	58.28	N/A	43.32	74.00	N/A	54.00	Vertical	PASS
3655.792	48.65	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4874.000	52.49	N/A	47.94	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
396.633	38.56	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1187.595	53.38	N/A	41.68	74.00	N/A	54.00	Horizontal	PASS
1984.400	63.78	N/A	46.38	74.00	N/A	54.00	Horizontal	PASS
2536.200	57.76	N/A	38.95	74.00	N/A	54.00	Horizontal	PASS
2772.300	53.18	N/A	40.79	74.00	N/A	54.00	Horizontal	PASS
3168.300	54.55	N/A	44.92	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1200.400	45.38	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1799.680	50.07	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2099.960	48.08	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3000.473	50.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3308.529	51.00	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4924.423	49.53	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)


**802.11g Test mode**

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1500.200	53.43	N/A	37.43	74.00	N/A	54.00	Horizontal	PASS
1799.900	57.57	N/A	38.60	74.00	N/A	54.00	Horizontal	PASS
2383.100	55.22	N/A	36.25	74.00	N/A	54.00	Horizontal	PASS
3000.200	52.63	N/A	36.65	74.00	N/A	54.00	Horizontal	PASS
3300.500	59.19	N/A	43.31	74.00	N/A	54.00	Horizontal	PASS
3617.100	58.94	N/A	46.87	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1809.284	50.47	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2099.960	50.15	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3008.874	50.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3300.127	50.90	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3616.585	51.00	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4826.405	48.90	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1049.940	50.65	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
1500.040	50.24	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2594.800	53.62	N/A	38.94	74.00	N/A	54.00	Horizontal	PASS
3000.473	50.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3300.000	56.73	N/A	40.50	74.00	N/A	54.00	Horizontal	PASS
3654.600	55.14	N/A	46.02	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1500.040	46.18	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1800.300	54.04	N/A	37.41	74.00	N/A	54.00	Vertical	PASS
2099.960	47.68	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3008.874	50.01	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3655.792	48.34	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5677.760	46.71	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1500.200	53.65	N/A	37.27	74.00	N/A	54.00	Horizontal	PASS
1799.900	53.97	N/A	37.94	74.00	N/A	54.00	Horizontal	PASS
2100.300	55.55	N/A	39.71	74.00	N/A	54.00	Horizontal	PASS
2543.700	58.81	N/A	46.68	74.00	N/A	54.00	Horizontal	PASS
3299.900	54.99	N/A	43.28	74.00	N/A	54.00	Horizontal	PASS
3692.900	51.81	N/A	40.50	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1199.760	47.40	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1800.320	50.64	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3000.473	49.56	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3300.100	56.57	N/A	44.46	74.00	N/A	54.00	Vertical	PASS
3692.199	46.72	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5775.777	46.66	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

**802.11n(HT20) Test mode**

Plots for Channel = 1




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1386.200	52.75	N/A	37.48	74.00	N/A	54.00	Horizontal	PASS
1584.100	52.48	N/A	34.69	74.00	N/A	54.00	Horizontal	PASS
1782.000	64.79	N/A	47.76	74.00	N/A	54.00	Horizontal	PASS
1980.000	58.87	N/A	41.49	74.00	N/A	54.00	Horizontal	PASS
2390.400	63.47	N/A	42.29	74.00	N/A	54.00	Horizontal	PASS
2571.100	63.03	N/A	49.29	74.00	N/A	54.00	Horizontal	PASS
3168.100	58.85	N/A	42.60	74.00	N/A	54.00	Horizontal	PASS
3618.900	56.29	N/A	44.71	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1386.100	53.89	N/A	39.30	74.00	N/A	54.00	Vertical	PASS
1584.100	52.59	N/A	37.93	74.00	N/A	54.00	Vertical	PASS
1782.200	57.38	N/A	39.67	74.00	N/A	54.00	Vertical	PASS
1980.100	56.21	N/A	39.76	74.00	N/A	54.00	Vertical	PASS
2772.100	54.11	N/A	38.87	74.00	N/A	54.00	Vertical	PASS
3168.400	63.22	N/A	49.17	74.00	N/A	54.00	Vertical	PASS
3366.200	56.71	N/A	43.17	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 25GHz)

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1782.100	58.74	N/A	43.12	74.00	N/A	54.00	Horizontal	PASS
1980.100	57.11	N/A	41.78	74.00	N/A	54.00	Horizontal	PASS
2376.100	54.48	N/A	39.09	74.00	N/A	54.00	Horizontal	PASS
2514.700	55.63	N/A	43.19	74.00	N/A	54.00	Horizontal	PASS
2574.400	55.40	N/A	39.09	74.00	N/A	54.00	Horizontal	PASS
2772.400	52.86	N/A	36.23	74.00	N/A	54.00	Horizontal	PASS
3168.300	58.51	N/A	41.43	74.00	N/A	54.00	Horizontal	PASS
3655.000	57.45	N/A	46.96	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1782.000	51.28	N/A	43.30	74.00	N/A	54.00	Vertical	PASS
1782.100	57.60	N/A	43.56	74.00	N/A	54.00	Vertical	PASS
1980.100	56.95	N/A	40.51	74.00	N/A	54.00	Vertical	PASS
2772.100	54.45	N/A	38.32	74.00	N/A	54.00	Vertical	PASS
3168.100	64.70	N/A	48.01	74.00	N/A	54.00	Vertical	PASS
3366.200	55.46	N/A	43.81	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)



Plot for Channel = 11




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1584.100	53.42	N/A	38.97	74.00	N/A	54.00	Horizontal	PASS
1782.000	58.82	N/A	45.43	74.00	N/A	54.00	Horizontal	PASS
1980.000	56.67	N/A	41.31	74.00	N/A	54.00	Horizontal	PASS
2178.200	53.50	N/A	36.33	74.00	N/A	54.00	Horizontal	PASS
2376.100	54.45	N/A	37.28	74.00	N/A	54.00	Horizontal	PASS
2574.000	52.96	N/A	37.72	74.00	N/A	54.00	Horizontal	PASS
2970.200	53.25	N/A	37.89	74.00	N/A	54.00	Horizontal	PASS
3168.400	58.25	N/A	44.05	74.00	N/A	54.00	Horizontal	PASS
3366.200	52.30	N/A	38.94	74.00	N/A	54.00	Horizontal	PASS
3693.000	55.69	N/A	45.11	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1386.100	53.70	N/A	38.54	74.00	N/A	54.00	Vertical	PASS
1584.100	54.79	N/A	38.67	74.00	N/A	54.00	Vertical	PASS
1782.200	56.79	N/A	42.01	74.00	N/A	54.00	Vertical	PASS
1980.100	57.50	N/A	40.04	74.00	N/A	54.00	Vertical	PASS
2178.300	48.28	N/A	34.27	74.00	N/A	54.00	Vertical	PASS
2772.000	53.79	N/A	37.59	74.00	N/A	54.00	Vertical	PASS
3168.400	61.51	N/A	44.84	74.00	N/A	54.00	Vertical	PASS
3366.200	54.90	N/A	43.87	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)



Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power spectral density (PSD)	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{ dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Attenuator 1	(N/A.)	10dB	Resnet	N/A	N/A
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2019.04.09	2020.04.08
USB Wideband Power Sensor	MY54210011	U2021XA	Agilent	2019.04.16	2020.04.15
RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial cable	CB02	RF02	Morlab	N/A	N/A
SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A
Computer	T430i	Think Pad	Lenovo	N/A	N/A

4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY56400093	N9038A	KEYSIGHT	2019.05.08	2020.05.09
LISN	812744	NSLK 8127	Schwarzbeck	2019.05.08	2020.05.09
Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2019.05.08	2020.05.09
Coaxial cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A

4.3 List of Software Used

Description	Manufacturer	Software Version
Test system	Tonscend	V2.6
Power Panel	Agilent	V3.8
MORLAB EMCR V1.2	MORLAB	V 1.0

**4.4 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY54130016	N9038A	Agilent	2018.08.04	2019.08.03
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2019.05.08	2020.05.09
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2019.02.15	2020.02.14
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2018.08.06	2019.08.05
Test Antenna – Horn	BBHA9170 #774	BBHA9170	Schwarzbeck	2018.08.02	2019.08.01
Coaxial cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
1-18GHz pre-Amplifier	MA02	TS-PR18	Rohde& Schwarz	2019.05.08	2020.05.09
18-26.5GHz pre-Amplifier	MA03	TS-PR18	Rohde& Schwarz	2019.05.08	2020.05.09
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2018.12.01	2019.11.30
Anechoic Chamber	N/A	9m*6m*6m	CRT	2017.11.19	2020.11.18

_____ END OF REPORT _____