

Shenzhen Silver Star Intelligent Technology Co., Ltd.

(User Manual_Inxni-01)

Specifications:

Model No. :	Inxni -01
Battery :	3V
Dimensions :	90.0*64.0*11.0mm
Transmit frequency	2430 MHz
Data Transmit mode	FSK
Ambient Temperature :	0~40°C

Applications :

- Robotic vacuum cleaner and beds Remote controls.
- Other electric furniture controls.

FCC ID: 2AGE6- INXNI01

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Shenzhen Silver Star Intelligent Technology Co., Ltd.

(User Manual_Inxni-01)

Use:

Button function, see the attached diagram

Electrical performance:

1. 3V use alkaline battery-powered, Operating Current $\leq 18\text{mA}$
2. Wireless remote control distance of ≥ 5 meters
3. Standby operating current $\leq 10\mu\text{A}$

Size and Funtion Diagram :

