

FCC 47 CFR MPE REPORT

Shenzhen Silver Star Intelligent Technology Co., Ltd.

Robot Vacuum Cleaner

Model Number: RS11

FCC ID: 2AGE6-RS11

Prepared for:	Shenzhen Silver Star Intelligent Technology Co., Ltd.
	Building A1, Silver Star Hi-Tech Industrial Park, Guanguang Road, Guanlan Street, Longhua District, Shenzhen 518110, China.
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2108069
Date of Test:	Apr. 22~Aug. 03, 2021
Date of Report:	Aug. 06, 2021

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	17.39	54.828	17±2	2.5	1.778
	2437	17.44	55.463	17±2	2.5	1.778
	2462	17.46	55.719	17±2	2.5	1.778
IEEE 802.11g	2412	19.38	86.696	19±2	2.5	1.778
	2437	18.78	75.509	18±2	2.5	1.778
	2462	18.71	74.302	18±2	2.5	1.778
IEEE 802.11n HT20	2412	18.94	78.343	18±2	2.5	1.778
	2437	18.74	74.817	18±2	2.5	1.778
	2462	18.68	73.790	18±2	2.5	1.778
IEEE 802.11n HT40	2422	18.75	74.989	18±2	2.5	1.778
	2437	18.67	73.621	18±2	2.5	1.778
	2452	18.73	74.645	18±2	2.5	1.778

3. Calculated Result and Limit

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
2.4G Band						
IEEE 802.11b	19	2.5	1.778	0.02810	1	Complies
IEEE 802.11g	21	2.5	1.778	0.04454	1	Complies
IEEE 802.11n HT20	20	2.5	1.778	0.03538	1	Complies
IEEE 802.11n HT40	20	2.5	1.778	0.03538	1	Complies

End of Test Report