

# Appendix 6

## RF Exposure Information

FCC ID: 2AGEG-DELBT0001  
 Model: RF-BM-N16B2C1C

**Maximum transmitter power:**

Frequency (MHz)	Maximum peak output power (dBm)	Output power(mW)
2402	-1.22	0.76
2440	-1.12	0.77
2480	-1.65	0.68

**For FCC**

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$$

for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,<sup>24</sup> where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>25</sup>
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

**Result:**

$$(0.76/5) \cdot \sqrt{2.402} = 0.236 < 3.0$$

$$(0.77/5) \cdot \sqrt{2.440} = 0.241 < 3.0$$

$$(0.68/5) \cdot \sqrt{2.480} = 0.214 < 3.0$$

**Conclusion:**

No SAR is required.