

Oct. 15th. 2020

TUV SUD America Inc.
10 Centennial Drive
Peabody, MA 01960, USA

Attention: Director of Certification

**RE: Analysis of RF Exposure for RF Exposure for Portable and Mobile use per KDB 447498 D01
RF Exposure Procedure and Equipment Authorization Policies for Mobile and Portable Devices
v06 and RSS-102 Issue 5 March 2015**

FCC ID: 2AGF8-TXMBR
IC: 20931-TXMBR

Portable exposure SAR Exemption Calculation using a 5 mm separation distance:

As per Clause 4.3.1 (a) of KDB 447498 D01 v06:

$$\left(\frac{\text{max.power of channel, including tune-up tolerance, mW}}{\text{min.test separation distance, mm}} \right) \times \left(\sqrt{f(\text{GHz})} \right) \leq 3.0$$

$$\left(\frac{0.43 \text{ mW}}{5 \text{ mm}} \right) \times \left(\sqrt{2.481(\text{GHz})} \right) \leq 3.0$$

0.135 ≤ 3.0 (complies)

The EUT complies with the exemption limits for routine evaluation based on frequency and separation distance as per Table 1 of RSS-102 Issue 5 March 2015 with an EIRP of 0.43 mW.
See separate RSS-102 Annex A exhibit for more details.

All calculations were based on peak power (worst case than source-based time-averaged maximum conducted output power).

Sincerely,



Hiroaki Suzuki

Authorized Signatory

Title: Deputy Manager of RF Group