



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

Test Report

Report No.: CQASZ20240400589E-02
Applicant: Shenzhen Buzz Tech CO., LTD
Address of Applicant: 10th Floor, Guang Chang Bldg, 74#, BaoMin 1st Rd, Bao An Shenzhen, Guangdong, China

Equipment Under Test (EUT):

Product: Smart watch
Model No.: Y3, P115, P113, P114, P116, P117, P118, P119, P121, P122, P123, S71, S72, J01, J02, T01, T02
Test Model No.: Y3
Brand Name: N/A
FCC ID: 2AGFWY3
Standards: 47 CFR Part 15, Subpart C
Date of Receipt: 2024-04-01
Date of Test: 2024-04-01 to 2024-04-11
Date of Issue: 2024-04-11
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above.

Tested By: _____

Lewis Zhou

(Lewis Zhou)

Reviewed By: _____

Timo Lei

(Timo Lei)

Approved By: _____

Alex

(Alex Wang)



1 Version

Revision History Of Report

| Report No. | Version | Description | Issue Date |
|----------------------|---------|----------------|------------|
| CQASZ20240400589E-02 | Rev.01 | Initial report | 2024-04-11 |

2 Test Summary

| Test Item | Test Requirement | Test method | Result |
|---|---|------------------|--------|
| Antenna Requirement | 47 CFR Part 15, Subpart C Section 15.203/15.247 (c) | ANSI C63.10 2013 | PASS |
| AC Power Line Conducted Emission | 47 CFR Part 15, Subpart C Section 15.207 | ANSI C63.10 2013 | PASS |
| Conducted Peak Output Power | 47 CFR Part 15, Subpart C Section 15.247 (b)(1) | ANSI C63.10 2013 | PASS |
| 6dB Occupied Bandwidth | 47 CFR Part 15, Subpart C Section 15.247 (a)(2) | ANSI C63.10 2013 | PASS |
| Power Spectral Density | 47 CFR Part 15, Subpart C Section 15.247 (e) | ANSI C63.10 2013 | PASS |
| Band-edge for RF Conducted Emissions | 47 CFR Part 15, Subpart C Section 15.247(d) | ANSI C63.10 2013 | PASS |
| RF Conducted Spurious Emissions | 47 CFR Part 15, Subpart C Section 15.247(d) | ANSI C63.10 2013 | PASS |
| Radiated Spurious Emissions | 47 CFR Part 15, Subpart C Section 15.205/15.209 | ANSI C63.10 2013 | PASS |
| Restricted bands around fundamental frequency (Radiated Emission) | 47 CFR Part 15, Subpart C Section 15.205/15.209 | ANSI C63.10 2013 | PASS |

3 Contents

| | Page |
|---|-----------|
| 1 VERSION | 2 |
| 2 TEST SUMMARY | 3 |
| 3 CONTENTS | 4 |
| 4 GENERAL INFORMATION | 5 |
| 4.1 CLIENT INFORMATION | 5 |
| 4.2 GENERAL DESCRIPTION OF EUT | 5 |
| 4.3 ADDITIONAL INSTRUCTIONS | 7 |
| 4.4 TEST ENVIRONMENT | 8 |
| 4.5 DESCRIPTION OF SUPPORT UNITS | 8 |
| 4.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY | 9 |
| 4.7 TEST LOCATION | 10 |
| 4.8 TEST FACILITY | 10 |
| 4.9 DEVIATION FROM STANDARDS | 10 |
| 4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER | 10 |
| 4.11 EQUIPMENT LIST | 11 |
| 5 TEST RESULTS AND MEASUREMENT DATA | 12 |
| 5.1 ANTENNA REQUIREMENT | 12 |
| 5.2 CONDUCTED EMISSIONS | 13 |
| 5.3 CONDUCTED PEAK OUTPUT POWER | 17 |
| 5.4 6dB OCCUPY BANDWIDTH | 21 |
| 5.5 POWER SPECTRAL DENSITY | 25 |
| 5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS | 29 |
| 5.7 SPURIOUS RF CONDUCTED EMISSIONS | 32 |
| 5.8 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS | 41 |
| 5.8.1 <i>Spurious Emissions</i> | 41 |
| 6 PHOTOGRAPHS - EUT TEST SETUP | 48 |
| 6.1 RADIATED SPURIOUS EMISSION | 48 |
| 6.2 CONDUCTED EMISSIONS TEST SETUP | 49 |
| 7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS | 50 |

4 General Information

4.1 Client Information

| | |
|--------------------------|---|
| Applicant: | Shenzhen Buzz Tech CO., LTD |
| Address of Applicant: | 10th Floor, Guang Chang Bldg, 74#, BaoMin 1st Rd, Bao An Shenzhen, Guangdong, China |
| Manufacturer: | Shenzhen Buzz Tech CO., LTD |
| Address of Manufacturer: | 10th Floor, Guang Chang Bldg, 74#, BaoMin 1st Rd, Bao An Shenzhen, Guangdong, China |
| Factory: | Shenzhen Buzz Tech CO., LTD |
| Address of Factory: | 10th Floor, Guang Chang Bldg, 74#, BaoMin 1st Rd, Bao An Shenzhen, Guangdong, China |

4.2 General Description of EUT

| | |
|---------------------------|--|
| Product Name: | Smart watch |
| Model No.: | Y3, P115, P113, P114, P116, P117, P118, P119, P121, P122, P123, S71, S72, J01, J02, T01, T02 |
| Test Model No.: | Y3 |
| Trade Mark: | N/A |
| Software Version: | V1.3 |
| Hardware Version: | R3042-1.3 |
| Operation Frequency: | 2402MHz~2480MHz |
| Bluetooth Version: | V5.2 |
| Modulation Type: | GFSK |
| Transfer Rate: | 1Mbps, 2Mbps |
| Number of Channel: | 40 |
| Product Type: | <input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable |
| Test Software of EUT: | RTLBTAPP |
| Antenna Type: | FPC antenna |
| Antenna Gain: | -5.09dBi |
| EUT Power Supply: | Li-ion battery: DC 3.7V 270mAh, Charge by DC 5V for adapter |
| Simultaneous Transmission | <input type="checkbox"/> Simultaneous TX is supported and evaluated in this report. <input checked="" type="checkbox"/> Simultaneous TX is not supported. |

Note:

Model No.: Y3, P115, P113, P114, P116, P117, P118, P119, P121, P122, P123, S71, S72, J01, J02, T01, T02

The circuit design, layout, components used and internal wiring are all the same, except for the color difference

| Operation Frequency each of channel | | | | | | | |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 0 | 2402MHz | 10 | 2422MHz | 20 | 2442MHz | 30 | 2462MHz |
| 1 | 2404MHz | 11 | 2424MHz | 21 | 2444MHz | 31 | 2464MHz |
| 2 | 2406MHz | 12 | 2426MHz | 22 | 2446MHz | 32 | 2466MHz |
| 3 | 2408MHz | 13 | 2428MHz | 23 | 2448MHz | 33 | 2468MHz |
| 4 | 2410MHz | 14 | 2430MHz | 24 | 2450MHz | 34 | 2470MHz |
| 5 | 2412MHz | 15 | 2432MHz | 25 | 2452MHz | 35 | 2472MHz |
| 6 | 2414MHz | 16 | 2434MHz | 26 | 2454MHz | 36 | 2474MHz |
| 7 | 2416MHz | 17 | 2436MHz | 27 | 2456MHz | 37 | 2476MHz |
| 8 | 2418MHz | 18 | 2438MHz | 28 | 2458MHz | 38 | 2478MHz |
| 9 | 2420MHz | 19 | 2440MHz | 29 | 2460MHz | 39 | 2480MHz |

Note:


In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel | Frequency |
|----------------------------|-----------|
| The lowest channel (CH0) | 2402MHz |
| The middle channel (CH19) | 2440MHz |
| The highest channel (CH39) | 2480MHz |

4.3 Additional Instructions

| EUT Test Software Settings: | | |
|---|---|----------------|
| Mode: | <input checked="" type="checkbox"/> Special software is used. <input type="checkbox"/> Through engineering command into the engineering mode. engineering command: ###3646633### | |
| EUT Power level: | Class2 (Power level is built-in set parameters and cannot be changed and selected) | |
| Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT. | | |
| Mode | Channel | Frequency(MHz) |
| GFSK | CH0 | 2402 |
| | CH19 | 2440 |
| | CH39 | 2480 |

Run Software:



4.4 Test Environment

| Operating Environment: | |
|------------------------|---|
| Temperature: | 24.5°C |
| Humidity: | 59% RH |
| Atmospheric Pressure: | 1009mbar |
| Test Mode: | Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT. |

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

| Description | Manufacturer | Model No. | Certification | Supplied by |
|-------------|--------------|-----------|---------------|-------------|
| Adapter | / | / | / | CQA |

2) Cable

| Cable No. | Description | Manufacturer | Cable Type/Length | Supplied by |
|-----------|-------------|--------------|-------------------|-------------|
| / | / | / | / | / |

4.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

| No. | Item | Uncertainty |
|-----|------------------------------------|--------------------|
| 1 | Radiated Emission (Below 1GHz) | 5.12dB |
| 2 | Radiated Emission (Above 1GHz) | 4.60dB |
| 3 | Conducted Disturbance (0.15~30MHz) | 3.34dB |
| 4 | Radio Frequency | 3×10^{-8} |
| 5 | Duty cycle | 0.6 % |
| 6 | Occupied Bandwidth | 1.1% |
| 7 | RF conducted power | 0.86dB |
| 8 | RF power density | 0.74 |
| 9 | Conducted Spurious emissions | 0.86dB |
| 10 | Temperature test | 0.8°C |
| 11 | Humidity test | 2.0% |
| 12 | Supply voltages | 0.5 % |
| 13 | Frequency Error | 5.5 Hz |

4.7 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

4.8 Test Facility

- **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

- **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.9 Deviation from Standards

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List


| Test Equipment | Manufacturer | Model No. | Instrument No. | Calibration Date | Calibration Due Date |
|---|--------------|------------------------|----------------|------------------|----------------------|
| EMI Test Receiver | R&S | ESR7 | CQA-005 | 2023/09/08 | 2024/09/07 |
| Spectrum analyzer | R&S | FSU26 | CQA-038 | 2023/09/08 | 2024/09/07 |
| Spectrum analyzer | R&S | FSU40 | CQA-075 | 2023/09/08 | 2024/09/07 |
| Preamplifier | MITEQ | AFS4-00010300-18-10P-4 | CQA-035 | 2023/09/08 | 2024/09/07 |
| Preamplifier | MITEQ | AMF-6D-02001800-29-20P | CQA-036 | 2023/09/08 | 2024/09/07 |
| Preamplifier | EMCI | EMC184055SE | CQA-089 | 2023/09/08 | 2024/09/07 |
| Loop antenna | Schwarzbeck | FMZB1516 | CQA-060 | 2021/09/16 | 2024/09/15 |
| Bilog Antenna | R&S | HL562 | CQA-011 | 2021/09/16 | 2024/09/15 |
| Horn Antenna | R&S | HF906 | CQA-012 | 2021/09/16 | 2024/09/15 |
| Horn Antenna | Schwarzbeck | BBHA 9170 | CQA-088 | 2021/09/16 | 2024/09/15 |
| Coaxial Cable (Above 1GHz) | CQA | N/A | C007 | 2023/09/08 | 2024/09/07 |
| Coaxial Cable (Below 1GHz) | CQA | N/A | C013 | 2023/09/08 | 2024/09/07 |
| RF cable(9KHz~40GHz) | CQA | RF-01 | CQA-079 | 2023/09/08 | 2024/09/07 |
| Antenna Connector | CQA | RFC-01 | CQA-080 | 2023/09/08 | 2024/09/07 |
| Power Sensor | KEYSIGHT | U2021XA | CQA-30 | 2023/09/08 | 2024/09/07 |
| N1918A Power Analysis Manager Power Panel | Agilent | N1918A | CQA-074 | 2023/09/08 | 2024/09/07 |
| Power meter | R&S | NRVD | CQA-029 | 2023/09/08 | 2024/09/07 |
| Power divider | MIDWEST | PWD-2533-02-SMA-79 | CQA-067 | 2023/09/08 | 2024/09/07 |
| EMI Test Receiver | R&S | ESR7 | CQA-005 | 2023/09/08 | 2024/09/07 |
| LISN | R&S | ENV216 | CQA-003 | 2023/09/08 | 2024/09/07 |
| Coaxial cable | CQA | N/A | CQA-C009 | 2023/09/08 | 2024/09/07 |
| DC power | KEYSIGHT | E3631A | CQA-028 | 2023/09/08 | 2024/09/07 |

Note:

The temporary antenna connector is soldered on the pcb board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.


5 Test results and Measurement Data

5.1 Antenna Requirement

| | |
|--|---|
| <p>Standard requirement:</p> | <p>47 CFR Part 15C Section 15.203 /247(c)</p> |
| <p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> | |
| <p>EUT Antenna:</p> |  |
| <p>The antenna is FPC antenna. The connection/connection type between the antenna to the EUT's antenna port is: unique coupling This is either permanently attachment or a unique coupling that satisfies the requirement.</p> | |


5.2 Conducted Emissions

| | | | |
|-----------------------|---|--------------|-----------|
| Test Requirement: | 47 CFR Part 15C Section 15.207 | | |
| Test Method: | ANSI C63.10: 2013 | | |
| Test Frequency Range: | 150kHz to 30MHz | | |
| Limit: | Frequency range (MHz) | Limit (dBuV) | |
| | | Quasi-peak | Average |
| | 0.15-0.5 | 66 to 56* | 56 to 46* |
| | 0.5-5 | 56 | 46 |
| | 5-30 | 60 | 50 |
| | * Decreases with the logarithm of the frequency. | | |
| Test Procedure: | <ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. | | |

| | |
|----------------------|--|
| <p>Test Setup:</p> |  |
| <p>Test Mode:</p> | <p>Charging mode</p> |
| <p>Test Voltage:</p> | <p>AC 120V/60Hz</p> |
| <p>Test Results:</p> | <p>Pass</p> |

Measurement Data

Live line:




| | Read Freq | Read Level | Factor | Level | Limit | Over | Remark | Pol/Phase |
|-------|-----------|------------|--------|-------|-------|--------|---------|-----------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | | |
| 1 | 0.455 | 19.37 | 9.66 | 29.03 | 46.78 | -17.75 | Average | Line |
| 2 | 0.455 | 25.11 | 9.66 | 34.77 | 56.78 | -22.01 | QP | Line |
| 3 | 0.570 | 19.39 | 9.77 | 29.16 | 46.00 | -16.84 | Average | Line |
| 4 | 0.570 | 24.66 | 9.77 | 34.43 | 56.00 | -21.57 | QP | Line |
| 5 | 0.615 | 19.89 | 9.82 | 29.71 | 46.00 | -16.29 | Average | Line |
| 6 | 0.615 | 25.81 | 9.82 | 35.63 | 56.00 | -20.37 | QP | Line |
| 7 | 1.020 | 19.25 | 9.75 | 29.00 | 46.00 | -17.00 | Average | Line |
| 8 | 1.020 | 24.20 | 9.75 | 33.95 | 56.00 | -22.05 | QP | Line |
| 9 PP | 1.490 | 19.64 | 10.81 | 30.45 | 46.00 | -15.55 | Average | Line |
| 10 | 1.490 | 24.56 | 10.81 | 35.37 | 56.00 | -20.63 | QP | Line |
| 11 | 1.580 | 19.02 | 10.98 | 30.00 | 46.00 | -16.00 | Average | Line |
| 12 QP | 1.580 | 24.66 | 10.98 | 35.64 | 56.00 | -20.36 | QP | Line |

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




| | | Read | | Limit | Over | | | |
|----|------|-------|--------|-------|-------|-------|----------------|---------|
| | Freq | Level | Factor | Level | Line | Limit | Remark | |
| | MHz | dBuV | dB | dBuV | dBuV | dB | Pol/Phase | |
| 1 | PP | 0.575 | 21.09 | 9.78 | 30.87 | 46.00 | -15.13 Average | Neutral |
| 2 | QP | 0.575 | 28.11 | 9.78 | 37.89 | 56.00 | -18.11 QP | Neutral |
| 3 | | 0.635 | 19.63 | 9.84 | 29.47 | 46.00 | -16.53 Average | Neutral |
| 4 | | 0.635 | 25.50 | 9.84 | 35.34 | 56.00 | -20.66 QP | Neutral |
| 5 | | 0.990 | 19.19 | 9.71 | 28.90 | 46.00 | -17.10 Average | Neutral |
| 6 | | 0.990 | 24.03 | 9.71 | 33.74 | 56.00 | -22.26 QP | Neutral |
| 7 | | 1.300 | 19.74 | 9.72 | 29.46 | 46.00 | -16.54 Average | Neutral |
| 8 | | 1.300 | 24.57 | 9.72 | 34.29 | 56.00 | -21.71 QP | Neutral |
| 9 | | 1.630 | 20.35 | 9.73 | 30.08 | 46.00 | -15.92 Average | Neutral |
| 10 | | 1.630 | 25.30 | 9.73 | 35.03 | 56.00 | -20.97 QP | Neutral |
| 11 | | 2.575 | 13.82 | 9.76 | 23.58 | 46.00 | -22.42 Average | Neutral |
| 12 | | 2.575 | 21.46 | 9.76 | 31.22 | 56.00 | -24.78 QP | Neutral |

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


5.3 Conducted Peak Output Power

| | |
|-------------------|--|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (b)(1) |
| Test Method: | ANSI C63.10 2013 |
| Test Setup: |  <p style="text-align: center;"><i>Remark: Offset=Cable loss+ attenuation factor.</i></p> |
| Limit: | 30dBm |
| Test Mode: | Transmitting with GFSK modulation. |
| Test Results: | Pass |


Measurement Data

| GFSK mode (1Mbps) | | | |
|-------------------|-------------------------|-------------|--------|
| Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest | -0.58 | 30.00 | Pass |
| Middle | -1.31 | 30.00 | Pass |
| Highest | -1.64 | 30.00 | Pass |
| GFSK mode (2Mbps) | | | |
| Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |
| Lowest | -0.98 | 30.00 | Pass |
| Middle | -1.27 | 30.00 | Pass |
| Highest | -1.54 | 30.00 | Pass |


BLE_1M_Ant1_2402



BLE_1M_Ant1_2440




BLE_1M_Ant1_2480




Date: 11.APR.2024 09:28:33

BLE_2M_Ant1_2402




Date: 11.APR.2024 09:29:40

BLE_2M_Ant1_2440




Date: 11.APR.2024 09:30:41

BLE 2M Ant1 2480




5.4 6dB Occupy Bandwidth

| | |
|-------------------|---|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (a)(2) |
| Test Method: | ANSI C63.10 2013 |
| Test Setup: |  <p style="text-align: center;"><i>Remark: Offset=Cable loss+ attenuation factor.</i></p> |
| Limit: | ≥ 500 kHz |
| Instruments Used: | Refer to section 4.11 for details. |
| Test Results: | Pass |

Measurement Data


| GFSK mode (1Mbps) | | | |
|-------------------|----------------------------|-------------|--------|
| Test channel | 6dB Occupy Bandwidth (MHz) | Limit (kHz) | Result |
| Lowest | 0.68 | ≥500 | Pass |
| Middle | 0.68 | ≥500 | Pass |
| Highest | 0.68 | ≥500 | Pass |
| GFSK mode (2Mbps) | | | |
| Test channel | 6dB Occupy Bandwidth (MHz) | Limit (kHz) | Result |
| Lowest | 1.14 | ≥500 | Pass |
| Middle | 1.14 | ≥500 | Pass |
| Highest | 1.14 | ≥500 | Pass |

BLE_1M_Ant1_2402




Date: 2 APR 2024 15:22:13

BLE_1M_Ant1_2440




Date: 2 APR 2024 15:25:34

BLE_1M_Ant1_2480




Date: 2 APR 2024 15:27:13

BLE 2M Ant1 2402




Date: 2 APR 2024 15:31:37

BLE 2M Ant1 2440




Date: 2 APR 2024 15:34:34

BLE 2M Ant1 2480



Date: 2 APR 2024 15:36:26


5.5 Power Spectral Density


| | |
|-------------------|--|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (e) |
| Test Method: | ANSI C63.10 2013 |
| Test Setup: |  <p style="text-align: center;"><i>Remark: Offset=Cable loss+ attenuation factor.</i></p> |
| Limit: | ≤8.00dBm/3kHz |
| Test Mode: | Transmitting with GFSK modulation. |
| Test Results: | Pass |

Measurement Data

| GFSK mode (1Mbps) | | | |
|-------------------|-----------------------------------|------------------|--------|
| Test channel | Power Spectral Density (dBm/3kHz) | Limit (dBm/3kHz) | Result |
| Lowest | -10.98 | ≤8.00 | Pass |
| Middle | -9.88 | ≤8.00 | Pass |
| Highest | -9.92 | ≤8.00 | Pass |
| GFSK mode (2Mbps) | | | |
| Test channel | Power Spectral Density (dBm/3kHz) | Limit (dBm/3kHz) | Result |
| Lowest | -14.23 | ≤8.00 | Pass |
| Middle | -13.27 | ≤8.00 | Pass |
| Highest | -13.45 | ≤8.00 | Pass |


Test plot as follows:






Date: 2 APR 2024 15:27:34

BLE_2M_Ant1_2402




Date: 2 APR 2024 15:31:57


BLE_2M_Ant1_2440




Date: 2 APR 2024 15:34:55




5.6 Band-edge for RF Conducted Emissions

| | |
|-------------------|---|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (d) |
| Test Method: | ANSI C63.10 2013 |
| Test Setup: |  <p style="text-align: center;">Spectrum Analyzer</p> <p style="text-align: center;">E.U.T</p> <p style="text-align: center;">Non-Conducted Table</p> <p style="text-align: center;">Ground Reference Plane</p> <p><i>Remark: Offset=Cable loss+ attenuation factor.</i></p> |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test Mode: | Transmitting with GFSK modulation. |
| Test Results: | Pass |


| TestMode | ChName | Freq(MHz) | RefLevel[dBm] | Result[dBm] | Limit[dBm] | Verdict |
|----------|--------|-----------|---------------|-------------|------------|---------|
| BLE_1M | Low | 2402 | 4.92 | -45.55 | ≤-15.08 | PASS |
| | High | 2480 | 5.75 | -44.16 | ≤-14.25 | PASS |
| BLE_2M | Low | 2402 | 4.66 | -29.69 | ≤-15.34 | PASS |
| | High | 2480 | 5.43 | -44.81 | ≤-14.57 | PASS |




BLE 2M Ant1 High 2480




5.7 Spurious RF Conducted Emissions

| | |
|-------------------|---|
| Test Requirement: | 47 CFR Part 15C Section 15.247 (d) |
| Test Method: | ANSI C63.10 2013 |
| Test Setup: |  <p style="text-align: center;"><i>Remark: Offset=Cable loss+ attenuation factor.</i></p> |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test Mode: | Transmitting with GFSK modulation. |
| Test Results: | Pass |


Test plot as follows:






Date: 2 APR 2024 15:24:50

BLE_1M_Ant1_2440_0~Reference




Date: 2 APR 2024 15:26:03

BLE_1M_Ant1_2440_30~1000



Date: 2 APR 2024 15:26:10


BLE_1M_Ant1_2440_1000~26500




BLE_1M_Ant1_2480_0~Reference




BLE_1M_Ant1_2480_30~1000




BLE_1M_Ant1_2480_1000~26500



BLE_2M_Ant1_2402_0~Reference




BLE_2M_Ant1_2402_30~1000



Date: 2 APR 2024 15:33:51

BLE_2M_Ant1_2402_1000~26500




Date: 2 APR 2024 15:34:13

BLE_2M_Ant1_2440_0~Reference




Date: 2 APR 2024 15:35:04

BLE_2M_Ant1_2440_30~1000




Date: 2 APR 2024 15:35:10

BLE_2M_Ant1_2440_1000~26500




Date: 2 APR 2024 15:35:32

BLE_2M_Ant1_2480_0~Reference




Date: 2 APR 2024 15:38:26

BLE_2M_Ant1_2480_30~1000



Date: 2 APR 2024 15:38:32

BLE_2M_Ant1_2480_1000~26500



Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o), The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.8 Radiated Spurious Emission & Restricted bands

| 5.8.1 Spurious Emissions | | | | | |
|--|--|----------------------------------|----------------|------------|--------------------------|
| Test Requirement: | 47 CFR Part 15C Section 15.209 and 15.205 | | | | |
| Test Method: | ANSI C63.10 2013 | | | | |
| Test Site: | Measurement Distance: 3m (Semi-Anechoic Chamber) | | | | |
| Receiver Setup: | Frequency | Detector | RBW | VBW | Remark |
| | 0.009MHz-0.090MHz | Peak | 10kHz | 30kHz | Peak |
| | 0.009MHz-0.090MHz | Average | 10kHz | 30kHz | Average |
| | 0.090MHz-0.110MHz | Quasi-peak | 10kHz | 30kHz | Quasi-peak |
| | 0.110MHz-0.490MHz | Peak | 10kHz | 30kHz | Peak |
| | 0.110MHz-0.490MHz | Average | 10kHz | 30kHz | Average |
| | 0.490MHz -30MHz | Quasi-peak | 10kHz | 30kHz | Quasi-peak |
| | 30MHz-1GHz | Quasi-peak | 100 kHz | 300kHz | Quasi-peak |
| | Above 1GHz | Peak | 1MHz | 3MHz | Peak |
| Peak | | 1MHz | 10Hz | Average | |
| Limit: | Frequency | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark | Measurement distance (m) |
| | 0.009MHz-0.490MHz | 2400/F(kHz) | - | - | 300 |
| | 0.490MHz-1.705MHz | 24000/F(kHz) | - | - | 30 |
| | 1.705MHz-30MHz | 30 | - | - | 30 |
| | 30MHz-88MHz | 100 | 40.0 | Quasi-peak | 3 |
| | 88MHz-216MHz | 150 | 43.5 | Quasi-peak | 3 |
| | 216MHz-960MHz | 200 | 46.0 | Quasi-peak | 3 |
| | 960MHz-1GHz | 500 | 54.0 | Quasi-peak | 3 |
| | Above 1GHz | 500 | 54.0 | Average | 3 |
| <p>Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.</p> | | | | | |

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:


- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 Note: For the radiated emission test above 1GHz:
 Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both

| | |
|-------------------------------|--|
| | <p>horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz)</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p> |
| <p>Exploratory Test Mode:</p> | <p>Transmitting with GFSK modulation. Transmitting mode.</p> |
| <p>Final Test Mode:</p> | <p>Through Pre-scan, find the 1Mbps of data type and GFSK modulation is the worst case. For below 1GHz part, through pre-scan, the worst case is the highest channel. Only the worst case is recorded in the report.</p> |
| <p>Test Results:</p> | <p>Pass</p> |

Radiated Emission below 1GHz


30MHz~1GHz, the worst case

Test mode: Transmitting mode Horizontal



| | Read Freq | Read Level | Read Factor | Limit Level | Limit Line | Over Limit | Remark | Pol/Phase |
|------|-----------|------------|-------------|-------------|------------|------------|--------|------------|
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | |
| 1 | 32.52 | 10.27 | 15.25 | 25.52 | 40.00 | -14.48 | Peak | HORIZONTAL |
| 2 | 82.65 | 9.17 | 9.84 | 19.01 | 40.00 | -20.99 | Peak | HORIZONTAL |
| 3 | 250.30 | 12.18 | 12.09 | 24.27 | 46.00 | -21.73 | Peak | HORIZONTAL |
| 4 | 348.03 | 10.60 | 14.90 | 25.50 | 46.00 | -20.50 | Peak | HORIZONTAL |
| 5 | 562.66 | 10.40 | 18.92 | 29.32 | 46.00 | -16.68 | Peak | HORIZONTAL |
| 6 pp | 881.41 | 10.49 | 23.92 | 34.41 | 46.00 | -11.59 | Peak | HORIZONTAL |

| | | |
|----------------------------|-------------------|----------|
| 30MHz~1GHz, the worst case | | |
| Test mode: | Transmitting mode | Vertical |



| | Read Freq | Read Level | Factor | Level | Limit Line | Over Limit | Remark | Pol/Phase |
|------|-----------|------------|--------|--------|------------|------------|--------|-----------|
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | | |
| 1 pp | 30.75 | 13.84 | 15.71 | 29.55 | 40.00 | -10.45 | Peak | VERTICAL |
| 2 | 37.02 | 14.57 | 13.87 | 28.44 | 40.00 | -11.56 | Peak | VERTICAL |
| 3 | 97.46 | 9.76 | 10.49 | 20.25 | 43.50 | -23.25 | Peak | VERTICAL |
| 4 | 316.59 | 8.88 | 14.13 | 23.01 | 46.00 | -22.99 | Peak | VERTICAL |
| 5 | 501.18 | 12.46 | 18.29 | 30.75 | 46.00 | -15.25 | Peak | VERTICAL |
| 6 | 845.09 | 9.72 | 24.08 | 33.80 | 46.00 | -12.20 | Peak | VERTICAL |

Transmitter Emission above 1GHz

| Worse case mode: | | GFSK(1Mbps) | | Test channel: | | Lowest | |
|------------------|---------------|-------------|----------------|----------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | | H/V |
| 2390 | 55.69 | -9.2 | 46.49 | 74 | -27.51 | Peak | H |
| 2400 | 56.24 | -9.39 | 46.85 | 74 | -27.15 | Peak | H |
| 4804 | 52.92 | -4.33 | 48.59 | 74 | -25.41 | Peak | H |
| 7206 | 48.53 | 1.01 | 49.54 | 74 | -24.46 | Peak | H |
| 2390 | 52.29 | -9.2 | 43.09 | 74 | -30.91 | Peak | V |
| 2400 | 51.20 | -9.39 | 41.81 | 74 | -32.19 | Peak | V |
| 4804 | 52.91 | -4.33 | 48.58 | 74 | -25.42 | Peak | V |
| 7206 | 48.24 | 1.01 | 49.25 | 74 | -24.75 | Peak | V |

| Worse case mode: | | GFSK(1Mbps) | | Test channel: | | Middle | |
|------------------|---------------|-------------|----------------|----------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | | H/V |
| 4880 | 51.81 | -4.11 | 47.70 | 74 | -26.30 | peak | H |
| 7320 | 49.39 | 1.51 | 50.90 | 74 | -23.10 | peak | H |
| 4880 | 54.08 | -4.11 | 49.97 | 74 | -24.03 | peak | V |
| 7320 | 51.00 | 1.51 | 52.51 | 74 | -21.49 | peak | V |

| Worse case mode: | | GFSK(1Mbps) | | Test channel: | | Highest | |
|------------------|---------------|-------------|----------------|----------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dB μ V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) | | H/V |
| 2483.5 | 55.17 | -9.29 | 45.88 | 74 | -28.12 | Peak | H |
| 4960 | 52.48 | -4.04 | 48.44 | 74 | -25.56 | Peak | H |
| 7440 | 51.04 | 1.57 | 52.61 | 74 | -21.39 | Peak | H |
| 2483.5 | 56.35 | -9.29 | 47.06 | 74 | -26.94 | Peak | V |
| 4960 | 49.79 | -4.04 | 45.75 | 74 | -28.25 | Peak | V |
| 7440 | 49.80 | 1.57 | 51.37 | 74 | -22.63 | Peak | V |

| Worse case mode: | | GFSK(2Mbps) | | Test channel: | | Lowest | |
|------------------|---------------|-------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 2390 | 53.27 | -9.2 | 44.07 | 74 | -29.93 | Peak | H |
| 2400 | 57.21 | -9.39 | 47.82 | 74 | -26.18 | Peak | H |
| 4804 | 54.23 | -4.33 | 49.90 | 74 | -24.10 | Peak | H |
| 7206 | 50.09 | 1.01 | 51.10 | 74 | -22.90 | Peak | H |
| 2390 | 54.20 | -9.2 | 45.00 | 74 | -29.00 | Peak | V |
| 2400 | 51.71 | -9.39 | 42.32 | 74 | -31.68 | Peak | V |
| 4804 | 52.51 | -4.33 | 48.18 | 74 | -25.82 | Peak | V |
| 7206 | 50.23 | 1.01 | 51.24 | 74 | -22.76 | Peak | V |

| Worse case mode: | | GFSK(2Mbps) | | Test channel: | | Middle | |
|------------------|---------------|-------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 4880 | 50.91 | -4.11 | 46.80 | 74 | -27.20 | peak | H |
| 7320 | 50.41 | 1.51 | 51.92 | 74 | -22.08 | peak | H |
| 4880 | 52.12 | -4.11 | 48.01 | 74 | -25.99 | peak | V |
| 7320 | 49.49 | 1.51 | 51.00 | 74 | -23.00 | peak | V |

| Worse case mode: | | GFSK(2Mbps) | | Test channel: | | Highest | |
|------------------|---------------|-------------|----------------|---------------|--------|---------------|-----------|
| Frequency | Meter Reading | Factor | Emission Level | Limits | Over | Detector Type | Ant. Pol. |
| (MHz) | (dBμV) | (dB) | (dBμV/m) | (dBμV/m) | (dB) | | H/V |
| 2483.5 | 54.58 | -9.29 | 45.29 | 74 | -28.71 | Peak | H |
| 4960 | 51.62 | -4.04 | 47.58 | 74 | -26.42 | Peak | H |
| 7440 | 50.48 | 1.57 | 52.05 | 74 | -21.95 | Peak | H |
| 2483.5 | 56.58 | -9.29 | 47.29 | 74 | -26.71 | Peak | V |
| 4960 | 50.92 | -4.04 | 46.88 | 74 | -27.12 | Peak | V |
| 7440 | 49.89 | 1.57 | 51.46 | 74 | -22.54 | Peak | V |

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6 Photographs - EUT Test Setup

6.1 Radiated Spurious Emission

9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:



6.2 Conducted Emissions Test Setup



7 Photographs - EUT Constructional Details

Refer to Photographs - EUT Constructional Details OF EUT for CQASZ20240400589E-01.

*** END OF REPORT ***