

APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
Lakeshore Learning Materials

Gear-Bot
Model No.: GG127

FCC ID: 2AGG4GG127

Prepared for : Lakeshore Learning Materials
Address : 2695 E. Dominguez St., Carson, California 90895, United States

Prepared by : Shenzhen Accurate Technology Co., Ltd.
Address : 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20181150
Date of Test : July 5-July 12, 2018
Date of Report : July 13, 2018

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Special Accessory and Auxiliary Equipment	4
1.3. Description of Test Facility	5
1.4. Measurement Uncertainty.....	5
2. MEASURING DEVICE AND TEST EQUIPMENT	6
3. OPERATION OF EUT DURING TESTING	7
3.1. Operating Mode	7
3.2. Configuration and peripherals	7
4. TEST PROCEDURES AND RESULTS	8
5. 20DB BANDWIDTH MEASUREMENT.....	9
5.1. Block Diagram of Test Setup.....	9
5.2. The Requirement For Section 15.215(c).....	9
5.3. Operating Condition of EUT	9
5.4. Test Procedure	9
5.5. Test Result	10
6. BAND EDGE COMPLIANCE TEST	12
6.1. Block Diagram of Test Setup.....	12
6.2. The Requirement For Section 15.249.....	12
6.3. EUT Configuration on Measurement	12
6.4. Operating Condition of EUT	13
6.5. Test Procedure	13
6.6. Test Result	13
7. RADIATED SPURIOUS EMISSION TEST	18
7.1. Block Diagram of Test Setup.....	18
7.2. The Limit For Section 15.249.....	19
7.3. Restricted bands of operation	20
7.4. Configuration of EUT on Measurement	20
7.5. Operating Condition of EUT	21
7.6. Test Procedure	21
7.7. Data Sample.....	22
7.8. The Field Strength of Radiation Emission Measurement Results	22
8. ANTENNA REQUIREMENT.....	35
8.1. The Requirement	35
8.2. Antenna Construction	35
9. PHOTO OF EUT.....	36

Test Report Certification

Applicant : Lakeshore Learning Materials
Address : 2695 E. Dominguez St., Carson, California 90895, United States
Product : Gear-Bot
Model No. : GG127

Measurement Procedure Used:

**FCC Rules and Regulations Part 15 Subpart C Section 15.249
ANSI C63.10: 2013**

The EUT was tested according to FCC 47CFR 15.249 for compliance to FCC 47CFR 15.249 requirements

The device described above is tested by Shenzhen Accurate Technology Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.249 limits. The measurement results are contained in this test report and Shenzhen Accurate Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Shenzhen Accurate Technology Co., Ltd.

Date of Test : July 5-July 12, 2018
Date of Report : July 13, 2018

Prepared by : _____
(Sean Yang, Engineer)

Approved & Authorized Signer : _____
(Sean Liu, Manager)



1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product	:	Gear-Bot
Model Number	:	GG127
Frequency Range	:	2411-2459MHz
Number of Channels	:	2411, 2413, 2415, 2417, 2419, 2421, 2423, 2431, 2433, 2435, 2437, 2441, 2443, 2445, 2447, 2457, 2455, 2459MHz
Modulation Type	:	GFSK
Type of Antenna	:	Integral Antenna
Max antenna gain	:	0dBi
Power Supply	:	DC 6V (AA size batteries (1.5V) x4)

1.2. Special Accessory and Auxiliary Equipment

N/A

1.3. Description of Test Facility

EMC Lab	:	Recognition of accreditation by Federal Communications Commission (FCC) The Designation Number is CN1189 The Registration Number is 708358
		Listed by Innovation, Science and Economic Development Canada (ISED) The Registration Number is 5077A-2
		Accredited by China National Accreditation Service for Conformity Assessment (CNAS) The Registration Number is CNAS L3193
		Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01
Name of Firm	:	Shenzhen Accurate Technology Co., Ltd.
Site Location	:	1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

1.4. Measurement Uncertainty

Conducted Emission Expanded Uncertainty	=	2.23dB, k=2
Radiated emission expanded uncertainty (9kHz-30MHz)	=	3.08dB, k=2
Radiated emission expanded uncertainty (30MHz-1000MHz)	=	4.42dB, k=2
Radiated emission expanded uncertainty (Above 1GHz)	=	4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde & Schwarz	ESR	101817	Jan. 06, 2018	Jan. 05, 2019
Spectrum Analyzer	Rohde&Schwarz	FSV40	101495	Jan. 06, 2018	Jan. 05, 2019
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 06, 2018	Jan. 05, 2019
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 06, 2018	Jan. 05, 2019
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 06, 2018	Jan. 05, 2019
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 06, 2018	Jan. 05, 2019
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 06, 2018	Jan. 05, 2019
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 06, 2018	Jan. 05, 2019

3. OPERATION OF EUT DURING TESTING

3.1. Operating Mode


The mode is used: **Transmitting mode**

Low Channel: 2411MHz

Middle Channel: 2433MHz

High Channel: 2459MHz

3.2. Configuration and peripherals




4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.215(c)	20dB Bandwidth	Compliant
Section 15.249(d)	Band Edge Compliance Test	Compliant
Section 15.205(a), Section 15.209(a), Section 15.249, Section 15.35	Radiated Spurious Emission Test	Compliant
Section 15.207	AC Power Line Conducted Emission Test	N/A
Section 15.203	Antenna Requirement	Compliant

Note: The EUT is powered by the battery 6V, so the conducted emission is not applicable and skipped

5. 20DB BANDWIDTH MEASUREMENT

5.1. Block Diagram of Test Setup



5.2. The Requirement For Section 15.215(c)

The bandwidth of a frequency hopping channel is the 20 dB emission bandwidth, measured with the hopping stopped. The system RF bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset. The hopset shall be such that the near-term distribution of frequencies appears random, with sequential hops randomly distributed in both direction and magnitude of change in the hopset while the long-term distribution appears evenly distributed.

5.3. Operating Condition of EUT

5.3.1. Setup the EUT and simulator as shown as Section 5.1.

5.3.2. Turn on the power of all equipment.

5.3.3. Let the EUT work in TX modes measure it. The transmit frequency are 2411-2459 MHz. We select 2411MHz, 2433MHz, and 2459MHz TX frequency to transmit.

5.4. Test Procedure

5.4.1. Place the EUT on the table and set it in transmitting mode.

5.4.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

5.4.3. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz, Detector function=peak, Trace=max hold, Sweep=auto.


5.4.4. Set the measured low, middle and high frequency and test 20dB bandwidth with spectrum analyzer.

5.5. Test Result

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2411	0.300
Middle	2433	0.294
High	2459	0.292


The spectrum analyzer plots are attached as below.

Low channel




Date: 5.JUL.2018 15:28:36

Middle channel



Date: 5.JUL.2018 15:29:48


High channel



Date: 5.JUL.2018 15:30:28

6. BAND EDGE COMPLIANCE TEST

6.1. Block Diagram of Test Setup



6.2. The Requirement For Section 15.249

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

6.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2411-2459 MHz. We select 2411MHz, 2459MHz TX frequency to transmit.

6.5. Test Procedure

Radiate Band Edge:

6.5.1. The EUT is placed on a turntable, which is 1.5m above the ground plane and worked at highest radiated power.

6.5.2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.

6.5.3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

6.5.4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

RBW=1MHz, VBW=1MHz

6.5.5. The band edges was measured and recorded.

6.6. Test Result

Pass.

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

3. Display the measurement of peak values.


4. The average measurement was not performed when peak measured data under the limit of average detection.

The spectral diagrams are attached as below.

Job No.: star2016 #2644
 Standard: FCC PK
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 23 C / 48 %
 EUT: Gear-Bot
 Mode: TX 2411MHz
 Model: GG127
 Manufacturer: Lakeshore Learning Materials

Polarization: Horizontal
 Power Source: DC 6V
 Date: 2018/07/12
 Time: 17:10:31
 Engineer Signature: star
 Distance: 3m

Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	47.20	0.79	47.99	74.00	-26.01	peak	250	301	
2	2390.000	38.15	0.79	38.94	54.00	-15.06	AVG	250	55	
3	2400.000	53.68	0.88	54.56	74.00	-19.44	peak	250	406	
4	2400.000	44.65	0.88	45.53	54.00	-8.47	AVG	250	66	

Job No.: star2016 #2645

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Gear-Bot

Mode: TX 2411MHz

Model: GG127

Manufacturer: Lakeshore Learning Materials

Polarization: Vertical

Power Source: DC 6V


Date: 2018/07/12

Time: 17:11:14

Engineer Signature: star

Distance: 3m


Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	38.00	0.79	38.79	74.00	-35.21	peak	250	220	
2	2390.000	29.12	0.79	29.91	54.00	-24.09	AVG	250	122	
3	2400.000	45.62	0.88	46.50	74.00	-27.50	peak	250	102	
4	2400.000	36.42	0.88	37.30	54.00	-16.70	AVG	250	61	

Job No.: star2016 #2647	Polarization: Horizontal
Standard: FCC PK	Power Source: DC 6V
Test item: Radiation Test	Date: 2018/07/12
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 17:14:19
EUT: Gear-Bot	Engineer Signature: star
Mode: TX 2459MHz	Distance: 3m
Model: GG127	
Manufacturer: Lakeshore Learning Materials	


Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.23	1.10	49.33	74.00	-24.67	peak	250	301	
2	2483.500	38.15	1.10	39.25	54.00	-14.75	AVG	250	56	
3	2500.000	40.59	1.10	41.69	74.00	-32.31	peak	250	145	
4	2500.000	30.65	1.10	31.75	54.00	-22.25	AVG	250	62	

Job No.: star2016 #2646	Polarization: Vertical
Standard: FCC PK	Power Source: DC 6V
Test item: Radiation Test	Date: 2018/07/12
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 17:13:12
EUT: Gear-Bot	Engineer Signature: star
Mode: TX 2459MHz	Distance: 3m
Model: GG127	
Manufacturer: Lakeshore Learning Materials	

Note: Report No.: ATE20181150




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	37.83	1.10	38.93	74.00	-35.07	peak	250	122	
2	2483.500	29.15	1.10	30.25	54.00	-23.75	AVG	200	31	
3	2500.000	38.37	1.10	39.47	74.00	-34.53	peak	250	56	
4	2500.000	29.42	1.10	30.52	54.00	-23.48	AVG	200	102	

7. RADIATED SPURIOUS EMISSION TEST

7.1. Block Diagram of Test Setup


7.1.1. Block diagram of connection between the EUT and peripherals




(EUT: Gear-Bot)

7.1.2. Semi-Anechoic Chamber Test Setup Diagram


(A) Radiated Emission Test Set-Up, Frequency below 30MHz



(B) Radiated Emission Test Set-Up, Frequency 30-1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1GHz



7.2. The Limit For Section 15.249

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph A8.4(4), the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

7.3.Restricted bands of operation

7.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

7.4.Configuration of EUT on Measurement

The equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.5. Operating Condition of EUT

7.5.1. Setup the EUT and simulator as shown as Section 7.1.

7.5.2. Turn on the power of all equipment.

7.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2411-2459 MHz. We select 2411MHz, 2433MHz, and 2459MHz TX frequency to transmit.

7.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground (Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground (Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver is set at 9 kHz in below 30MHz. and set at 120 kHz in 30-1000MHz, and 1MHz in above 1000MHz.

The final measurement in band 9-90 kHz, 110-490 kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

RBW (120 kHz), VBW (300 kHz) for QP detector below 1GHz

Peak detector above 1GHz

RBW (1 MHz), VBW (3MHz) for Peak measurement

RBW (1 MHz), VBW (10Hz) for AV measurement

7.7.Data Sample

Frequency(MHz)	Reading (dB μ v)	Factor (dB/m)	Result (dB μ v/m)	Limit (dB μ v/m)	Margin (dB)	Remark
X.XX	30.21	-17.87	12.34	40.00	-27.66	QP

Frequency(MHz) = Emission frequency in MHz

Reading(dB μ v) = Uncorrected Analyzer/Receiver reading

Factor (dB/m) = Antenna factor + Cable Loss – Amplifier gain

Result(dB μ v/m) = Reading(dB μ v) + Factor(dB/m)

Limit (dB μ v/m) = Limit stated in standard

Margin (dB) = Result(dB μ v/m) - Limit (dB μ v/m)

QP = Quasi-peak Reading

Calculation Formula:

Margin(dB) = Result (dB μ V/m)–Limit(dB μ V/m)

Result(dB μ V/m)= Reading(dB μ V)+ Factor(dB/m)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit.

7.8.The Field Strength of Radiation Emission Measurement Results

Pass.

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

2. *: Denotes restricted band of operation.

3. The EUT is tested radiation emission at Low, Middle, High channel in three axes. The worst emissions are reported in all channels.

4. Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz and 18 to 26.5GHz.

Job No.: STAR2016 #2608

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Gear-Bot

Mode: TX 2411MHz

Model: GG127

Manufacturer: Lakeshore Learning Materials

Polarization: Horizontal

Power Source: DC 6V


Date: 18/07/05/

Time: 18/40/34

Engineer Signature: star

Distance: 3m

Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	195.1365	50.28	-12.30	37.98	43.50	-5.52	QP	200	187	
2	325.5957	48.26	-8.21	40.05	46.00	-5.95	QP	200	92	
3	519.0647	43.57	-3.86	39.71	46.00	-6.29	QP	200	348	
4	574.6258	41.50	-2.63	38.87	46.00	-7.13	QP	200	278	
5	709.1823	40.40	-0.92	39.48	46.00	-6.52	QP	200	291	
6	823.7217	43.48	1.22	44.70	46.00	-1.30	QP	200	235	

Job No.: STAR2016 #2607

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Gear-Bot

Mode: TX 2411MHz

Model: GG127

Manufacturer: Lakeshore Learning Materials

Polarization: Vertical

Power Source: DC 6V


Date: 18/07/05/

Time: 18/38/57

Engineer Signature: star

Distance: 3m

Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	197.8926	50.00	-12.28	37.72	43.50	-5.78	QP	100	168	
2	219.8447	51.40	-11.51	39.89	46.00	-6.11	QP	100	190	
3	417.6409	36.12	-5.87	30.25	46.00	-15.75	QP	100	203	
4	478.8455	39.13	-4.90	34.23	46.00	-11.77	QP	100	293	
5	734.4913	32.46	-0.56	31.90	46.00	-14.10	QP	100	301	
6	839.1816	39.31	1.47	40.78	46.00	-5.22	QP	100	68	

Job No.: STAR2016 #2609

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Gear-Bot

Mode: TX 2433MHz

Model: GG127

Manufacturer: Lakeshore Learning Materials

Polarization: Horizontal

Power Source: DC 6V


Date: 18/07/05/

Time: 18/44/17

Engineer Signature: star

Distance: 3m


Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	226.8934	43.98	-11.19	32.79	46.00	-13.21	QP	200	100	
2	321.0605	42.11	-8.40	33.71	46.00	-12.29	QP	200	136	
3	377.2590	39.46	-7.04	32.42	46.00	-13.58	QP	200	105	
4	483.9094	40.95	-4.81	36.14	46.00	-9.86	QP	200	47	
5	691.9867	36.14	-1.22	34.92	46.00	-11.08	QP	200	100	
6	857.0247	43.00	1.65	44.65	46.00	-1.35	QP	200	121	

Job No.: STAR2016 #2610	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 6V
Test item: Radiation Test	Date: 18/07/05/
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 18/45/14
EUT: Gear-Bot	Engineer Signature: star
Mode: TX 2433MHz	Distance: 3m
Model: GG127	
Manufacturer: Lakeshore Learning Materials	

Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	194.4533	45.00	-12.32	32.68	43.50	-10.82	QP	100	308	
2	224.5192	46.13	-11.26	34.87	46.00	-11.13	QP	100	323	
3	417.6409	34.23	-5.87	28.36	46.00	-17.64	QP	100	128	
4	475.4990	33.90	-4.95	28.95	46.00	-17.05	QP	100	133	
5	747.4825	33.91	-0.33	33.58	46.00	-12.42	QP	100	197	
6	827.4933	40.00	1.30	41.30	46.00	-4.70	QP	100	214	

Job No.: STAR2016 #2612

Polarization: Horizontal

Standard: FCC Class B 3M Radiated

Power Source: DC 6V

Test item: Radiation Test

Date: 18/07/05/

Temp.(C)/Hum.(%) 23 C / 48 %

Time: 18/48/02

EUT: Gear-Bot

Engineer Signature: star


Mode: TX 2459MHz

Distance: 3m

Model: GG127

Manufacturer: Lakeshore Learning Materials

Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	223.7333	42.75	-11.30	31.45	46.00	-14.55	QP	200	333	
2	308.9125	40.00	-8.76	31.24	46.00	-14.76	QP	200	245	
3	447.9821	42.78	-5.38	37.40	46.00	-8.60	QP	200	162	
4	482.2155	43.57	-4.84	38.73	46.00	-7.27	QP	200	104	
5	699.3046	40.10	-1.08	39.02	46.00	-6.98	QP	200	130	
6	836.2441	43.00	1.45	44.45	46.00	-1.55	QP	200	122	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR2016 #2611	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 6V
Test item: Radiation Test	Date: 18/07/05/
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 18/46/17
EUT: Gear-Bot	Engineer Signature: star
Mode: TX 2459MHz	Distance: 3m
Model: GG127	
Manufacturer: Lakeshore Learning Materials	


Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	207.1226	45.12	-12.06	33.06	43.50	-10.44	QP	100	277	
2	224.5192	49.00	-11.26	37.74	46.00	-8.26	QP	100	293	
3	420.5803	38.13	-5.75	32.38	46.00	-13.62	QP	100	138	
4	494.1983	35.46	-4.58	30.88	46.00	-15.12	QP	100	147	
5	640.6109	33.98	-1.90	32.08	46.00	-13.92	QP	100	199	
6	821.7103	37.20	1.18	38.38	46.00	-7.62	QP	100	168	

Job No.: STAR2016 #2640	Polarization: Horizontal
Standard: FCC PK	Power Source: DC 6V
Test item: Radiation Test	Date: 2018/07/09
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 21:16:30
EUT: Gear-Bot	Engineer Signature: star
Mode: TX 2411MHz	Distance: 3m
Model: GG127	
Manufacturer: Lakeshore Learning Materials	

Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2411.003	89.67	0.91	90.58	114.00	-23.42	peak	250	43	
2	2411.003	78.65	0.91	79.56	94.00	-14.44	AVG	200	320	
3	4812.016	51.99	7.53	59.52	74.00	-14.48	peak	200	147	
4	4812.016	42.99	7.53	50.52	54.00	-3.48	AVG	200	46	

Job No.: STAR2016 #2641

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Gear-Bot

Mode: TX 2411MHz

Model: GG127

Manufacturer: Lakeshore Learning Materials

Polarization: Vertical

Power Source: DC 6V


Date: 2018/07/09

Time: 21:17:30

Engineer Signature: star

Distance: 3m


Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2411.003	84.13	0.91	85.04	114.00	-28.96	peak	250	63	
2	2411.003	78.23	0.91	79.14	94.00	-14.86	AVG	250	154	
3	4812.016	50.00	7.53	57.53	74.00	-16.47	peak	250	147	
4	4812.016	42.12	7.53	49.65	54.00	-4.35	AVG	250	122	

Job No.: STAR2016 #2643	Polarization: Horizontal
Standard: FCC PK	Power Source: DC 6V
Test item: Radiation Test	Date: 2018/07/09
Temp.(C)/Hum.(%) 23 C / 48 %	Time: 21:20:26
EUT: Gear-Bot	Engineer Signature: star
Mode: TX 2433MHz	Distance: 3m
Model: GG127	
Manufacturer: Lakeshore Learning Materials	

Note: Report No.: ATE20181150




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2433.071	88.84	1.00	89.84	114.00	-24.16	peak	150	246	
2	2433.071	82.36	1.00	83.36	94.00	-10.64	AVG	150	141	
3	4866.075	52.98	7.92	60.90	74.00	-13.10	peak	150	306	
4	4866.075	43.00	7.92	50.92	54.00	-3.08	AVG	150	287	

Job No.: STAR2016 #2642
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Gear-Bot
Mode: TX 2433MHz
Model: GG127
Manufacturer: Lakeshore Learning Materials

Polarization: Vertical
Power Source: DC 6V
Date: 2018/07/09
Time: 21:19:28
Engineer Signature: star
Distance: 3m

Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2433.071	85.08	1.00	86.08	114.00	-27.92	peak	250	302	
2	2433.071	78.61	1.00	79.61	94.00	-14.39	AVG	250	25	
3	4866.075	50.47	7.92	58.39	74.00	-15.61	peak	200	14	
4	4866.075	42.10	7.92	50.02	54.00	-3.98	AVG	200	166	

Job No.: STAR2016 #2638

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Gear-Bot

Mode: TX 2459MHz

Model: GG127

Manufacturer: Lakeshore Learning Materials

Polarization: Horizontal

Power Source: DC 6V


Date: 2018/07/09

Time: 21:10:25

Engineer Signature: star

Distance: 3m

Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2459.013	89.41	1.09	90.50	114.00	-23.50	peak	250	102	
2	2459.013	79.65	1.09	80.74	94.00	-13.26	AVG	200	165	
3	4918.490	52.21	8.37	60.58	74.00	-13.42	peak	200	170	
4	4918.364	42.32	8.38	50.70	54.00	-3.30	AVG	200	94	

Job No.: STAR2016 #2639

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Gear-Bot

Mode: TX 2459MHz

Model: GG127

Manufacturer: Lakeshore Learning Materials

Polarization: Vertical

Power Source: DC 6V


Date: 2018/07/09

Time: 21:11:37

Engineer Signature: star

Distance: 3m

Note: Report No.: ATE20181150



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2459.013	85.16	1.09	86.25	114.00	-27.25	peak	200	216	
2	2459.013	78.65	1.09	79.74	94.00	-14.26	AVG	150	332	
3	4918.490	49.61	8.37	57.98	74.00	-16.02	peak	150	242	
4	4918.776	40.62	8.38	49.00	54.00	-5.00	AVG	150	55	


8. ANTENNA REQUIREMENT

8.1.The Requirement



According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



8.2.Antenna Construction



Device is equipped with unique antenna, which isn't displaced by other antenna. Therefore, the equipment complies with the antenna requirement of Section 15.203.





9. PHOTO OF EUT









----- THE END OF TEST REPORT -----