

RF Exposure Evaluation

FCC ID: 2AGGR-B5

1. Client Information

Applicant : Shenzhen Rivers Technology Co.,Limited
Address : A#1611, Zhantao Technology Building, Longhua New District, Shenzhen, China
Manufacturer : Shenzhen Rivers Technology Co.,Limited
Address : A#1611, Zhantao Technology Building, Longhua New District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Middle Glass Keyboard(SKU:6928514351118)			
Models No.	:	B5			
Brand Name	:	Bastron			
Model Difference	:	N/A			
Product Description	Operation Frequency: Bluetooth:2402~2480MHz				
	Number of Channel: Bluetooth:79 Channels				
	Max Peak Output Power: Bluetooth: 1.84 dBm(GFSK)				
	Antenna Gain: 2 dBi PCB Antenna				
	Modulation Type: GFSK (1 Mbps)				
Power Supply	:	DC Voltage supplied from Host System by USB cable. DC power by Li-ion Battery.			
Power Rating	:	DC 5.0V by USB cable. DC 3.7V 1.92Wh Li-ion Battery.			
Connecting I/O Port(S)	:	Please refer to the User's Manual			

Note:

More test information about the EUT please refer the RF Test Report.

[TB-RF-074-1.0](#)

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v05r02.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR}$$
$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 7.5.0 \text{ for 10-g SAR}$$

2.

Calculation:

Test separation: 5mm					
Bluetooth Mode (GFSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	1.84	± 0.5	1.714	0.531	3.0
2.441	1.15	± 0.5	1.462	0.457	3.0
2.480	-0.01	± 0.5	1.119	0.353	3.0

So standalone SAR measurements are not required.