

# RF EXPOSURE REPORT

## FOR

<b>Applicant</b>	:	Guangdong Hisense Broadband Technology Co., Ltd
<b>Address</b>	:	No.8 Hisense Road, Tangxia Town, Pengjiang District, Jiangmen City, Guangdong Province
<b>Equipment under Test</b>	:	GPON SFU ONT
<b>Model No.</b>	:	7285G
<b>Trade Mark</b>	:	iPhotonix, CORNING, Hisense
<b>FCC ID</b>	:	2AGHCHBMT07
<b>Manufacturer</b>	:	Guangdong Hisense Broadband Technology Co., Ltd
<b>Address</b>	:	No.8 Hisense Road, Tangxia Town, Pengjiang District, Jiangmen City, Guangdong Province

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

**Tel:** +86-0769-89201699, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

# TABLE OF CONTENTS

- Test report declares.....3
- 1. General information .....5
  - 1.1. Description of Equipment.....5
  - 1.2. Assess laboratory .....6
- 2. RF Exposure evaluation for FCC .....6
  - 2.1. Requirement .....6
  - 2.2. Calculation Method .....7
  - 2.3. Estimation Result.....7

## TEST REPORT DECLARE

<b>Applicant</b>	:	Guangdong Hisense Broadband Technology Co., Ltd
<b>Address</b>	:	No.8 Hisense Road, Tangxia Town, Pengjiang District, Jiangmen City, Guangdong Province
<b>Equipment under Test</b>	:	GPON SFU ONT
<b>Model No.</b>	:	7285G
<b>Trade mark</b>	:	iPhotonix, CORNING, Hisense
<b>Manufacturer</b>	:	Guangdong Hisense Broadband Technology Co., Ltd
<b>Address</b>	:	No.8 Hisense Road, Tangxia Town, Pengjiang District, Jiangmen City, Guangdong Province

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R18030203-1E3		
<b>Date of Receipt:</b>	Mar. 06, 2018	<b>Date of Test:</b>	Mar. 06, 2018 ~ Apr. 24, 2018

**Prepared By:**

*Sam Li*

**Sam Li/Engineer**

**Approved By:**



**Kevin Feng/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

### Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Apr. 24, 2018	

## 1. General information

### 1.1. Description of Equipment

EUT* Name	: GPON SFU ONT
Model Number	: 7285G
EUT function description	: Please reference user manual of this device
Power supply	: DC 12V from external AC Adapter
Radio Specification	: 2.4G: IEEE 802.11b/g/n : 5G: IEEE802.11n/a/ac
Operation frequency	: 2.4G: IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11n HT20: 2412MHz—2462MHz IEEE 802.11n HT40: 2422MHz—2452MHz : 5G: IEEE 802.11a: 5180MHz-5240MHz, 5745MHz-5825MHz IEEE 802.11n HT20: 5180MHz-5240MHz, 5745MHz-5825MHz IEEE 802.11n HT40: 5190MHz-5230MHz, 5755MHz-5795MHz IEEE 802.11ac HT20: 5180MHz-5240MHz, 5745MHz-5825MHz IEEE 802.11ac HT40: 5190MHz-5230MHz, 5755MHz-5795MHz IEEE 802.11ac HT80: 5210MHz, 5775MHz
Modulation	: 2.4G: IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) : 5G: IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Data rate	: 2.4G: IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: up to 150 Mbps IEEE 802.11n HT40: up to 300 Mbps : 5G: IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: up to 150 Mbps, HT40: up to 300 Mbps IEEE 802.11ac VHT20: up to 150 Mbps, VHT40: up to 300 Mbps VHT80: up to 886.7 Mbps
Antenna Type	: Integrated metal antenna 1: 2.4G band maximum PK gain 2.38dBi Integrated metal antenna 2: 2.4G band maximum PK gain 2.87dBi 2.4G directional gain of MIMO mode is 5.64dBi : External PCB antenna 1: 5G band maximum PK gain 3.89dBi Integrated metal antenna 2: 5G band maximum PK gain 3.85dBi Integrated metal antenna 3: 5G band maximum PK gain 4.17dBi 5G directional gain of MIMO mode is 8.74dBi
Sample Type	: Series production

## 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-89201699, E-mail: ddt@dgddt.com, <http://www.dgddt.com>

CNAS Accreditation No. L6451; A2LA Accreditation No. 3870.01

## 2. RF Exposure evaluation for FCC

### 2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

## 2.2. Calculation Method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = Peak RF output power (mW)

**G** = EUT Antenna numeric gain (numeric)=

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance,  $d=0.2\text{m}$ , as well as the gain of the used antenna, the RF power density can be obtained.

## 2.3. Estimation Result

Mode	PK Output power (dBm)	Output power (mW)	Antenna Gain (dBi)	MPE Values ( $\text{mW/cm}^2$ )	MPE Limit ( $\text{mW/cm}^2$ )
2.4G WIFI Max power	25.16	328.10	5.64	0.368	1
5G WIFI Max power	26.51	447.71	8.74	0.778	1

Note: The estimation distance is 20cm

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold

**END OF REPORT**