

RF Exposure Report

FCC ID: 2AGJ417U5K

Applicant: Specialty Technologies, LLC

Address: 340 Victoria Rd Youngstown Ohio 44515, USA

Manufacturer: Specialty Technologies, LLC

Address: 340 Victoria Rd Youngstown Ohio 44515, USA

Product: Powered Subwoofer

Brand(s): SVS

Test Model(s): SB17-Ultra Evolution, PB17-Ultra Evolution, SB-5000 Evolution,
PB-5000 Evolution

Series Model(s): N/A

Test Date: Mar. 12, 2024~ Jun. 02, 2024

Issued Date: Jul. 09, 2024

Issued By: Hwa-Hsing (Dongguan) Testing Co., Ltd.

Address: No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park,
HuangJiang Town, Dongguan City, People's Republic of China


Test Firm Registration No.: 915896

Designation No.: CN1255

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01
IEEE C95.1


The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Nature Lee

Reviewed by :



Dragon Long

Approved by :



Scott He

"This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. Our report includes all the tests requested by you and the results thereof based upon the information that you provided to us. The report would be invalid without specific stamp of test institute and the signatures of tester and approver."

Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)Tel: [0769-83078199](#)Web.: [www.hwa-hsing.com](#)E-Mail: [customerservice.dg@hwa-hsing.com](#)Release
Ver. 1.5

Table of contents

Release control record	3
1 General Information	4
1.1 General Description of EUT	4
2 RF exposure limit	5
2.1 MPE calculation formula	5
3 Calculation result of maximum conducted power	6
Appendix – Information on the Testing Laboratories	7

Test Report No.: 23121406-SE-US-01

Release control record

Issue No.	Reason for change	Date issued
23121406-SE-US-01	Original Release	Jul. 09, 2024

Test Report No.: 23121406-SE-US-01

1 General Information**1.1 General Description of EUT**

Product	Powered Subwoofer
Sample No.	HS2403120017, HS2403120018, HS2403120019, HS2403120020
Test Model(s)	SB17-Ultra Evolution, PB17-Ultra Evolution, SB-5000 Evolution, PB-5000 Evolution
Series Model(s)	N/A
Status of EUT	Engineering Prototype
Power Supply Rating	AC 100-240V 50/60Hz 15A
Modulation Type	GFSK for DTS
Transfer Rate	1 Mbps, 2Mbps
Operating Frequency	2402 ~ 2480MHz
Number of Channel	40
Maximum Output Power	6.06dBm (Average)
Antenna Type	Wire Antenna
Antenna Gain	2.85dBi Gain
Antenna Connector	N/A
Accessory Device	N/A
Data Cable Supplied	AC Cable: 180cm Non-shielded, Detachable

Note:

1. Please refer to the EUT photo document (Reference No.: 23121406-01&02) for detailed product photo.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.
3. Model difference: All models are identical with each other except for model name, software, appearance, size of loud speaker and size of the main unit.

Test Report No.: 23121406-SE-US-01

2 RF exposure limit

Limits for maximum permissible exposure (MPE)

Limits for general population / uncontrolled exposure				
Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Average time (minutes)
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30
Note: F = Frequency in MHz				

2.1 MPE calculation formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

*Where:*Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Classification:

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

Test Report No.: 23121406-SE-US-01

3 Calculation result of maximum conducted power

The antennas provided to the EUT, please refer to the following table:

Function	Frequency (MHz)	Antenna Gain (dBi)	Antenna Type	Transmit and Receive Chain	Maximum AVG Power
BLE	2402-2480	2.85	Dipole	1TX,1RX	6.06dBm

Frequency (MHz)	Max power (mW)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm ²)	Limit (mW/cm ²)
2402-2480	4.0365	2.85	20	0.001548	1.0

Conclusion:

Therefore, the worst-case situation is 0.001548 mW/cm², which is less than "1". This confirmed that the device compliance with FCC 1.1310 MPE limit.

Test Report No.: 23121406-SE-US-01

Appendix – Information on the Testing Laboratories

We, [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#), A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values “HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT”, commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Contact Tel: [0769-83078199](#)

Email: Customerservice.dg@hwa-hsing.com

Web Site: www.hwa-hsing.com

--- END ---